
≡ Hide menu

Lecture: Part of Speech Tagging

- ✔ Video: Week Introduction
- **Video:** Part of Speech Tagging
- Reading: Part of Speech Tagging
- Lab: Lecture Notebook Working with text files
- ✔ Video: Markov Chains
- Reading: Markov Chains
- Video: Markov Chains and POS Tags 4 min
- Reading: Markov Chains and POS Tags 6 min
- ✔ Video: Hidden Markov Models 3 min
- Reading: Hidden Markov Models
- ✔ Video: Calculating Probabilities
- Reading: Calculating Probabilities 5 min
- Video: Populating the Transition Matrix 4 min
- Reading: Populating the Transition Matrix 6 min
- **Video:** Populating the Emission Matrix 2 min
- Reading: Populating the Emission Matrix 5 min
- Lab: Lecture Notebook Working with tags and Numpy 20 min
- ✔ Video: The Viterbi Algorithm 4 min
- Reading: The Viterbi Algorithm 5 min
- **Video:** Viterbi: Initialization 2 min
- Reading: Viterbi Initialization
- **Video:** Viterbi: Forward Pass
- Reading: Viterbi: Forward Pass
- **Video:** Viterbi: Backward Pass
- 5 min Reading: Viterbi: Backward Pass

Viterbi: Forward Pass

This will be best illustrated with an example:



 $\begin{bmatrix} \mathbf{w}_1 \\ \mathbf{w}_2 \end{bmatrix} \begin{bmatrix} \mathbf{w}_3 \\ \mathbf{w}_3 \end{bmatrix}$


		W ₁	W ₂	 w _K
	t ₁	C _{1,1}	C _{1,2}	C _{1,K}
	t _N	C _{N,1}	C _{N,2}	C _{N,K}

$$c_{1,2} = \max_{k} c_{k,1} * a_{k,1} * b_{1,cindex(w_2)}$$

So to populate a cell (i.e. 1,2) in the image above, you have to take the max of [kth cells in the previous column, times the corresponding transition probability of the kth POS to the first POS times the emission probability of the first POS and the current word you are looking at]. You do that for all the cells. Take a paper and a pencil, and make sure you understand how it is done.

The general rule is $ci, j = \max_{k} ck, j-1 * ak, i * bi, cindex(wj)$

Now to populate the **D** matrix, you will keep track of the argmax of where you came from as follows:



) =		w ₁	W ₂	 w _K
	t ₁	d _{1,1}	d _{1,2}	d _{1,K}
	t _N	d _{N,1}	d _{N,2}	d _{N,K}

$$c_{i,j} = \max_k c_{k,j-1} * a_{k,i} * b_{i,cindex(w_j)}$$
 $d_{i,j} = \operatorname*{argmax}_k c_{k,j-1} * a_{k,i} * b_{i,cindex(w_j)}$

Note that the only difference between c^{ij} and d^{ij} , is that in the former you compute the probability and in the latter you keep track of the index of the row where that probability came from. So you keep track of which k was used to get that max probability.

Mark as completed





< Previous Next >