

Hide menu

LSTMs and Named Entity Recognition

- ✓

**Video:** Week Introduction  
1 min
- ✓

**Video:** RNNs and Vanishing Gradients  
6 min
- ✓

**Reading:** RNNs and Vanishing Gradients  
6 min
- ✓

**Reading:** (Optional) Intro to optimization in deep learning: Gradient Descent  
10 min
- ✓

**Lab:** Vanishing Gradients  
15 min
- ✓

**Video:** Introduction to LSTMs  
4 min
- ✓

**Reading:** Introduction to LSTMs  
3 min
- ✓

**Video:** LSTM Architecture  
3 min
- ⊞

**Reading:** LSTM Architecture  
4 min
- ▶

**Video:** Introduction to Named Entity Recognition  
3 min
- ⊞

**Reading:** Introduction to Named Entity Recognition  
2 min
- ▶

**Video:** Training NERs: Data Processing  
4 min
- ⊞

**Reading:** Training NERs: Data Processing  
5 min
- ⊞

**Reading:** Long Short-Term Memory (Deep Learning Specialization C5)  
10 min
- ▶

**Video:** Computing Accuracy  
1 min
- ⊞

**Reading:** Computing Accuracy  
2 min
- ▶

**Video:** Week Conclusion  
32 sec

Lecture Notes (Optional)

Practice Quiz

Assignment: Named Entity Recognition (NER)


Week 2 > LSTM Architecture

Previous Next

LSTM Architecture

The LSTM architecture could get complicated and don't worry about it if you do not understand it. I personally prefer looking at the equation, but I will try to give you a visualization for now and later this week we will take a look at the equations.

Gates in LSTM



Note the forget gate (1), input gate (2) and output gate (3) marked in blue. In contrast with vanilla RNNs, there is the cell state in addition to the hidden state. The idea of the **forget gate** to drop the information that is no longer important. It makes use of the previous hidden state  $h^{<t_0>}$  and the input  $x^{<t_1>}$ . The **input gate** makes sure to keep the relevant information that needs to be stored. Finally the **output gate** creates an output that is used at the current step.

LSTM equations (optional):

For better understanding, take a look at the LSTM equations and relate them to the figure above.

The forget gate:  $f = \sigma(W^f[ht-1; xt] + bf)$  (marked with a blue 1)

The input gate:  $i = \sigma(W^i[ht-1; xt] + bi)$  (marked with a blue 2)

The gate gate (candidate memory cell):  $g = \tanh(W^g[ht-1; xt] + bg)$

The cell state:  $ct = f \odot ct-1 + i \odot g$

The output gate:  $o = \sigma(W^o[ht-1; xt] + bo)$  (marked with a blue 3)

The output of LSTM unit:  $ht = ot \odot \tanh(ct)$

Mark as completed