

















- Course Shortcuts
- > Student Lounge
- > Q&A
- > Explore a Neural Network
- > Use Convolutional NeuralNetworks for Image Analysis
- Analyze Sequence Data with Neural Sequence Models
 - Module Introduction:
 Analyze Sequence Data
 with Neural Sequence
 Models
 - Adapt Neural Networks for Sequence Models
 - Review Neural Sequence Models
 - Find the Embedded Relationship of Words
 - Formalize Word Embeddings
 - Use Word Embeddings to Predict Sentiment
 - Review Deep Averaging
 Networks
 - Translate Text with
 Recurrent Neural
 Networks
 - Review Recurrent Neural
 Networks
 - Sequence Models Cheat
 Sheet
 - Implement Neural Sequence Models for Sentiment Analysis
 - Module Wrap-up: Analyze
 Sequence Data with
 Neural Sequence Models
 - Course Exit Survey
 - Thank You and Farewell

Deep Learning and Neural Networks >

◆ Previous

Formalize Word Embeddings

Word embeddings are essentially mappings from words to vectors. For example, we might decide that the word "flower" should be represented by a vector $[1.2, 3.4, \ldots, 4.6]$.

This mapping is usually contained in a **dictionary**, which is a set of words. Since it cannot include all words ever used in a given language, there can be a special "word" that represents all the other words not in your dictionary. So if you have a dictionary of size n and you want to represent each word as a vector of size d, then your word embedding is essentially an $n \times d$ matrix where each row corresponds to a word.

The problem we have now is how to learn this dictionary. The intuition to learn a word embedding is simple: words that appear in similar contexts should have similar word

vectors. For example, the words "ship" and "boat" probably appear in almost identical contexts and should be very similar in representation. The words "ship" and "water" should probably be closer together than "ship" and "philosophy."

Concretely, we represent each word i as a vector \mathbf{w}_i . We define the predicted probability that word i is followed by word j as the softmax probability of their inner products (with respect to all words k in the dictionary):

$$P(i|j) = rac{\exp(\mathbf{w}_i^ op \mathbf{w}_j)}{\sum_k \exp(\mathbf{w}_i^ op \mathbf{w}_k)}$$

Now, given a sequence of m words, the log likelihood of observing this sequence is $\log[P(s_2|s_1)P(s_3|s_2)\dots P(s_m|s_{m-1})] = \sum_{i=1}^{m-1} \log P(s_{i+1}|s_i)$. Note that the log likelihood function is a function of the word embeddings.

With the probability and log likelihood defined, what we need to do is download a large corpus of data from the internet and then maximize the log likelihood function, or equivalently minimize the negative log likelihood function by using SGD. The model thus finds the word embeddings that best explain the corpus.

Sometimes, word embeddings capture the meaning of words so well that the embeddings show interesting geometric properties such as $\mathbf{w}_{king} - \mathbf{w}_{man} + \mathbf{w}_{woman} \approx \mathbf{w}_{queen}$.

☆ Key Points

Word embeddings are words mapped to vectors that convey the meaning of this word.

Word embeddings have multiple convenient properties that make them great inputs for sequence models.

Next **▶**

Stay Connected

> Course Resources