

4th class–

1- How python works:

i- Compilation process:

While running a Python script (.py), the Python compiler first checks your code for syntax errors. If the code is valid, it translates the source code into an intermediate format called Bytecode.

i-What is Bytecode: It is a low-level, platform-independent set of instructions. It isn't machine code that CPU understands. Only Pvm only understand bycode instructions. it is specific to Python.

ii-It is often stored in a folder named `__pycache__` with a .pyc extension.

ii. Interpretation

The Bytecode is then sent to the Python Virtual Machine (PVM). The PVM contains the Interpreter,

i-The Interpreter reads the Bytecode line-by-line.

ii-It converts each line into Machine Code (binary 0s and 1s) that your specific computer hardware can execute.

2. Compiler

What it does: It translates the entire source code into machine code all at once before the program runs.

3. Interpreter

What it does: It translates and executes the code line-by-line during runtime.

–5th class–

1. Data Types in Python

Data types 5 types such as:

- Int: numbers (e.g., 10, -5).
 - Float: Decimal numbers (e.g., 10.5, 3.14).
 - String: in quotes (e.g., "Hello").
 - bool: either True or False.
 - None: It indicates that a variable exists but doesn't have a value yet.
-

2. Operators in Python

- + (Addition), - (Subtraction), * (Multiplication), / (Division)
- // (Floor Division): Returns the whole number after division (e.g., $7 // 2 = 3$).
- % (Modulus): Returns the remainder (e.g., $7 \% 2 = 1$).
- (Exponent): Power (e.g., $2^3 = 8$).

Another Comparison Operators

- == (Equal), != (Not Equal)
- > (Greater than), < (Less than)
- >= (Greater than or equal), <= (Less than or equal)

C. Logical Operators

- and: Returns True if both statements are true.
- or: Returns True if one statement is true.
- not: Reverses the result (e.g., not (True) is False)

D. Assignment Operators

Used to assign values to variables.

- = (Assignment), += (Add and assign), -= (Subtract and assign).

----6th class---

1. Input & Type Conversion

By default, the `input()` function always takes data as a String.

- Concatenation: Using `+` with inputs will join them as text (e.g., `"10" + "20"` results in `"1020"`).
- Type Casting: To perform math, need to convert the string to an integer using `int()`.
 - *Example:* `result = int(first) + int(second)`

2. String Formatting Approaches

several ways to combine strings and variables:

- f-strings : The most modern and readable way.
 - *Syntax:* `f"Hello {name}"`
- `.join()` Method: *Syntax:* `" ".join([first_name, last_name])`
- `.format()` Method: Uses placeholders `{}` to insert values.
 - *Syntax:* `"{} {}".format(a, b)`, if i extend 1 variable, then will be needed `{}` more extra one.
- String Multiplication: Make repetition a string multiple times using `*`.
 - *Example:* `"sorry " * 1000`

3. Useful String Methods

Python built-in functions:

- `.upper()` / `.lower()`: Converts text to all capital or all small letters.
- `.title()`: Capitalizes the first letter of every word.
- `.capitalize()`: Capitalizes only the very first letter of the string.
- `.swapcase()`: Flips cases (Lower to right , Upper to Lower).
- `.count("x")`: Counts how many times a specific character appears.
- `.find("word")`: Returns the index (position) of the first occurrence of a word.

4. Variable Overriding

In Python, variables are dynamic. If i assign a new value to an existing variable name, the old value is replaced (overridden).

- *Example:* If number = 10 and then number = 30, the final value stored is 30.

—7th Class—

Python String Methods and Operations

1. Fundamental String Operations

Python strings are indexed sequences of characters where indexing starts at 0 and negative indexing starts from the end at -1.

Operation	Description	Example (x = "hello world")
len(x)	Returns the total number of characters in the string.	11
Indexing [i]	Accesses a character at a specific position.	x[4] → 'o'
Negative Indexing [-i]	Accesses characters starting from the end.	x[-1] → 'd'

String Slicing

i-x[0:5] / x[:5]: Extracts characters from index 0 up to (but not including) index 5 (example: "hello").

ii-x[6:]: Extracts characters from index 6 to the very end (example:"world").

2.String Modification Methods

1-.replace(): Replaces a specific part of the string with new text.

- `"rocky".replace("r", "p")` → output: `'pocky'`

2-.strip(): Removes extra spaces from both the start and the end.

- `" hello ".strip()` → output: `'hello'`

3.lstrip(): Removes spaces only from the left side.

- `" hello ".lstrip()` → output: `'hello '`

4.rstrip(): Removes spaces only from the right side.

- `" hello ".rstrip()` → output: `' hello'`

5.upper(): Converts all letters to uppercase.

- `"python".upper()` → output: `'PYTHON'`

6.lower(): Converts all letters to lowercase.

- `"PYTHON".lower()` → output: `'python'`

7.title(): Capitalizes the first letter of every word.

- `"hello world".title()` → output: `'Hello World'`

8.split(): Splits the string into a list based on a separator.

- `"a,b,c".split(",")` → output: `['a', 'b', 'c']`

9.capitalize(): Capitalizes only the first letter of the entire string.

- `"hello".capitalize()` → output: `'Hello'`

Methods:

1-.startswith(): Checks if the string starts with a specific value.

- `"apple".startswith("a")` → output: True

2-.endswith(): Checks if the string ends with a specific value.

- `"apple".endswith("e")` → output: True

3-.find(): Returns the index position of the first occurrence of a value.

- `"hello".find("e")` → output: 1

4-.count(): Counts how many times a value appears in the string.

- `"banana".count("a")` → output: 3

5-.isdigit(): Checks if all characters in the string are numbers.

- `"123".isdigit()` → output: True

6-.isalpha(): Checks if all characters in the string are letters.

- `"hello".isalpha()` → output: True

4. String Validation

Basically, return True or False.

- `.isalpha()`: True if all characters are alphabetic (A-Z).
- `.isdigit()`: True if all characters are digits (0-9).

- `.isalnum()`: True if all characters are alphanumeric (letters or numbers).
- `.isspace()`: True if the string consists only of whitespace.
- `.istitle()`: True if the string follows title case rules.
- `.islower()`: True if all characters are lowercase.

5. Input and Output Formatting

User Input

```
1-name = input("Enter your name: ")
```

```
2-age = int(input("Enter your age: "))
```

Printing Techniques

1. Standard Print: `print("Name:", name, "Age:", age)` or,
2. F-String: `print(f"Your name is {name} and your age is {age}")`.

—8th Class—

if Statement: Executes the code block only if the condition is **True**.

- `if age >= 18:` → **Result:** Checks if age is 18 or more.

elif (else if): Used to check multiple conditions one after another if the previous ones were False.

- `elif score >= 80:` → **Result:** Checks this only if the first `if` failed.

else: Executes only if none of the above conditions are met.

- `else :` → **Result:** The final option and if any of the condition fail then else condition will work

—9th class—

The Python ternary operator evaluates a condition and returns a specific value in a single line

Ternary operator = [Value_If_True] if [Condition] else [Value_If_False].

```
status = "Pass" if marks >= 40 else "Fail"
```

i-**Logic:** If marks are 40 or more, status is "Pass"; otherwise, it is "Fail".

ii-**Output:** "Pass" (if marks = 50)

10 th 11 th no class

python data types - int, string, float (decimal), bool (yes/no), None (no value).

7620

input() gives string for value and, float is type casting of value
int, float (32 bit) is fixed and not 64 bit. Ex: name = int(input("your name"))

'full_name' = first_name + " " + last_name.

61125 only first_name = "R"

last - name, "H."

stunt (" " pin

7 No.

Docstring = multiline comment.

Alphabet (A-z; a-z).

Numeric (0-9 any digit).
Alphanumeric (A-Z, a-z, 0-9).

Stripe) = left, right space remove

$L_n(\cdot) = \text{left}$ " " , Right space - Rsmpr

isalpha = only alphabet character (space, comma, etc. not included).

is digit; 0 isalnum = (A, a, 0-9) निम्न स्पष्टीकरण (क) में दी गयी है।

25 space (concat string empty string check ops) text: " "

data type check = type(3) // Number, type("Rocky") // string

11 $\Rightarrow$ datatype $\rightarrow$ list("rock") = o/p = r, o, c, k // simple string list @ list iterate each item on
 from list of "rock", 1, 2, 3, 4, from list of "rock", from 1 to 4

List - mutable - get ordered way (for array, array list, string, bool, obj, list)

- ↳ duplicate allow ∞ , zero indexed, heterogeneous types allow (data mix)

* Siddik = [] - empty list // faster // better lexical syntax.

Siddik: list() → empty list → constructor syntax // Get usage by typing data

type of list is converted into list() using

```
Ex: chars → list('Hello') // list of convert 2/2 - output - 'H', 'e', 'l', 'l', 'o'
```

```
mixed = [42, 'Hello', 3.14, True] // O/P 26th [42, 'Hello', 3.14, True]
```

- append method - 2nd only list add array, string extend & list with unlimited

insert (1, "Lychee") // 12; index 9 add (insertion) 2/8

ternore, delete, pop (variable w/size in pop value return arr) → pop remove the first element

Last 2 part of data structure part of object oriented item covered in 1st part

GAVISOL 1: (7/7/2019) 11 GAVISOL [1,2,3,4,5] print 2/2

Repetitive operations [0] * 3 will print 3 times.

Accessing Elements. fruits = ["apple", "banana", "cherry", "date", "pineapple"]

	0	1	2	3	4
index					
neg index	-5	-4	-3	-2	-1

print(fruits[1]) // banana, print(fruits[-2]) // date

licing → fruits[2:4] // 2 to 4 index, 4 last index not include
 fruits[:3] // 0-3 index.
 fruits[3:] // 3 to last index.

fruits[0:4:2] = 0 to 4 index, 4 last index not include, 2 step
 fruits[2:4:2] = 2 to 4 index, 4 last index not include, 2 step
 fruits[::2] = 0 to last index, 2 step
 fruits[::3] = 0 to last index, 3 step
 fruits[-1:-2:-1] = last index to second last index, reverse

Replacement value
 fruits[0:3] = ["Mango", "Lichee", "Dragon"] // 0-2 index value replace
 print(fruits) // value updated and assign again

fruits[1:1] = ["Mango", "Lichee", "Dragon"] // 1 index value replace
 fruits[2:4] = [] // empty list, delete process, 2/3 index delete
 fruits[1] = ["Lichee"] // 1 index insert, 2 index replacement
 del fruits[0] // 0 index value delete; del fruits[1:3] // 1-2 index delete

Concatenation:
 fruits1 = ["a", "b", "c", "d"], fruits2 = ["e", "f", "g"]
 fruits = fruits1 + fruits2 = print(fruits) // ["a", "b", "c", "d", "e", "f", "g"]

append fruits.append("Mango") // last index value add
 ("Mango", "Banana") // possible 2 arguments

extend fruits.extend(["Mango"]) // list extend method use, fruits.extend(["Mango", "Banana"])
 ("Mango", "Banana") // list extend method use, fruits.extend(["Mango", "Banana"])

fruits.insert(1, "Lichee") // 1 index value insert

Remove:
 fruits.remove("apple") // apple remove, 1 index value delete
 fruits.pop() // last index value delete, 1 index value delete
 fruits.pop(1) // 1 index value delete, 1 index value delete
 fruits.pop(-1) // last index value delete, 1 index value delete

fruits.pop(2) // 2 index value delete, 2 index value delete

fruits.clear() // list empty

fruits.sort() // sort alphabetically, fruits.sort(reverse=True) // reverse sort

fruits.index() // index value, fruits.count("apple") // apple count

```
1 #sum(), numbers=[0,1,2,3,4], sum(numbers)
```

13th class - loop → loop ২টা এমন একটি process যার চক্রান্ত repeated হয়
until condition true থাকে.

while loop structure: $-i=1$ / O/P- $\frac{1}{3}$ / 1D list - names = ["Rohit", "Ali", "M"]
 $\text{while } i \leq 5$ / $\frac{4}{5}$ / print(names[0])
 $\text{print}(i)$
 $i+=1$ / 2D list - students = [

3D list - list of list of list
data = [[[1, 2], [3, 4]], [[5, 6], [7, 8]], [[9, 10], [11, 12]]]

print(data[0][1][0]) // 3
print(data[1][0][1]) // 6
print(data[2][1][0]) // 11