

# WEEK 13

Question 1

Correct

[Flag question](#)

Given an array of numbers, find the index of the smallest array element (the pivot), for which the sums of all elements to the left and to the right are equal. The array may not be reordered.

Example

arr=[1,2,3,4,6]

- the sum of the first three elements,  $1+2+3=6$ . The value of the last element is 6.
- Using zero based indexing, arr[3]=4 is the pivot between the two subarrays.
- The index of the pivot is 3.

```
7
8 int balancedSum(int arr_count, int* arr)
9 {
10     int totalsum=0;
11     for(int i=0;i<arr_count;i++){
12         totalsum+=arr[i];
13     }
14     int lefts=0;
15     for(int i=0;i<arr_count;i++){
16         int rights=totalsum-lefts-arr[i];
17
18         if(lefts==rights){
19             return i;
20         }else{
21             lefts+=arr[i];
22         }
23     }
24     return 1;
25 }
26
27
```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,3}; printf("%d", balancedSum(4, arr))	2	2	✓

Passed all tests! ✓

Question 2

Correct

[Flag question](#)

Calculate the sum of an array of integers.

```

8  int arraySum(int numbers_count, int *numbers)
9  {
10     int sum=0;
11     for(int i=0;i<numbers_count;i++){
12         sum+=numbers[i];
13     }
14     return sum;
15 }
16

```

	Test	Expected	Got	
✓	int arr[] = {1,2,3,4,5}; printf("%d", arraySum(5, arr))	15	15	✓

Passed all tests! ✓

Question **3**  
Correct  
[Flag question](#)

Given an array of  $n$  integers, rearrange them so that the sum of the absolute differences of all adjacent elements is minimized. Then, compute the sum of those absolute differences. Example  $n = 5$   $arr = [1, 3, 3, 2, 4]$  If the list is rearranged as  $arr' = [1, 2, 3, 3, 4]$ , the absolute differences are  $|1 - 2| = 1$ ,  $|2 - 3| = 1$ ,  $|3 - 3| = 0$ ,  $|3 - 4| = 1$ . The sum of those differences is  $1 + 1 + 0 + 1 = 3$ . Function Description Complete the function minDiff in the editor below. minDiff has the following parameter: arr: an integer array Returns: int: the sum of the absolute differences of adjacent elements Constraints  $2 \leq n \leq 105$   $0 \leq arr[i] \leq 109$ , where  $0 \leq i < n$  Input Format For Custom Testing The first line of input contains an integer,  $n$ , the size of arr. Each of the following  $n$  lines contains an integer that describes  $arr[i]$  (where  $0 \leq i < n$ ). Sample Case 0 Sample Input For Custom Testing STDIN Function ----- 5  $\rightarrow$  arr[] size  $n = 5$  5  $\rightarrow$  arr[] = [5, 1, 3, 7, 3] 1 3 7 3 Sample Output 6 Explanation  $n = 5$   $arr = [5, 1, 3, 7, 3]$  If arr is rearranged as  $arr' = [1, 3, 3, 5, 7]$ , the differences are minimized. The final answer is  $|1 - 3| + |3 - 3| + |3 - 5| + |5 - 7| = 6$ . Sample Case 1 Sample Input For Custom Testing STDIN Function ----- 2  $\rightarrow$  arr[] size  $n = 2$  3  $\rightarrow$  arr[] = [3, 2] 2 Sample Output 1 Explanation  $n = 2$   $arr = [3, 2]$  There is no need to rearrange because there are only two elements. The final answer is  $|3 - 2| = 1$ .

```

8  int minDiff(int arr_count, int* arr)
9  {
10
11     for(int i=0;i<arr_count-1;i++){
12         for(int j=i+1;j<arr_count;j++){
13             if(arr[i]>arr[j]){
14                 int temp=arr[i];
15                 arr[i]=arr[j];
16                 arr[j]=temp;
17             }
18         }
19     }
20     int sum=0;
21
22     for(int i=0;i<arr_count-1;i++){
23         sum+=arr[i+1]-arr[i];
24     }
25
26     return sum;
27 }
28

```

	Test	Expected	Got	
✓	int arr[] = {5, 1, 3, 7, 3}; printf("%d", minDiff(5, arr))	6	6	✓

Passed all tests! ✓