

Student 32 **ROHIT KUMAR SEKAR** 19238223494

4 / 4 submitted

Q1. ARRAYS

CODE

```
#include<stdio.h>
int main (){
    int n,a[100],i,j=0;
    scanf("%d",&n);
    for(i=0;i<n;i++){
        scanf("%d",&a[i]);
    }
    for(i=0;i<n;i++){
        if(a[i]!=0)
            printf("%d ",a[i]);
    }
    for(i=0;i<n;i++){
        if(a[i]==0)
            printf("0 ");
    }
    return 0;
}
```

INPUT

```
4
0 1 3 0 0 2
```

OUTPUT

(no output)

Q2. ARRAYS

CODE

```
#include<stdio.h>
int main(){
    int a[100],n,i,j,c;
    scanf("%d",&n);
    for(i=0;i<n;i++){
        scanf("%d",&a[i]);
    }
    for(i=0;i<n;i++){
        c=1;
        if(a[i]==-1) continue;
        for(j=i+1;j<n;j++){
            if(a[i]==a[j]){
                c++;
                a[j]=-1;
            }
        }
        printf("%d\t\t\t\t\t",a[i],c);
    }
    return 0;
}
```

INPUT

```
5
2 2 5 1 3
```

OUTPUT

(no output)

Q3. ARRAYS

CODE

```
#include<stdio.h>
int main(){
    int a[100],n,i,last;
    scanf("%d",&n);
    for(i=0;i<n;i++){
        scanf("%d",&a[i]);
        last=a[i-1];
        for(j=n-1;j>0;j--){
            a[j]=a[j-1];
        }
        a[0]=last;
        for (i=0; i<n; i++)
            printf("%d ",a[i]);
    }
    return 0;
}
```

INPUT

```
5
1 2 3 4 5
```

OUTPUT

(no output)

Q4. ARRAYS

CODE

```
#include<stdio.h>
int main (){
    int n,a[3][3],i,j;
    scanf("%d",&n);
    for(i=0;i<n;i++){
        for(j=0;j<n;j++){
            scanf("%d",&a[i][j]);
        }
        for(j=0;j<n;j++){
            for(i=n-1;i>0;i--){
                printf("%d ",a[i][j]);
            }
            printf("\n");
        }
    }
    return 0;
}
```

INPUT

```
3
1 2 3
4 5 6
7 8 9
```

OUTPUT

(no output)