



Cu		Thk. Cu Foil	
Layer	(mils)	t(oz)	
1	2.70	2 oz	
2	2.70	2 oz	
Layers		Drill Type	
1 - 2		PTH	
		Via Fill	
		--	
TOTAL 62 MILS +/-10% thickness board			


DRILL CHART: TOP to BOTTOM				
ALL UNITS ARE IN MILS				
FIGURE	SIZE	TOLERANCE	PLATED	QTY
•	12.0	+3.0/-10.0	PLATED	365
⊙	20.0	+3.0/-3.0	PLATED	21
•	40.0	+3.0/-3.0	PLATED	6
⊙	63.0	+3.0/-3.0	PLATED	4
⊙	150.0	+3.0/-3.0	PLATED	4



NOTES:

- Specifications.
 - Fabricate IAW IPC600, latest revision.
 - Producibility study - It is the responsibility of the supplier to conduct a thorough review of the artwork and media for manufacturability in the supplier's process compliance to all applicable specifications. Customer must be advised in writing (in advance of manufacturing) of any changes, revisions, or corrections made or recommendations to ensure conformance to standards, and of any specifications that cannot be met.
 - This drawing is to be used in conjunction with the provided gerber and drill data when applicable.
 - All notes are "Unless Otherwise Specified."
- Material.
 - FR406.
 - Color to be opaque.
- Soldermask
Solder mask both sides with (green color) liquid photoimageable soldermask, 003 max. thickness.
Soldermask over bare copper.
Soldermask is allowed in via holes.
- Drilling
 - All hole diameters are finished sizes.
 - All hole to be +/- .003 from true position unless otherwise specified.
 - All hole diameters to be +/- .003 unless otherwise specified.
 - An NC drill file has been supplied - see drill table.
- Finish
 - Plate thru with copper .0010 min to .002 max. thickness drill size dimension apply after plating.
 - Use gold immersion over nickel.
 - Finished boards shall not have nicks, scratches, voids, exposed copper, poor plating, all misdrilled holes.
- Silkscreen
 - Silkscreen using white non-conductive epoxy or equivalent (both sides).
 - No silkscreen allowed on exposed lands.
 - Silkscreen must be a minimum of 3mm away from fiducial marks.
 - Minimum clearance between silkscreen legend and vias, pads, or holes to be .005.
 - Silkscreen is allowed in via holes.
- Electrical Test
 - All boards shall be 100% electrically tested for opens/short at 10 volts. MIL-SPEC boards to be tested at 40 volts.
 - Apply test stamp in non-legend area on solder side of PCB.
 - Test is required on both sides of the board.
- Cleanliness
 - Boards shall be free of fiber glass dust or any other foreign material.
 - Finished boards must conform to 0.01 MG/IN max NaCl ionic contamination as measured by the omega meter 600SMD.
- Packaging
There shall be a max of 25 units per package, individually wrapped, and shipped in cardboard cratons with sufficient surrounding material to prevent shipping damage.
- Bow and Twist
Bow and twist to be .007 IN/IN or .090 max according to IPC-A-600D.
- Inspection
 - Automatic optical inspection of all layers required.
 - The impedance should be controlled by stackup layer.
- Inside corners should be rounded-off
- Changes to board geometries and apertures are not allowed unless they are approved by customer.
- Rounding is allowed on 90 degree corners with the size of standard routing bit.

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED

	FAB DRAWING		COMPANY NAME: ROHM SEMICONDUCTOR USA		UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES	
	DESIGNER: PTHBC		PROJECT NAME: BU90005GWZ-E2EVK-101		TOLERANCES	
	CHECKER: INITIAL		FAB NUMBER: NUMBER		DECIMALS ANGLES F.2-1 0.00 F.3-4 0.005 F.5-6 0.005	
	DATE: 2014-02-12		REV. 00		SHEET: 1 OF 2	
	100					