

保定华联领世科技有限公司

Baoding Hualian Top Technology Co.,Ltd

Add:Dazhuze Village,Fuchang Township,Jingxiu District,Baoding City,China

Tel: 86-312-8918666

Fax:86-312-3263555

Methyl Hydroxyethyl cellulose (MHEC)

CAS NO.:9032-42-2

Introduction:

Methyl Hydroxyethyl cellulose (MHEC) is widely used in waterborne latex coatings, construction and building materials, printing ink, oil drilling and other aspects, play a role in thickening and water retention, improve the construction performance, used in dry and wet mortar products.

Specification:

Chemical Name Hydroxyethyl Cellulose

Appearance White or off-white powder

Moisture Content $\leq 5\%$

Ash Content $\leq 5\%$

Gel Temp 60-90°C

PH value 5-9

Viscosity 400-200,000 mPa.s (NDJ-1, 2% solution, 20°C)

Application:

1. Pharmaceutical is used as hydrophilic gel skeleton material, pore-forming agent and coating agent for preparing sustained-release preparations. It can also be used as thickening, suspension, dispersing, bonding, emulsifying, film forming and water retaining agent.
2. Food processing can also be used as, bonding, emulsification, film forming, thickening, suspension, dispersion, water retention agent, etc.
3. Used as additives for toothpaste, cosmetics, detergents and so on in daily chemical industry.
4. Used as cement, gypsum, lime of the gelling agent, water-retaining agent, is the fine powder building materials admixture.

保定华联领世科技有限公司

Baoding Hualian Top Technology Co.,Ltd

Add:Dazhuze Village,Fuchang Township,Jingxiu District,Baoding City,China

Tel: 86-312-8918666

Fax:86-312-3263555

5. Hydroxyethylmethyl cellulose is widely used as an excipient for pharmaceutical preparations, including oral tablets, suspensions, and topical preparations.

It has similar properties to methyl cellulose, but the presence of hydroxyethyl makes it more water-soluble in water, more compatible with salt, and has a higher condensation temperature.

Package & Storage:

Packaged by 25kgs per bag,12Tons with pallet/20'FCL;14Tons without pallet/20'FCL;

Below 30℃,in a dry cool place,avoid long time high pressure storage,please seal the unspent powder,avoid damp and exposure to air.