



JINJI CHEMICAL

MHEC/HEMC

Technical Data Sheet

Methyl Hydroxyethyl Cellulose (MHEC), also named as HEMC, is a nonionic natural polymer derived from refined cotton linter. It provides many of the same benefits as other cellulose derivatives, such as efficiently thickening and highly water retention. However, it has the characteristics of dissolving faster and having better dispersibility than other celluloses. MHEC has excellent performance in various mortars, putties and tile adhesives which use the cement, gypsum, lime, as the main cementitious materials.

General Information:

Trade Name: **Methyl Hydroxyethyl Cellulose / Hydroxyethyl Methyl Cellulose**

Cas No.: 9032-42-2

Properties:

Appearance: White or Off White Powder

Content of Hydroxyethyl: 4%-12%

Content of Methoxy: 21%-31%

Moisture: ≤5%

PH Value: 6.0-8.0

Temperature of Gelation: 75°C -90°C

Viscosity (NDJ 2% Solution, 20°C): 180,000-200,000 Mpas

Viscosity (Brookfield 2% Solution, 25°C): 75,000-85,000 Mpas

Water Retention: 95%-98%



JINJI CHEMICAL

Performance:

- ✓ Good thickening performance and improve the viscosity and anti-sagging performance.
- ✓ Highly Water Retention and reduce cracking.
- ✓ Good construction performance and extend the open time.
- ✓ Good leveling, Distributed evenly, Suspending, Easy workability.

Application:

Skim Coat: Wall Putty, Gypsum plaster

Adhesive mortar: Tile adhesive, Tile grout

Masonry mortar: Blocks Jointing mortar, Panel Jointing mortars

Plastering mortar: Interior wall plastering mortar, External wall plastering mortar, Spray mortar

Flooring mortar: Self-leveling mortar

Thermal insulation mortar: ETIFS and ETICS mortar

Waterproof mortar

Dry-mixed concrete

Packaging:

25kg/bag inner with PE bags

Storage and Handling:

Should be stored in dry and cool environment

Storage under pressure should also be avoided

It's recommended to use within 2 years, storage in high humidity and temperature will increase the risk of blocking

Do not stack pallets on top of each other

Practice care and caution to avoid explosive conditions