

Technical Data Sheet

Introduction

METHYL HYDROXYETHYL CELLULOSE

MHEC is a nonionic cellulose ether that provides many of the same benefits as other methyl cellulose derivatives, such as the ability to efficiently thicken and provide water retention. MHEC is mainly used for water retention agents, thickeners, suspending agents, stabilizers, and emulsifier. MHEC has excellent performance in water-based paints and construction industries.

Application

- ✧ Wall putty/Skim coat
- ✧ Tile adhesive/Tile grouts
- ✧ Dry mixed mortar
- ✧ EIFS & ETICS mortar
- ✧ Plaster for gypsum board base
- ✧ Cement-based structural plaster.

Properties

Content of Hydroxyethyl	4%-12%
Content of Methoxy	21%-31%
Ash Content	≤2.5%
Moisture	≤5%
PH Value	5.5-8.5
Temperature of Gelation	60℃ -75℃
Viscosity※	50,000-200,000※
Water Retention	95% - 98%

Packing and Storage

- ✧ Standard packing: 25kg/bag inner with PE bags
- ✧ Should be stored in dry and cool environment
- ✧ It's recommended to use within 2 years.
- ✧ Storage under pressure should also be avoided
- ✧ Do not stack pallets on top of each other
- ✧ Practice care and caution to avoid explosive conditions