

HL-4050

Technical Data Sheet

Introduction

Redispersible polymer powder

HL-4050 is a kind of co-polymer powder of vinyl acetate and ethylene. Which manufactured from the latex by spray-drying process.

It have high flexibility, venerability, good resistance to saponification and durability; It can improve water retention, flexural strength, tensile strength and abrasion resistance.

Application

HL-4050 is the type that we introduction of foreign technology and raw material. Given good flowability and application property, improve the cohesion, impact resistance, abrasion resistance and weatherability of mortar.

Improve sealability, anti-permeability and bonding strength of mortar obviously.

Increase the flexibility and waterproofness of exterior wall putty.

Recommend main usage

Interior and exterior wall putty
Exterior insulation series mortar
Gypsum based products
Tile adhesive

Properties

Appearance	White powder, free-flowing
Based polymer	VAC/E
Ash Content	13±2%
Solid content	98-100%
Bulk Density	400-600g/L
Average particle size	80-120
PH Value	6-8
MFFT	≤5℃
Tg	16±2℃

Packaging & Storage

25kg multilayer paper bags with polyethylene intermediate layer. Keep it in cool, dry place avoiding direct sunshine.

To avoid caking, HL-4050 redispersible polymer powder is recommended stacked bags, storage time should not exceed SIX months.

Contact information

The product specification information is based on our present state of knowledge and provide general notes on our products and application. It should therefore not be construed as guaranteeing specific properties of the products of their suitability for specific application. This product specification is not signed, Users are advised to make their own tests to determine the safety and suitability of each such product or product combination for their own purposes. If you have any questions, please contact our R&D center of sales people from