



Context-Free Grammar: Definition

- A context-free grammar $G=(V,T,P,S)$, where:
 - V : set of variables or non-terminals
 - T : set of terminals (= alphabet $\cup \{\epsilon\}$)
 - P : set of *productions*, each of which is of the form
 $V \Rightarrow \alpha_1 \mid \alpha_2 \mid \dots$
 - Where each α_i is an arbitrary string of variables and terminals
 - $S \Rightarrow$ start variable

CFG for the language of binary palindromes:

$G=(\{A\},\{0,1\},P,A)$

$P: A \Rightarrow 0 A 0 \mid 1 A 1 \mid 0 \mid 1 \mid \epsilon$



More examples

- Parenthesis matching in code
- Syntax checking
- In scenarios where there is a general need for:
 - Matching a symbol with another symbol, or
 - Matching a count of one symbol with that of another symbol, or
 - Recursively substituting one symbol with a string of other symbols



Example #2

- Language of balanced paranthesis
e.g., $()(((())))((()))\dots$
- CFG?

$\begin{array}{l} \underline{G}: \\ S \Rightarrow (S) \mid SS \mid \varepsilon \end{array}$

How would you “interpret” the string “ $(((()))())$ ” using this grammar?



Example #3

- A grammar for $L = \{0^m 1^n \mid m \geq n\}$

- CFG?

G:
 $S \Rightarrow 0S1 \mid A$
 $A \Rightarrow 0A \mid \varepsilon$

How would you interpret the string “00000111”
using this grammar?



More examples

- $L_1 = \{0^n \mid n \geq 0\}$
- $L_2 = \{0^n \mid n \geq 1\}$
- $L_3 = \{0^i 1^j 2^k \mid i=j \text{ or } j=k, \text{ where } i, j, k \geq 0\}$
- $L_4 = \{0^i 1^j 2^k \mid i=j \text{ or } i=k, \text{ where } i, j, k \geq 1\}$




Applications of CFLs & CFGs

- Compilers use parsers for syntactic checking
- Parsers can be expressed as CFGs
 1. Balancing paranthesis:
 - $B \Rightarrow BB \mid (B) \mid \textit{Statement}$
 - $\textit{Statement} \Rightarrow \dots$
 2. If-then-else:
 - $S \Rightarrow SS \mid \textit{if Condition then Statement else Statement} \mid \textit{if Condition then Statement} \mid \textit{Statement}$
 - $\textit{Condition} \Rightarrow \dots$
 - $\textit{Statement} \Rightarrow \dots$
 3. C paranthesis matching { ... }
 4. Pascal *begin-end* matching
 5. YACC (Yet Another Compiler-Compiler)




Structure of a production



The above is same as:

1. $A \Longrightarrow \alpha_1$
2. $A \Longrightarrow \alpha_2$
3. $A \Longrightarrow \alpha_3$
- ...
- K. $A \Longrightarrow \alpha_k$



CFG conventions

- Terminal symbols $\leq a, b, c \dots$
- Non-terminal symbols $\leq A, B, C, \dots$
- Terminal or non-terminal symbols $\leq X, Y, Z$
- Terminal strings $\leq w, x, y, z$
- Arbitrary strings of terminals and non-terminals $\leq \alpha, \beta, \gamma, \dots$

String membership

How to say if a string belong to the language defined by a CFG?

1. Derivation
 - Head to body
2. Recursive inference
 - Body to head

Both are equivalent forms

Example:

- $w = 01110$
- Is w a palindrome?

G:
 $A \Rightarrow 0A0 \mid 1A1 \mid 0 \mid 1 \mid \varepsilon$

$A \Rightarrow 0A0$
 $\Rightarrow 01A10$
 $\Rightarrow 01110$



Simple Expressions...

- We can write a CFG for accepting simple expressions
- $G = (V, T, P, S)$
 - $V = \{E, F\}$
 - $T = \{0, 1, a, b, +, *, (,)\}$
 - $S = \{E\}$
 - P :
 - $E \Rightarrow E + E \mid E * E \mid (E) \mid F$
 - $F \Rightarrow aF \mid bF \mid 0F \mid 1F \mid a \mid b \mid 0 \mid 1$



Generalization of derivation

- Derivation is *head* \Rightarrow *body*
- $A \Rightarrow X$ (A derives X in a single step)
- $A \Rightarrow_G^* X$ (A derives X in a multiple steps)
- Transitivity:
IF $A \Rightarrow_G^* B$, and $B \Rightarrow_G^* C$, THEN $A \Rightarrow_G^* C$



Context-Free Language

- The language of a CFG, $G=(V,T,P,S)$, denoted by $L(G)$, is the set of terminal strings that have a derivation from the start variable S .
 - $L(G) = \{ w \text{ in } T^* \mid S \Rightarrow^*_G w \}$

Left-most & Right-most Derivation Styles

G:

$E \Rightarrow E + E \mid E * E \mid (E) \mid F$

$F \Rightarrow aF \mid bF \mid 0F \mid 1F \mid \varepsilon$

Derive the string $a^*(ab+10)$ from G:

$E \stackrel{*}{\Rightarrow}_G a^*(ab+10)$

Left-most
derivation:

Always
substitute
leftmost
variable

$\begin{aligned}
 & \blacksquare E \\
 & \blacksquare \Rightarrow E * E \\
 & \blacksquare \Rightarrow F * E \\
 & \blacksquare \Rightarrow a * E \\
 & \blacksquare \Rightarrow a * (E) \\
 & \blacksquare \Rightarrow a * (E + E) \\
 & \blacksquare \Rightarrow a * (F + E) \\
 & \blacksquare \Rightarrow a * (aF + E) \\
 & \blacksquare \Rightarrow a * (abF + E) \\
 & \blacksquare \Rightarrow a * (ab + E) \\
 & \blacksquare \Rightarrow a * (ab + F) \\
 & \blacksquare \Rightarrow a * (ab + 1F) \\
 & \blacksquare \Rightarrow a * (ab + 10F) \\
 & \blacksquare \Rightarrow a * (ab + 10)
 \end{aligned}$

Right-most
derivation:

Always
substitute
rightmost
variable

$\begin{aligned}
 & \blacksquare E \\
 & \blacksquare \Rightarrow E * E \\
 & \blacksquare \Rightarrow E * (E) \\
 & \blacksquare \Rightarrow E * (E + E) \\
 & \blacksquare \Rightarrow E * (E + F) \\
 & \blacksquare \Rightarrow E * (E + 1F) \\
 & \blacksquare \Rightarrow E * (E + 10F) \\
 & \blacksquare \Rightarrow E * (E + 10) \\
 & \blacksquare \Rightarrow E * (F + 10) \\
 & \blacksquare \Rightarrow E * (aF + 10) \\
 & \blacksquare \Rightarrow E * (abF + 0) \\
 & \blacksquare \Rightarrow E * (ab + 10) \\
 & \blacksquare \Rightarrow F * (ab + 10) \\
 & \blacksquare \Rightarrow aF * (ab + 10) \\
 & \blacksquare \Rightarrow a * (ab + 10)
 \end{aligned}$



Leftmost vs. Rightmost derivations

Q1) For every leftmost derivation, there is a rightmost derivation, and vice versa. True or False?

True - will use parse trees to prove this

Q2) Does every word generated by a CFG have a leftmost and a rightmost derivation?

Yes – easy to prove (reverse direction)

Q3) Could there be words which have more than one leftmost (or rightmost) derivation?

Yes – depending on the grammar




Parse trees


Parse Trees

- Each CFG can be represented using a *parse tree*:
 - Each internal node is labeled by a variable in V
 - Each leaf is terminal symbol
 - For a production, $A \Rightarrow X_1 X_2 \dots X_k$, then any internal node labeled A has k children which are labeled from X_1, X_2, \dots, X_k from left to right

Parse tree for production and all other subsequent productions:



Examples




Parse tree for $a + 1$

G:

$E \Rightarrow E + E \mid E * E \mid (E) \mid F$

$F \Rightarrow aF \mid bF \mid 0F \mid 1F \mid 0 \mid 1 \mid a \mid b$

Recursive inference





Parse tree for 0110

Derivation

G:


$A \Rightarrow 0A0 \mid 1A1 \mid 0 \mid 1 \mid \epsilon$

Parse Trees, Derivations, and Recursive Inferences




Interchangeability of different CFG representations

- Parse tree \Rightarrow left-most derivation
 - DFS left to right
- Parse tree \Rightarrow right-most derivation
 - DFS right to left
- \Rightarrow left-most derivation \equiv right-most derivation
- Derivation \Rightarrow Recursive inference
 - Reverse the order of productions
- Recursive inference \Rightarrow Parse trees
 - bottom-up traversal of parse tree



Connection between CFLs and RLs



What kind of grammars result for regular languages?



CFLs & Regular Languages


- A CFG is said to be *right-linear* if all the productions are one of the following two forms: $A \Rightarrow wB$ (or) $A \Rightarrow w$

Where:


- A & B are variables,
- w is a string of terminals

- Theorem 1: Every right-linear CFG generates a regular language
- Theorem 2: Every regular language has a right-linear grammar
- Theorem 3: Left-linear CFGs also represent RLs

Some Examples



Right linear CFG?



Right linear CFG?

➤ $A \Rightarrow 01B \mid C$
 $B \Rightarrow 11B \mid 0C \mid 1A$
 $C \Rightarrow 1A \mid 0 \mid 1$

Finite Automaton?



Ambiguity in CFGs and CFLs



Ambiguity in CFGs

- A CFG is said to be *ambiguous* if there exists a string which has more than one left-most derivation

Example:

$S \Rightarrow AS \mid \varepsilon$

$A \Rightarrow A1 \mid 0A1 \mid 01$

Input string: 00111

Can be derived in two ways

LM derivation #1:

$S \Rightarrow AS$

$\Rightarrow 0A1S$

$\Rightarrow 0A11S$

$\Rightarrow 00111S$

$\Rightarrow 00111$

LM derivation #2:


$S \Rightarrow AS$

$\Rightarrow A1S$

$\Rightarrow 0A11S$

$\Rightarrow 00111S$

$\Rightarrow 00111$



Why does ambiguity matter?


$E \Rightarrow E + E \mid E * E \mid (E) \mid a \mid b \mid c \mid 0 \mid 1$

Values are
different !!!

string = $a * b + c$

• LM derivation #1:


$E \Rightarrow E + E \Rightarrow E * E + E$
 $\Rightarrow^* a * b + c$



$(a*b)+c$

• LM derivation #2

$E \Rightarrow E * E \Rightarrow a * E \Rightarrow$
 $a * E + E \Rightarrow^* a * b + c$



$a*(b+c)$

The calculated value depends on which
of the two parse trees is actually used.



Removing Ambiguity in Expression Evaluations

- It MAY be possible to remove ambiguity for some CFLs
 - E.g., in a CFG for expression evaluation by imposing rules & restrictions such as precedence
 - This would imply rewrite of the grammar

Modified unambiguous version:

- Precedence: $()$, $*$, $+$

$$\begin{aligned} E &\Rightarrow E + T \mid T \\ T &\Rightarrow T * F \mid F \\ F &\Rightarrow I \mid (E) \\ I &\Rightarrow a \mid b \mid c \mid 0 \mid 1 \end{aligned}$$

Ambiguous version:

$$E \Rightarrow E + E \mid E * E \mid (E) \mid a \mid b \mid c \mid 0 \mid 1$$

How will this avoid ambiguity?



Inherently Ambiguous CFLs

- However, for some languages, it may not be possible to remove ambiguity
- A CFL is said to be *inherently ambiguous* if every CFG that describes it is ambiguous

Example:

- $L = \{ a^n b^n c^m d^m \mid n, m \geq 1 \} \cup \{ a^n b^m c^m d^n \mid n, m \geq 1 \}$
- L is inherently ambiguous
- Why?

Input string: $a^n b^n c^n d^n$



Summary

- Context-free grammars
- Context-free languages
- Productions, derivations, recursive inference, parse trees
- Left-most & right-most derivations
- Ambiguous grammars
- Removing ambiguity
- CFL/CFG applications
 - parsers, markup languages