

# **Festive Feather Holiday Lights**

Created by Tony DiCola



Last updated on 2015-12-22 03:10:16 PM EST

## **Guide Contents**

Guide Contents	2
Overview	3
Color Sensing Lights	5
Parts	5
Wiring	6
Sketch	7
Bluetooth Low Energy Lights	10
Parts	10
Wiring	11
Sketch	11

### Overview

Spice up your holiday decorations using Adafruit's Feather boards (http://adafru.it/keK) to add interactivity in a tiny package. Feathers are little Arduino-compatible microcontrollers that give you all the functionality of a full-size Arduino in a much smaller and battery-friendly package.

You can put a Feather into almost any project, like these festive holiday lights that animate and change color at your command. The 32u4 Feather (http://adafru.it/keL) combined with a color (http://adafru.it/keM) and proximity (http://adafru.it/keN) sensor lets you change the color of holiday lights by holding up a brightly colored object to them. The Bluefruit LE Feather (http://adafru.it/keO) lets you change the color of lights using a smartphone or tablet and the Bluefruit LE app. Your holiday decorations will be full of joy with Adafruit's Feathers!



To build these projects you'll want to be familiar with the basics of Arduino. Check out these guides for some background information:


- Learn Arduino Series (http://adafru.it/ja3)
- Adafruit Arduino IDE Setup (http://adafru.it/jAc)

You'll also need to do a little bit of soldering to assemble Feather boards. If you're new to soldering be sure to see the guide to excellent soldering (http://adafru.it/dxy).

Finally for Bluetooth Low Energy it will help to skim these guides for some background information:

- Introduction to Bluetooth Low Energy (http://adafru.it/iCS)
- Bluefruit LE Connect for iOS (http://adafru.it/iCm)

# Color Sensing Lights



These holiday lights change their color when you hold an object up to them. A proximity sensor detects when an object is near, and a color sensor detects the object's color so the lights can change to match it--like a chameleon!

#### **Parts**

To build these lights you'll need the following parts:

- 32u4 Feather (http://adafru.it/keL)
- VCNL4010 Proximity Sensor (http://adafru.it/466)
- TCS34725 Color Sensor (http://adafru.it/1334)
- NeoPixels (http://adafru.it/dYn)
  - You can use a strip, ring, matrix, or even bare pixels. Just make sure your power supply can handle all the pixels you intend to use!

#### 5V Power Supply

I recommend the 5 volt 10 amp supply (http://adafru.it/eCD) as it can handle lighting
up to about 150 NeoPixels. Remember each pixel can take up to 60mA alone! Also a
DC power jack terminal adapter (http://adafru.it/368) makes it easy to connect a power

supply to the circuit.


 Breadboard (http://adafru.it/keP), jumper wires (http://adafru.it/fE2), and soldering tools (http://adafru.it/fE3).

# Wiring

First follow the guide for each component to assemble and test it:

- Adafruit 32u4 Feather Guide (http://adafru.it/keQ)
- Adafruit TCS34725 Color Sensor Guide (http://adafru.it/keR)
- Adafruit VCNL4010 Product Page (http://adafru.it/466)

Then wire up the components as shown below:



Connect power supply ground to 32u4 Feather ground, TCS34725 ground, VCNL4010 ground, and NeoPixel ground.

- Connect power supply 5V to 32u4 Feather USB pin, TCS34725 VDD pin, VCNL4010 VIN pin, and NeoPixel +5V.
- Connect 32u4 Feather SCL to TCS34725 SCL, VCNL4010 SCL.
- Connect 32u4 Feather SDA to TCS34725 SDA, VCNL4010 SDA.
- Connect 32u4 Feather pin 5 to TCS34725 LED pin.
- Connect 32u4 Feather pin 6 to NeoPlxel signal input (Din).

### Sketch

Before loading the sketch make sure you have the following libraries installed. Remember you can use the Arduino library manager (http://adafru.it/fCN) to easily search for and install them:


- Adafruit TCS34725 Library (http://adafru.it/cb1)
- Adafruit NeoPixel Library (http://adafru.it/aZU)

Next download the sketch from its home on GitHub (http://adafru.it/keS) by clicking the button below:

**Download Sketches** 

http://adafru.it/keT

Unzip the archive and load the **Feather\_32u4\_Lights** sketch in the Arduino IDE.



Near the top of the sketch are **#define** values that you can adjust for your light configuration:

- PIXEL\_COUNT Set this to the number of NeoPixels you're using.
- PIXEL\_PIN Set this to the pin connected to the NeoPixel input (pin 6 if you followed the wiring).
- PIXEL\_TYPE Set this to the type of NeoPixel. Use the default unless you know you're
  using a different type of NeoPixel (see the strandtest example in the NeoPixel library for
  more information on types of NeoPixels).
- **ANIMATION\_PERIOD\_MS** This is the amount of time a single animation frame takes (in milliseconds). Adjust this to slow down and speed up the animation.
- TCS\_LED\_PIN Set this to the digitial pin connected to the TCS color sensor LED pin (pin 5 if you followed the wiring).
- PROXIMITY\_THRESHOLD This is the proximity value that's used to consider an object close enough to read its color with the TCS sensor. You can tune this by looking at the serial

monitor output to see the stream of proximity values and adjusting the threshold to be near the values you see when an object is near the sensor.

You can also adjust a part of the code depending on if you're using a VCNL4010 or older VCNL4000 proximity sensor:

// Create VCNL sensor object (defined in this sketch).

// If you're using a VCNL4010 sensor use this line:

Adafruit VCNL4010 vcnl = Adafruit VCNL4010();

// However if you're using a VCNL4000 sensor comment the above line and uncomment this one: //Adafruit\_VCNL4000 vcnl = Adafruit\_VCNL4000();


Make sure only one of the lines above is uncommented, depending on what sensor you're using.

Now load the sketch on your hardware, then open the serial monitor at 115200 baud. You should see proximity measurement values printed continuously to the console.

Move a colored object right above the VCNL and TCS color sensor. If the proximity value crosses the threshold the TCS sensor's LED will turn on and read the color of the object. The sensor will wait about a second for you to remove the object, then the lights will start to animate using the color of the object.

Woo hoo, that's all there is to the 32u4 Feather Color Sensing Holiday Lights project! This project is great for coloring lights on the tree using brightly wrapped gifts.

## Bluetooth Low Energy Lights



These holiday lights can be controlled right from your smartphone or tablet. Just open the Bluefruit LE app and use its color picker to choose the best color for any celebration.

## **Parts**

To build these lights you'll need the following parts:

- Bluefruit LE Feather (http://adafru.it/keO)
- NeoPixels (http://adafru.it/dYn)
  - You can use a strip, ring, matrix, or even bare pixels. Just make sure your power supply can handle all the pixels you intend to use!
- 5V Power Supply
  - I recommend the 5 volt 10 amp supply (http://adafru.it/eCD) as it can handle lighting
    up to about 150 NeoPixels. Remember each pixel can take up to 60mA alone! Also a
    DC power jack terminal adapter (http://adafru.it/368) makes it easy to connect a power
    supply to the circuit.
- Breadboard (http://adafru.it/keP), jumper wires (http://adafru.it/fE2), and soldering


#### tools (http://adafru.it/fE3).

# Wiring

First follow the guide for each component to assemble and test it:

Adafruit Bluefruit LE Feather Guide (http://adafru.it/kcc)

Then wire up the components as shown below:



- Connect power supply ground to Bluefruit LE Feather ground and NeoPixel ground.
- Connect power supply 5V to Bluefruit LE Feather USB pin and NeoPixel +5V.
- Connect Bluefruit LE Feather pin 6 to NeoPlxel signal input (Din).

### Sketch

Before loading the sketch make sure you have the following libraries installed. Remember you can

use the Arduino library manager (http://adafru.it/fCN) to easily search for and install them:


- Adafruit Bluefruit nRF51 (http://adafru.it/f4V)
- Adafruit NeoPixel Library (http://adafru.it/aZU)

Next download the sketch from its home on GitHub (http://adafru.it/keS) by clicking the button below:

#### **Download Sketches**

http://adafru.it/keT

Unzip the archive and load the Feather\_BluefruitLE\_Lights sketch in the Arduino IDE.



Near the top of the sketch are **#define** values that you can adjust to suite your light configuration:

- PIXEL\_COUNT Set this to the number of NeoPixels you're using.
- **PIXEL\_PIN** Set this to the pin connected to the NeoPixel input (pin 6 if you followed the wiring).
- **PIXEL\_TYPE** Set this to the type of NeoPixel. Use the default unless you know you're using a different type of NeoPixel (see the strandtest example in the NeoPixel library for more information on types of NeoPixels).
- **ANIMATION\_PERIOD\_MS** This is the amount of time a single animation frame takes (in milliseconds). Adjust this to slow down and speed up the animation.

Upload the sketch to your hardware and you should see the lights turn on and animate with a red color. Now use the Bluefruit LE app on an iOS (http://adafru.it/iCm) or Android (http://adafru.it/f4G) device and connect to the Bluefruit Feather in **Controller** mode. Use the **Color Picker** to pick a color and **send** it to the Bluefruit--woo hoo, the lights will change color!

Check out the Bluetooth NeoPixel Goggles project (http://adafru.it/keU) for a little more explanation about using the color picker.

That's all there is to the Bluefruit LE Feather holiday light project! Use the color picker on your phone/table to control your holiday lights with ease!

© Adafruit Industries Last Updated: 2015-12-22 03:10:16 PM EST Page 13 of 13