



KMK

Relational Data

Data sets

X

A	B	C
a	t	1
b	u	2
c	v	3

Y

E	F	G
a	x	3
b	y	2
d	z	1

`left_join(X,Y, join = c("A"="E"))`

A*	B	C
a	t	1
b	u	2
c	v	3

E*	F	G
a	x	3
b	y	2
d	z	1

A	B	C	F	G
a	t	1	x	3
b	u	2	y	2
c	v	3	NA	NA

`right_join(X,Y, join = c("A"="E"))`

A*	B	C
a	t	1
b	u	2
c	v	3

E*	F	G
a	x	3
b	y	2
d	z	1

A*	B	C	F	G
a	t	1	x	3
b	u	2	y	2
d	NA	NA	z	1

`inner_join(X,Y, join = c("A"="E"))`

A*	B	C
a	t	1
b	u	2
c	v	3

E*	F	G
a	x	3
b	y	2
d	z	1

A*	B	C	F	G
a	t	1	x	3
b	u	2	y	2

`full_join(X,Y, join = c("A"="E"))`

A*	B	C
a	t	1
b	u	2
c	v	3

E*	F	G
a	x	3
b	y	2
d	z	1

A*	B	C	F	G
a	t	1	x	3
b	u	2	y	2
c	v	3	NA	NA
d	NA	NA	z	1

`semi_join(X,Y, join = c("A"="E"))`

A*	B	C
a	t	1
b	u	2
c	v	3

E*	F	G
a	x	3
b	y	2
d	z	1

A*	B	C
a	t	1
b	u	2

anti_join(X,Y, join = c("A"="E"))

A*	B	C
a	t	1
b	u	2
c	v	3

E*	F	G
a	x	3
b	y	2
d	z	1

A*	B	C
c	v	3