



## Data Analysis & Visualisation

CSC3062

BEng (CS & SE), MEng (CS & SE), BIT & CIT

Dr Reza Rafiee

Semester 1 - 2019/2020



### This is R



### This is R


```
# Start
# Clustering 450K methylation CpGs probes written by Dr Reza Rafiee
# Research Associate, Northern Institute for Cancer Research, Newcastle University
# This script loads 20,000 methylation probes (from 450K methylation profiling) and doing clustering analysis
library(mclust) # Gaussian Mixture Modelling package for Model-Based Clustering, Classification, and Density Estimation
library(scatterplot3d)
library(pheatmap)
library(apcluster) # Affinity Propagation Clustering
load("~/20KBetaValues 51InfantSHH.RData")
                                    # 20,000 probes
length(colnames(BetaValues_51Samples_20K)) # n=51
# Performs a principal components analysis on the given data matrix and returns the results as an object of class prcomp
PCA_Comp_Scaled_Centered <- prcomp(t(BetaValues_51Samples_20K), center = TRUE, scale=T) # scale =T is appropriate for high-dimens
summary(PCA Comp Scaled Centered)
```

### This is R

# The language of data science



### R ranking




### Ranking

- Survey of data mining experts
- R is first
- 50% more use than Python



### R ranking



### Ranking

- Survey of data mining experts
- R is first
- 50% more use than Python

### Free & open source

### Vector operations

### Great community

9000+
packages



### R Programming – general properties

- An open source programming language freely available under the GNU public license (written in primarily C and Fortran). It's an interpreted language.
- A powerful tool to work with data (statistical computing and data analysis).
- Highly extensible through the use of user-submitted packages for specific functions or specific areas of study.
- Including thousands of packages, designed, maintained, and widely used by data scientist and statisticians.
- Advanced users can write C, C++, Java, .NET or Python code to manipulate R objects directly.
- Portable and works equally well on Windows, Linux, Mac OS.
- R has stronger **object-oriented programming facilities** than most statistical computing languages.
- Writing and running R scripts could be either in
  - The command line interface or a Graphical User Interface called RStudio.





### R Programming; R packages

- A great advantage to the open source nature of R is that users have contributed a huge number of packages for solving a vast majority of data analysis problems.
- For example, there are packages specifically directed to visualise data, non-parametric statistics, signal processing, bioinformatics and so on.
- Two steps to use any packages.
  - First, they must be installed on your system, and this is an one-time step.
  - Second, once a package is installed, it **must be loaded** by calling the *library()* function with the name of the library as an argument.
- Some examples of using installed packages in R:
  - library(NMF) # Nonnegative Matrix Factorization (Algorithms and Framework) package
  - library(mclust) # Gaussian Mixture Modelling package for Model-Based Clustering, Classification, and Density Estimation
  - library(shiny) # Web Application Framework for R
- CRAN (The Comprehensive R Archive Network)
  - https://cran.r-project.org/



RGui (64-bit)

### R Programming; The command line interface

### The command line interface



- 🗇 ×






```
File Edit View Misc Packages Windows Help
R Console
 R version 3.6.1 (2019-07-05) -- "Action of the Toes"
 Copyright (C) 2019 The R Foundation for Statistical Computing
 Platform: x86 64-w64-mingw32/x64 (64-bit)
 R is free software and comes with ABSOLUTELY NO WARRANTY.
 You are welcome to redistribute it under certain conditions.
 Type 'license()' or 'licence()' for distribution details.
  Natural language support but running in an English locale
 R is a collaborative project with many contributors.
 Type 'contributors()' for more information and
 'citation()' on how to cite R or R packages in publications.
 Type 'demo()' for some demos, 'help()' for on-line help, or
 'help.start()' for an HTML browser interface to help.
 Type 'q()' to quit R.
```




- The command line interface
- To clear the console: CTRL + Enter





- The command line interface
- To clear the console: CTRL + Enter




- The command line interface
- To clear the console: CTRL + Enter





- The command line interface
- To clear the console: **CTRL** + **Enter**





- The command line interface
- R is a case-sensitive language (similar to Unix/Linux)

> <a href="Print">Print("Welcome to Data Analysis and visualisation module!")</a>
Error in Print("Welcome to Data Analysis and visualisation module!"):

could not find function "Print"

>




### R Programming; help.start() command

The command line interface

print() is an R function

R is a case-sensitive language (similar to Unix/Linux)






### R Programming; help.start() command

- The command line interface
- R is a case-sensitive language (similar to Unix/Linux)


- print() is an R function
- help.start()





### R Programming; RStudio

### RStudio







**Environment** 



### How to install R & RStudio

- R refers to a software environment that comes with a GUI (Graphical User Interface). R GUI looks more similar to the old DOS console than to SPSS or Stata.
  - For different OS (Linux, Win or Mac, etc. users): <a href="https://cran.r-project.org/">https://cran.r-project.org/</a>
- RStudio is an IDE (Integrated Development Environment) that makes R easier to use. It includes a code editor, debugging and visualization tools.
  - For different platforms: <a href="https://rstudio.com/products/rstudio/download/">https://rstudio.com/products/rstudio/download/</a>
- To download and install R and RStudio (Win or Mac)
  - Step by step: ttps://courses.edx.org/courses/UTAustinX/UT.7.01x/3T2014/56c5437b88fa43cf828bff5371c6a924/

### R Programming; R-object

- In contrast to other programming languages like C and java, the variables in R are not declared as some data type. The variables are assigned with R-Objects and the data type of the R-object becomes the data type of the variable. There are many types of R-objects.
- The frequently used R-Objects:
  - Vectors
  - Lists
  - Matrices
  - Arrays
  - Factors
  - Data Frames