



# Data Analysis & Visualisation

**CSC3062**

**BEng (CS & SE), MEng (CS & SE), BIT & CIT**

**Dr Reza Rafiee**

**Semester 1 – 2019/2020**



**QUEEN'S  
UNIVERSITY  
BELFAST**

SCHOOL OF  
ELECTRONICS,  
ELECTRICAL  
ENGINEERING AND  
COMPUTER SCIENCE

# This is R





QUEEN'S  
UNIVERSITY  
BELFAST

SCHOOL OF  
ELECTRONICS,  
ELECTRICAL  
ENGINEERING AND  
COMPUTER SCIENCE

# R Programming; Revision

# Revision



# R Programming; Review

## Base R Cheat Sheet

### Getting Help

#### Accessing the help files

##### ?mean

Get help of a particular function.

**help.search('weighted mean')**

Search the help files for a word or phrase.

**help(package = 'dplyr')**

Find help for a package.

#### More about an object

##### str(iris)

Get a summary of an object's structure.

##### class(iris)

Find the class an object belongs to.

### Using Libraries

##### install.packages('dplyr')

Download and install a package from CRAN.

##### library(dplyr)

Load the package into the session, making all its functions available to use.

##### dplyr::select

Use a particular function from a package.

##### data(iris)

Load a built-in dataset into the environment.

### Working Directory

##### getwd()

Find the current working directory (where inputs are found and outputs are sent).

##### setwd('C://file/path')

Change the current working directory.

**Use projects in RStudio to set the working directory to the folder you are working in.**

### Vectors

#### Creating Vectors

c(2, 4, 6)	2 4 6	Join elements into a vector
2:6	2 3 4 5 6	An integer sequence
seq(2, 3, by=0.5)	2.0 2.5 3.0	A complex sequence
rep(1:2, times=3)	1 2 1 2 1 2	Repeat a vector
rep(1:2, each=3)	1 1 1 2 2 2	Repeat elements of a vector

#### Vector Functions

<b>sort(x)</b>	<b>rev(x)</b>
Return x sorted.	Return x reversed.
<b>table(x)</b>	<b>unique(x)</b>
See counts of values.	See unique values.

#### Selecting Vector Elements

##### By Position

<b>x[4]</b>	The fourth element.
<b>x[-4]</b>	All but the fourth.
<b>x[2:4]</b>	Elements two to four.
<b>x[-(2:4)]</b>	All elements except two to four.
<b>x[c(1, 5)]</b>	Elements one and five.

##### By Value

<b>x[x == 10]</b>	Elements which are equal to 10.
<b>x[x &lt; 0]</b>	All elements less than zero.
<b>x[x %in% c(1, 2, 5)]</b>	Elements in the set 1, 2, 5.

##### Named Vectors

<b>x['apple']</b>	Element with name 'apple'.
-------------------	----------------------------

### Programming

#### For Loop

```
for (variable in sequence){  
  Do something  
}
```

##### Example

```
for (i in 1:4){  
  j <- i + 10  
  print(j)  
}
```

#### While Loop

```
while (condition){  
  Do something  
}
```

##### Example

```
while (i < 5){  
  print(i)  
  i <- i + 1  
}
```

#### If Statements

```
if (condition){  
  Do something  
} else {  
  Do something different  
}
```

##### Example

```
if (i > 3){  
  print('Yes')  
} else {  
  print('No')  
}
```

#### Functions

```
function_name <- function(var){  
  Do something  
  return(new_variable)  
}
```

##### Example

```
square <- function(x){  
  squared <- x*x  
  return(squared)  
}
```

### Reading and Writing Data

Input	Output	Description
df <- read.table('file.txt')	write.table(df, 'file.txt')	Read and write a delimited text file.
df <- read.csv('file.csv')	write.csv(df, 'file.csv')	Read and write a comma separated value file. This is a special case of read.table/write.table.
load('file.Rdata')	save(df, file = 'file.Rdata')	Read and write an R data file, a file type special for R.

#### Conditions

a == b	Are equal	a > b	Greater than	a >= b	Greater than or equal to	is.na(a)	Is missing
a != b	Not equal	a < b	Less than	a <= b	Less than or equal to	is.null(a)	Is null



# R Programming; Review

## Base R Cheat Sheet

### Getting Help

#### Accessing the help files

##### ?mean

Get help of a particular function.

**help.search('weighted mean')**

Search the help files for a word or phrase.

**help(package = 'dplyr')**

Find help for a package.

#### More about an object

##### str(iris)

Get a summary of an object's structure.

##### class(iris)

Find the class an object belongs to.

### Using Libraries

#### install.packages('dplyr')

Download and install a package from CRAN.

#### library(dplyr)

Load the package into the session, making all its functions available to use.

#### dplyr::select

Use a particular function from a package.

#### data(iris)

Load a built-in dataset into the environment.

### Working Directory

#### getwd()

Find the current working directory (where inputs are found and outputs are sent).

#### setwd('C://file/path')

Change the current working directory.

**Use projects in RStudio to set the working directory to the folder you are working in.**

### Vectors

#### Creating Vectors

c(2, 4, 6)	2 4 6	Join elements into a vector
2:6	2 3 4 5 6	An integer sequence
seq(2, 3, by=0.5)	2.0 2.5 3.0	A complex sequence
rep(1:2, times=3)	1 2 1 2 1 2	Repeat a vector
rep(1:2, each=3)	1 1 1 2 2 2	Repeat elements of a vector

#### Vector Functions

<b>sort(x)</b>	<b>rev(x)</b>
Return x sorted.	Return x reversed.
<b>table(x)</b>	<b>unique(x)</b>
See counts of values.	See unique values.

#### Selecting Vector Elements

##### By Position

<b>x[4]</b>	The fourth element.
<b>x[-4]</b>	All but the fourth.
<b>x[2:4]</b>	Elements two to four.
<b>x[-(2:4)]</b>	All elements except two to four.
<b>x[c(1, 5)]</b>	Elements one and five.

##### By Value

<b>x[x == 10]</b>	Elements which are equal to 10.
<b>x[x &lt; 0]</b>	All elements less than zero.
<b>x[x %in% c(1, 2, 5)]</b>	Elements in the set 1, 2, 5.

##### Named Vectors

<b>x['apple']</b>	Element with name 'apple'.
-------------------	----------------------------

### Programming

#### For Loop

```
for (variable in sequence){  
  Do something  
}
```

##### Example

```
for (i in 1:4){  
  j <- i + 10  
  print(j)  
}
```

#### While Loop

```
while (condition){  
  Do something  
}
```

##### Example

```
while (i < 5){  
  print(i)  
  i <- i + 1  
}
```

#### If Statements

```
if (condition){  
  Do something  
} else {  
  Do something different  
}
```

##### Example

```
if (i > 3){  
  print('Yes')  
} else {  
  print('No')  
}
```

#### Functions

```
function_name <- function(var){  
  Do something  
  return(new_variable)  
}
```

##### Example

```
square <- function(x){  
  squared <- x*x  
  return(squared)  
}
```

### Reading and Writing Data

Input	Output	Description
df <- read.table('file.txt')	write.table(df, 'file.txt')	Read and write a delimited text file.
df <- read.csv('file.csv')	write.csv(df, 'file.csv')	Read and write a comma separated value file. This is a special case of read.table/write.table.
load('file.Rdata')	save(df, file = 'file.Rdata')	Read and write an R data file, a file type special for R.

#### Conditions

a == b	Are equal	a > b	Greater than	a >= b	Greater than or equal to	is.na(a)	Is missing
a != b	Not equal	a < b	Less than	a <= b	Less than or equal to	is.null(a)	Is null



# R Programming; Review

## Base R Cheat Sheet

### Getting Help

#### Accessing the help files

##### ?mean

Get help of a particular function.

**help.search('weighted mean')**

Search the help files for a word or phrase.

**help(package = 'dplyr')**

Find help for a package.

#### More about an object

##### str(iris)

Get a summary of an object's structure.

##### class(iris)

Find the class an object belongs to.

### Using Libraries

#### install.packages('dplyr')

Download and install a package from CRAN.

#### library(dplyr)

Load the package into the session, making all its functions available to use.

#### dplyr::select

Use a particular function from a package.

#### data(iris)

Load a built-in dataset into the environment.

### Working Directory

#### getwd()

Find the current working directory (where inputs are found and outputs are sent).

#### setwd('C://file/path')

Change the current working directory.

Use projects in RStudio to set the working directory to the folder you are working in.

### Vectors

#### Creating Vectors

c(2, 4, 6)	2 4 6	Join elements into a vector
2:6	2 3 4 5 6	An integer sequence
seq(2, 3, by=0.5)	2.0 2.5 3.0	A complex sequence
rep(1:2, times=3)	1 2 1 2 1 2	Repeat a vector
rep(1:2, each=3)	1 1 1 2 2 2	Repeat elements of a vector

#### Vector Functions

<b>sort(x)</b>	<b>rev(x)</b>
Return x sorted.	Return x reversed.
<b>table(x)</b>	<b>unique(x)</b>
See counts of values.	See unique values.

#### Selecting Vector Elements

##### By Position

<b>x[4]</b>	The fourth element.
<b>x[-4]</b>	All but the fourth.
<b>x[2:4]</b>	Elements two to four.
<b>x[-(2:4)]</b>	All elements except two to four.
<b>x[c(1, 5)]</b>	Elements one and five.

##### By Value

<b>x[x == 10]</b>	Elements which are equal to 10.
<b>x[x &lt; 0]</b>	All elements less than zero.
<b>x[x %in% c(1, 2, 5)]</b>	Elements in the set 1, 2, 5.

##### Named Vectors

<b>x['apple']</b>	Element with name 'apple'.
-------------------	----------------------------

### Programming

#### For Loop

```
for (variable in sequence){  
  Do something  
}
```

#### Example

```
for (i in 1:4){  
  j <- i + 10  
  print(j)  
}
```

#### While Loop

```
while (condition){  
  Do something  
}
```

#### Example

```
while (i < 5){  
  print(i)  
  i <- i + 1  
}
```

#### If Statements

```
if (condition){  
  Do something  
} else {  
  Do something different  
}
```

#### Example

```
if (i > 3){  
  print('Yes')  
} else {  
  print('No')  
}
```

#### Functions

```
function_name <- function(var){  
  Do something  
  return(new_variable)  
}
```

#### Example

```
square <- function(x){  
  squared <- x*x  
  return(squared)  
}
```

### Reading and Writing Data

Input	Output	Description
df <- read.table('file.txt')	write.table(df, 'file.txt')	Read and write a delimited text file.
df <- read.csv('file.csv')	write.csv(df, 'file.csv')	Read and write a comma separated value file. This is a special case of read.table/write.table.
load('file.Rdata')	save(df, file = 'file.Rdata')	Read and write an R data file, a file type special for R.

Conditions	a == b	Are equal	a > b	Greater than	a >= b	Greater than or equal to	is.na(a)	Is missing
	a != b	Not equal	a < b	Less than	a <= b	Less than or equal to	is.null(a)	Is null



# R Programming; Review

## Base R Cheat Sheet

### Getting Help

#### Accessing the help files

##### ?mean

Get help of a particular function.

**help.search('weighted mean')**

Search the help files for a word or phrase.

**help(package = 'dplyr')**

Find help for a package.

#### More about an object

##### str(iris)

Get a summary of an object's structure.

##### class(iris)

Find the class an object belongs to.

### Using Libraries

#### install.packages('dplyr')

Download and install a package from CRAN.

#### library(dplyr)

Load the package into the session, making all its functions available to use.

#### dplyr::select

Use a particular function from a package.

#### data(iris)

Load a built-in dataset into the environment.

### Working Directory

#### getwd()

Find the current working directory (where inputs are found and outputs are sent).

#### setwd('C://file/path')

Change the current working directory.

Use projects in RStudio to set the working directory to the folder you are working in.

### Vectors

#### Creating Vectors

c(2, 4, 6)	2 4 6	Join elements into a vector
2:6	2 3 4 5 6	An integer sequence
seq(2, 3, by=0.5)	2.0 2.5 3.0	A complex sequence
rep(1:2, times=3)	1 2 1 2 1 2	Repeat a vector
rep(1:2, each=3)	1 1 1 2 2 2	Repeat elements of a vector

#### Vector Functions

<b>sort(x)</b>	<b>rev(x)</b>
Return x sorted.	Return x reversed.
<b>table(x)</b>	<b>unique(x)</b>
See counts of values.	See unique values.

#### Selecting Vector Elements

##### By Position

<b>x[4]</b>	The fourth element.
<b>x[-4]</b>	All but the fourth.
<b>x[2:4]</b>	Elements two to four.
<b>x[-(2:4)]</b>	All elements except two to four.
<b>x[c(1, 5)]</b>	Elements one and five.

##### By Value

<b>x[x == 10]</b>	Elements which are equal to 10.
<b>x[x &lt; 0]</b>	All elements less than zero.
<b>x[x %in% c(1, 2, 5)]</b>	Elements in the set 1, 2, 5.

##### Named Vectors

<b>x['apple']</b>	Element with name 'apple'.
-------------------	----------------------------

### Programming

#### For Loop

```
for (variable in sequence){  
  Do something  
}
```

#### Example

```
for (i in 1:4){  
  j <- i + 10  
  print(j)  
}
```

#### While Loop

```
while (condition){  
  Do something  
}
```

#### Example

```
while (i < 5){  
  print(i)  
  i <- i + 1  
}
```

#### If Statements

```
if (condition){  
  Do something  
} else {  
  Do something different  
}
```

#### Example

```
if (i > 3){  
  print('Yes')  
} else {  
  print('No')  
}
```

#### Functions

```
function_name <- function(var){  
  Do something  
  return(new_variable)  
}
```

#### Example

```
square <- function(x){  
  squared <- x*x  
  return(squared)  
}
```

### Reading and Writing Data

Input	Ouput	Description
<b>df &lt;- read.table('file.txt')</b>	<b>write.table(df, 'file.txt')</b>	Read and write a delimited text file.
<b>df &lt;- read.csv('file.csv')</b>	<b>write.csv(df, 'file.csv')</b>	Read and write a comma separated value file. This is a special case of read.table/write.table.
<b>load('file.Rdata')</b>	<b>save(df, file = 'file.Rdata')</b>	Read and write an R data file, a file type special for R.

#### Conditions

<b>a == b</b>	Are equal	<b>a &gt; b</b>	Greater than	<b>a &gt;= b</b>	Greater than or equal to	<b>is.na(a)</b>	Is missing
<b>a != b</b>	Not equal	<b>a &lt; b</b>	Less than	<b>a &lt;= b</b>	Less than or equal to	<b>is.null(a)</b>	Is null





# R Programming; Review

## Base R Cheat Sheet

### Getting Help

#### Accessing the help files

##### ?mean

Get help of a particular function.

**help.search('weighted mean')**

Search the help files for a word or phrase.

**help(package = 'dplyr')**

Find help for a package.

#### More about an object

##### str(iris)

Get a summary of an object's structure.

##### class(iris)

Find the class an object belongs to.

### Using Libraries

#### install.packages('dplyr')

Download and install a package from CRAN.

#### library(dplyr)

Load the package into the session, making all its functions available to use.

#### dplyr::select

Use a particular function from a package.

#### data(iris)

Load a built-in dataset into the environment.

### Working Directory

#### getwd()

Find the current working directory (where inputs are found and outputs are sent).

#### setwd('C://file/path')

Change the current working directory.

**Use projects in RStudio to set the working directory to the folder you are working in.**

### Vectors

#### Creating Vectors

c(2, 4, 6)	2 4 6	Join elements into a vector
2:6	2 3 4 5 6	An integer sequence
seq(2, 3, by=0.5)	2.0 2.5 3.0	A complex sequence
rep(1:2, times=3)	1 2 1 2 1 2	Repeat a vector
rep(1:2, each=3)	1 1 1 2 2 2	Repeat elements of a vector

#### Vector Functions

<b>sort(x)</b>	<b>rev(x)</b>
Return x sorted.	Return x reversed.
<b>table(x)</b>	<b>unique(x)</b>
See counts of values.	See unique values.

#### Selecting Vector Elements

##### By Position

<b>x[4]</b>	The fourth element.
<b>x[-4]</b>	All but the fourth.
<b>x[2:4]</b>	Elements two to four.
<b>x[-(2:4)]</b>	All elements except two to four.
<b>x[c(1, 5)]</b>	Elements one and five.

##### By Value

<b>x[x == 10]</b>	Elements which are equal to 10.
<b>x[x &lt; 0]</b>	All elements less than zero.
<b>x[x %in% c(1, 2, 5)]</b>	Elements in the set 1, 2, 5.

##### Named Vectors

<b>x['apple']</b>	Element with name 'apple'.
-------------------	----------------------------

### Programming

#### For Loop

```
for (variable in sequence){  
  Do something  
}
```

##### Example

```
for (i in 1:4){  
  j <- i + 10  
  print(j)  
}
```

#### While Loop

```
while (condition){  
  Do something  
}
```

##### Example

```
while (i < 5){  
  print(i)  
  i <- i + 1  
}
```

#### If Statements

```
if (condition){  
  Do something  
} else {  
  Do something different  
}
```

##### Example

```
if (i > 3){  
  print('Yes')  
} else {  
  print('No')  
}
```

#### Functions

```
function_name <- function(var){  
  Do something  
  return(new_variable)  
}
```

##### Example

```
square <- function(x){  
  squared <- x*x  
  return(squared)  
}
```

### Reading and Writing Data

Input	Output	Description
df <- read.table('file.txt')	write.table(df, 'file.txt')	Read and write a delimited text file.
df <- read.csv('file.csv')	write.csv(df, 'file.csv')	Read and write a comma separated value file. This is a special case of read.table/write.table.
load('file.Rdata')	save(df, file = 'file.Rdata')	Read and write an R data file, a file type special for R.

#### Conditions

a == b	Are equal	a > b	Greater than	a >= b	Greater than or equal to	is.na(a)	Is missing
a != b	Not equal	a < b	Less than	a <= b	Less than or equal to	is.null(a)	Is null





# R Programming; Review

## Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

as.logical	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE).
as.numeric	1, 0, 1	Integers or floating point numbers.
as.character	'1', '0', '1'	Character strings. Generally preferred to factors.
as.factor	'1', '0', '1', levels: '1', '0'	Character strings with preset levels. Needed for some statistical models.

## Maths Functions

log(x)	Natural log.	sum(x)	Sum.
exp(x)	Exponential.	mean(x)	Mean.
max(x)	Largest element.	median(x)	Median.
min(x)	Smallest element.	quantile(x)	Percentage quantiles.
round(x, n)	Round to n decimal places.	rank(x)	Rank of elements.
signif(x, n)	Round to n significant figures.	var(x)	The variance.
cor(x, y)	Correlation.	sd(x)	The standard deviation.

## Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```







## The Environment

ls()	List all variables in the environment.
rm(x)	Remove x from the environment.
rm(list = ls())	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

## Matrixes

```
m <- matrix(x, nrow = 3, ncol = 3)
Create a matrix from x.
```

 m[2, ] - Select a row	 t(m) Transpose
 m[, 1] - Select a column	 m %*% n Matrix Multiplication
 m[2, 3] - Select an element	 solve(m, n) Find x in: m * x = n

## Lists

```
l <- list(x = 1:5, y = c('a', 'b'))
A list is collection of elements which can be of different types.
```

l[[2]]	l[1]	l\$x	l['y']
Second element of l.	New list with only the first element.	Element named x.	New list with only element named y.

Also see the **dplyr** library.

## Data Frames

```
df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))
A special case of a list where all elements are the same length.
```

x	y
1	a
2	b
3	c

### List subsetting

df\$x	df[[2]]
-------	---------

### Understanding a data frame

View(df)	See the full data frame.
head(df)	See the first 6 rows.

### Matrix subsetting

df[, 2]	df[2, ]	df[2, 2]
---------	---------	----------

nrow(df)  
Number of rows.

ncol(df)  
Number of columns.

dim(df)  
Number of columns and rows.

cbind - Bind columns.

rbind - Bind rows.

## Strings

Also see the **stringr** library.

paste(x, y, sep = ' ')	Join multiple vectors together.
paste(x, collapse = ' ')	Join elements of a vector together.
grep(pattern, x)	Find regular expression matches in x.
gsub(pattern, replace, x)	Replace matches in x with a string.
toupper(x)	Convert to uppercase.
tolower(x)	Convert to lowercase.
nchar(x)	Number of characters in a string.

## Factors

factor(x)	Turn a vector into a factor. Can set the levels of the factor and the order.
cut(x, breaks = 4)	Turn a numeric vector into a factor but 'cutting' into sections.

## Statistics




lm(x ~ y, data=df) Linear model.	t.test(x, y) Perform a t-test for difference between means.	prop.test Test for a difference between proportions.
glm(x ~ y, data=df) Generalised linear model.	pairwise.t.test Perform a t-test for paired data.	aov Analysis of variance.
summary Get more detailed information out a model.		

## Distributions

	Random Variates	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	pnorm	qnorm
Poisson	rpois	dpois	ppois	qpois
Binomial	rbinom	dbinom	pbinom	qbinom
Uniform	runif	dunif	punif	qunif

## Plotting

Also see the **ggplot2** library.

 plot(x) Values of x in order.	 plot(x, y) Values of x against y.	 hist(x) Histogram of x.
--	--	--

## Dates

See the **lubridate** library.



# R Programming; Review

## Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

<b>as.logical</b>	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE).
<b>as.numeric</b>	1, 0, 1	Integers or floating point numbers.
<b>as.character</b>	'1', '0', '1'	Character strings. Generally preferred to factors.
<b>as.factor</b>	'1', '0', '1', levels: '1', '0'	Character strings with preset levels. Needed for some statistical models.

## Maths Functions

<b>log(x)</b>	Natural log.	<b>sum(x)</b>	Sum.
<b>exp(x)</b>	Exponential.	<b>mean(x)</b>	Mean.
<b>max(x)</b>	Largest element.	<b>median(x)</b>	Median.
<b>min(x)</b>	Smallest element.	<b>quantile(x)</b>	Percentage quantiles.
<b>round(x, n)</b>	Round to n decimal places.	<b>rank(x)</b>	Rank of elements.
<b>signif(x, n)</b>	Round to n significant figures.	<b>var(x)</b>	The variance.
<b>cor(x, y)</b>	Correlation.	<b>sd(x)</b>	The standard deviation.

## Variable Assignment

```
> a <- 'apple'  
> a  
[1] 'apple'
```




## The Environment

<b>ls()</b>	List all variables in the environment.
<b>rm(x)</b>	Remove x from the environment.
<b>rm(list = ls())</b>	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

## Matrixes

```
m <- matrix(x, nrow = 3, ncol = 3)  
Create a matrix from x.
```

 <b>m[2, ]</b> - Select a row	<b>t(m)</b> Transpose <b>m %*% n</b> Matrix Multiplication <b>solve(m, n)</b> Find x in: $m \cdot x = n$
 <b>m[, 1]</b> - Select a column	
 <b>m[2, 3]</b> - Select an element	

## Lists

```
l <- list(x = 1:5, y = c('a', 'b'))
```

A list is collection of elements which can be of different types.

<b>l[[2]]</b> Second element of l.	<b>l[1]</b> New list with only the first element.	<b>l\$x</b> Element named x.	<b>l[y]</b> New list with only element named y.
---------------------------------------	--	---------------------------------	--



Also see the **dplyr** library.

## Data Frames

```
df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))  
A special case of a list where all elements are the same length.
```

x	y
1	a
2	b
3	c

**List subsetting**





**df\$x**  **df[[2]]** 

**Understanding a data frame**

**View(df)** See the full data frame.

**head(df)** See the first 6 rows.

**Matrix subsetting**

<b>df[, 2]</b> 	<b>nrow(df)</b> Number of rows.	<b>cbind</b> - Bind columns. 
<b>df[2, ]</b> 	<b>ncol(df)</b> Number of columns.	<b>rbind</b> - Bind rows. 
<b>df[2, 2]</b> 	<b>dim(df)</b> Number of columns and rows.	

## Strings

Also see the **stringr** library.

<b>paste(x, y, sep = ' ')</b>	Join multiple vectors together.
<b>paste(x, collapse = ' ')</b>	Join elements of a vector together.
<b>grep(pattern, x)</b>	Find regular expression matches in x.
<b>gsub(pattern, replace, x)</b>	Replace matches in x with a string.
<b>toupper(x)</b>	Convert to uppercase.
<b>tolower(x)</b>	Convert to lowercase.
<b>nchar(x)</b>	Number of characters in a string.

## Factors

<b>factor(x)</b> Turn a vector into a factor. Can set the levels of the factor and the order.	<b>cut(x, breaks = 4)</b> Turn a numeric vector into a factor but 'cutting' into sections.
--	---

## Statistics

<b>lm(x ~ y, data=df)</b> Linear model.	<b>t.test(x, y)</b> Perform a t-test for difference between means.	<b>prop.test</b> Test for a difference between proportions.
<b>glm(x ~ y, data=df)</b> Generalised linear model.	<b>pairwise.t.test</b> Perform a t-test for paired data.	<b>aov</b> Analysis of variance.
<b>summary</b> Get more detailed information out a model.		

## Distributions

	Random Variates	Density Function	Cumulative Distribution	Quantile
Normal	<b>rnorm</b>	<b>dnorm</b>	<b>pnorm</b>	<b>qnorm</b>
Poisson	<b>rpois</b>	<b>dpois</b>	<b>ppois</b>	<b>qpois</b>
Binomial	<b>rbinom</b>	<b>dbinom</b>	<b>pbinom</b>	<b>qbinom</b>
Uniform	<b>runif</b>	<b>dunif</b>	<b>punif</b>	<b>qunif</b>

## Plotting

Also see the **ggplot2** library.

 <b>plot(x)</b> Values of x in order.	 <b>plot(x, y)</b> Values of x against y.	 <b>hist(x)</b> Histogram of x.
---	---	---

## Dates

See the **lubridate** library.



# R Programming; Review

## Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

as.logical	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE).
as.numeric	1, 0, 1	Integers or floating point numbers.
as.character	'1', '0', '1'	Character strings. Generally preferred to factors.
as.factor	'1', '0', '1', levels: '1', '0'	Character strings with preset levels. Needed for some statistical models.

## Maths Functions

log(x)	Natural log.	sum(x)	Sum.
exp(x)	Exponential.	mean(x)	Mean.
max(x)	Largest element.	median(x)	Median.
min(x)	Smallest element.	quantile(x)	Percentage quantiles.
round(x, n)	Round to n decimal places.	rank(x)	Rank of elements.
signif(x, n)	Round to n significant figures.	var(x)	The variance.
cor(x, y)	Correlation.	sd(x)	The standard deviation.

## Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```







## The Environment

ls()	List all variables in the environment.
rm(x)	Remove x from the environment.
rm(list = ls())	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

## Matrixes

```
m <- matrix(x, nrow = 3, ncol = 3)
Create a matrix from x.
```

 m[2, ] - Select a row	 t(m) Transpose
 m[, 1] - Select a column	 m %*% n Matrix Multiplication
 m[2, 3] - Select an element	 solve(m, n) Find x in: m * x = n

## Lists

```
l <- list(x = 1:5, y = c('a', 'b'))
A list is collection of elements which can be of different types.
```

l[[2]]	l[1]	l\$x	l['y']
Second element of l.	New list with only the first element.	Element named x.	New list with only element named y.



Also see the **dplyr** library.

## Data Frames

```
df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))
A special case of a list where all elements are the same length.
```

x	y
1	a
2	b
3	c

**List subsetting**






df\$x  df[[2]] 

**Understanding a data frame**

View(df) See the full data frame.

head(df) See the first 6 rows.

### Matrix subsetting

df[, 2]		nrow(df) Number of rows.	<b>cbind</b> - Bind columns.
df[2, ]		ncol(df) Number of columns.	
df[2, 2]		dim(df) Number of columns and rows.	<b>rbind</b> - Bind rows.
			

## Strings

Also see the **stringr** library.

paste(x, y, sep = ' ')	Join multiple vectors together.
paste(x, collapse = ' ')	Join elements of a vector together.
grep(pattern, x)	Find regular expression matches in x.
gsub(pattern, replace, x)	Replace matches in x with a string.
toupper(x)	Convert to uppercase.
tolower(x)	Convert to lowercase.
nchar(x)	Number of characters in a string.

## Factors

factor(x)	cut(x, breaks = 4)
Turn a vector into a factor. Can set the levels of the factor and the order.	Turn a numeric vector into a factor but 'cutting' into sections.

## Statistics

lm(x ~ y, data=df) Linear model.	t.test(x, y) Perform a t-test for difference between means.	prop.test Test for a difference between proportions.
glm(x ~ y, data=df) Generalised linear model.	pairwise.t.test Perform a t-test for paired data.	aov Analysis of variance.
summary Get more detailed information out a model.		

## Distributions

	Random Variates	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	pnorm	qnorm
Poisson	rpois	dpois	ppois	qpois
Binomial	rbinom	dbinom	pbinom	qbinom
Uniform	runif	dunif	punif	qunif

## Plotting

Also see the **ggplot2** library.

 plot(x) Values of x in order.	 plot(x, y) Values of x against y.	 hist(x) Histogram of x.
--	--	--

## Dates

See the **lubridate** library.



# R Programming; Review

## Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

as.logical	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE).
as.numeric	1, 0, 1	Integers or floating point numbers.
as.character	'1', '0', '1'	Character strings. Generally preferred to factors.
as.factor	'1', '0', '1', levels: '1', '0'	Character strings with preset levels. Needed for some statistical models.

## Maths Functions

log(x)	Natural log.	sum(x)	Sum.
exp(x)	Exponential.	mean(x)	Mean.
max(x)	Largest element.	median(x)	Median.
min(x)	Smallest element.	quantile(x)	Percentage quantiles.
round(x, n)	Round to n decimal places.	rank(x)	Rank of elements.
signif(x, n)	Round to n significant figures.	var(x)	The variance.
cor(x, y)	Correlation.	sd(x)	The standard deviation.

## Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```







## The Environment

ls()	List all variables in the environment.
rm(x)	Remove x from the environment.
rm(list = ls())	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

## Matrixes

```
m <- matrix(x, nrow = 3, ncol = 3)
Create a matrix from x.
```

 m[2, ] - Select a row	 t(m) Transpose
 m[, 1] - Select a column	 m %*% n Matrix Multiplication
 m[2, 3] - Select an element	 solve(m, n) Find x in: m * x = n

## Lists

```
l <- list(x = 1:5, y = c('a', 'b'))
A list is collection of elements which can be of different types.
```

l[[2]]	l[[1]]	l\$x	l['y']
Second element of l.	New list with only the first element.	Element named x.	New list with only element named y.

Also see the **dplyr** library.

## Data Frames

```
df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))
A special case of a list where all elements are the same length.
```

x	y
1	a
2	b
3	c



**List subsetting**

df\$x	df[[2]]
-------	---------

**Understanding a data frame**

View(df)	See the full data frame.
head(df)	See the first 6 rows.

**Matrix subsetting**

df[, 2]	nrow(df) Number of rows.	 cbind - Bind columns.
df[2, ]	ncol(df) Number of columns.	 rbind - Bind rows.
df[2, 2]	dim(df) Number of columns and rows.	

## Strings

Also see the **stringr** library.

paste(x, y, sep = ' ')	Join multiple vectors together.
paste(x, collapse = ' ')	Join elements of a vector together.
grep(pattern, x)	Find regular expression matches in x.
gsub(pattern, replace, x)	Replace matches in x with a string.
toupper(x)	Convert to uppercase.
tolower(x)	Convert to lowercase.
nchar(x)	Number of characters in a string.

## Factors

factor(x)	Turn a vector into a factor. Can set the levels of the factor and the order.
cut(x, breaks = 4)	Turn a numeric vector into a factor but 'cutting' into sections.

## Statistics




lm(x ~ y, data=df) Linear model.	t.test(x, y) Perform a t-test for difference between means.	prop.test Test for a difference between proportions.
glm(x ~ y, data=df) Generalised linear model.	pairwise.t.test Perform a t-test for paired data.	aov Analysis of variance.
summary Get more detailed information out a model.		

## Distributions

	Random Variates	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	pnorm	qnorm
Poisson	rpois	dpois	ppois	qpois
Binomial	rbinom	dbinom	pbinom	qbinom
Uniform	runif	dunif	punif	qunif

## Plotting

Also see the **ggplot2** library.

 plot(x) Values of x in order.	 plot(x, y) Values of x against y.	 hist(x) Histogram of x.
--	--	--

## Dates

See the **lubridate** library.





# R Programming; Review

## Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

as.logical	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE).
as.numeric	1, 0, 1	Integers or floating point numbers.
as.character	'1', '0', '1'	Character strings. Generally preferred to factors.
as.factor	'1', '0', '1', levels: '1', '0'	Character strings with preset levels. Needed for some statistical models.

## Maths Functions

log(x)	Natural log.	sum(x)	Sum.
exp(x)	Exponential.	mean(x)	Mean.
max(x)	Largest element.	median(x)	Median.
min(x)	Smallest element.	quantile(x)	Percentage quantiles.
round(x, n)	Round to n decimal places.	rank(x)	Rank of elements.
signif(x, n)	Round to n significant figures.	var(x)	The variance.
cor(x, y)	Correlation.	sd(x)	The standard deviation.

## Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```




## The Environment

ls()	List all variables in the environment.
rm(x)	Remove x from the environment.
rm(list = ls())	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

## Matrixes

```
m <- matrix(x, nrow = 3, ncol = 3)
Create a matrix from x.
```

 m[2, ]	- Select a row	t(m)	Transpose
 m[, 1]	- Select a column	m %*% n	Matrix Multiplication
 m[2, 3]	- Select an element	solve(m, n)	Find x in: m * x = n

## Lists

```
l <- list(x = 1:5, y = c('a', 'b'))
A list is collection of elements which can be of different types.
```

l[[2]]	l[1]	l\$x	l['y']
Second element of l.	New list with only the first element.	Element named x.	New list with only element named y.

Also see the **dplyr** library.

## Data Frames

```
df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))
A special case of a list where all elements are the same length.
```

x	y
1	a
2	b
3	c




### List subsetting

df\$x	df[[2]]
-------	---------

### Understanding a data frame

View(df)	See the full data frame.
head(df)	See the first 6 rows.

### Matrix subsetting

df[, 2]	
df[2, ]	
df[2, 2]	

nrow(df)  
Number of rows.


ncol(df)  
Number of columns.

dim(df)  
Number of columns and rows.

cbind - Bind columns.



rbind - Bind rows.



## Strings

Also see the **stringr** library.

paste(x, y, sep = ' ')	Join multiple vectors together.
paste(x, collapse = ' ')	Join elements of a vector together.
grep(pattern, x)	Find regular expression matches in x.
gsub(pattern, replace, x)	Replace matches in x with a string.
toupper(x)	Convert to uppercase.
tolower(x)	Convert to lowercase.
nchar(x)	Number of characters in a string.

## Factors

factor(x)	Turn a vector into a factor. Can set the levels of the factor and the order.
cut(x, breaks = 4)	Turn a numeric vector into a factor but 'cutting' into sections.

## Statistics




lm(x ~ y, data=df)	Linear model.	t.test(x, y)	Preform a t-test for difference between means.	prop.test	Test for a difference between proportions.
glm(x ~ y, data=df)	Generalised linear model.	summary	Get more detailed information out a model.	pairwise.t.test	Preform a t-test for paired data.
				aov	Analysis of variance.

## Distributions

	Random Variates	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	pnorm	qnorm
Poisson	rpois	dpois	ppois	qpois
Binomial	rbinom	dbinom	pbinom	qbinom
Uniform	runif	dunif	punif	qunif

## Plotting

Also see the **ggplot2** library.

 plot(x)	Values of x in order.	 plot(x, y)	Values of x against y.	 hist(x)	Histogram of x.
---	-----------------------	--	------------------------	---	-----------------

## Dates

See the **lubridate** library.



# R Programming; Review

### Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

as.logical	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE)
as.numeric	1, 0, 1	Integers or floating point numbers
as.character	"1", "0", "1"	Character strings. Generally preferred to factors.
as.factor	"1", "0", "1", levels: "1", "0"	Character strings with preset levels. Needed for some statistical models.

### Maths Functions

log(x)	Natural log.	sum(x)	Sum.
exp(x)	Exponential.	mean(x)	Mean.
max(x)	Largest element.	median(x)	Median.
min(x)	Smallest element.	quantile(x)	Percentage quantiles.
round(x, n)	Round to n decimal places.	rank(x)	Rank of elements.
signif(x, n)	Round to n significant figures.	var(x)	The variance.
cor(x, y)	Correlation.	sd(x)	The standard deviation.

### Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```

### The Environment

ls()	List all variables in the environment.
rm(x)	Remove x from the environment.
rm(list = ls())	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

### Matrixes

`m <- matrix(x, nrow = 3, ncol = 3)`  
Create a matrix from x.

<code>m[2, 1]</code>	Select a row
<code>m[, 1]</code>	Select a column
<code>m[2, 3]</code>	Select an element

### Lists

`l <- list(x = 1:5, y = c('a', 'b'))`  
A list is a collection of elements which can be of different types.

<code>l[[2]]</code>	Second element of l
<code>l[[1]]</code>	New list with only the first element.
<code>l\$x</code>	Element named x.
<code>l[[y]]</code>	New list with only element named y.

### Data Frames

`df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))`  
A special case of a list where all elements are the same length.

### List subsetting

x	y
1	a
2	b
3	c

`df[1, 2]` `df[2, 1]` `df[2, 2]`

### Matrix subsetting

x	y
1	a
2	b
3	c

`df[1, 2]` `df[2, 1]` `df[2, 2]`

### Distributions

Random Variables	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	qnorm
Poisson	rpois	dpois	qpois
Binomial	rbinom	dbinom	qbinom
Uniform	runif	dunif	qunif

### Plotting

`plot(x)` Values of x in order.  
`plot(x, y)` Values of x against y.  
`hist(x)` Histogram of x.

### Dates

See the lubridate library.

### Strings

Also see the stringr library.

`paste(x, y, sep = ' ')` Join multiple vectors together.  
`paste(x, collapse = ' ')` Join elements of a vector together.  
`grep(pattern, x)` Find regular expression matches in x.  
`gsub(pattern, replace, x)` Replace matches in x with a string.  
`toupper(x)` Convert to uppercase.  
`tolower(x)` Convert to lowercase.  
`nchar(x)` Number of characters in a string.

### Factors

`factor(x)` Turn a vector into a factor. Can set the levels of the factor and the order.  
`cut(x, breaks = 4)` Turn a numeric vector into a factor but 'cutting' into sections.

### Statistics

`lm(x ~ y, data=df)` Linear model.  
`t.test(x, y)` Test for a difference between means.  
`prop.test` Test for a difference between proportions.  
`glm(x ~ y, data=df)` Generalised linear model.  
`summary` Get more detailed information out of a model.  
`pairwise.t.test` Perform a t-test for paired data.  
`aov` Analysis of variance.

### Distributions

Random Variables	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	qnorm
Poisson	rpois	dpois	qpois
Binomial	rbinom	dbinom	qbinom
Uniform	runif	dunif	qunif

### Plotting

`plot(x)` Values of x in order.  
`plot(x, y)` Values of x against y.  
`hist(x)` Histogram of x.

### Dates

See the lubridate library.

### Types

Converting between common data types in R. Can always go from a higher value in the table to a lower value.

as.logical	TRUE, FALSE, TRUE	Boolean values (TRUE or FALSE)
as.numeric	1, 0, 1	Integers or floating point numbers
as.character	"1", "0", "1"	Character strings. Generally preferred to factors.
as.factor	"1", "0", "1", levels: "1", "0"	Character strings with preset levels. Needed for some statistical models.

### Maths Functions

log(x)	Natural log.	sum(x)	Sum.
exp(x)	Exponential.	mean(x)	Mean.
max(x)	Largest element.	median(x)	Median.
min(x)	Smallest element.	quantile(x)	Percentage quantiles.
round(x, n)	Round to n decimal places.	rank(x)	Rank of elements.
signif(x, n)	Round to n significant figures.	var(x)	The variance.
cor(x, y)	Correlation.	sd(x)	The standard deviation.

### Variable Assignment

```
> a <- 'apple'
> a
[1] 'apple'
```

### The Environment

ls()	List all variables in the environment.
rm(x)	Remove x from the environment.
rm(list = ls())	Remove all variables from the environment.

You can use the environment panel in RStudio to browse variables in your environment.

### Matrixes

`m <- matrix(x, nrow = 3, ncol = 3)`  
Create a matrix from x.

<code>m[2, 1]</code>	Select a row
<code>m[, 1]</code>	Select a column
<code>m[2, 3]</code>	Select an element

### Lists

`l <- list(x = 1:5, y = c('a', 'b'))`  
A list is a collection of elements which can be of different types.

<code>l[[2]]</code>	Second element of l
<code>l[[1]]</code>	New list with only the first element.
<code>l\$x</code>	Element named x.
<code>l[[y]]</code>	New list with only element named y.

### Data Frames

`df <- data.frame(x = 1:3, y = c('a', 'b', 'c'))`  
A special case of a list where all elements are the same length.

### List subsetting

x	y
1	a
2	b
3	c

`df[1, 2]` `df[2, 1]` `df[2, 2]`

### Matrix subsetting

x	y
1	a
2	b
3	c

`df[1, 2]` `df[2, 1]` `df[2, 2]`

### Distributions

Random Variables	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	qnorm
Poisson	rpois	dpois	qpois
Binomial	rbinom	dbinom	qbinom
Uniform	runif	dunif	qunif

### Plotting

`plot(x)` Values of x in order.  
`plot(x, y)` Values of x against y.  
`hist(x)` Histogram of x.

### Dates

See the lubridate library.

### Strings

Also see the stringr library.

`paste(x, y, sep = ' ')` Join multiple vectors together.  
`paste(x, collapse = ' ')` Join elements of a vector together.  
`grep(pattern, x)` Find regular expression matches in x.  
`gsub(pattern, replace, x)` Replace matches in x with a string.  
`toupper(x)` Convert to uppercase.  
`tolower(x)` Convert to lowercase.  
`nchar(x)` Number of characters in a string.

### Factors

`factor(x)` Turn a vector into a factor. Can set the levels of the factor and the order.  
`cut(x, breaks = 4)` Turn a numeric vector into a factor but 'cutting' into sections.

### Statistics

`lm(x ~ y, data=df)` Linear model.  
`t.test(x, y)` Test for a difference between means.  
`prop.test` Test for a difference between proportions.  
`glm(x ~ y, data=df)` Generalised linear model.  
`summary` Get more detailed information out of a model.  
`pairwise.t.test` Perform a t-test for paired data.  
`aov` Analysis of variance.

### Distributions

Random Variables	Density Function	Cumulative Distribution	Quantile
Normal	rnorm	dnorm	qnorm
Poisson	rpois	dpois	qpois
Binomial	rbinom	dbinom	qbinom
Uniform	runif	dunif	qunif

### Plotting

`plot(x)` Values of x in order.  
`plot(x, y)` Values of x against y.  
`hist(x)` Histogram of x.

### Dates

See the lubridate library.

# Any Questions?