


Rohith Gandhi
May 5, 2018 · 4 min read · Listen



Naive Bayes Classifier



What is a classifier?

A classifier is a machine learning model that is used to discriminate different objects based on certain features.

Principle of Naive Bayes Classifier:

A Naive Bayes classifier is a probabilistic machine learning model that's used for classification task. The crux of the classifier is based on the Bayes theorem.

Bayes Theorem:

$$P(A|B) = \frac{P(B|A)P(A)}{P(B)}$$

Using Bayes theorem, we can find the probability of **A** happening, given that **B** has occurred. Here, **B** is the evidence and **A** is the hypothesis. The assumption made here is that the predictors/features are independent. That is presence of one particular feature does not affect the other. Hence it is called naive.

Example:

Let us take an example to get some better intuition. Consider the problem of playing golf. The dataset is represented as below.

	OUTLOOK	TEMPERATURE	HUMIDITY	WINDY	PLAY GOLF
0	Rainy	Hot	High	False	No
1	Rainy	Hot	High	True	No
2	Overcast	Hot	High	False	Yes
3	Sunny	Mild	High	False	Yes
4	Sunny	Cool	Normal	False	Yes
5	Sunny	Cool	Normal	True	No
6	Overcast	Cool	Normal	True	Yes
7	Rainy	Mild	High	False	No
8	Rainy	Cool	Normal	False	Yes
9	Sunny	Mild	Normal	False	Yes
10	Rainy	Mild	Normal	True	Yes
11	Overcast	Mild	High	True	Yes
12	Overcast	Hot	Normal	False	Yes
13	Sunny	Mild	High	True	No

We classify whether the day is suitable for playing golf, given the features of the day. The columns represent these features and the rows represent individual entries. If we take the first row of the dataset, we can observe that it is not suitable for playing golf if the outlook is rainy, temperature is hot, humidity is high and it is not windy. We make two assumptions here, one as stated above we consider that these predictors are independent. That is, if the temperature is hot, it does not necessarily mean that the humidity is high. Another assumption made here is that all the predictors have an equal effect on the outcome. That is, the day being windy does not have more importance in deciding to play golf or not.

According to this example, Bayes theorem can be rewritten as:

$$P(y|X) = \frac{P(X|y)P(y)}{P(X)}$$

The variable **y** is the class variable(play golf), which represents if it is suitable to play golf or not given the conditions. Variable **X** represent the parameters/features.

X is given as,

$$X = (x_1, x_2, x_3, \dots, x_n)$$

Here x_1, x_2, \dots, x_n represent the features, i.e they can be mapped to outlook, temperature, humidity and windy. By substituting **X** and expanding using the chain rule we get,

$$P(y|x_1, \dots, x_n) = \frac{P(x_1|y)P(x_2|y)\dots P(x_n|y)P(y)}{P(x_1)P(x_2)\dots P(x_n)}$$

Now, you can obtain the values for each by looking at the dataset and substitute them into the equation. For all entries in the dataset, the denominator does not change, it remain static. Therefore, the denominator can be removed and a proportionality can be introduced.

$$P(y|x_1, \dots, x_n) \propto P(y) \prod_{i=1}^n P(x_i|y)$$

In our case, the class variable(**y**) has only two outcomes, yes or no. There could be cases where the classification could be multivariate. Therefore, we need to find the class **y** with maximum probability.

$$y = \operatorname{argmax}_y P(y) \prod_{i=1}^n P(x_i|y)$$

Using the above function, we can obtain the class, given the predictors.

Types of Naive Bayes Classifier:

Multinomial Naive Bayes:


This is mostly used for document classification problem, i.e whether a document belongs to the category of sports, politics, technology etc. The features/predictors used by the classifier are the frequency of the words present in the document.

Bernoulli Naive Bayes:

This is similar to the multinomial naive bayes but the predictors are boolean variables. The parameters that we use to predict the class variable take up only values yes or no, for example if a word occurs in the text or not.

Gaussian Naive Bayes:

When the predictors take up a continuous value and are not discrete, we assume that these values are sampled from a gaussian distribution.



Since the way the values are present in the dataset changes, the formula for conditional probability changes to,

$$P(x_i|y) = \frac{1}{\sqrt{2\pi\sigma_y^2}} \exp\left(-\frac{(x_i - \mu_y)^2}{2\sigma_y^2}\right)$$

Conclusion:

Naive Bayes algorithms are mostly used in sentiment analysis, spam filtering, recommendation systems etc. They are fast and easy to implement but their biggest disadvantage is that the requirement of predictors to be independent. In most of the real life cases, the predictors are dependent, this hinders the performance of the classifier.

👁 2.6K 💬 13

👁 2.6K 💬 13



Sign up for The Variable

By Towards Data Science

Every Thursday, the Variable delivers the very best of Towards Data Science: from hands-on tutorials and cutting-edge research to original features you don't want to miss. [Take a look.](#)

✉ Get this newsletter

More from Towards Data Science


Your home for data science. A Medium publication sharing concepts, ideas and codes.

Follow


👤 Natasha Sharma · May 5, 2018

Spam Detection with Logistic Regression

I still remember my first day in machine learning class. The first example which was provided to explain, how machine learning works, was... — I still remember my first day in machine learning class. The first example...



Machine Learning · 6 min read



👤 Gal Yona · May 5, 2018

Fast Near-Duplicate Image Search using Locality Sensitive Hashing

A quick 5-part tutorial on how deep learning combined with efficient approximate nearest neighbor queries can be used to perform fast... — P...




Machine Learning · 9 min read



👤 Shashank Gupta · May 5, 2018

Automated Survey Processing using Contextual Semantic Search

With the recent advances in deep learning, the ability of algorithms to analyze text has improved considerably. Now analyzing digital and... — ...




Machine Learning · 6 min read



👤 Shashank Ramesh · May 5, 2018

A guide to an efficient way to build neural network architectures- Part I: Hyper-parameter selection and tuning for Dense Networks using Hyperas on...

Intro — Intro "If you listen to your intuition you will always know what is..."




Deep Learning · 18 min read



👤 J Li · May 4, 2018 ⭐

Portfolio Optimization for Minimum Risk with Scipy — Efficient Frontier Explained

(This post is also available in my blog) — (This post is also available in my blog) Beyond the bound Given 4 assets' risk and return as following, wha...



Data Science · 5 min read




Read more from Towards Data Science

Recommended from Medium

👤 Ishika ... in The Business Club, IIT L...

Probability Distribution Functions: PDF, CDF, PMF

👤 Seb Bailey
Scientist to (Great) Data Scientist




👤 Kate Marie L... in Towards Data Sc...

A Day in the Life of a Data Scientist in San Francisco


👤 Yasmin Lukman
Original and Fake News Classification Model with the Tensorflow Framework and th...



👤 Vladimir Fedak
Big Data: Information visualization techniques



👤 Biseldev
UNDERSTANDING ISO 8601 AND UTC



👤 Justin Hart
Machine Learning Meets Fantasy Football — Part 2



👤 Aaka... in Jovian—Data Science a...

4 important soft skills for data science and machine learning practitioners



Q Search



Rohith Gandhi

2.7K Followers

What I cannot create, I do not understand - Richard Feynman. LinkedIn: www.linkedin.com/in/grohith327


Follow



More from Medium

👤 Ritwick Roy in Towards Data Science

The Naive Bayes classifier



👤 Sreekanth

Principal Component Analysis (PCA)



👤 Ali Asghar Heidari

Multi-strategy ensemble binary hunger games search for feature selection



👤 Yogesh Rawat

Confusion Matrix

