
Composition after pretraining

Rishi Ashish Shah · November 2026 · github.com/RS-010806/composition

If a model knows “red” and “rectangle”, can a few examples teach it every color-shape combination, so that the examples needed grow as **colors plus shapes** rather than **colors times shapes**? Exploiting this during large-scale pretraining is hard, so I tested the two later stages where it could be used: **post-training** and **in-context learning**.



Share of never-seen combinations named correctly (color and shape both right). (a) Small CNN trained from scratch on 26 combinations, 5 seeds. (b) Ridge heads on frozen Gemini image embeddings (*gemini-embedding-2*), 20 seeds; error bars are sd over seeds. (c) Gemini 3.5 Flash-Lite with 11 labeled examples in made-up words; labels give exact names out of trials. (d) Heads from (b) trained on confounded examples plus 20 images labeled by Gemini 3.5 Flash-Lite in context; scored on 160 images of the 10 held-out combinations.

Setup

Grid. 6 colors × 6 shapes = 36 combinations. Ten are held out of every training set, example set and unlabeled pool, and used only for scoring.

Example set	Combinations	Property
cross	11: one full row and one full column	every color and shape, none tied to one partner
random	11 of the 26 shown	same budget, no design
confounded	6: each color with one shape	every word, but attributes never vary independently

Settings. (a) a small JAX CNN with color and shape heads, trained on 12,000 images; (b) linear heads on frozen Gemini image embeddings, with one label per attribute or one per combination; (c) in context, with made-up two-word names (“dax wug”) that must be learned from the examples, color word or shape word first; (d) in-context labels used as post-training data.

Findings

1. **After pretraining, 11 examples cover the grid.** The cross gives **100%** in post-training (20/20 seeds, all 25 other combinations) and **64/64** in context across Gemini 3.5 Flash-Lite, Gemini 3.1 Flash-Lite and Gemma 4 26B-A4B. A CNN trained from scratch on 26 combinations gets **30%**: colors right (98%), shapes not (31%).
2. **Which combinations matters more than how many.** Random 11 reach 82%. Confounded 6 reach **0%** in post-training, since the labels never say which word names which attribute. One label per combination also gets 0%.
3. **In context, the language prior fills the gap.** With confounded examples, all 64 answers follow one of the two readings the examples allow, and 54/64 take the first word as the color, as in English: right when the language puts color first (27/32), wrong when it puts shape first (5/32).
4. **In-context labels work as post-training data.** Labels from the model in context (16/20 right) lift confounded post-training from **0%** to **100%**. With the word order reversed, the labels (5/20 right, 15 swapped) pass the error on: 1%, with color and shape swapped on 92% of images.

What it means

Composition is cheap after pretraining, not before it: **C + S − 1 examples cover C × S combinations**, provided the examples are deconfounded and the targets are factorized (one label per attribute). Where post-training data are confounded, as natural data usually are, the model’s own in-context labels can fill the gap, and they carry its priors with them.


Next

The pilot is a perception version of the augmentation in Lampinen et al. (2025), who found that in-context learning generalizes more flexibly than fine-tuning and improved fine-tuning by adding in-context inferences to its data. Next: real attribute-object pairs that natural data confound (material and object in images, verb and object in video), and compounds whose parts change each other’s meaning (“red wine”, “fake gun”), where an additive prior should fail. The open question is when the in-context prior can be trusted to fill gaps in post-training data.

The Jain pair on the newest Gemini models

Part 2 · details in pair/

Two dinner requests for Jain guests. The textbook one (“a quick aloo matar recipe”) needs the root-vegetable rule: no potatoes. The rarer one (“dinner during Paryushan”) needs a festival rule on top: many families give up all fresh vegetables and cook from dried or stored food.



Passing responses out of samples. A dinner plan passes if it serves no root or fresh vegetables, or flags each one to check with the guests. · = not run. † = run through Google AI Studio. Each response was graded by two LLM graders (they agreed on 235 of 243); every disagreement was resolved by reading the response.

Findings

1. **The newest Flash model applies the rarer rule; the newest Flash-Lite still does not.** Gemini 3.8 Flash applies it in **10/10** dinner plans (3 Flash 10/10, 3.1 Pro 9/9). Gemini 3.5 Flash-Lite applies it in **0/10** (3.1 Flash-Lite 0/10, Gemma 4 0/10). The small models do handle the textbook rule (27/30).
2. **The rule is missing, not the reasoning.** Asked directly what Jains avoid during Paryushan, the small models state the stricter rule in 1/30 answers (most say only “green leafy vegetables”); the larger models do in 12/12.
3. **Context helps; thinking and examples do not.** One sentence stating the rule lifts Gemma 4 to 10/10 and 3.1 Flash-Lite to 7/10. A high thinking level gives 0/20, and a worked example of combining kosher and Passover rules gives 1/30.
4. **The newest small model also misfiles a category.** Given the rule, 3.5 Flash-Lite restates it in 10/10 answers, yet 8/10 menus still add fresh curry leaves to the tempering.

How the two parts connect

Both point the same way. Composition is cheap when the parts are already known: 11 examples cover 36 combinations after pretraining, and once the rarer rule is supplied in context, Gemma 4 combines it with the dinner request in 10 of 10 answers. It fails when a part is missing, as the festival rule is in the small models, and more thinking does not recover it (0/20 at a high thinking level).

Method

Gemini API with model-default settings and no search grounding, 2 and 3 November 2026; 10 samples per model and prompt where the free tier allowed (exceptions are visible in the table). The graders, Gemini 3.5 and 3.1 Flash-Lite, list each recommended food and classify it at temperature 0; verdicts then follow fixed rules.

Caveats

Part 1: synthetic images on a 6 × 6 grid; post-training means light heads on frozen embeddings, not fine-tuning the model; 8 to 16 in-context trials per cell with one prompt template; the pilot uses one image per unlabeled combination and one teacher model. Part 2: 10 samples per cell and one wording per prompt; the graders are small models, checked by hand on every disagreement.

References

A. K. Lampinen, A. Chaudhry, S. C. Y. Chan, C. Wild, D. Wan, A. Ku, J. Bornschein, R. Pascanu, M. Shanahan, J. L. McClelland. On the generalization of language models from in-context learning and finetuning: a controlled study. arXiv:2505.00661, 2025.

Paryushan practice: JainGPT, “What Jains Eat During Paryushan” (jaingpt.com/guides/paryushan-food-rules); Wikipedia, “Jain vegetarianism” (the narrower leafy-greens reading).

Code, data and per-run results: github.com/RS-010806/composition (MIT License).