

TEM Enterprise Product Preview Technical Submission

Prepared for Pratham Agarwal, IIM Bangalore

Post-meeting submission | 14 September 2026 | Application release 81f7a0b

This submission records the implemented website and freight-emissions demonstration, the reasons for the principal design decisions, and the evidence used to verify the work. The deployed application and editable source are available for review.




Figure 1. Desktop and mobile views of production build 81f7a0b. The desktop view supports scenario comparison; the mobile view presents inputs before the illustrative scene.

Implemented scope

The delivery comprises a responsive landing page, immediate emissions estimator, NIFTY 500 company lookup, editable shipment workspace, road/rail/ocean/air calculations, mode and monthly analytics, a validation demonstration, and a stateless analysis API. The workspace exports CSV, PDF and a Power BI import pack.

Audience and data. The principal audience is sustainability and supply-chain teams at India-focused listed enterprises. The official NIFTY 500 source snapshot contains 501 records, retrieved on 14 September 2026. Company names are real; shipment activity and resulting emissions are synthetic examples, not customer data.

Institutional and certification references concern the original product. The [SGS statement for TEMT v1.3](#) does not certify this separate demonstration engine. No exclusivity or customer relationship is asserted.

[Deployed application](#) | [Source repository](#)

1. Calculation method and data

The browser and server import the same TypeScript calculator, version temt-demo-1.0.0. Each accepted transport leg is evaluated using a published well-to-wheel (WTW) default factor. This includes fuel or energy supply and vehicle operation within the stated factor boundary.

Emissions (kg CO₂e) = tonnes × kilometres × factor (kg CO₂e / tonne-km)

Profile	Factor	Published scope and reference
Road: India diesel HCV	0.0663	30–50 t gross vehicle weight; GLEC v3.2, p. 106
Rail: India	0.0106	Mixed national traction; p. 97
Ocean: dry container	0.01145	Middle East/India; converted from 114.5 g/TEU-km at 10 t/TEU; p. 112
Air: short haul	1.363	Distance ≤1,500 km; p. 94
Air: long haul	0.788	Distance >1,500 km; p. 94

All factors are kg CO₂e per tonne-km. Source: [Smart Freight Centre, GLEC Framework v3.2 \(October 2025\)](#). Source URLs and assumptions are retained with the factor records.

Default estimator arithmetic

For 1,000 tonnes travelling 1,000 km by road, the baseline is $1,000 \times 1,000 \times 0.0663 = 66,300$ kg CO₂e. Moving 30% of the same activity to rail gives $(700 \times 1,000 \times 0.0663) + (300 \times 1,000 \times 0.0106) = 49,590$ kg CO₂e. The estimated difference is 16,710 kg (16.71 t), or 25.2036%.

This compares equal transport activity and distance. It does not assess route availability, terminal movements, first/last-mile distances, capacity, cost or an operationally feasible rail substitution.

Factor and record assumptions

Published defaults already include their stated adjustments: road uses a 5% distance adjustment, 68.3% load and 14.4% empty running; ocean uses 70% fleet loading and 15% distance adjustment. Air uses a 55% belly/45% freighter mix and the published 95 km adjustment. These adjustments are not applied again. No additional aviation radiative-forcing multiplier is added. India road and rail defaults are preliminary estimates.

Each row requires shipmentId, legIndex, date, subsidiary, mode, profile, tonnes and kilometres. Dates use YYYY-MM-DD. Optional origin and destination labels describe the leg. Accepted legs aggregate by mode, month and subsidiary; filters act after validation. Compensated summation and unrounded intermediate values limit avoidable numerical error. Display rounding does not alter exported calculation inputs.

2. Data validation and API controls




Figure 2. Production-build validation example: three accepted legs across two shipments produce 1,394.33 kg CO₂e. The missing-load control is visible but inactive.

Validation rules. Required identifiers must be non-empty and bounded in length. Leg indices must be positive integers, dates must be real calendar dates, and tonnes and kilometres must be finite and positive. Mode and profile must agree; air profiles must match the distance threshold. Numerical-range and maximum-row checks apply.

Shipment integrity. An invalid leg, duplicate leg index or missing index in a shipment excludes that entire identifiable shipment. Invalid rows without an identifiable shipment are rejected individually. Introducing the missing load in the example excludes both TEMT-002 legs; the remaining TEMT-001 leg produces 1,034.28 kg CO₂e.

CSV import. Imports require a .csv file, all required headers and an explicit profile for every row, with limits of 2 MiB and 1,000 legs. Import is all-or-nothing: any parse or validation failure leaves the existing dataset unchanged. Imported rows remain in the browser until the user requests server analysis.

Endpoint	Contract
GET /api/health	Status, engine version and persistence: none; /health is an alias.
GET /api/factors	Versioned factors, methodology boundary and maximum leg count.
POST /api/analyze	application/json; body {"rows": [...]}; returns analysis and validation results.

The API uses Helmet headers, no-store responses, a 2 MiB JSON limit and a default 60-request/minute/IP limit on factors and analysis. Health and CORS preflight requests are outside that limit. Exact allowed origins govern browser access; requests without an Origin header remain possible. CORS is not authentication. Controlled error responses omit internal details. Shipment bodies are processed in memory without persistence or request-body logging.

3. Architecture and interface decisions

Deployment. Next.js, React and Tailwind produce a static frontend served from Render's CDN. A separate free Express service in Singapore performs requested analyses. Both use the same calculator package; no database is required for this demonstration. CSS animation, SVG scenes, Recharts and Lucide support the interface.

Availability behaviour. The landing estimator works locally without waiting for the API. During server analysis, the interface offers a manual 'Process in browser' action after eight seconds. The request times out after 90 seconds; errors or timeout use the local engine. Dataset edits invalidate stale responses, and the interface identifies the result's processing origin. The free API may suspend when idle.




Figure 3. Landing reporting from production build 81f7a0b, and the retained public workspace capture. The visible FMCG dataset is unchanged: 24 shipments, 32 legs and 453.64 t CO₂e.

Evaluation sequence. A visitor first changes freight weight, distance and rail share, then opens the workspace with those three inputs preserved in the URL. Sector and transport-mode examples expose calculated activity. The reporting preview switches between mode and month views and provides exact chart data. This sequence connects the initial estimate to inspectable records.

Interaction and accessibility. Connect, Measure, Compare and Report chapters provide context without blocking the estimator. Playback has pause and manual controls, pauses off-screen or in a hidden tab, and uses manual playback for reduced-motion or supported data-saving preferences. Mobile layouts prioritise the result and native input controls. These are design decisions, not evidence of conversion improvement.

Reporting. The current filtered view can be exported as CSV, a PDF report or a Power BI import pack. Outputs preserve factor/version context, relevant inputs and validation information. CSV formula-injection protection is tested. The Power BI pack supports importing files; it does not establish a live Power BI connection.

4. Verification, delivery and next steps

Release 81f7a0b passed 112 automated tests, TypeScript checks, source-integrity checks and production builds. Tests cover calculator validation, imports/exports, API controls and estimator-to-workspace parity. The [successful CI run](#) records the validated application release.

Public-site Lighthouse 13.4.1	Desktop	Mobile
Performance score	100	91
Accessibility / best practices / SEO	100 / 100 / 100	100 / 100 / 100
First contentful paint	0.3 s	2.0 s
Largest contentful paint	0.6 s	2.9 s
Total blocking time	0 ms	50 ms (54 ms raw)
Cumulative layout shift	0	0

Public audits ran on 14 September 2026 at 03:08 IST. Mobile used simulated 4× CPU slowdown and 150 ms RTT; desktop used 1× and 40 ms RTT. Performance floors of 95 desktop and 90 mobile were met. These are laboratory observations on a shared machine, not field Core Web Vitals or an accessibility certification.

API observation. The one-leg default scenario returned 66,300 kg CO₂e with exact browser/server parity. The observed engine duration was 1.82 ms and HTTP duration, including response transfer, was 112.83 ms. An initial health request took 23.25 s with unknown prior idle time. These individual observations do not establish latency guarantees or controlled cold-start performance.

Review material

[Live application](#) | [Analysis workspace](#) | [Source repository](#)

[Sample shipment CSV](#) | [Sample PDF report](#) | [Power BI import pack](#)

The repository retains source references, UX rationale, test records, raw Lighthouse JSON and the API measurement file in docs/. Screenshots document the interface; four show the local production build, while the unchanged workspace capture is from the prior public release.

Proposed production work and limitations

Before enterprise use, proposed work includes SSO and role-based access, tenant isolation, governed factor updates, persistent audit trails, reviewed data retention, approved logistics integrations, monitored paid capacity and repeatable load testing. None of these controls is represented as implemented in this stateless preview.

Default-factor scenarios are not carrier measurements, a complete corporate inventory, or assured reporting. Production decisions require verified activity data and reviewed methodological boundaries. Partner references, company names and original-product certification do not establish integration, endorsement or certification of this demonstration.

[IIMB: DPIIT adoption and ULIP](#) | [NSE: NIFTY 500 source snapshot](#)