

Problem Scenario: hi

Loudacre Inc. is a leading electronics retailer

- More than 1,000 brick and mortar stores
- Loudacre also has a thriving e-commerce Web site

Loudacre has hired you to help find value in its data

- You will process and analyse data from internal and external sources
- Identify opportunities to increase revenue
- Find new ways to reduce costs
 - Help other departments achieve their goals

Ques 1: List all the databases in the RDBMS

Ans: `sqoop list databases --connect`

`jdbc:mysql://localhost/ --username training --password training`

Ques 2: Make a directory on HDFS named as /Loudacre

Ans: `hdfs dfs -mkdir /user/training/Loudacre`

Ques 3: Import accounts, accountdevice, webpage into the directory /Loudacre separately

Ans: a) `scoop import --connect jdbc:mysql://localhost/ --username training -password training -table accounts -target -dir /user/training/Ironhack/loudacre/accounts`

b) `sqoop import --connect jdbc:mysql://localhost/ --username training -password training -table accountdevice -target -dir /user/training/Ironhack/loudacre/accountdevice`

c) `scoop import --connect jdbc:mysql://localhost/ --username training -password training -table webpage -target -dir /user/training/Ironhack/loudacre/webpage`

Ques 4: Import table accounts in /user/training changing the mappers to 10 and changing the field terminator to ':'. Also split them on the basis of state.

Ans : `sqoop import --m 10 --connect jdbc:mysql://localhost/loudacre --username training --password training --table accounts --target-dir /user/training/account --fields-terminated-by : --split-by state`

Ques 5: Import the Complete names of people having accounts in Loudacre

ex: firstname <space> last_name

ex: Britney Spears

Ans: sqoop import \

--connect jdbc:mysql://localhost/loudacre \

--username training \

--password training \

--target-dir

/user/training/ironhack/loudacre/accountsbasedonname \

--query "SELECT acct_num, CONCAT(first_name,'
,last_name) AS full_name FROM accounts WHERE \
\$CONDITIONS" \

--split-by acct_num \

--m 1

Ques 6: Import only those records where device_id is between 10 and 50 in table accountdevice.

Ans - sqoop import --connect

jdbc:mysql://localhost/loudacre --username training --
password training --target-dir

/user/training/ironhack/loudacre/accountsname --query
"SELECT device_id,id FROM accountdevice WHERE
device_id BETWEEN 1 and 50 AND \ \$CONDITIONS" --
split-by id

Ques 7: Copy the acct no. from the table customerservicerep where customer name is Roger Miller.

Ans: `sqoop import --connect jdbc:mysql://localhost/loudacre --username training --password training --table customerservicerep --target-dir /user/training/ironhack/loudacre/customername --where "cs_name = 'Roger Miller'"`