

A Polynomial Time Subsumption Algorithm for \mathcal{EL}^\perp under Rational Closure

Giovanni Casini, Umberto Straccia, Thomas Meyer

July 10, 2015

Abstract

In this paper we consider Description Logics (DLs) under Rational Closure (RC), a well-known framework for non-monotonic reasoning in DLs. Specifically, we address the concept subsumption decision problem under RC for the DL \mathcal{EL}^\perp , a notable DL representative of the OWL profile OWL EL.

Previous subsumption decision procedures for DLs under RC have been defined for more expressive DLs. These procedures, however, do not scale down in the sense that they remain exponential for \mathcal{EL}^\perp , even if the monotonic subsumption decision problem is polynomial. Our main contribution here is to define a polynomial time subsumption procedure for \mathcal{EL}^\perp under RC. We also adapt it to known extensions of RC for DLs, such as Lexicographic Closure, Defeasible Inheritance-based DLs, and two versions of Relevant Closure. Since the basic language requirement is to have conjunction on the left-hand side of so-called Generalised Concept Inclusions, we show that our procedure can be adapted to any other DL having this feature as well.

1 Introduction

Description logics (DLs) [3] provide the logical foundation of formal ontologies of the OWL family [48].

Among the various extensions proposed to enhance the representational capabilities of DLs, endowing them with non-monotonic features is still a main issue, as documented by the past 20 years of technical development [4, 5, 7, 10, 13, 14, 18, 21, 22, 23, 24, 29, 33, 36, 37, 41, 45, 46, 52, 54]. We refer the reader to the recent work of Bonatti et al. [7] and Giordano et al. [33] for discussions about the various approaches.

We recall that a typical problem that can successfully be addressed using non-monotonic formalisms is reasoning with ontologies in which some classes are exceptional w.r.t. some properties of their superclasses, as illustrated next [53].

Example 1 *We know that blood cells of a cow, avian red blood cells and mammalian red blood cells are vertebrate red blood cells, and that vertebrate red blood cells normally have a cell membrane. We also know that vertebrate red blood cells normally have a nucleus, but that mammalian red blood cells normally don't.*

A classical formalisation of the ontology above would imply that mammalian red blood cells do not exist, since, being a subclass of vertebrate red blood cells, they would have a nucleus,

but they are an atypical subclass that does not have a nucleus. Therefore, mammalian red blood cells would and would not have a nucleus at the same time. Unlike a classical approach, the use of a non-monotonic formalism may allow to deal with such exceptional classes.

Between the various proposals to inject non-monotonicity into DLs, the preferential approach seems to be a particularly promising one, mostly because it is based on one of the most comprehensive and successful frameworks for non-monotonic reasoning in the propositional case, namely the *KLM approach* [40]. One of the main constructions in the preferential approach is *Rational Closure* (RC) [43]. RC is a procedure that has some interesting properties: the conclusions are intuitive, and the decision procedure can be reduced to a series of classical decision problems, sometimes preserving the computational complexity of the classical decision problem too. In recent years there has been a flurry of activity about DLs and RC [12, 16, 17, 18, 19, 20, 21, 25, 26, 27, 34, 35, 36].

As pointed out by Bonatti et al. [7], usually, non-monotonic extensions do not preserve the tractability of low-complexity DLs [9, 15, 18, 28, 32, 45],¹ which is also the case for current algorithms for DLs under RC. Specifically, procedures developed so far to reason with DLs under RC need a DL language that is closed under the propositional operators. A drawback of such a requirement is that we cannot apply RC directly to low-complexity DL languages, such as \mathcal{EL}^\perp [2] whose subsumption decision problem is in P, without losing the computational benefit of such languages. That is, these procedures do not scale down, in the sense that they remain exponential for \mathcal{EL}^\perp [18].

The main contribution of our work is to show here that, despite the expressive limitations of \mathcal{EL}^\perp , we can effectively define a procedure that implements RC for \mathcal{EL}^\perp in such a way that deciding subsumption under RC for \mathcal{EL}^\perp remains polynomial. This result is of particular importance as \mathcal{EL}^\perp is closely related to the semantic web language standard OWL EL [50], an OWL 2 profile [49]. We then also illustrate how to adapt our procedure to various extensions of RC for DLs, such as Lexicographic Closure [20], Defeasible Inheritance-based DLs [19], and Relevant Closures [16]. Eventually, as the basic language requirement is to have conjunction on the left-hand side of so-called Generalised Concept Inclusion [3], our procedure can be adapted to any other DL having this feature as well.

We proceed as follows: Section 2 introduces the DL \mathcal{EL}^\perp and Rational Closure; Section 3 contains the main result of the paper, that is, a polynomial procedure to decide subsumption under RC for defeasible \mathcal{EL}^\perp ; in Section 4, we adapt our procedure to various extensions of RC for DLs. Section 5 concludes and addresses related work.

All relevant proofs are in the appendix.

2 Preliminaries

In the following we briefly present the DL \mathcal{EL}^\perp and the previously proposed procedure to decide subsumption under Rational Closure for the DL \mathcal{ALC} .

2.1 The Description Logic \mathcal{EL}^\perp

\mathcal{EL}^\perp is the DL \mathcal{EL} with the addition of the empty concept \perp [2]. Note that considering \mathcal{EL} only would not make sense in our case as \mathcal{EL} knowledge bases are always concept-

¹Among the few exceptions are proposals by Bonatti et al. [7, 9].

satisfiable, while the notion of defeasible reasoning is built over a notion of conflict (see Example 1) which needs to be expressible in the language.

The vocabulary is given by a set of *atomic concepts* $N_{\mathcal{C}} = \{A_1, A_2, \dots\}$ and a set of *atomic roles* $N_{\mathcal{R}} = \{r_1, r_2, \dots\}$. Concept expressions C, D, \dots are built according to the following syntax:

$$C, D \rightarrow A \mid \top \mid \perp \mid C \sqcap D \mid \exists r.C .$$

An *ontology* \mathcal{T} (or *TBox*, or *knowledge base*) is a finite set of *Generalised Concept Inclusion* (GCI) axioms $C \sqsubseteq D$ (C is subsumed by D), meaning that all the objects in the concept C are also in the concept D . We use the expression $C = D$ as a shorthand for having both $C \sqsubseteq D$ and $D \sqsubseteq C$. An *interpretation* is a pair $\mathcal{I} = \langle \Delta^{\mathcal{I}}, \cdot^{\mathcal{I}} \rangle$, where $\Delta^{\mathcal{I}}$ is a non-empty set, called *interpretation domain* and $\cdot^{\mathcal{I}}$ is an *interpretation function*

1. mapping atomic concepts A into subsets $A^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}}$;
2. mapping roles r into a subset $r^{\mathcal{I}} \subseteq \Delta^{\mathcal{I}} \times \Delta^{\mathcal{I}}$.

An interpretation \mathcal{I} *satisfies (is a model of)* $C \sqsubseteq D$ if $C^{\mathcal{I}} \subseteq D^{\mathcal{I}}$, denoted $\mathcal{I} \models C \sqsubseteq D$. \mathcal{I} *satisfies (is a model of)* an ontology \mathcal{T} if it satisfies each axiom in it. An axiom α is *entailed* by a \mathcal{T} if any model of \mathcal{T} is a model of α , denoted as $\mathcal{T} \models \alpha$.

2.2 Rational Closure in \mathcal{ALC}

We briefly recap RC for the DL \mathcal{ALC} [12, 18, 27], which in turn is based on its original formulation for Propositional Logic [43]. As mentioned earlier, there is work addressing RC for DLs as well [25, 35, 34, 36].

A *defeasible GCI* axiom is of the form $C \sqsubset D$, that is read as ‘Typically, an instance of C is also an instance of D ’. We extend ontologies with a *DBox* \mathcal{D} , i.e. finite set of defeasible GCIs and denote an ontology as $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, where \mathcal{T} is a TBox and \mathcal{D} is a DBox.

Example 2 We can formalise the information in Example 1 with the following ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ with

$$\begin{aligned} \mathcal{T} = \{ & \text{CRBC} \sqsubseteq \text{MRBC}, \\ & \text{ARBC} \sqsubseteq \text{VRBC}, \\ & \text{MRBC} \sqsubseteq \text{VRBC}, \\ & \exists \text{hasN}.\top \sqcap \text{NotN} \sqsubseteq \perp \} \end{aligned}$$

$$\begin{aligned} \mathcal{D} = \{ & \text{VRBC} \sqsubset \exists \text{hasCM}.\top, \\ & \text{VRBC} \sqsubset \exists \text{hasN}.\top, \\ & \text{MRBC} \sqsubset \text{NotN} \} . \end{aligned}$$

Given a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, RC responds to some basic desiderata: the axioms in \mathcal{T} and \mathcal{D} are included into the set of the derivable axioms, that moreover satisfy the following properties.

$$(\text{Ref}) \ C \sqsubset C \quad (\text{LLE}) \ \frac{\models C = D, \ C \sqsubset E}{D \sqsubset E}$$

$$\begin{array}{c}
\text{(And)} \frac{C \sqsubseteq D, C \sqsubseteq E}{C \sqsubseteq D \sqcap E} \quad \text{(Or)} \frac{C \sqsubseteq E, D \sqsubseteq E}{C \sqcup D \sqsubseteq E} \\
\text{(RW)} \frac{C \sqsubseteq D, \models D \sqsubseteq E}{C \sqsubseteq E} \quad \text{(CM)} \frac{C \sqsubseteq D, C \sqsubseteq E}{C \sqcap D \sqsubseteq E} \\
\text{(RM)} \frac{C \sqsubseteq E, C \not\sqsubseteq \neg D}{C \sqcap D \sqsubseteq E}
\end{array}$$

Reflexivity (Ref), Left Logical Equivalence (LLE), Right Conjunction (And), Left Disjunction (Or), and Right Weakening (RW) are all properties that correspond to well-known properties of the classical subsumption relation \sqsubseteq . Cautious Monotonicity (CM) and Rational Monotonicity (RM) are constrained forms of Monotonicity that are useful and desirable in modelling defeasible reasoning. (CM) guarantees that our inferences are cumulative, that is, whatever we can conclude about typical C s (e.g. that they are in D), we can add such information to C ($C \sqcap D$) and still derive all the information associated to typical C s ($C \sqcap D \sqsubseteq E$). The stronger principle (RM) models the principle of *presumption of typicality*, that is, if the typical elements of a class C satisfy certain properties (e.g. E) and we are not informed that a subclass $C \sqcap D$ of C is atypical ($C \not\sqsubseteq \neg D$), then we can assume that the typical elements of $C \sqcap D$ satisfy all the properties characterising the typical elements of C ($C \sqcap D \sqsubseteq E$). We refer to the work of Briitz et al.[12] and Lehmann and Magidor [43] for a deeper explanation of the meaning of such properties and why they are desirable for modelling defeasible reasoning.

RC is a form of inferential closure that satisfies all the properties above; it is based on the semantic notion of ranked interpretation and on the directly connected notion of ranked entailment, which we illustrated next.

Definition 1 (Ranked interpretation) A ranked interpretation is a triple $R = \langle \Delta^R, \cdot^R, \preceq^R \rangle$, where Δ^R and \cdot^R are as in the classical DL interpretations, while \preceq^R is a modular preference relation, that is, a preorder satisfying the following property:

Modularity: \preceq^R is modular if and only if there is a ranking function $rk : \Delta^R \rightarrow \mathbb{N}$ s.t. for every $x, y \in \Delta^R$, $x \preceq^R y$ iff $rk(x) \leq rk(y)$.²

$a \preceq^R b$ means that the individual a is considered at least as typical as the individual b . Furthermore, a modular preorder allows to partition the domain Δ^R of a ranked interpretation R into a sequence of *layers*,

$$\langle L_0^R, \dots, L_n^R, \dots \rangle,$$

where for every object x , $x \in L_0^R$ iff $x \in \min_{\preceq^R}(\Delta^R)$ and $x \in L_{i+1}^R$ iff $x \in \min_{\preceq^R}(\Delta^R \setminus \bigcup_{0 \leq j \leq i} L_j^R)$. From this partition, we can define the *height* of an individual a as

$$h_R(a) = i \text{ iff } a^R \in L_i^R.$$

²This definition of modularity is stronger than the classical one ([43], p.21), which states that “a preorder \preceq over a set Δ is *modular* iff there is a totally ordered set Ω (let \leq be the total preorder defined over Ω) and a function $r : \Delta \rightarrow \Omega$ s.t. for every $a, b \in \Delta$, $a \preceq b$ iff $r(a) \leq r(b)$ ”. Our definition of modularity implies that the order \preceq is well-founded, a property that is not implied by the definition above. While this difference is relevant to prove a representation result associating the class of the rational defeasible subsumption relations to the ranked interpretations, it is irrelevant for our purposes.

The lower the height, the more typical is the individual in the interpretation. We can also think of a level of typicality for the concepts: the *height* of a concept in an interpretation R ($h_R(C)$) as the lowest (most typical) layer in which the concept appears: i.e.

$$h_R(C) = i \text{ iff } \min_{\preceq^R}(C^R) \subseteq L_i^R .$$

Definition 2 (Ranked model) *An interpretation $R = \langle \Delta^R, \cdot^R, \preceq^R \rangle$ satisfies (is a model of) $C \sqsubseteq D$ (denoted $R \models C \sqsubseteq D$) iff $C^R \subseteq D^R$, and satisfies (is a model of) $C \sqsubset D$ iff $\min_{\preceq^R}(C^R) \subseteq D^R$ (denoted $R \models C \sqsubset D$). R satisfies (is a model of) $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ iff $R \models \alpha$ for all axioms $\alpha \in \mathcal{T} \cup \mathcal{D}$.*

Hence, $C \sqsubset D$ is satisfied iff all the most typical individuals in C^R are also in D^R . We say that two ontologies are *rationally equivalent* iff they are satisfied by exactly the same ranked models, and that an ontology is *rationally consistent* iff there is at least a ranked model that satisfies it.

Remark 1 *Note that from the above definition of the satisfiability of an axiom $C \sqsubset D$ we obtain the following correspondence: for every ranked model R ,*

$$R \models C \sqsubseteq \perp \text{ iff } R \models C \sqsubset \perp .$$

This allows for the translation of every classical axiom $C \sqsubseteq D$ into a defeasible axiom $C \sqcap \neg D \sqsubset \perp$. Note also that such a translation is not feasible in \mathcal{EL}^\perp , as \neg is not supported in \mathcal{EL}^\perp .

Now, the definition of ranked entailment follows directly from the notion of ranked model. So, let $\mathfrak{R}^\mathcal{K}$ be the class of the ranked models of an ontology \mathcal{K} .

Definition 3 (Ranked Entailment) *Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and a defeasible axiom $C \sqsubset D$, \mathcal{K} rationally entails $C \sqsubset D$ (denoted $\mathcal{K} \models_{\mathfrak{R}} C \sqsubset D$) iff $\forall R \in \mathfrak{R}^\mathcal{K}, R \models C \sqsubset D$.*

Ranked entailment has a main drawback, since it is weak from the inferential point of view and does not satisfy the (RM) property [12, 43]. RC is a kind of entailment that extends Ranked Entailment, allowing to overcome such limitations, and we are going to define this notion as next. RC is based on a notion of *exceptionality* that is built on Ranked Entailment.

Definition 4 (Exceptionality) *A concept C is exceptional w.r.t. an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ iff $\mathcal{K} \models_{\mathfrak{R}} \top \sqsubset \neg C$. That is to say, C is exceptional w.r.t. \mathcal{K} iff, for every model $R \in \mathfrak{R}^\mathcal{K}$,*

$$C^R \cap \min_{\preceq^R}(\Delta^R) = \emptyset .$$

An axiom $C \sqsubset D$ is exceptional w.r.t. \mathcal{K} iff C is exceptional.

Intuitively, a concept is exceptional w.r.t. an ontology iff it is not possible to have it satisfied by any typical individual (i.e., an individual in the layer 0, that corresponds to $\min_{\preceq^R}(\Delta^R)$) in any ranked model of the ontology.

Iteratively applied, the notion of exceptionality allows to associate to every concept C a *rank value* w.r.t. an ontology \mathcal{K} in the following way.

1. A concept C has rank 0 ($r_{\mathcal{K}}(C) = 0$) iff it is not exceptional w.r.t. \mathcal{K} , and we set $r_{\mathcal{K}}(C \sqsubseteq D) = 0$ for every defeasible axiom having C as antecedent. The set of the axioms in \mathcal{D} with rank 0 is denoted as \mathcal{D}_0^r .
2. A concept C has rank 1 iff it does not have rank 0 and it is not exceptional w.r.t. the ontology \mathcal{K}^1 composed by \mathcal{T} and the exceptional part of \mathcal{D} , that is $\mathcal{K}^1 = \langle \mathcal{T}, \mathcal{D} \setminus \mathcal{D}_0^r \rangle$. If $r_{\mathcal{K}}(C) = 1$, then we set $r_{\mathcal{K}}(C \sqsubseteq D) = 1$. The set of the axioms in \mathcal{D} with rank 1 is denoted as \mathcal{D}_1^r .
3. In general, C has rank i iff it does not have rank $i - 1$ and it is not exceptional wrt $\mathcal{K}^i = \langle \mathcal{T}, \mathcal{D} \setminus \bigcup_{j=0}^{i-1} \mathcal{D}_j^r \rangle$. If $r_{\mathcal{K}}(C) = i$, then we set $r_{\mathcal{K}}(C \sqsubseteq D) = i$. The set of the axioms in \mathcal{D} with rank i is denoted \mathcal{D}_i^r .
4. By iterating the previous step, we eventually reach a (possibly empty) subset $\mathcal{E} \subseteq \mathcal{D}$ s.t. all the axioms in \mathcal{E} are exceptional.³ If $\mathcal{E} \neq \emptyset$ we define the rank value of the axioms in \mathcal{E} as ∞ , and the set \mathcal{E} is denoted \mathcal{D}_{∞}^r .

As a consequence, according to the procedure above, \mathcal{D} can be partitioned into a sequence $\langle \mathcal{D}_0^r, \dots, \mathcal{D}_n^r, \mathcal{D}_{\infty}^r \rangle$ ($n \geq 0$), where \mathcal{D}_{∞}^r may be possibly empty. The procedure allows to give a rank value to every concept and every defeasible subsumption. Using the rank values we can define the notion of RC as follows:

Definition 5 (Rational Closure) *We say that $C \sqsubseteq D$ is in the RC of an ontology \mathcal{K} iff*

$$r_{\mathcal{K}}(C \sqcap D) < r_{\mathcal{K}}(C \sqcap \neg D) \text{ or } r_{\mathcal{K}}(C) = \infty .$$

Informally, the above definition says that $C \sqsubseteq D$ is in the rational closure of \mathcal{K} if the instances of $C \sqcap D$ are more typical than the instances of $C \sqcap \neg D$.

3 Rational Closure in \mathcal{EL}^{\perp}

We now present a subsumption decision procedure under RC for \mathcal{EL}^{\perp} . To do so, we first introduce a semantic characterisation of RC, and then we build on that a decision procedure for \mathcal{EL}^{\perp} .

The translation of the characterisation of RC, as described in Section 2.2, into a procedure that is adequate for \mathcal{EL}^{\perp} is not immediate. This is due to two main problems. The first one is a theoretical problem, and the second one is a computational one.

Concerning the first issue, let us note that two main structural properties among those presented in Section 2.2, namely (OR) and (RM), cannot be properly expressed in the \mathcal{EL}^{\perp} . Therefore, a defeasible subsumption relation defined over \mathcal{EL}^{\perp} can at most satisfy the set of rules (REF)-(CM), that is, it can be characterised at most as a defeasible subsumption relation corresponding to a *cumulative* relation [40],⁴ which, however, is acknowledged to be inferentially too weak—weaker than Ranked Entailment.

³Since \mathcal{D} is finite, we must reach such a point.

⁴So, we can define a notion of cumulative entailment in the ‘classical’ way. That is, we can decide the consequences of an ontology by taking under consideration all its cumulative models ([40], Section 3.5).

Example 3 *Related to Example 2, we have no piece of information forcing us to conclude that avian red blood cells represent an atypical subclass of vertebrate red blood cell, and so we would like to presume that they actually behave like typical vertebrate red blood cells. That means in the specific case that we should be able to derive that they have a nucleus and a cell membrane. This kind of conclusion, that is the simple inheritance of typical properties by subclasses that do not show any kind of atypicality, is not derivable using cumulative or ranked entailment, while it is possible to derive them if we refer to RC.*

This kind of reasoning is called *presumption of typicality* ([42], Section 3.1): that is, we always assume in our reasoning that we are in the most typical/expected situation that is conceivable, given the information at our disposal.

Even if we cannot express the presumption of typicality in \mathcal{EL}^\perp syntactically, by means of properties like (RM) defined over the defeasible subsumption relation, we can still characterise it semantically. This will allow us then to define also for \mathcal{EL}^\perp the analogous version of RC: namely, an inference operation that preserves the presumption of typicality and allows to infer desirable conclusions by extending Ranked Entailment.

The second issue, the computational one, is about the computational complexity of our procedure. That is, we want also to define a procedure for Rational Closure in \mathcal{EL}^\perp that preserves the polytime complexity of the classical (monotone) subsumption problem for \mathcal{EL}^\perp , which is not the case for the procedure proposed by Britz et al. [12].

3.1 Semantic Characterisation of RC for DLs

As seen in Section 2.2, entailment under RC can be decided using two ingredients:

- the ranking function r based on the notion of ranked entailment.
- the decision rule stating that an axiom $C \sqsubseteq D$ is derivable iff $r(C \sqcap D) < r(C \sqcap \neg D)$.

The second step, as it is, cannot be defined directly in \mathcal{EL}^\perp as concept complementation is not supported. While we can formalise a conflict ($C \sqcap D \sqsubseteq \perp$), we cannot express that two concepts are complementary. Moreover, the procedures for RC so far make use of negation and disjunction to compute the ranking function, and so they are not appropriate for \mathcal{EL}^\perp either.

In order to define a procedure for Rational Closure in \mathcal{EL}^\perp that preserves the computational complexity of \mathcal{EL}^\perp , we have to bypass this expressivity problem. To do so, we proceed in the following way.

1. We give a semantic characterisation of the RC of an ontology \mathcal{K} ;
2. We define a procedure that makes use only of the expressivity of \mathcal{EL}^\perp and is correct and complete w.r.t. the introduced semantic characterisation of RC.

Concerning the first step, the semantical construction we are going to present is inspired by a semantical characterisation of RC for propositional logic by Booth and Paris [11]. Specifically, let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be a defeasible ontology, and let $\mathfrak{R}^\mathcal{K}$ be the class of the ranked models of \mathcal{K} ; also, let Δ be a countable infinite domain, and $\mathfrak{R}_\Delta^\mathcal{K}$ be the set of ranked models of \mathcal{K} that use Δ as domain. The following proposition states that $\mathfrak{R}_\Delta^\mathcal{K}$ is sufficient to define $\models_\mathfrak{R}$, i.e. we can rely on a single countable infinite domain Δ .

Proposition 1 For an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and a defeasible axiom $C \sqsubseteq D$, $\mathcal{K} \models_{\mathfrak{R}} C \sqsubseteq D$ iff

$$\forall R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}, R \models C \sqsubseteq D .$$

Using the set $\mathfrak{R}_{\Delta}^{\mathcal{K}}$, if it is not empty, we define a new ranked model $R_{\mathcal{K}}^{\cup} = \langle \Delta^{R_{\mathcal{K}}^{\cup}}, \cdot^{R_{\mathcal{K}}^{\cup}}, \prec^{R_{\mathcal{K}}^{\cup}} \rangle$ in the following way. Concerning the domain $\Delta^{R_{\mathcal{K}}^{\cup}}$, we consider in $\Delta^{R_{\mathcal{K}}^{\cup}}$ one copy of Δ for each model in $\mathfrak{R}_{\Delta}^{\mathcal{K}}$. Specifically, given $\Delta = \{a, b \dots\}$, we indicate as $\Delta_R = \{a_R, b_R \dots\}$ a copy of the domain Δ associated to an interpretation $R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}$ and define

$$\Delta^{R_{\mathcal{K}}^{\cup}} = \bigcup_{R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}} \Delta_R .$$

Also the interpretation function and the preferential relation are defined referring directly to the models in $\mathfrak{R}_{\Delta}^{\mathcal{K}}$. That is, for every $a_R, b_{R'} \in \Delta^{R_{\mathcal{K}}^{\cup}}$,

- $a_R \in A^{R_{\mathcal{K}}^{\cup}}$ iff $a \in A^R$, for every atomic concept A ;
- $\langle a_R, b_{R'} \rangle \in r^{R_{\mathcal{K}}^{\cup}}$ iff $R = R'$ and $\langle a, b \rangle \in r^R$, for every role r ;
- $a_R \preceq^{R_{\mathcal{K}}^{\cup}} b_{R'}$ iff $h_R(a) \leq h_{R'}(a)$.

It is easy to prove by induction on the construction of the concepts that, for every $a_R \in \Delta^{R_{\mathcal{K}}^{\cup}}$ and for every concept C , $a_R \in C^{R_{\mathcal{K}}^{\cup}}$ iff $a \in C^R$. Eventually, we can prove that $R_{\mathcal{K}}^{\cup}$ is a ranked model characterising the Rational Closure of \mathcal{K} , as in Definition 5.

Proposition 2 Let \mathcal{K} be an ontology having a ranked model. Then $R_{\mathcal{K}}^{\cup}$ is a model of \mathcal{K} and for any pair of concepts C, D , $R_{\mathcal{K}}^{\cup} \models C \sqsubseteq D$ iff $r_{\mathcal{K}}(C \sqcap D) < r_{\mathcal{K}}(C \sqcap \neg D)$ or $r_{\mathcal{K}}(C) = \infty$.

An immediate consequence is the following result.

Corollary 1 $C \sqsubseteq D$ is in the RC of a KB \mathcal{K} iff $R_{\mathcal{K}}^{\cup} \models C \sqsubseteq D$.

This concludes the first part.⁵

3.2 Subsumption Decision Procedure for \mathcal{EL}^{\perp} under RC

Now we are going to introduce a decision procedure for RC. Unlike the algorithm in [12], this method neither uses negation nor disjunction and is directly applicable to \mathcal{EL}^{\perp} .

Specifically, consider a defeasible \mathcal{EL}^{\perp} ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ with $\mathcal{T} = \{E_1 \sqsubseteq F_1, \dots, E_m \sqsubseteq F_m\}$ and $\mathcal{D} = \{C_1 \sqsubseteq D_1, \dots, C_n \sqsubseteq D_n\}$. We will define two procedures: the first one is a *ranking* procedure, that transforms the initial ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ into a rationally equivalent ontology $\mathcal{K}^* = \langle \mathcal{T}^*, \mathcal{D}^* \rangle$, where \mathcal{D}^* is partitioned into a sequence $\mathcal{D}_0, \dots, \mathcal{D}_n$, with each \mathcal{D}_i containing the defeasible axioms with rank i ; the second one uses \mathcal{K}^* to decide whether an axiom $C \sqsubseteq D$ is in the RC of \mathcal{K} .

⁵ An alternative semantic characterisation of RC for DLs has been given by Giordano et al. [27]. It follows immediately that the two are equivalent.

Procedure Exceptional(\mathcal{T}, \mathcal{E})

Input: \mathcal{T} and $\mathcal{E} \subseteq \mathcal{D}$

Output: $\mathcal{E}' \subseteq \mathcal{E}$ such that \mathcal{E}' is the set of exceptional axioms w.r.t. $\langle \mathcal{T}, \mathcal{E} \rangle$

```

1  $\mathcal{E}' := \emptyset$ ;
2  $\mathcal{T}_{\delta_{\mathcal{E}}} = \mathcal{T} \cup \{C \sqcap \delta_{\mathcal{E}} \sqsubseteq D \mid C \sqsubset D \in \mathcal{E}\}$ , where  $\delta_{\mathcal{E}}$  is a new atomic concept;
3 foreach  $C \sqsubset D \in \mathcal{E}$  do
4   if  $\mathcal{T}_{\delta_{\mathcal{E}}} \models C \sqcap \delta_{\mathcal{E}} \sqsubseteq \perp$  then
5      $\mathcal{E}' := \mathcal{E}' \cup \{C \sqsubset D\}$ ;
6 return  $\mathcal{E}'$ 

```

3.2.1 The Ranking Procedure

Given an ontology $\langle \mathcal{T}, \mathcal{D} \rangle$, the ranking procedure is defined by means of two procedures: one for finding exceptional axioms and one for determining the rank value of axioms, as defined in Section 2.2.

In the following, given an ontology $\langle \mathcal{T}, \mathcal{E} \rangle$, and a new atomic concept $\delta_{\mathcal{E}}$, we define $\mathcal{T}_{\delta_{\mathcal{E}}}$ as

$$\mathcal{T}_{\delta_{\mathcal{E}}} = \mathcal{T} \cup \{C \sqcap \delta_{\mathcal{E}} \sqsubseteq D \mid C \sqsubset D \in \mathcal{E}\} . \quad (1)$$

Find exceptional axioms: given an ontology $\langle \mathcal{T}, \mathcal{E} \rangle$, the first step is to compute the exceptional axioms $C \sqsubset D$ in \mathcal{E} . To do so, given $\mathcal{T}_{\delta_{\mathcal{E}}}$ we check if

$$\mathcal{T}_{\delta_{\mathcal{E}}} \models C \sqcap \delta_{\mathcal{E}} \sqsubseteq \perp .$$

Remark 2 *Informally, we introduce the atom δ as a way of representing the information that characterises the lowest rank. Hence, its introduction is aimed at the formalisation in the classical framework of the typicality of the lowest layer: $C \sqcap \delta$ is introduced to represent the individuals falling under C and lying in the lowest layer.*

We can prove that this procedure is correct w.r.t. the exceptionality step of the RC characterisation given in Section 2.2 (see Definition 4).

Proposition 3 *For an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{E} \rangle$ and $C \sqsubset D \in \mathcal{E}$, if $\mathcal{T}_{\delta_{\mathcal{E}}} \models C \sqcap \delta_{\mathcal{E}} \sqsubseteq \perp$ then for every model $R \in \mathfrak{R}^{\mathcal{K}}$, $C^R \cap \min_{\prec R}(\Delta^R) = \emptyset$.*

Hence, the set $\mathcal{E}' = \{C \sqsubset D \in \mathcal{E} \mid \mathcal{T}_{\delta_{\mathcal{E}}} \models C \sqcap \delta_{\mathcal{E}} \sqsubseteq \perp\}$ contains only defeasible axioms that are exceptional w.r.t. $\langle \mathcal{T}, \mathcal{E} \rangle$. The simple algorithm **Exceptional**(\mathcal{T}, \mathcal{E}) illustrates how to compute the exceptional axioms.

Find rank value of the axioms: now we use algorithm **Exceptional** to define a procedure to find the rank value of axioms in \mathcal{D} .

Algorithm **ComputeRanking**(\mathcal{K}) illustrates how we do it, which we comment on next.

We start considering an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$. Lines 8-10 loop until we reach a (possibly empty) fixed-point of exceptional axioms.

Procedure ComputeRanking(\mathcal{K})

Input: Ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$

Output: Ontology $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ and the partitioning (ranking) $\mathfrak{R} = \{\mathcal{D}_0, \dots, \mathcal{D}_n\}$ for \mathcal{D}^*

```

1  $\mathcal{T}^* := \mathcal{T}$ ;
2  $\mathcal{D}^* := \mathcal{D}$ ;
3  $\mathfrak{R} := \emptyset$ ;
4 repeat
5    $i := 0$ ;
6    $\mathcal{E}_0 := \mathcal{D}^*$ ;
7    $\mathcal{E}_1 := \text{Exceptional}(\mathcal{T}^*, \mathcal{E}_0)$ ;
8   while  $\mathcal{E}_{i+1} \neq \mathcal{E}_i$  do
9      $i := i + 1$ ;
10     $\mathcal{E}_{i+1} := \text{Exceptional}(\mathcal{T}^*, \mathcal{E}_i)$ ;
11     $\mathcal{D}_\infty := \mathcal{E}_i$ ;
12     $\mathcal{D}^* := \mathcal{D}^* \setminus \mathcal{D}_\infty$ ;
13     $\mathcal{T}^* := \mathcal{T}^* \cup \{C \sqsubseteq \perp \mid C \sqsubset D \in \mathcal{D}_\infty\}$ ;
14 until  $\mathcal{D}_\infty = \emptyset$ ;
15 for  $j = 1$  to  $i$  do
16    $\mathcal{D}_{j-1} := \mathcal{E}_{j-1} \setminus \mathcal{E}_j$ ;
17    $\mathfrak{R} := \mathfrak{R} \cup \{\mathcal{D}_{j-1}\}$ ;
18 return  $\langle \langle \mathcal{T}^*, \mathcal{D}^* \rangle, \mathfrak{R} \rangle$ 

```

Remark 3 Since the set \mathcal{D} is finite and at every step of the exceptionality procedure $\mathcal{E}_{i+1} \subseteq \mathcal{E}_i$ holds, we will necessarily reach a fixed point, that is, $\mathcal{E}_{i+1} = \mathcal{E}_i$ for some i .

We can prove that this procedure is correct w.r.t. the infinite rank of the RC procedure, that is, that all the defeasible axioms that are in the fixed point are axioms that have infinite rank value in the RC (see Section 2.2, Step 4).

Corollary 2 If a defeasible axiom $C \sqsubset D$ is in the fixed point of the exceptionality procedure, i.e. at some step of the algorithm **ComputeRanking**, $C \sqsubset D \in \mathcal{D}_\infty$,⁶ then $C \sqsubset D \in \mathcal{D}_\infty^r$.

Hence, each axiom $C \sqsubset D$ in the fixed point of the exceptionality function is eliminated from \mathcal{D}^* (line 12) and we add $C \sqsubseteq \perp$ to \mathcal{T}^* (line 13). We repeat the loop in lines 5 - 13 until no exceptional axioms can be found anymore (i.e., $\mathcal{E}_i = \mathcal{E}_{i+1} = \emptyset$, for some $i \geq 0$).

Remark 4 Note that the loop in between lines 5 - 13 allows us to move all the strict knowledge possibly ‘hidden’ inside the DBox to the TBox. That is, there may be defeasible axioms in the DBox that are actually equivalent to classical axioms, and, thus, can be moved from the DBox to the TBox as classical inclusion axioms. Example 4 illustrates such a case.

⁶Line 11 of algorithm **ComputeRanking**.

Lines 15-17 determine the rank value of the remaining defeasible axioms not in \mathcal{D}_∞ . That is, set \mathcal{D}_{j-1} is the set of axioms of rank $j-1$ ($1 \leq j \leq i$) and are those axioms in $\mathcal{E}_{j-1} \setminus \mathcal{E}_j$.

Indeed, we can prove now that the algorithm **ComputeRanking** correctly computes the rank value of the axioms in \mathcal{D} . To do so, first we prove that the transformation of a KB $\langle \mathcal{T}, \mathcal{D} \rangle$ into $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ does not affect the rational closure.

Proposition 4 *The ontology $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ is rationally equivalent to the ontology $\langle \mathcal{T}, \mathcal{D} \rangle$.*

The fact that $\langle \mathcal{T}, \mathcal{D} \rangle$ and $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ are rationally equivalent means that (if $\langle \mathcal{T}, \mathcal{D} \rangle$ is rationally consistent), for a fixed domain Δ , they have exactly the same model R_K^\cup . From this fact and Proposition 2 we can immediately conclude that the RCs of the two KBs are equivalent. That is,

Proposition 5 *For every pair of concepts C, D , $C \sqsubseteq D$ is in the RC of $\langle \mathcal{T}, \mathcal{D} \rangle$ iff it is in the RC of $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$.*

Remark 5 *As our semantic characterisation of RC and Proposition 5 indicate, RC is a form of closure that is not affected by the syntactic form of the axioms in the ontology, that is, given two ontologies that are equivalent from the semantic point of view, their RC is the same.*

Now we can prove that, once we have transformed the ontology $\langle \mathcal{T}, \mathcal{D} \rangle$ into the equivalent ontology $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$, the exceptionality function is also complete w.r.t. the ranking procedure of RC. That is,

Proposition 6 *Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be an ontology base s.t. $\mathcal{D}_\infty = \emptyset$. For $C \sqsubseteq D \in \mathcal{D}$, if $C^R \cap \min_{\prec_R} \Delta^R = \emptyset$ for every model $R \in \mathfrak{R}^{\mathcal{K}}$, then $\mathcal{T}_{\delta_{\mathcal{D}}} \models C \sqcap \delta_{\mathcal{D}} \sqsubseteq \perp$.*

The main proposition now is a direct consequence of Propositions 3 and 6.

Proposition 7 *Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, consider the sets $\mathcal{T}^*, \mathcal{D}_0, \dots, \mathcal{D}_n$ as determined by **ComputeRanking**(\mathcal{K}). Then for every defeasible axiom $C \sqsubseteq D \in \mathcal{D}$, $r_{\mathcal{K}}(C \sqsubseteq D) = i$ ($0 \leq i \leq n$) iff $C \sqsubseteq D$ is in \mathcal{D}_i , and $r_{\mathcal{K}}(C \sqsubseteq D) = \infty$ iff $C \sqsubseteq \perp \in \mathcal{T}^*$.*

This completes the description of the axiom ranking procedure.

Next we describe some examples that illustrate the behaviour of the ranking procedure. The following example shows a case in which there is non-defeasible knowledge ‘hidden’ in a DBox and that more than one cycle of the lines 4-14 in Algorithm **ComputeRanking** is needed to extract this information.

Example 4 *Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be an ontology with*

$$\begin{aligned} \mathcal{T} &= \{ \quad A \sqsubseteq B, \\ &\quad B \sqcap D \sqsubseteq \perp \quad \} \\ \mathcal{D} &= \{ \quad B \sqsubseteq C, \\ &\quad A \sqsubseteq D, \\ &\quad E \sqsubseteq \exists r.A \quad \} . \end{aligned}$$

It can be verified that the execution of `ComputeRanking`(\mathcal{K}) is as follows:

```

 $\mathcal{T}^* = \mathcal{T}, \mathcal{D}^* = \mathcal{D}, \mathfrak{R} = \emptyset$ 
repeat1   $i = 0$    $\mathcal{E}_0 = \mathcal{D}^*, \mathcal{E}_1 = \{A \sqsubset D\}$ 
            $i = 1$    $\mathcal{E}_2 = \{A \sqsubset D\}$  (end while)
            $\mathcal{D}_\infty = \mathcal{E}_2 = \{A \sqsubset D\}$ 
            $\mathcal{D}^* = \mathcal{D}^* \setminus \{A \sqsubset D\} = \{B \sqsubset C, E \sqsubset \exists r.A\}$ 
            $\mathcal{T}^* = \mathcal{T}^* \cup \{A \sqsubseteq \perp\} = \{A \sqsubseteq B, B \sqcap D \sqsubseteq \perp, A \sqsubseteq \perp\}$ 

repeat2   $i = 0$    $\mathcal{E}_0 = \mathcal{D}^*, \mathcal{E}_1 = \{E \sqsubset \exists r.A\}$ 
            $i = 1$    $\mathcal{E}_2 = \{E \sqsubset \exists r.A\}$  (end while)
            $\mathcal{D}_\infty = \mathcal{E}_2 = \{E \sqsubset \exists r.A\}$ 
            $\mathcal{D}^* = \mathcal{D}^* \setminus \{E \sqsubset \exists r.A\} = \{B \sqsubset C\}$ 
            $\mathcal{T}^* = \mathcal{T}^* \cup \{E \sqsubseteq \perp\} = \{A \sqsubseteq B, B \sqcap D \sqsubseteq \perp, A \sqsubseteq \perp, E \sqsubseteq \perp\}$ 

repeat3   $i = 0$    $\mathcal{E}_0 = \mathcal{D}^*, \mathcal{E}_1 = \emptyset$ 
            $i = 1$    $\mathcal{E}_2 = \emptyset$  (end while)
            $\mathcal{D}_\infty = \mathcal{E}_2$ 
            $\mathcal{D}^* = \mathcal{D}^* \setminus \emptyset = \{B \sqsubset C\}$ 
            $\mathcal{T}^* = \mathcal{T}^* \cup \emptyset = \{A \sqsubseteq B, B \sqcap D \sqsubseteq \perp, A \sqsubseteq \perp, E \sqsubseteq \perp\}$  (end repeat)

for       $j = 1$    $\mathcal{D}_0 = \mathcal{E}_0 \setminus \mathcal{E}_1 = \{B \sqsubset C\}$ 
            $\mathfrak{R} = \mathfrak{R} \cup \{\mathcal{D}_0\} = \{\mathcal{D}_0\}$  (end for)

```

Therefore, `ComputeRanking`(\mathcal{K}) terminates with

$$\begin{aligned}
\mathcal{T}^* &= \{ A \sqsubseteq B, B \sqcap D \sqsubseteq \perp, A \sqsubseteq \perp, E \sqsubseteq \perp \} \\
\mathcal{D}^* &= \{ B \sqsubset C \} \\
\mathfrak{R} &= \{ \mathcal{D}_0 \} \\
\mathcal{D}_0 &= \{ B \sqsubset C \}.
\end{aligned}$$

The only defeasible axiom in \mathcal{D}^* that is not exceptional is $B \sqsubset C$, which has rank 0. Axioms $A \sqsubset D$ and $E \sqsubset \exists r.A$ have rank ∞ instead.

Example 5 Consider the ontology \mathcal{K} in Example 2. It can be verified that the execution of

`ComputeRanking`(\mathcal{K}) is as follows:

```

 $\mathcal{T}^* = \mathcal{T}, \mathcal{D}^* = \mathcal{D}, \mathfrak{R} = \emptyset$ 
repeat1   $i = 0$    $\mathcal{E}_0 = \mathcal{D}^*, \mathcal{E}_1 = \{\text{MRBC} \sqsubseteq \text{NotN}\}$ 
            $i = 1$    $\mathcal{E}_2 = \emptyset$ 
            $i = 2$    $\mathcal{E}_3 = \emptyset$  (end while)
            $\mathcal{D}_\infty = \mathcal{E}_3 = \emptyset$ 
            $\mathcal{D}^* = \mathcal{D}^* \setminus \emptyset = \mathcal{D}$ 
            $\mathcal{T}^* = \mathcal{T}^* \cup \emptyset = \mathcal{T}$  (end repeat)

for   $j = 1$    $\mathcal{D}_0 = \mathcal{E}_0 \setminus \mathcal{E}_1 = \{\text{VRBC} \sqsubseteq \exists \text{hasCM}.\top, \text{VRBC} \sqsubseteq \exists \text{hasN}.\top\}$ 
            $\mathfrak{R} = \mathfrak{R} \cup \{\mathcal{D}_0\} = \{\mathcal{D}_0\}$ 
            $j = 2$    $\mathcal{D}_1 = \mathcal{E}_1 \setminus \mathcal{E}_2 = \{\text{MRBC} \sqsubseteq \text{NotN}\}$ 
            $\mathfrak{R} = \mathfrak{R} \cup \{\mathcal{D}_1\} = \{\mathcal{D}_0, \mathcal{D}_1\}$  (end for)

```

Therefore, `ComputeRanking`(\mathcal{K}) terminates with

$$\begin{aligned}
\mathcal{T}^* &= \{ \text{CRBC} \sqsubseteq \text{MRBC}, \text{ARBC} \sqsubseteq \text{VRBC}, \text{MRBC} \sqsubseteq \text{VRBC}, \exists \text{hasN}.\top \sqcap \text{NotN} \sqsubseteq \perp \} \\
\mathcal{D}^* &= \{ \text{VRBC} \sqsubseteq \exists \text{hasCM}.\top, \text{VRBC} \sqsubseteq \exists \text{hasN}.\top, \text{MRBC} \sqsubseteq \text{NotN} \} \\
\mathfrak{R} &= \{ \mathcal{D}_0, \mathcal{D}_1 \} \\
\mathcal{D}_0 &= \{ \text{VRBC} \sqsubseteq \exists \text{hasCM}.\top, \text{VRBC} \sqsubseteq \exists \text{hasN}.\top \} \\
\mathcal{D}_1 &= \{ \text{MRBC} \sqsubseteq \text{NotN} \}.
\end{aligned}$$

Defeasible axioms in \mathcal{D}_0 have rank value 0, while the axiom in \mathcal{D}_1 has rank value 1.

So far, we have defined an algorithm that determines the rank value of the axioms in a KB, which is based on a sequence of classical \mathcal{EL}^\perp subsumption decision steps (those in the `Exceptional` algorithm, line 4.).

3.2.2 A Decision Procedure for Rational Closure

Now, we provide an algorithm to decide whether a defeasible axiom $C \sqsubseteq D$ is in the RC of an \mathcal{EL}^\perp KB. So, given a KB \mathcal{K} , let us assume that we have applied to it the `ComputeRanking` algorithm and, thus, the returned KB does not have defeasible inclusion axioms with ∞ as rank value.

In the following, given $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ as the output of the `ComputeRanking` algorithm, with \mathcal{D} partitioned into $\mathcal{D}_0, \dots, \mathcal{D}_n$, and given new atomic concepts δ_i ($0 \leq i \leq n$), we define \mathcal{T}_{δ_i} as

$$\mathcal{T}_{\delta_i} = \mathcal{T} \cup \{ C \sqcap \delta_i \sqsubseteq D \mid C \sqsubseteq D \in \bigcup_{i \leq j \leq n} \mathcal{D}_j \}. \quad (2)$$

Example 6 (Example 5 cont.) From $\langle \langle \mathcal{T}^*, \mathcal{D}^* \rangle, \mathfrak{R} \rangle$ in Example 5, we get by definition that

$$\begin{aligned}
\mathcal{T}_{\delta_0}^* &= \mathcal{T}^* \cup \{ \\
&\quad \text{VRBC} \sqcap \delta_0 \sqsubseteq \exists \text{hasCM}.\top, \\
&\quad \text{VRBC} \sqcap \delta_0 \sqsubseteq \exists \text{hasN}.\top, \\
&\quad \text{MRBC} \sqcap \delta_0 \sqsubseteq \text{NotN} \}.
\end{aligned}$$

and

$$\mathcal{T}_{\delta_1}^* = \mathcal{T}^* \cup \{\text{MRBC} \sqcap \delta_1 \sqsubseteq \text{NotN}\} .$$

Note that we get the following results:

$$\begin{aligned} \mathcal{T}_{\delta_0}^* &\models \text{MRBC} \sqcap \delta_0 \sqsubseteq \perp \\ \mathcal{T}_{\delta_0}^* &\not\models \text{VRBC} \sqcap \delta_0 \sqsubseteq \perp \\ \mathcal{T}_{\delta_1}^* &\not\models \text{MRBC} \sqcap \delta_1 \sqsubseteq \perp \end{aligned}$$

We define now an inference relation \vdash_{rc} , and then we prove that it corresponds to the RC. The decision procedure is the following.

Definition 6 (Inference relation \vdash_{rc}) Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be the output of the `ComputeRanking` algorithm, with \mathcal{D} partitioned into $\mathcal{D}_0, \dots, \mathcal{D}_n$, and consider a defeasible subsumption axiom $C \sqsubseteq D$. Let i (if it exists) be the lowest integer s.t. $0 \leq i \leq n$ and

$$\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp .$$

If such an i exists, let

$$\mathcal{K} \vdash_{rc} C \sqsubseteq D \text{ iff } \mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq D .$$

If there is not such an i , let

$$\mathcal{K} \vdash_{rc} C \sqsubseteq D \text{ iff } \mathcal{T} \models C \sqsubseteq D .$$

The first point determines the rank of the concept C (i.e., the lowest i s.t. $\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp$), while the second one establishes whether all the most typical individuals in C (the ones in Layer i) fall also under the concept D (i.e., $\mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq D$). If such an i does not exists, we cannot associate to C any of the defeasible information in \mathcal{D} , hence $\mathcal{K} \vdash_{rc} C \sqsubseteq D$ iff $\mathcal{T} \models C \sqsubseteq D$.

Algorithm `RationalClosure` illustrates how to decide defeasible entailment under RC.

Example 7 (Example 6 cont.) We want to decide whether the red blood cells of a cow (CRBC) should presumably have a nucleus, that is, whether $\text{CRBC} \sqsubseteq \exists \text{hasN}.\top$, $\text{CRBC} \sqsubseteq \text{notN}$, or neither of them are in the RC of \mathcal{K} .

First of all we check which is the rank of CRBC, then to check whether we can conclude that the typical elements of CRBC are in $\text{hasN}.\top$ (or in notN). We have that

$$\begin{aligned} \mathcal{T}_{\delta_0}^* &\models \text{CRBC} \sqcap \delta_0 \sqsubseteq \perp \\ \mathcal{T}_{\delta_1}^* &\not\models \text{CRBC} \sqcap \delta_1 \sqsubseteq \perp . \end{aligned}$$

Hence CRBC is of rank 1, and we can associate to it the defeasible information of rank 1, that is, we can use the TBox $\mathcal{T}_{\delta_1}^*$.

$$\begin{aligned} \mathcal{T}_{\delta_1}^* &\not\models \text{CRBC} \sqcap \delta_1 \sqsubseteq \exists \text{hasN}.\top \\ \mathcal{T}_{\delta_1}^* &\models \text{CRBC} \sqcap \delta_1 \sqsubseteq \text{notN} . \end{aligned}$$

Therefore, we conclude that it's not the case that the red blood cells of cows presumably have a nucleus. That is, `RationalClosure`($\mathcal{K}, \text{CRBC} \sqsubseteq \exists \text{hasN}.\top$) and `RationalClosure`($\mathcal{K}, \text{CRBC} \sqsubseteq \text{notN}$) return respectively **false** and **true**.

Procedure RationalClosure(\mathcal{K}, α)

Input: Ontology \mathcal{K} and defeasible axiom α of the form $C \sqsubseteq D$
Output: **true** iff $C \sqsubseteq D$ is in the Rational Closure of \mathcal{K}
1 $CL := \mathcal{T} \models C \sqsubseteq D$ //Check if α holds classically;
2 **if** CL **then**
3 **return** CL
4 $\langle \mathcal{T}^*, \mathcal{D}^* \rangle, \{\mathcal{D}_0, \dots, \mathcal{D}_n\} := \text{ComputeRanking}(\mathcal{K})$;
5 $CL := \mathcal{T}^* \models C \sqsubseteq D$ //Check if α holds classically, after finding strict knowledge in \mathcal{D} ;
6 **if** CL **then**
7 **return** CL
8 //Compute C 's rank i ;
9 $i := 0$; $\mathcal{D}_{\mathfrak{R}} := \mathcal{D}^*$;
10 $\mathcal{T}_{\delta_0} := \mathcal{T}^* \cup \{E \sqcap \delta_0 \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D}_{\mathfrak{R}}\}$, where δ_0 is a new atomic concept;
11 **while** $\mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq \perp$ **and** $\mathcal{D}_{\mathfrak{R}} \neq \emptyset$ **do**
12 $\mathcal{D}_{\mathfrak{R}} := \mathcal{D}_{\mathfrak{R}} \setminus \mathcal{D}_i$; $i := i + 1$;
13 $\mathcal{T}_{\delta_i} := \mathcal{T}^* \cup \{E \sqcap \delta_i \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D}_{\mathfrak{R}}\}$, where δ_i is a new atomic concept;
14 // Check now if α holds under RC;
15 **if** $\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp$ **then**
16 **return** $\mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq D$
17 **else**
18 **return** CL

The following proposition shows that the inference relation \vdash_{rc} is correct and complete w.r.t. RC, in particular w.r.t. the semantic characterisation of RC we have given in Section 3.1.

Proposition 8 *Given a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, its characteristic RC-model $R_{\mathcal{K}}^{\cup}$, and a defeasible subsumption axiom $C \sqsubseteq D$. Then,*

$$\mathcal{K} \vdash_{rc} C \sqsubseteq D \text{ iff } R_{\mathcal{K}}^{\cup} \models C \sqsubseteq D .$$

Furthermore, as we have moved into \mathcal{T}^* all the classical information possibly ‘hidden’ in \mathcal{D} , the strict information in the RC of $\langle \mathcal{T}, \mathcal{D} \rangle$ can be derived from \mathcal{T}^* alone. That is:

Proposition 9 *$C \sqsubseteq D$ is in the rational closure of $\langle \mathcal{T}, \mathcal{D} \rangle$ iff $\mathcal{T}^* \models C \sqsubseteq D$.*

From Proposition 9 we also obtain immediately a consistency test for a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$.

Proposition 10 *An ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ is rationally inconsistent iff $\mathcal{T}^* \models \top \sqsubseteq \perp$.*

3.3 Normal Form.

Usually, a classical \mathcal{EL}^{\perp} ontology is transformed into a normal form to which one then applies a subsumption decision procedure (see, e.g. [2]). In the following, we extend the notion of normal form to defeasible \mathcal{EL}^{\perp} ontologies, and show that our subsumption decision procedure works fine for normalised ontologies as well.

So, let us recap that an \mathcal{EL}^{\perp} ontology is in *normal form* if the axioms in it have the form:

- $C_1 \sqsubseteq D$
- $C_1 \sqcap C_2 \sqsubseteq D$
- $\exists R.C_1 \sqsubseteq D$
- $C_1 \sqsubseteq \exists R.C_2$

where $C_1, C_2 \in \mathbf{N}_{\mathcal{C}} \cup \{\top\}$ and $D \in \mathbf{N}_{\mathcal{C}} \cup \{\top, \perp\}$. One may transform axioms in normal form by applying the following rules:

$$\text{R1 } C \sqcap \hat{D} \sqsubseteq E \mapsto \hat{D} \sqsubseteq A, C \sqcap A \sqsubseteq E;$$

$$\text{R2 } \exists R.\hat{C} \sqsubseteq D \mapsto \hat{C} \sqsubseteq A, \exists R.A \sqsubseteq D;$$

$$\text{R3 } \perp \sqsubseteq D \mapsto \emptyset.$$

$$\text{R4 } \hat{C} \sqsubseteq \hat{D} \mapsto \hat{C} \sqsubseteq A, A \sqsubseteq \hat{D};$$

$$\text{R5 } B \sqsubseteq \exists R.\hat{C} \mapsto B \sqsubseteq \exists R.A, A \sqsubseteq \hat{C};$$

$$\text{R6 } B \sqsubseteq C \sqcap D \mapsto B \sqsubseteq C, B \sqsubseteq D,$$

where $\hat{C}, \hat{D} \notin \mathbf{N}_{\mathcal{C}} \cup \{\top\}$, and A is a new atomic concept. Rules R1-R3 are applied first, then rules R4-R6 are applied, until no more rule can be applied. It is easily verified that the transformation is time polynomial and entailment preserving, i.e., given a TBox \mathcal{T} and its normal form transformation \mathcal{T}' , then $\mathcal{T} \models C \sqsubseteq D$ iff $\mathcal{T}' \models C \sqsubseteq D$ for every C, D .

The above result is not sufficient to guarantee that we can apply this kind of transformation also to defeasible KBs. The problem is that the notion of *logical equivalence* in a preferential setting, or *rational equivalence* as we have called it up to now, follows rules that are slightly different from the ones characterising logical equivalence in classical reasoning. In particular, we are allowed to substitute a concept with a logically equivalent one on the left of a defeasible subsumption relation (LLE allows it) and on the right (a consequence of RW). However, there are cases of expressions that are equivalent in their classical formulation but not equivalent in the preferential one. For example, the two axioms $C \sqsubseteq D$ and $\top \sqsubseteq \neg C \sqcup D$ are equivalent, while $C \sqsubset D$ and $\top \sqsubset \neg C \sqcup D$ are not rationally equivalent. Therefore, the normal form transformation rules have to be designed in way to preserve rational equivalence.

So, let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be an ontology. We say that \mathcal{D} is in *normal form* if each defeasible axiom in \mathcal{D} is of the form $A \sqsubset B$, where $A, B \in \mathbf{N}_{\mathcal{C}}$. We say that \mathcal{K} is in *normal form* if \mathcal{T} and \mathcal{D} are in normal form. We next show how to transform $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ into normal form. First, we replace every axiom $C \sqsubset D \in \mathcal{D}$ with an axiom $A_C \sqsubset A_D$ (with A_C, A_D new atomic concepts), and add $A_C = C$ and $A_D = D$ to the TBox \mathcal{T} (they are both valid \mathcal{EL}^\perp expressions); then we apply the classical \mathcal{EL}^\perp normalisation steps to the axioms in \mathcal{T} . In this way, we end up with a new knowledge base $\langle \mathcal{T}', \mathcal{D}' \rangle$ that is in normal form. This transformation still remains time polynomial.

Example 8 A normal form of the KB in Example 2 is $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ with

$$\begin{aligned} \mathcal{T} = \{ & \text{CRBC} \sqsubseteq \text{MRBC}, \\ & \text{ARBC} \sqsubseteq \text{VRBC}, \\ & \text{MRBC} \sqsubseteq \text{VRBC}, \\ & \exists \text{hasN}.\top \sqsubseteq A_1, \\ & A_1 \sqsubseteq \exists \text{hasN}.\top, \\ & A_2 \sqsubseteq \exists \text{hasCM}.\top, \\ & \exists \text{hasCM}.\top \sqsubseteq A_2, \\ & A_1 \sqcap \text{NotN} \sqsubseteq \perp \} \\ \mathcal{D} = \{ & \text{VRBC} \sqsubseteq A_2, \\ & \text{VRBC} \sqsubseteq A_1, \\ & \text{MRBC} \sqsubseteq \text{NotN} \} . \end{aligned}$$

Now, we can prove that the ranking procedure gives back equivalent results whether we apply it to $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ or to its normal form transformation $\mathcal{K}' = \langle \mathcal{T}', \mathcal{D}' \rangle$.

Lemma 1 *Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and the correspondent ontology in normal form $\mathcal{K}' = \langle \mathcal{T}', \mathcal{D}' \rangle$, $C \sqsubseteq D \in \mathcal{D}_i$ for some i iff $A_C \sqsubseteq A_D \in \mathcal{D}'_i$, where A_C is the new atomic concept corresponding to C ($A_C = C \in \mathcal{T}'$), and analogously for A_D ($A_D = C \in \mathcal{T}'$).*

We conclude with the following proposition showing that we can work directly with KBs in normal form.

Proposition 11 *Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and its normal form translation $\mathcal{K}' = \langle \mathcal{T}', \mathcal{D}' \rangle$, for every pair of \mathcal{EL}^\perp -concepts C, D , $\mathcal{K} \vdash_{rc} C \sqsubseteq D$ iff $\mathcal{K}' \vdash_{rc} C \sqsubseteq D$.*

It is immediate to see that using a KB in normal form, all steps of our RC decision procedure use classical \mathcal{EL}^\perp TBoxes in normal form (as axioms $A_C \sqcap \delta_i \sqsubseteq A_D$ are in normal form, too).

3.4 Computational Complexity

Classical subsumption can be decided in polynomial time for \mathcal{EL}^\perp [2]. We next show that our subsumption decision procedure under RC requires a polynomial number of classical subsumption test and, thus, is polynomial overall w.r.t. to the size of a KB.

As we have seen, the entire procedure can be reduced to a sequence of classical entailments tests, while all other operations are linearly bound by the size of the KB. Therefore, in order to determine the computational complexity of our method, we have to check, given a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ as input, how many classical entailment tests are required in the worst case.

It is easily verified that algorithm **Exceptional**(\mathcal{T}, \mathcal{E}) performs at most $|\mathcal{E}| \in \mathcal{O}(|\mathcal{D}|)$ subsumption test. Now, let us analyse **ComputeRanking**(\mathcal{K}). Line 7 requires $\mathcal{O}(|\mathcal{D}|)$ subsumption test. Lines 8 - 10 require at most $\mathcal{O}(|\mathcal{D}|^2)$ subsumption tests as at each round $|\mathcal{E}_{i+1}|$ is $|\mathcal{E}_i| - 1$ in the worst case. As at each **repeat** round $|\mathcal{D}^*|$ decreases in size (at line 12) and, thus, the **repeat** loop is iterated at most $\mathcal{O}(|\mathcal{D}|)$ times. Therefore, **ComputeRanking** requires at most $\mathcal{O}(|\mathcal{D}|^3)$ subsumption tests. As each subsumption test is polynomially bounded by the size of \mathcal{K} , we have the following result.

Proposition 12 *The ranking procedure, `ComputeRanking`, of a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ runs in polynomial time w.r.t. the size of \mathcal{K} .*

Note that if the KB remains unchanged in between several defeasible subsumption tests, the ranking procedure needs to be executed only once. Now consider `RationalClosure`(\mathcal{K}, α). Lines 1 - 3 require one subsumption test. In line 4, the value of n is bounded by $|\mathcal{D}|$ and line 4 requires at most $\mathcal{O}(|\mathcal{D}|^3)$ subsumption tests. Lines 5 - 7 require one subsumption test.

The loop in lines 11 - 13 is executed at most $|\mathcal{D}|$ times (as at each loop $|\mathcal{D}_{\mathfrak{N}}|$ decreases), at each iteration we make one subsumption test only, and there are at most two subsumption tests between lines 15 - 18. Hence, `RationalClosure`(\mathcal{K}, α) requires at most $\mathcal{O}(|\mathcal{D}|^3 + |\mathcal{D}|)$ subsumption tests. Since each subsumption test is polynomially bounded by the size of \mathcal{K} , we have the following result.

Proposition 13 *The procedure `RationalClosure`, that decides whether the defeasible inclusion axiom $C \sqsubseteq D$ is in the RC of $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, runs in polynomial time w.r.t. the size of \mathcal{K} .*

4 Extensions of RC

So far, we have considered RC [40, 42, 47]: both the procedural and the semantic characterisations are well defined, and directly model a principle that is at the base of typicality reasoning, that is, the *presumption of typicality*. Moreover RC is a *syntactically independent* form of closure. That is, all the KBs that are rationally equivalent generate the same RC (that is a property that, as far as we know, none of the closure operations extending RC satisfy). Yet, for many applications it is well-known that the main limitation of RC from an inferential point of view is that an exceptional subclass cannot inherit *any* of the typical properties of its superclass.

Example 9 *Consider Examples 5 and 7. The mammalian red blood cells are an exceptional subclass of the vertebrate red blood cells since they do not have a nucleus. So, the conflict determining the exceptionality of MRBC is determined by the axioms $\text{VRBC} \sqsubseteq \exists \text{hasN}.\top$ and $\text{MRBC} \sqsubseteq \text{NotN}$, while there is no conflict w.r.t. $\text{VRBC} \sqsubseteq \exists \text{hasCM}.\top$. Hence, we would like still to conclude that mammalian red blood cells have a cell membrane (i.e., $\text{MRBC} \sqsubseteq \exists \text{hasCM}.\top$). However, as shown in Example 5, $\text{VRBC} \sqsubseteq \exists \text{hasCM}.\top \in \mathcal{D}_0$ and the rank of MRBC is 1 and, thus, we cannot conclude $\text{MRBC} \sqsubseteq \exists \text{hasCM}.\top$ under RC.*

In order to overcome such inferential limits, some closure operations extending RC have been proposed. We take under consideration here three proposals: an adaptation for \mathcal{ALC} [20, 45] of the Lexicographic Closure that Lehmann proposed for Propositional Logic [42], an extension of RC based on the use of inheritance nets to identify the axioms taking part to each specific conflict [19], and an extension of RC based on the notion of *justifications* [16]. In the following, we shall briefly explain how to adapt such forms of closure to \mathcal{EL}^\perp , using as a starting point the polynomial RC procedure for \mathcal{EL}^\perp presented so far.

4.1 Lexicographic Closure in \mathcal{EL}^\perp

The *Lexicographic Closure* (LC) is an extension of RC that Lehmann proposed for Propositional Logic [42]. The author distinguishes between a *prototypical* and a *presumptive* reading of the defeasible conditionals, where (using our formalism) the defeasible subsumption

‘ $bird \sqsubset fly$ ’ is read in the former case as ‘*Typical birds fly*’, and in the latter case as ‘*Birds are presumed to fly, unless we are informed of the contrary*’. Lehmann argues that the first reading, modelling the *presumption of typicality*, is correctly modelled by the RC, while he proposes LC to model the second notion, combining the *presumption of typicality* with a *presumption of independence* ([42], Section 3.1), that says that if a class is not typical with respect to one property (e.g., a penguin is a bird that does not fly) we should assume that it still inherits typical properties of a superclass if we are not forced to conclude otherwise (e.g., penguins still have wings and feathers like typical birds).

DL adaptations of LC have been proposed [20, 45]. However, as for RC, the decision procedures make use of negation and disjunction. To adapt them to \mathcal{EL}^\perp , we are going to reformulate the procedure in [20]. To do so, we may use the fact that LC is based on the same ranking procedure as for RC. Therefore, replacing the ranking procedure with the one presented here is all what is needed to reformulate LC for \mathcal{EL}^\perp .

First we compute the rank of the axioms in the DBox exactly as for RC (see Section 3.2.1). Now, assume we have a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ that has been processed by the ranking procedure. That is, $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ has been transformed, using the ranking procedure in Section 3.2.1, into $\mathcal{K}^* = \langle \mathcal{T}^*, \mathcal{D}^* \rangle$, where \mathcal{D}^* is partitioned into a sequence $\mathcal{D}_0, \dots, \mathcal{D}_n$, with each \mathcal{D}_i containing the defeasible axioms with rank i . The main difference with RC is the procedure to decide whether a defeasible inclusion $C \sqsubset D$ is in the closure of a KB. Specifically, given the sets $\mathcal{D}_0, \dots, \mathcal{D}_n$, we associate with each subset Δ of \mathcal{D}^* an *index* string $\langle m_0, \dots, m_n \rangle_\Delta$ with $m_i = |\Delta \cap \mathcal{D}_{n-i}|$.⁷ After that, we build a lexicographic ordering \geq_{lex} between index strings in the following way (where Δ, Θ are two subsets of \mathcal{D}^*):

$$\langle m_0, \dots, m_n \rangle_\Delta \geq_{lex} \langle l_0, \dots, l_n \rangle_\Theta \text{ iff for every } i \ (0 \leq i \leq n)$$

- i. $m_i \geq l_i$, or
- ii. if $m_i < l_i$ then there is $j < i$ with $m_j > l_j$.

Next, we define the *seriousness ordering* \prec_{ser} between two subsets Δ, Θ of \mathcal{D}^* as

$$\Delta \prec_{ser} \Theta \text{ iff } \langle m_0, \dots, m_n \rangle_\Delta >_{lex} \langle m'_0, \dots, m'_n \rangle_\Theta,$$

where, as usual, $>_{lex}$ is the strict part of \geq_{lex} .⁸ Note that there is an inversion in the order of the arguments between the relations \prec_{ser} and \geq_{lex} ; such an inversion is due to the fact that, dealing with preference relations (as \prec_{ser} is), there is the common habit to consider the ‘lower’ element as the preferred one, and we have preserved such an interpretation also in the case of \prec_{ser} , which is in agreement with the other preference relations we consider in this paper.

Remark 6 *Note that for $\Theta \subseteq \Delta$, we always have that $\Delta \prec_{ser} \Theta$, i.e., a set is more serious than (is preferred to) any of its subsets.*

We recap that the aim of the lexicographic closure is to maximise the amount of defeasible information that can be associated with a concept C , that is, the preferred sets of defeasible axioms (i.e., the minimal ones w.r.t. \prec_{ser}) that are consistent with C w.r.t. the KB.

⁷That is, m_0 is the number of axioms from \mathcal{D}_n contained in Δ , m_1 is the number of axioms from $\mathcal{D}_{(n-1)}$ in Δ , and so on.

⁸You may read $\Delta \prec_{ser} \Theta$ as ‘ Δ is more serious than Θ ’.

So, for every $\Theta \subseteq \mathcal{D}^*$ and new atomic concept δ_Θ , we define a new TBox \mathcal{T}_Θ as⁹

$$\mathcal{T}_\Theta = \mathcal{T} \cup \{C \sqcap \delta_\Theta \sqsubseteq D \mid C \sqsubseteq D \in \Theta\} . \quad (3)$$

The decision step is eventually the following.

Definition 7 (Inference relation \vdash_{lex}) Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be the output of the `ComputeRanking` algorithm, with \mathcal{D} partitioned into $\mathcal{D}_0, \dots, \mathcal{D}_n$, and consider a defeasible subsumption axiom $C \sqsubseteq D$. Let $\min_{C, \prec_{ser}}(\mathcal{D})$ be the set containing the sets $\Theta \subseteq \mathcal{D}$ s.t.

- $\mathcal{T}_\Theta \not\models C \sqcap \delta_\Theta \sqsubseteq \perp$,
- for all the $\Delta \subseteq \mathcal{D}$ s.t. $\Delta \prec_{ser} \Theta$, $\mathcal{T}_\Delta \models C \sqcap \delta_\Delta \sqsubseteq \perp$.

That is, $\min_{C, \prec_{ser}}(\mathcal{D})$ is the set of most serious subsets of \mathcal{D} that are compatible with C . Now, if $\min_{C, \prec_{ser}}(\mathcal{D}) \neq \emptyset$ then

$$\mathcal{K} \vdash_{lex} C \sqsubseteq D \text{ iff } \forall \Theta \in \min_{C, \prec_{ser}}(\mathcal{D}), \mathcal{T}_\Theta \models C \sqcap \delta_\Theta \sqsubseteq D ,$$

otherwise (case $\min_{C, \prec_{ser}}(\mathcal{D}) = \emptyset$)

$$\mathcal{K} \vdash_{lex} C \sqsubseteq D \text{ iff } \mathcal{T} \models C \sqsubseteq D .$$

Example 10 (Example 9 cont.) Consider the output $\langle \langle \mathcal{T}^*, \mathcal{D}^* \rangle, \mathfrak{R} \rangle$ of the ranking procedure as Example 5. Let us check whether $\text{MRBC} \sqsubseteq \exists \text{hasCM.T}$ holds under lexicographic entailment (recall that the axiom is not entailed under RC, see Example 9). To this end, we have to find out which are the most serious subsets of \mathcal{D} that are compatible with MRBC, i.e. $\min_{\text{MRBC}, \prec_{ser}}(\mathcal{D})$. It can be shown that $|\min_{\text{MRBC}, \prec_{ser}}(\mathcal{D})| = 1$ and it contains

$$\mathcal{D}' = \{\text{VRBC} \sqsubseteq \exists \text{hasCM.T}, \text{MRBC} \sqsubseteq \text{NotN}\} .$$

It is easily verified that

$$\mathcal{T}_{\mathcal{D}'} \models \text{MRBC} \sqcap \delta_{\mathcal{D}'} \sqsubseteq \text{hasCM.T} ,$$

holds and, consequently, $\mathcal{K} \vdash_{lex} \text{MRBC} \sqsubseteq \exists \text{hasCM.T}$.

The following example illustrates a case in which we have more than one most serious set of defeasible information.

Example 11 Consider the following KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$:

$$\begin{aligned} \mathcal{T} &= \{C \sqcap D = F, F \sqcap E \sqsubseteq \perp, C \sqsubseteq H, D \sqsubseteq H\} \\ \mathcal{D} &= \{A \sqsubseteq G, A \sqsubseteq C, A \sqsubseteq D, A \sqcap B \sqsubseteq E\} . \end{aligned}$$

We ask whether we can conclude $A \sqcap B \sqsubseteq G$ and $A \sqcap B \sqsubseteq H$ under LC.

$A \sqcap B$ is an exceptional class w.r.t. A because of the axioms $C \sqcap D = F, F \sqcap E \sqsubseteq \perp$. It can be verified that under RC we would be able to derive neither $A \sqcap B \sqsubseteq G$ nor $A \sqcap B \sqsubseteq H$. Instead, under LC we have two subsets of \mathcal{D} that, among the subsets of \mathcal{D} that are compatible with $A \sqcap B$, are the most serious ones:

$$\Delta' = \{A \sqsubseteq G, A \sqsubseteq D, A \sqcap B \sqsubseteq E\}$$

⁹See in comparison Eq. (1).

$$\Delta'' = \{A \sqsubseteq G, A \sqsubseteq C, A \sqcap B \sqsubseteq E\}.$$

Either using Δ' or using Δ'' we can conclude both $A \sqcap B \sqsubseteq G$ and $A \sqcap B \sqsubseteq H$, that consequently are in the LC of \mathcal{K} , i.e.,

$$\mathcal{K} \vdash_{lex} A \sqcap B \sqsubseteq G$$

$$\mathcal{K} \vdash_{lex} A \sqcap B \sqsubseteq H.$$

In any case, let us recall the following property stating that any conclusion that can be drawn under RC holds under LC as well.

Proposition 14 *Given a knowledge base $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, then for every pair of \mathcal{EL}^\perp -concepts C, D , if $\mathcal{K} \vdash_{rc} C \sqsubseteq D$ then $\mathcal{K} \vdash_{lex} C \sqsubseteq D$.*

The intuition behind this property is as follows. Given $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, let $\langle \langle \mathcal{T}^*, \mathcal{D}^* \rangle, \mathfrak{R} \rangle$ be the output of the ranking procedure and consider a concept C .

- Under RC, we associate to C a set of inclusions $\mathcal{D}_i \cup \dots \cup \mathcal{D}_n$, represented via \mathcal{T}_{δ_i} , where i is the rank of C .
- Under LC instead, we associate to C , a set of sets $\Theta_1, \dots, \Theta_j$ which are those in $\min_{C, \prec_{ser}}(\mathcal{D})$. These are represented by the TBoxes $\mathcal{T}_{\Theta_1}, \dots, \mathcal{T}_{\Theta_j}$.
- It can be shown that each Θ_k is a superset of $\mathcal{D}_i \cup \dots \cup \mathcal{D}_n$ from which Proposition 14 follows.

Remark 7 *As a consequence, the candidate sets Θ to look for to determine $\min_{C, \prec_{ser}}(\mathcal{D})$ can be built by adding to $\mathcal{D}_i \cup \dots \cup \mathcal{D}_n$ any possible strict subset $\Psi \subset \mathcal{D}_0 \cup \dots \cup \mathcal{D}_{i-1}$, with $\Psi \subset \mathcal{D}_j$ ($0 \leq j \leq i-1$)¹⁰ i.e.*

$$\Theta = \Psi \cup \mathcal{D}_i \cup \dots \cup \mathcal{D}_n.$$

Proposition 14, together with Remark 7 and the definition of \prec_{ser} allow us to define Algorithm **LexicographicClosure** which decides defeasible entailment under LC.

Computational Complexity. Let us determine the computational complexity of the **LexicographicClosure** procedure. Lines 1 - 17 are essentially the same as the **RationalClosure** procedure and, thus, require at most $\mathcal{O}(|\mathcal{D}|^3 + |\mathcal{D}|)$ subsumption tests. To compute $\min_{C, \prec_{ser}}(\mathcal{D})$, each loop in between lines 24 - 39 involves two subsumption test. Let us determine now the number of such loops. It can easily be verified that in the worst case, we run over all possible subsets $\Theta' = \Psi_j \cup \mathcal{D}_i \cup \dots \cup \mathcal{D}_n$, where $\Psi_j \subseteq \mathcal{D}_0 \cup \dots \cup \mathcal{D}_{i-1}$ and, thus, we may have $\mathcal{O}(2^{|\mathcal{D}|})$ loops. Therefore, in the worst case the loop in between lines 24 - 39 may require as many as $\mathcal{O}(2^{|\mathcal{D}|})$ subsumption tests. Furthermore, note that the elements in $\min C$, i.e. $\min_{C, \prec_{ser}}(\mathcal{D})$, all have the same cardinality and, thus, the size of $\min C$ is bounded by $\binom{|\mathcal{D}|}{k}$, for some positive $k \geq |\overline{\mathcal{D}}|$. That is, $|\min C|$ is bounded by $2^{|\mathcal{D}|}$.¹¹ Consequently, lines 43 - 45, may require $\mathcal{O}(2^{|\mathcal{D}|})$ subsumption tests as well. Hence, we have

¹⁰Recall that C 's rank is i .

¹¹More precisely, from $\binom{|\mathcal{D}|}{k} = \binom{|\mathcal{D}|}{n-k}$ it follows that the maximum of the function $f(k) = \binom{|\mathcal{D}|}{k}$ is reached at $\lfloor |\mathcal{D}|/2 \rfloor$ and, thus, $|\min C|$ is bounded by $\binom{|\mathcal{D}|}{\lfloor |\mathcal{D}|/2 \rfloor}$, which asymptotically tends to $2^{|\mathcal{D}|}$.

Proposition 15 *The procedure `LexicographicClosure`, that decides whether the defeasible inclusion axiom $C \sqsubseteq D$ is in the LC of $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, may require in worst case $\mathcal{O}(2^{|\mathcal{D}|})$ \mathcal{EL}^\perp subsumption tests, each of which runs in polynomial time w.r.t. the size of \mathcal{K} .*

Remark 8 *Note that the exponential amount of subsumption tests seems to be an inherent property of LC and indeed, exhibits the same behaviour [20]. However, unlike other approaches [20], where the decision procedure makes use of negation and disjunction, here we may entirely rely on a \mathcal{EL}^\perp , polynomial time subsumption decision procedure and, thus, `LexicographicClosure` may be more efficient in practice.*

4.2 Defeasible Inheritance-based Description Logics

Another extension of RC for DLs is the defeasible inheritance-based approach [19]. In such an approach the axioms in the TBox and in the DBox are translated into an inheritance net, which extends [55]; such a construction allows to apply the RC procedure locally, in such a way that if we want to decide whether $C \sqsubseteq D$ holds, the exceptionality ranking and the RC are calculated considering only the information in the KB that has some connection to C and D (for more details, we refer the reader to [19]).

The adaptation of the inheritance-based decision procedure [19] to \mathcal{EL}^\perp can be formalised in the following way. First of all, we assume that a KB $\langle \mathcal{T}, \mathcal{D} \rangle$ has already been transformed into *normal form*, as discussed in Section 3.3. Then, we create an inheritance net $\mathbf{N}_{\mathcal{K}}$ representing the content of the KB. The procedure is essentially the one presented by Casini and Straccia [19]. That is, given a KB $\langle \mathcal{T}, \mathcal{D} \rangle$:

1. for every atomic concept appearing in the axioms in \mathcal{K} , we create a corresponding node in the net;
2. for every axiom $A \sqsubseteq B \in \mathcal{D}$, we add the defeasible link $A \rightarrow B$ to the net;
3. for every axiom $A \sqcap B \sqsubseteq \perp \in \mathcal{T}$ we add the symmetric incompatibility link $A \nleftrightarrow B$ to the net;
4. for all the remaining axioms (in normal form) $C \sqsubseteq D \in \mathcal{T}$, we introduce (if not already present) two nodes in the net representing the concepts C and D , respectively, and add the strict connection $C \Rightarrow D$ to the net;
5. we then complete the inheritance net $\mathbf{N}_{\mathcal{K}}$ doing a total classification of the concepts appearing as nodes in the net. That is, for concepts C, D , where C and concept D are either atomic concepts or of the form $\exists R.F$, and E (not being \top), that have a node representation in $\mathbf{N}_{\mathcal{K}}$, if $\mathcal{T} \models C \sqcap D \sqsubseteq E$ holds then
 - (a) if $C \sqcap D \sqsubseteq E$ is in normal form then we add also a link $C, D \Leftrightarrow^\sqcap E$ (the conjunction of C and D is subsumed by E) to the net $\mathbf{N}_{\mathcal{K}}$;
 - (b) otherwise we first normalise $C \sqcap D \sqsubseteq E$ into axioms τ_i of the form $\exists R.F \sqsubseteq A$ or $A \sqsubseteq \exists R.F$ and into one axiom of the form $A_1 \sqcap A_2 \sqsubseteq F$. Then, the axioms τ_i are addressed as by Step 4. before, while for axiom $A_1 \sqcap A_2 \sqsubseteq F$ we add a link $A_1, A_2 \Leftrightarrow^\sqcap F$ to $\mathbf{N}_{\mathcal{K}}$.

Note that nodes in \mathbf{N}_K represent concepts that are either \perp, \top atomic, of the form $\exists R.F$ or the conjunction of two atomic concepts.

Then, in order to decide a query $A \sqsubseteq B$, we take under consideration all the *ducts* starting in A and ending into B ; a *duct* is a kind of path that takes under consideration also the conjunctions, represented by the links ' \Leftrightarrow^\square ' (see [19], Definition 3.2).

We shall use the Greek letters π, σ, \dots to indicate the ducts. Informally, a duct $\pi = \langle C, \sigma, D \rangle$ starts in node C , passes through the links in σ , and ends into node D . Specifically,

Definition 8 (Duct) Ducts are defined as follows (where $\star \in \{\Rightarrow, \nRightarrow, \rightarrow\}$):

1. every link $C \star D$ in \mathbf{N} is a duct $\pi = \langle C, D \rangle$ in \mathbf{N} ;
2. if $\pi = \langle C, \sigma, D \rangle$ is a duct and $D \star E$ is a link in \mathbf{N} that does not already appear in σ , then $\pi' = \langle C, \sigma, E \rangle$ is a duct in \mathbf{N} ;
3. if $\pi = \langle C, \sigma, D \rangle$ is a duct and $E \star C$ is a link in \mathbf{N} that does not already appear in σ , then $\pi' = \langle E, \sigma, D \rangle$ is a duct in \mathbf{N} ;
4. if $\langle C, \sigma, D \rangle$ and $\langle C, \sigma', E \rangle$ are ducts and $D, E \Leftrightarrow^\square F$ is a link in \mathbf{N} that does not already appear in $\langle C, \sigma, D \rangle$ and in $\langle C, \sigma', E \rangle$, $\langle C, \frac{\sigma, D}{\sigma', E}, F \rangle$ is a duct.

Given a node representing C and a node representing D , we consider only the axioms in $\langle \mathcal{T}, \mathcal{D} \rangle$ corresponding to links appearing in the ducts from C to D , and we compute the RC of only such a portion of the KB.

Specifically, the procedure for the closure of a KB $\langle \mathcal{T}, \mathcal{D} \rangle$ using the Defeasible Inheritance-based approach is as follows [19]:

Step 1. Given $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, check if \mathcal{K} is rationally consistent, i.e. check if the RC of \mathcal{K} is consistent. If it is consistent, then define an inheritance net \mathbf{N}_K from \mathcal{K} , as illustrated before.

Step 2. Set $\mathcal{D}_{in} = \mathcal{D}$.

For every pair of nodes $\langle C, D \rangle$ such that C and D appear in the net \mathbf{N}_K , do the following:

- compute the set of all ducts starting in C and ending into D , and let $\Delta_{C,D}$ be the set of all the defeasible links $E \rightarrow F$ appearing in such ducts;
- consider the KB $\mathcal{K}' = \langle \mathcal{T}, \mathcal{D}' \rangle$, where $\mathcal{D}' \subseteq \mathcal{D}$ is the set of the defeasible axioms corresponding to the defeasible links in $\Delta_{C,D}$;
- if $C \sqsubseteq D$ is in the RC of \mathcal{K}' (i.e. $\mathcal{K}' \vdash_{rc} C \sqsubseteq D$), then add $C \sqsubseteq D$ to \mathcal{D}_{in} .

Step 3. Finally, let $\mathcal{K}_{in} = \langle \mathcal{T}, \mathcal{D}_{in} \rangle$. Compute the RC of \mathcal{K}_{in} and eventually define the non-monotonic inference relation \vdash_{in} as

$$\mathcal{K} \vdash_{in} C \sqsubseteq D \text{ iff } \mathcal{K}_{in} \vdash_{rc} C \sqsubseteq D .$$

The above procedure is illustrated in Algorithm `InheritanceBasedRationalClosure`(\mathcal{K}, α).




Figure 1: Inheritance net built from Example 12.

Example 12 (Example 8 cont.) Consider Example 8. The inheritance net N_K built from K is illustrated in Figure 1.

We want to check whether $K \vdash_{in} MRBC \sqsubseteq \exists hasCM.\top$ holds. To do so, we compute all ducts between $MRBC$ and $hasCM.\top$. Actually, there is only one and it includes the defeasible link representing $VRBC \sqsubseteq A_2$. Therefore, in Step 10. of the `InheritanceBasedRationalClosure` algorithm, we set $\mathcal{D}' = \{VRBC \sqsubseteq A_2\}$.

It can be verified that $MRBC \sqsubseteq A_2$ is in the RC of $K' = \langle \mathcal{T}, \mathcal{D}' \rangle$ and, thus, by Step. 13, $MRBC \sqsubseteq A_2$ is added to \mathcal{D}_{in} , from which $K \vdash_{in} MRBC \sqsubseteq \exists hasCM.\top$ follows.

Computational Complexity. Let us now address the computational complexity of the `InheritanceBasedRationalClosure` procedure. To start with, that the normalisation Step 1 can be done in linear time from [2], yielding a normalised KB whose size is linear in the size of K .

From the result in Section 4 it follows that Step 2 requires at most $\mathcal{O}(|\mathcal{D}|^3 + |\mathcal{D}|)$ subsumption tests.

Let us now estimate the cost of Step 5. The first step of the construction of N_K creates as many nodes as there are atomic concepts in K and, thus, both size and time bound is $\mathcal{O}(|K|)$. The second step is obviously bounded both in time and size of number of edges by $\mathcal{O}(|\mathcal{D}|)$. Similarly, the third and forth step can be done together and is bounded both in time and size of number of new nodes and edges by $\mathcal{O}(|\mathcal{T}|)$. Therefore, so far Steps 1 - 4. can be done in time $\mathcal{O}(|K|)$, while for network N_K , the number of both nodes and edges is bounded by $\mathcal{O}(|K|)$. Eventually, it can easily be verified that including the fifth step of the construction of N_K , the overall time bound of the construction of N_K is time and size (number of nodes as well as edges) bounded by $\mathcal{O}(|K|^2)$.

The number of iterations of Steps 7 - 12 is bounded by $\mathcal{O}(|K|^4)$, as there are at most $\mathcal{O}(|K|^2)$ nodes in N_K . Step 8 is the same step as illustrated by Casini and Straccia [19], in which it is shown that $\Delta_{C,D}$ can be computed in polynomial time w.r.t. to the size of K (Sections 3.1.6 and 3.2.5 [19]). For ease of presentation, let us indicate with δ_K the time bound to compute $\Delta_{C,D}$. Moreover, the size of both $\Delta_{C,D}$ and \mathcal{D}' is bounded by $\mathcal{O}(|\mathcal{D}|)$ and, thus, the size of K' is bounded by $\mathcal{O}(|K|)$. Therefore, Step 12 requires at most $\mathcal{O}(|\mathcal{D}|^3 + |\mathcal{D}|)$ subsumption tests. In summary, the computation time of iterations Steps 7 - 12 is bounded

by $\mathcal{O}(\delta_{\mathcal{K}} \cdot |\mathcal{K}|^4)$ plus the time required to perform $\mathcal{O}(|\mathcal{K}|^4(|\mathcal{D}|^3 + |\mathcal{D}|))$ subsumption tests.

Finally, the size of \mathcal{D}_{in} is bounded by $\mathcal{O}(|\mathcal{K}|^2)$ and, thus, Step 15 may require at most $\mathcal{O}(|\mathcal{K}|^6 + |\mathcal{K}|^2)$ subsumption tests.

Therefore, we have the following result.

Proposition 16 *The procedure `InheritanceBasedRationalClosure`, that decides whether the defeasible inclusion axiom $C \sqsubseteq D$ is in the Inheritance-based RC of $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, i.e. decides whether $\mathcal{K} \vdash_{in} C \sqsubseteq D$ holds, runs in polynomial time w.r.t. the size of \mathcal{K} .*

4.3 Relevant Closure

Relevant Closure [16] is another form of closure that extends RC and is defined so far for \mathcal{ALC} and DLs beyond it. Relevant closure is based on the ranking procedure for RC, but given a KB $\langle \mathcal{T}, \mathcal{D} \rangle$ and a query $C \sqsubseteq D$, it identifies just the parts of the KB that are relevant w.r.t. the particular query.

Specifically, we assume that we have already applied the ranking procedure (procedure `ComputeRanking`) to the KB, that is, all the classical knowledge is contained in the TBox and the DBox \mathcal{D} is partitioned into $\{\mathcal{D}_1, \dots, \mathcal{D}_n\}$. Now, given a query $C \sqsubseteq D$, informally, the part of the KB that is relevant w.r.t. the query is the part of the KB that causes conflicts that make C exceptional. That is, given $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and a query $C \sqsubseteq D$ we identify all the *justifications* for the (possible) exceptionality of C , that is, all the information in \mathcal{K} that causes C to be exceptional.

Definition 9 (Justification) *For $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, $\mathcal{J} \subseteq \mathcal{D}$, and concept C , \mathcal{J} is a C -justification w.r.t. \mathcal{K} iff C is exceptional for $\langle \mathcal{T}, \mathcal{J} \rangle$ (i.e. $\top \sqsubseteq \neg C$ is rationally entailed by $\langle \mathcal{T}, \mathcal{J} \rangle$) and for every $\mathcal{J}' \subset \mathcal{J}$, C is not exceptional for $\langle \mathcal{T}, \mathcal{J}' \rangle$.*

The notion of justification, combined with our decision procedure to determine exceptionality (procedure `Exceptional`), gives us the following procedural characterisation of the above defined notion.

Corollary 3 *\mathcal{J} is a C -justification w.r.t. $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ iff $\mathcal{J} \subseteq \mathcal{D}$ and for new atom δ*

$$\mathcal{T} \cup \{C \sqcap \delta \sqsubseteq D \mid C \sqsubseteq D \in \mathcal{J}\} \models C \sqcap \delta \sqsubseteq \perp,$$

and for every $\mathcal{J}' \subset \mathcal{J}$,

$$\mathcal{T} \cup \{C \sqcap \delta \sqsubseteq D \mid C \sqsubseteq D \in \mathcal{J}'\} \not\models C \sqcap \delta \sqsubseteq \perp.$$

The choice of the term *justification* is not accidental, since it closely mirrors the notion of a justification for classical DLs, where a justification for a sentence α is a minimal set implying α [39] (it corresponds also to the notion of *kernel* in the base-revision literature [38]).

The principle of Relevant Closure is to consider as defeasible only the information that is in the justification of the antecedent of the query, that is, only the information that creates conflicts that make the antecedent exceptional. All the rest of the information contained in the KB is not considered eliminable. In this way we can preserve the *presumption of independence*. The main procedure is the *Basic Relevant Closure*, whose adaptation to \mathcal{EL}^\perp is explained next.

1. Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be a KB s.t. all the classical information is contained in the TBox \mathcal{T} and the DBox \mathcal{D} has been partitioned into $\{\mathcal{D}_0, \dots, \mathcal{D}_n\}$. Let $C \sqsubseteq D$ be our query.
2. Compute the set $\mathcal{J}^{\mathcal{K}}(C) = \{\mathcal{J}_1, \dots, \mathcal{J}_m\}$ of all C -justifications w.r.t. \mathcal{K} .
3. Let $\overline{\mathcal{J}} := \bigcup_{j=1}^m \mathcal{J}_j$ be the union of all C -justifications w.r.t. \mathcal{K} .
4. $i := 0$.
5. Let $\mathcal{J}'_i := \overline{\mathcal{J}} \cap \bigcup_{j \geq i} \mathcal{D}_j$.
6. Check whether

$$\mathcal{T} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D} \setminus \overline{\mathcal{J}}\} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{J}'_i\} \models C \sqcap \delta \sqsubseteq \perp .$$

- (a) If that's true and $i < n$, set $i := i + 1$ and go to Step 5.
 - (b) If that's true and $i = n$, set $\mathcal{J}'_i := \emptyset$ and proceed to the next step.
 - (c) If it is not the case then proceed to the next step.
7. Finally, $C \sqsubseteq D$ is in the Basic Relevant Closure of \mathcal{K} iff

$$\mathcal{T} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D} \setminus \overline{\mathcal{J}}\} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{J}'_i\} \models C \sqcap \delta \sqsubseteq D .$$

The above procedure is illustrated in Algorithm **BasicRelevantClosure**.

Example 13 (Example 9 cont.) Consider Example 9 and the query $\text{MRBC} \sqsubseteq \text{hasCM.T}$. By running the **BasicRelevantClosure** algorithm, it can be verified that the only MRBC-justification is the set

$$\mathcal{J}_1 := \{\text{VRBC} \sqsubseteq \exists \text{hasN.T}, \text{MRBC} \sqsubseteq \text{NotN}\}$$

and $\overline{\mathcal{J}} = \mathcal{J}_1$. Therefore, $\text{VRBC} \sqsubseteq \text{hasCM.T}$ is in the set $\mathcal{D} \setminus \overline{\mathcal{J}}$ and, thus, $\text{MRBC} \sqsubseteq \text{hasCM.T}$ is in the Basic Relevant Closure of \mathcal{K} .

The procedure of **BasicRelevantClosure** can be refined in order to improve the inferential power, obtaining the *Minimal Relevant Closure* [16]. The difference between the Basic and the Minimal version of the Relevant Closure is that the latter, given a query $C \sqsubseteq D$ and the set $\mathcal{J}^{\mathcal{K}}(C)$ containing the C -justifications, of every justification in $\mathcal{J}^{\mathcal{K}}(C)$ we consider as relevant only the axioms that are more prone to be eliminated by the RC procedure, that is, the axioms with the lower rank.

So, given a justification \mathcal{J} , let

$$\mathcal{J}_{\min}^{\mathcal{K}} := \{D \sqsubseteq E \mid r_{\mathcal{K}}(D) \leq r_{\mathcal{K}}(F) \text{ for every } F \sqsubseteq G \in \mathcal{J}\} ,$$

and

$$\mathcal{J}_{\min} := \bigcup_{\mathcal{J} \in \mathcal{J}^{\mathcal{K}}(C)} \mathcal{J}_{\min}^{\mathcal{K}} .$$

The procedure for *Minimal Relevant Closure* corresponds exactly to the one for the Basic Closure, simply using \mathcal{J}_{\min} as the relevant set of axioms, instead of $\overline{\mathcal{J}}$.

Algorithm **MinimalRelevantClosure** details the procedure for Minimal Relevant Closure.

The following example shows the different inferential behaviour of Minimal Relevant Closure w.r.t. Basic Relevant Closure.

Example 14 (Example 13 cont.) Consider the KB in Example 13. Now, suppose that we also know that mammalian sickle cells are mammalian red blood cells, that mammalian red blood cells normally have a bioconcave shape, but that mammalian sickle cells normally do not (they normally have a crescent shape). We represent this new information as

$$\mathcal{T}' = \mathcal{T} \cup \{\text{MSC} \sqsubseteq \text{MRBC}, \exists \text{hasS.BC} \sqcap \exists \text{hasS.Cr} \sqsubseteq \perp\}$$

and

$$\mathcal{D}' = \mathcal{D} \cup \{\text{MRBC} \sqsubseteq \exists \text{hasS.BC}, \text{MSC} \sqsubseteq \exists \text{hasS.Cr}\}.$$

Consider now the query of whether mammalian sickle cells don't have a nucleus, that is, whether $\text{MSC} \sqsubseteq \text{NotN}$ is in the Minimal Relevant Closure.

To this end, consider KB $\mathcal{K}' = \langle \mathcal{T}', \mathcal{D}' \rangle$. Please note now that there are two MSC-justifications w.r.t. \mathcal{K} , namely

$$\begin{aligned} \mathcal{J}^1 &= \{\text{MRBC} \sqsubseteq \text{NotN}, \text{VRBC} \sqsubseteq \exists \text{hasN.T}\} \\ \mathcal{J}^2 &= \{\text{MRBC} \sqsubseteq \exists \text{hasS.BC}, \text{MSC} \sqsubseteq \exists \text{hasS.Cr}\}. \end{aligned}$$

Basic Relevant Closure. To check whether $\text{MSC} \sqsubseteq \text{notN}$ is in the Basic Relevant Closure of \mathcal{K}' we have to consider as irrelevant, and hence not eliminable, only the axiom $\text{VRBC} \sqsubseteq \exists \text{hasCM.T}$ (the only axiom that does not appear in any MSC-justification), while all the other defeasible axioms appear in some MSC-justification and are eligible for being eliminating during the procedure. It turns out that $\text{MSC} \sqsubseteq \neg \exists \text{hasN.T}$ is not in the Basic Relevant Closure of \mathcal{K}' since $\text{MRBC} \sqsubseteq \text{notN}$ is eliminated by the procedure for Basic Relevant Closure, and hence $\text{MSC} \sqsubseteq \text{notN}$ is not in the Basic Relevant Closure of \mathcal{K}' .

Minimal Relevant Closure. On the other hand, to check if $\text{MSC} \sqsubseteq \text{notN}$ is in the Minimal Relevant Closure, note that $\mathcal{J}_{\min}^1 = \{\text{VRBC} \sqsubseteq \exists \text{hasN.T}\}$, and $\mathcal{J}_{\min}^2 = \{\text{MRBC} \sqsubseteq \exists \text{hasS.BC}\}$. Thus, the axiom $\text{MRBC} \sqsubseteq \text{notN}$ is not relevant in the minimal framework and, thus, not eliminable. Therefore, $\text{MSC} \sqsubseteq \text{notN}$ is in the Minimal Relevant Closure of \mathcal{K}' .

Computational Complexity. Even if developed with a different motivation (ontology repairing) the results by Ludwig et al. [44] are relevant w.r.t. our proposal: the paper shows that the identification of justifications in \mathcal{EL} is not a polynomial problem (a consequence of their Corollary 14) and, thus, neither are the decision problem of Basic Relevant Closure entailment nor the one of Minimal Relevant Closure entailment for \mathcal{EL}^\perp .

Proposition 17 *Basic Relevant Closure and Minimal Relevant Closure entailment problems cannot be decided in polynomial time.*

However, Ludwig et al. [44] also proposes a way to precompile repairs and label axioms that can be easily readapted to our problem. That is, we can precompile justifications and label the axioms depending on which justifications they take part into. Once we have done this precompilation of the justifications, which however may take exponential time w.r.t. the size of \mathcal{K} , after that the decision problem of Basic Relevant Closure entailment and Minimal Relevant Closure entailment can be resolved in polynomial time, as it is then a special case of the RC procedure (this is an immediate consequence of Proposition 13).

5 Conclusions and Closely Related Work

In this work, we have presented a novel procedure to decide subsumption under RC in the DL \mathcal{EL}^\perp . The main contribution is that the subsumption problem under RC can be decided in polynomial time, as is the case for monotonic \mathcal{EL}^\perp , and thus, the result extends to OWL 2 EL [50] as well. Specifically, we have shown that our procedure may decide subsumption under RC via a polynomial number of classical \mathcal{EL}^\perp subsumption tests. Furthermore, we have adapted the procedure also to some extensions of RC for DLs, such as the Lexicographic Closure, Defeasible Inheritance-based DLs and (Basic/Minimal) Relevant Closure. Additionally, for them, we have shown that the subsumption problem remains polynomial for Defeasible Inheritance-based \mathcal{EL}^\perp only.¹²

As the basic language requirement is, besides the possibility to express unsatisfiable KBs,¹³ to have conjunction on the left-hand side of GCIs, our procedure can be adapted to any other DL \mathcal{L} having this feature as well (e.g. OWL 2 RL [51]). Furthermore, subsumption under RC for \mathcal{L} may be decided using a polynomial number of classical \mathcal{L} subsumption tests. Therefore, if the classical subsumption problem for \mathcal{L} is in the complexity class \mathcal{C} then the subsumption problem under RC is in \mathcal{C} as well if \mathcal{C} is in P or higher, else it is in P. So, e.g. the subsumption problem under RC is in P for $DL-Lite_{horn}^H$ [1].

These results are non-trivial. Indeed, as pointed out in the introduction, non-monotonic DLs extensions usually do not preserve the tractability of \mathcal{EL}^\perp [6, 9, 12, 15, 16, 18, 19, 20, 21, 28, 30, 31, 32, 45]. An exception is the novel (but non-RC-based) approach proposed by Bonatti et al. [7], which is tractable for *any* tractable classical DL, and the specific \mathcal{EL} fragment based on circumscription proposed by Bonatti et al. [9, 8]).

Concerning future work, one of our aims is to determine whether the subsumption problem under RC still remains polynomial for various other tractable DLs of the *DL-Lite* family [1] that however do not support conjunction on the left-hand side of GCIs.

6 Appendix of Proofs

Proposition 1 *For an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and a defeasible axiom $C \sqsubseteq D$, $\mathcal{K} \models_{\mathfrak{R}} C \sqsubseteq D$ iff*

$$\forall R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}, R \models C \sqsubseteq D.$$

Proof: Let Δ be a countable infinite domain. If $\mathcal{K} \models_{\mathfrak{R}} C \sqsubseteq D$, then obviously $\forall R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}, R \models C \sqsubseteq D$.

On the other hand, assume $\forall R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}, R \models C \sqsubseteq D$. We have to prove that it is not possible that there is some R in $\mathfrak{R}^{\mathcal{K}}$ s.t. $R \not\models C \sqsubseteq D$. Let R be a model of \mathcal{K} and a counter-model of $C \sqsubseteq D$. We can easily prove that for a defeasible language built over the DL \mathcal{ALC} (or any of \mathcal{ALC} -sublanguages) and semantically characterised by the class of the ranked models, the Finite Model Property (and the Finite Counter-Model Property) holds (see Section 6.1). Then, if we have a ranked interpretation R that is a model of \mathcal{K} and a counter-model of $C \sqsubseteq D$ (with a domain that could be countable or uncountable), there

¹²Relevant Closure cannot be polynomial for \mathcal{EL}^\perp , our procedure runs in exponential time for Lexicographic Closure and non-polynomiality is suspected, but not yet proved.

¹³Otherwise, defeasible axioms do not cause any issue.

must be a model R_{fin} with a finite domain that is also a model of \mathcal{K} and a counter-model of $C \sqsubseteq D$. Given R_{fin} , then we can extend it to a model of \mathcal{K} that is a counter-model of $C \sqsubseteq D$ with a countable infinite domain. Hence, if there is a counter model of $\mathcal{K} \models_{\mathfrak{R}} C \sqsubseteq D$, there must be also a counter model with a countable domain, and we can consider only the models with a countable infinite domain in the definition of $\models_{\mathfrak{R}}$.

Now, let $R' = \langle \Delta', \cdot^{R'}, \preceq^{R'} \rangle$ be a model of \mathcal{K} and a counter-model of $C \sqsubseteq D$ with Δ' countable infinite. It is easy to build an isomorphic interpretation $R = \langle \Delta, \cdot^R, \preceq^R \rangle$: once we have defined a bijection $b : \Delta' \times \Delta$ (that must exist, being both Δ' and Δ countable infinite sets), we can define \cdot^R and \preceq^R in the following way:

- For every $r \in \mathbb{N}_{\mathcal{R}}$ and every $x, y \in \Delta'$, $\langle b(x), b(y) \rangle \in r^R$ iff $\langle x, y \rangle \in r^{R'}$;
- For every $C \in \mathbb{N}_{\mathcal{C}}$ and every $x \in \Delta'$, $b(x) \in C^R$ iff $x \in C^{R'}$;
- For every $x, y \in \Delta'$, $b(x) \preceq^R b(y)$ iff $x \preceq^{R'} y$.

It is easy to prove by induction on the construction of the concepts that for every concept C , $x \in C^{R'}$ iff $b(x) \in C^R$; moreover, $x \in \min_{\preceq^{R'}}(C^{R'})$ iff $b(x) \in \min_{\preceq^R}(C^R)$. Hence, if there is a counter model to $\mathcal{K} \models_{\mathfrak{R}} C \sqsubseteq D$ there must be also a counter model with Δ as domain.

Hence, we can use just the set of interpretations in $\mathfrak{R}_{\Delta}^{\mathcal{K}}$ to decide the consequences of \mathcal{K} w.r.t. ranked entailment. ■

Proposition 2 *Let \mathcal{K} be an ontology having a ranked model. Then $R_{\mathcal{K}}^{\cup}$ is a model of \mathcal{K} and for any pair of concepts C, D , $R_{\mathcal{K}}^{\cup} \models C \sqsubseteq D$ iff $r_{\mathcal{K}}(C \sqcap D) < r_{\mathcal{K}}(C \sqcap \neg D)$ or $r_{\mathcal{K}}(C) = \infty$.*

Proof: First of all we, have to prove that the exceptionality function

$$E_{\mathcal{T}}(\mathcal{D}) = \{C \sqsubseteq D \mid \langle \mathcal{T}, \mathcal{D} \rangle \models_{\mathfrak{R}} \top \sqsubseteq \neg C\}$$

is correctly represented in this model. By Proposition 1, the exceptionality function can be reformulated as

$$E_{\mathcal{T}}(\mathcal{D}) = \{C \sqsubseteq D \mid \forall R \in \mathfrak{R}_{\Delta}^{\mathcal{K}}, R \models \top \sqsubseteq \neg C\}$$

that clearly corresponds to say that

$$E_{\mathcal{T}}(\mathcal{D}) = \{C \sqsubseteq D \mid R_{\mathcal{K}}^{\cup} \models \top \sqsubseteq \neg C\}.$$

If we are dealing with a language without a negation operator, as \mathcal{EL}^{\perp} , the correspondent condition is

$$E_{\mathcal{T}}(\mathcal{D}) = \{C \sqsubseteq D \mid \min_{\preceq_{R_{\mathcal{K}}^{\cup}}}(\Delta^{R_{\mathcal{K}}^{\cup}}) \cap C^{R_{\mathcal{K}}^{\cup}} = \emptyset\}.$$

Now we have to prove that this correspondence is preserved for all the steps of the exceptionality function, that is, we have to prove that the model $R_{\mathcal{K}}^{\cup}$ is a correct semantical representation of the ranking procedure. That corresponds to say that for every concept C and every i , $0 < i \leq n$,

$$r_{\mathcal{K}}(C) = i \text{ iff } h_{R_{\mathcal{K}}^{\cup}}(C) = i.$$

We can prove it by induction on the rank value i ($i > 0$).

If $h_{R_K^\cup}(C) = i$ it is immediate that $r_K(C) \leq i$. We have now to prove that if $r_K(C) = i$ then $h_{R_K^\cup}(C) = i$. We can prove that by defining a model R in \mathfrak{R}^K s.t. $h_R(C) = i$.

So, given a KB $K = \langle \mathcal{T}, \mathcal{D} \rangle$, let $r_K(C) = i$, and let $\mathcal{D}_{\geq i}^r$ be the subset of \mathcal{D} containing the defeasible axioms with a rank value of at least i . Let \bar{M} be a ranked model of $\langle \mathcal{T}, \mathcal{D}_{\geq i}^r \rangle$ s.t. $h_{\bar{M}}(C) = 0$; such a model must exist, since $r_K(C) = i$, that is, C is not exceptional in $\langle \mathcal{T}, \mathcal{D}_{\geq i}^r \rangle$. We assume that M has a finite domain (we can, due to the FMP).

Now, let N be a model of $\langle \mathcal{T}, \mathcal{D} \rangle$ in \mathfrak{R}_Δ^K s.t. for all the axioms $C \sqsubseteq D \in (\mathcal{D} \setminus \mathcal{D}_{\geq i}^r)$ there is an individual satisfying $C \sqcap D$. The induction hypothesis guarantees that such a model exists. We define a new interpretation N' in the following way:

- $L_0^{N'} = L_0^N$;
- ...
- $L_{i-1}^{N'} = L_{i-1}^N$;
- $L_i^{N'} = L_i^N \cup L_0^M$;
- $L_{i+1}^{N'} = L_{i+1}^N \cup L_1^M$;
- ...

and so on, for all the layers of both N and M . N' is a model of $\langle \mathcal{T}, \mathcal{D} \rangle$ (easy to prove) s.t. $h_{N'}(C) = i$. Since N' is obtained from the composition of a model with Δ as domain and a model with a finite domain, it too has a countable domain and there is a model N'_Δ that is isomorphic to N' and has Δ as domain. So N'_Δ takes part in the construction of R_K^\cup , and $h_{R_K^\cup}(C) = i$.

This proves that for every C , $r_K(C) = i$ iff $h_{R_K^\cup}(C) = i$.

Eventually, since $R_K^\cup \models C \sqsubseteq D$ iff $h_{R_K^\cup}(C \sqcap D) < h_{R_K^\cup}(C \sqcap \neg D)$ (or $h_{R_K^\cup}(C) = \infty$), and $h_{R_K^\cup}(C \sqcap D) < h_{R_K^\cup}(C \sqcap \neg D)$ (or $h_{R_K^\cup}(C) = \infty$) iff $r_K(C \sqcap D) < r_K(C \sqcap \neg D)$ (or $r(C) = \infty$), this concludes the proof of the proposition. ■

Proposition 3 For an ontology $K = \langle \mathcal{T}, \mathcal{E} \rangle$ and $C \sqsubseteq D \in \mathcal{E}$, if $\mathcal{T}_{\delta_\mathcal{E}} \models C \sqcap \delta_\mathcal{E} \sqsubseteq \perp$ then for every model $R \in \mathfrak{R}^K$, $C^R \cap \min_{\prec^R}(\Delta^R) = \emptyset$.

Proof: If K is not rationally consistent (i.e., K does not have a ranked model), the proposition is trivially satisfied. Hence, assume K is rationally consistent.

So, let $R = \langle \Delta^R, \cdot^R, \prec^R \rangle$ a ranked model of K , defined over a signature $\mathbf{N}_\mathcal{C} \cup \mathbf{N}_\mathcal{R}$. We define a classical model $\mathcal{I}_\delta^R = \langle \Delta^R, \cdot^{\mathcal{I}_\delta^R} \rangle$ in the following way.

- \mathcal{I}_δ^R is defined over a new signature $\mathbf{N}'_\mathcal{C} \cup \mathbf{N}_\mathcal{R}$, with $\mathbf{N}'_\mathcal{C} = \mathbf{N}_\mathcal{C} \cup \{\delta_\mathcal{E}\}$;
- for every $r \in \mathbf{N}_\mathcal{R}$, $r^{\mathcal{I}_\delta^R} = r^R$;
- for every $C \in \mathbf{N}_\mathcal{C}$, $C^{\mathcal{I}_\delta^R} = C^R$;
- for every $x \in \Delta^R$, $x \in \delta_\mathcal{E}^{\mathcal{I}_\delta^R}$ iff $x \in \min_{\prec^R}(\Delta^R)$.

It is easy to check that if R is a model of $\langle \mathcal{T}, \mathcal{E} \rangle$, then \mathcal{I}_δ^R is a model of $\mathcal{T}_{\delta_\mathcal{E}}$: by induction on the construction of the concepts, it is immediate that for every concept C generated from the signature $\mathbf{N}_\mathcal{C} \cup \mathbf{N}_\mathcal{D}$ and every $x \in \Delta^R$, $x \in C^R$ iff $x \in C^{\mathcal{I}_\delta^R}$. Now, assume there is an axiom $C \sqsubseteq D \in \mathcal{T}_{\delta_\mathcal{E}}$ s.t. $\mathcal{I}_\delta^R \not\models C \sqsubseteq D$. If $C \sqsubseteq D \in \mathcal{T}$, it is immediate that $R \not\models C \sqsubseteq D$, that cannot be the case. Instead, if $C \sqsubseteq D$ has the form $E \sqcap \delta_\mathcal{E} \sqsubseteq D$, then if $E^R \cap \min_{\prec_R}(\Delta^R) \neq \emptyset$ we conclude $R \not\models E \sqsubseteq D$ (that cannot be the case, since $E \sqsubseteq D \in \mathcal{E}$), while if $E^R \cap \min_{\prec_R}(\Delta^R) = \emptyset$ it cannot be the case that $\mathcal{I}_\delta^R \not\models C \sqsubseteq D$, since $(E \sqcap \delta_\mathcal{E})^{\mathcal{I}_\delta^R} = \emptyset$ and so there is no object in Δ^R satisfying the antecedent. At this point it is immediate to see also that $C^R \cap \min_{\prec_R}(\Delta^R) = \emptyset$ iff $\mathcal{I}_\delta^R \models C \sqcap \delta_\mathcal{E} \sqsubseteq \perp$.

So, if every model of \mathcal{T}_δ satisfies $C \sqcap \delta_\mathcal{E} \sqsubseteq \perp$, we have that, for every ranked model R of \mathcal{K} , $C^R \cap \min_{\prec_R}(\Delta^R) = \emptyset$: if it was not the case for any model R' , at least one model of \mathcal{T}_δ (the model $\mathcal{I}_\delta^{R'}$ created from R') would not satisfy $C \sqcap \delta_\mathcal{E} \sqsubseteq \perp$. ■

Corollary 2 *If a defeasible axiom $C \sqsubseteq D$ is in the fixed point of the exceptionality procedure, i.e. at some step of the algorithm `ComputeRanking`, $C \sqsubseteq D \in \mathcal{D}_\infty$, then $C \sqsubseteq D \in \mathcal{D}_\infty^r$.*

Proof: The result is a direct consequence of the correctness of the exceptionality function w.r.t. the ranking procedure of RC (Proposition 3). Given a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, if at every step j , $E^j(\mathcal{D})$ is a subset of the axioms that are of rank j w.r.t. the RC of \mathcal{K} , and $C \sqsubseteq D$ is in the fixed point of the function E , then $C \sqsubseteq D$ is also in the fixed point of the RC ranking procedure. ■

Proposition 4 *The ontology $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ is rationally equivalent to the ontology $\langle \mathcal{T}, \mathcal{D} \rangle$.*

Proof: It is immediate to see that $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ implies $\langle \mathcal{T}, \mathcal{D} \rangle$ w.r.t. ranked entailment, since $C \sqsubseteq \perp \models_R C \sqsubseteq D$ for all the concepts C, D .

On the other hand, that $\langle \mathcal{T}, \mathcal{D} \rangle$ implies $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ is a direct consequence of Corollary 2, that implies that $\langle \mathcal{T}, \mathcal{D} \rangle \models_R C \sqsubseteq \perp$ for every $C \sqsubseteq \perp \in \mathcal{T}^* \setminus \mathcal{T}$. ■

Proposition 6 *Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be an ontology base s.t. $\mathcal{D}_\infty = \emptyset$. For $C \sqsubseteq D \in \mathcal{D}$, if $C^R \cap \min_{\prec_R} \Delta^R = \emptyset$ for every model $R \in \mathfrak{R}^\mathcal{K}$, then $\mathcal{T}_{\delta_\mathcal{D}} \models C \sqcap \delta_\mathcal{D} \sqsubseteq \perp$.*

Proof: Since the fixed point is empty, we have also that no axiom in \mathcal{D} has infinite rank (see Lemma 2 below).

Assume that there is an interpretation $\mathcal{I} = \langle \Delta^\mathcal{I}, \cdot^\mathcal{I} \rangle$ that is a model of \mathcal{T}_δ and there is an object a s.t. $a^\mathcal{I} \in (C \sqcap \delta)^\mathcal{I}$. We have to prove that then there is a ranked model R of $\langle \mathcal{T}, \mathcal{D} \rangle$ s.t. $C^R \cap \min_{\prec_R} \Delta^R \neq \emptyset$.

At first, we build a model $R^\mathcal{I} = \langle \Delta^\mathcal{I}, \cdot^\mathcal{I}, \prec^{R^\mathcal{I}} \rangle$ in the following way. We have a ranking of the set \mathcal{D} into $\mathcal{D}_1^r, \dots, \mathcal{D}_n^r$ ($\mathcal{D}_1^r, \dots, \mathcal{D}_n^r$ is the partition of \mathcal{D} obtained using the classical RC ranking procedure); assign to every object in $\Delta^\mathcal{I}$ a layer w.r.t. the defeasible axioms it satisfies, that is, an object x is in L_i iff either $x \in (C \sqcap D)^\mathcal{I}$ or $x \notin C^\mathcal{I}$ for every axiom $C \sqsubseteq D$ in every set \mathcal{D}_j^r , $i \leq j \leq n$, and, if $i \geq 1$, there is an axiom $E \sqsubseteq F$ in \mathcal{D}_{i-1}^r s.t. $x \in C^\mathcal{I}$ and $x \notin F^\mathcal{I}$. Note that, since \mathcal{I} is a model of \mathcal{T}_δ , all the individuals falling under $\delta^\mathcal{I}$ necessarily end up into the lower layer L_0 .

Consider each set of defeasible axioms \mathcal{D}_i^r . An object x satisfies the axioms in \mathcal{D}_i^r iff for every $C \sqsubseteq D \in \mathcal{D}_i^r$ either x falls under the concept $C \sqcap D$ (the individual *realises* the axiom) or x does not fall under C (the individual does not realise the axiom). Consider all possible

combinations (consistent with $\langle \mathcal{T}, \mathcal{D} \rangle$) of realisations and non-realizations of the axioms in \mathcal{D}_i^r : we want to be sure to have an individual in L_i that satisfies each such combination. If there is none, then create one and add it to the layer and modify the domain and the interpretation function accordingly. It is possible that the creation of such individual forces also the creation of other individuals related to it through some role; in such a case create them and add them to some layer accordingly to the constraints specified here above. The construction of the ranking procedure assures us that for every $C \sqsubseteq D \in \mathcal{D}_i^r$ it is possible to add an individual realising it (otherwise $C \sqsubseteq D \in \mathcal{D}_\infty^r$, but we have assumed that $\mathcal{D}_\infty^r = \emptyset$).

The final model we obtain is a model of $\langle \mathcal{T}, \mathcal{D} \rangle$, since it is a model of \mathcal{T} and for every axiom in \mathcal{D} there is at least an individual satisfying $C \sqcap D$ that is preferred to all the other individuals satisfying $C \sqcap \neg D$. In such a model, $C^R \cap \min_{\prec^R} \Delta^R \neq \emptyset$ since we have an individual a originally satisfying $C \sqcap \delta$, that consequently now satisfies C and is in L_0 . ■

Lemma 2 (*) *Let $\langle \mathcal{T}, \mathcal{D} \rangle$ be an ontology base s.t. $\mathcal{D}_\infty = \emptyset$. Then there is no $C \sqsubseteq D \in \mathcal{D}$ s.t. $r_{\mathcal{K}}(C \sqsubseteq D) = \infty$.*

Proof: If $\mathcal{D}_\infty = \emptyset$ then we have partitioned the set \mathcal{D} into $\mathcal{D}_0, \dots, \mathcal{D}_n$. Note that if $\mathcal{D}_\infty = \emptyset$, it must be that the TBox \mathcal{T}_{δ_0} (and all its subsets) is consistent.

Consider now the ontology $\langle \mathcal{T}, \mathcal{D}_n \rangle$ and the correspondent classical TBox \mathcal{T}_{δ_n} . For any $C \sqsubseteq D$ in \mathcal{D}_n there must be at least a classical model \mathcal{J} of \mathcal{T}_{δ_n} s.t. $\mathcal{J} \not\models C \sqcap \delta_n \sqsubseteq \perp$. Take one such model for each $C \sqsubseteq D$ in \mathcal{D}_n , and let $\mathcal{I} = \langle \Delta_{\mathcal{I}}, \cdot^{\mathcal{I}} \rangle$ be the interpretation obtained by unifying all such models. It is immediate to see that \mathcal{I} is a model of \mathcal{T}_{δ_n} such that $\mathcal{I} \not\models C \sqcap \delta_n \sqsubseteq \perp$ for any $C \sqsubseteq D$ in \mathcal{D}_n . Let's define a ranked model $R^{\mathcal{I}} = \langle \Delta^{\mathcal{I}}, \cdot^{R^{\mathcal{I}}}, \prec^{R^{\mathcal{I}}} \rangle$ in the following way:

- If $\mathbf{N}_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$ is the signature used of \mathcal{I} , $R^{\mathcal{I}}$ is defined over a new signature $\mathbf{N}'_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$, with $\mathbf{N}'_{\mathcal{C}} = \mathbf{N}_{\mathcal{C}} \setminus \{\delta_n\}$;
- for every $r \in \mathbf{N}_{\mathcal{R}}$, $r^{R^{\mathcal{I}}} = r^{\mathcal{I}}$;
- for every $C \in \mathbf{N}'_{\mathcal{C}}$, $C^{R^{\mathcal{I}}} = C^{\mathcal{I}}$;
- for every $x, y \in \Delta^{\mathcal{I}}$, $x \prec^{R^{\mathcal{I}}} y$ iff $x \in \delta_n^{\mathcal{I}}$ and $y \notin \delta_n^{\mathcal{I}}$.

It is easy to see, in an analogous way as for the Proposition 3, that $R^{\mathcal{I}}$ is a model of $\langle \mathcal{T}, \mathcal{D}_n \rangle$, s.t. $R^{\mathcal{I}} \not\models C \sqsubseteq \perp$ for any $C \sqsubseteq D \in \mathcal{D}_n$. Now consider the ontology $\langle \mathcal{T}, \mathcal{D}_n \cup \mathcal{D}_{n-1} \rangle$ and the correspondent TBox $\mathcal{T}_{\delta_{n-1}} = \mathcal{T} \cup \{C \sqcap \delta_{i-1} \sqsubseteq D \mid C \sqsubseteq D \in \mathcal{D}_n \cup \mathcal{D}_{n-1}\}$. Take under consideration each conditional $C \sqsubseteq D \in \mathcal{D}_{n-1}$. $\mathcal{T}_{\delta_{n-1}}$ is consistent and for every $C \sqsubseteq D \in \mathcal{D}_{n-1}$ we do not derive $\mathcal{T}_{\delta_{n-1}} \models C \sqcap \delta_{n-1} \sqsubseteq \perp$ for none of the antecedents $C \sqcap \delta_{n-1}$ of the correspondent conditionals $C \sqcap \delta_{n-1} \sqsubseteq D$. Hence, for each $C \sqsubseteq D \in \mathcal{D}_{n-1}$ there must be a model $\mathcal{J}_{C|D} = \langle \Delta^{\mathcal{J}_{C|D}}, \cdot^{\mathcal{J}_{C|D}} \rangle$ of $\mathcal{T}_{\delta_{n-1}}$ s.t. $\mathcal{J}_{C|D} \not\models C \sqcap \delta_{n-1} \sqsubseteq \perp$. Note that, by the exceptionality procedure, we must have $\mathcal{J}_{C|D} \models E \sqcap \delta_{n-1} \sqsubseteq \perp$ for every $E \sqsubseteq F \in \mathcal{D}_n$.

Now consider the model \mathcal{I} and each model $\mathcal{J}_{C|D}$ (one for each $C \sqsubseteq D \in \mathcal{D}_{n-1}$), and define the interpretation $\mathcal{I}_{n-1} = \langle \Delta^{\mathcal{I}_{n-1}}, \cdot^{\mathcal{I}_{n-1}} \rangle$ in the following way:

- $\Delta^{\mathcal{I}_{n-1}} = \Delta^{\mathcal{I}} \cup \bigcup \{\Delta^{\mathcal{J}_{C|D}}\}$;

- $\mathcal{I}_{n-1} = \mathcal{I} \cup \bigcup \{\mathcal{J}_{C|D}\}.$

Now define a ranked model $R^{\mathcal{I}_{n-1}} = \langle \Delta^{\mathcal{I}_{n-1}}, \cdot^{R^{\mathcal{I}_{n-1}}}, \prec^{R^{\mathcal{I}_{n-1}}} \rangle$ in the following way:

- If $\mathbf{N}_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$ is the signature used of \mathcal{I}_{n-1} , $R^{\mathcal{I}}$ is defined over a new signature $\mathbf{N}'_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$, with $\mathbf{N}'_{\mathcal{C}} = \mathbf{N}_{\mathcal{C}} \setminus \{\delta_n, \delta_{n-1}\}$;
- for every $r \in \mathbf{N}_{\mathcal{R}}$, $r^{R^{\mathcal{I}_{n-1}}} = r^{\mathcal{I}_{n-1}}$;
- for every $C \in \mathbf{N}'_{\mathcal{C}}$, $C^{R^{\mathcal{I}_{n-1}}} = C^{\mathcal{I}_{n-1}}$;
- for every $x, y \in \Delta^{\mathcal{I}_{n-1}}$, $x \prec^{R^{\mathcal{I}}} y$ iff $x \in \delta_{n-1}^{\mathcal{I}_{n-1}}$ and $y \notin \delta_{n-1}^{\mathcal{I}_{n-1}}$, or $x \in \delta_n^{\mathcal{I}_{n-1}}$ and $y \notin \delta_{n-1}^{\mathcal{I}_{n-1}}$ and $y \notin \delta_n^{\mathcal{I}_{n-1}}$.

Again, it is easy to check that $R^{\mathcal{I}_{n-1}}$ is a model of $\langle \mathcal{T}, \mathcal{D}_n \cup \mathcal{D}_{n-1} \rangle$ s.t. $R^{\mathcal{I}_{n-1}} \not\models C \sqsubseteq \perp$ for any $C \sqsubseteq D \in \mathcal{D}_n \cup \mathcal{D}_{n-1}$. We can go on with this procedure until we arrive to \mathcal{D}_0 , obtaining a model R of $\langle \mathcal{T}, \mathcal{D} \rangle$ s.t. $R \not\models C \sqsubseteq \perp$ for any $C \sqsubseteq D \in \mathcal{D}$. ■

Proposition 7 *Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, consider the sets $\mathcal{T}^*, \mathcal{D}_0, \dots, \mathcal{D}_n$ as determined by $\text{ComputeRanking}(\mathcal{K})$. Then for every defeasible axiom $C \sqsubseteq D \in \mathcal{D}$, $r_{\mathcal{K}}(C \sqsubseteq D) = i$ ($0 \leq i \leq n$) iff $C \sqsubseteq D$ is in \mathcal{D}_i , and $r_{\mathcal{K}}(C \sqsubseteq D) = \infty$ iff $C \sqsubseteq \perp \in \mathcal{T}^*$.*

Proof: An immediate consequence of Proposition 3 is that if $C \sqsubseteq D$ is in the fixed point of the function $E_{\mathcal{T}}$ (and so $C \sqsubseteq \perp$ is in \mathcal{T}^*), $r_{\mathcal{K}}(C \sqsubseteq D) = \infty$: Proposition 3 guarantees that the set $E_{\mathcal{T}}(\mathcal{D})$ is a subset of the set of axioms in \mathcal{D} with rank 1, and then, due to this, $E_{\mathcal{T}}(E_{\mathcal{T}}(\mathcal{D}))$ just be a subset of the set of axioms in \mathcal{D} with rank 2, and so on. So, $C \sqsubseteq \perp \in \mathcal{T}^*$ implies $r_{\mathcal{K}}(C \sqsubseteq D) = \infty$.

Since we necessarily end up with a KB $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$ s.t. the the fixed point of the exceptionality procedure is empty, by Lemma 2 we immediately obtain that if $r_{\mathcal{K}}(C \sqsubseteq D) = \infty$ then $C \sqsubseteq \perp \in \mathcal{T}^*$ and, from the combination of the Propositions 3 and 6, the correctness of every application of the function $E_{\mathcal{T}}$, that is, $r_{\mathcal{K}}(C \sqsubseteq D) = i$ ($0 \leq i \leq n$) iff $C \sqsubseteq D$ is in \mathcal{D}_i . ■

Proposition 8 *Given a KB $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, its characteristic RC-model $R_{\mathcal{K}}^{\cup}$, and a defeasible subsumption axiom $C \sqsubseteq D$. Then*

$$\mathcal{K} \vdash_{rc} C \sqsubseteq D \text{ iff } R_{\mathcal{K}}^{\cup} \models C \sqsubseteq D .$$

Proof: Immediate from Lemma 3 below. ■

Lemma 3 (*) *Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and a concept C , $\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp$ iff $r_{\mathcal{K}}(C) \leq i$.*

Proof: From right to left. Assume $r_{\mathcal{K}}(C) \leq i$. Then in the model $R_{\mathcal{K}}^{\cup}$ there is an individual $x \in C^{R_{\mathcal{K}}^{\cup}}$ s.t. $h_{R_{\mathcal{K}}^{\cup}}(x) = i$. Now define the submodel $R_{\mathcal{K}_i}^{\cup}$ from $R_{\mathcal{K}}^{\cup}$ in the following way:

consider only the layers L_j s.t. $j \geq i$. If an individual in these layers is connected to any set of individuals in some L_k , with $k < i$, through a chain of roles, preserve such individuals and simply ‘move’ them to the highest layer of the model. It is easy to see that $R_{\mathcal{K}_i}^\cup$ is a model of $\langle \mathcal{T}^*, \mathcal{D}_i \cup \dots \cup \mathcal{D}_n \rangle$: $R_{\mathcal{K}}^\cup$ is a model of $\langle \mathcal{T}^*, \mathcal{D}^* \rangle$, hence $R_{\mathcal{K}_i}^\cup$ is a model of \mathcal{T}^* too; from Proposition 2 we know that $r_{\mathcal{K}}(C) = i$ iff $h_{R_{\mathcal{K}}^\cup}(C) = i$, hence, by Proposition 7, for every axiom $C \sqsubseteq D$ in $\mathcal{D}_i \cup \dots \cup \mathcal{D}_n$, $h_{R_{\mathcal{K}_i}^\cup}(C \sqcap D) < h_{R_{\mathcal{K}_i}^\cup}(C \sqcap \neg D)$.

Let’s us now define the classical DL-interpretation $\mathcal{I}^{R_{\mathcal{K}_i}^\cup} = \langle \Delta^{R_{\mathcal{K}_i}^\cup}, \mathcal{I}^{R_{\mathcal{K}_i}^\cup} \rangle$ in the following way:

- $\mathcal{I}^{R_{\mathcal{K}_i}^\cup}$ is defined over a new signature $\mathbf{N}'_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$, with $\mathbf{N}'_{\mathcal{C}} = \mathbf{N}_{\mathcal{C}} \cup \{\delta_i\}$, where $\mathbf{N}_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$ is the signature used in the model $R_{\mathcal{K}_i}^\cup$;
- for every $r \in \mathbf{N}_{\mathcal{R}}$, $r^{\mathcal{I}^{R_{\mathcal{K}_i}^\cup}} = r^{R_{\mathcal{K}_i}^\cup}$;
- for every $C \in \mathbf{N}_{\mathcal{C}}$, $C^{\mathcal{I}^{R_{\mathcal{K}_i}^\cup}} = C^{R_{\mathcal{K}_i}^\cup}$;
- for every $x \in \Delta^{R_{\mathcal{K}_i}^\cup}$, $x \in \delta^{\mathcal{I}^{R_{\mathcal{K}_i}^\cup}}$ iff $x \in \min_{\prec_{R_{\mathcal{K}_i}^\cup}}(\Delta^{R_{\mathcal{K}_i}^\cup})$.

It is easy to see that $\mathcal{I}^{R_{\mathcal{K}_i}^\cup}$ is a model of \mathcal{T}_{δ_i} , and $\mathcal{I}^{R_{\mathcal{K}_i}^\cup} \not\models C \sqcap \delta_i \sqsubseteq \perp$. Hence $\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp$, and by monotonicity also $\mathcal{T}_{\delta_j} \not\models C \sqcap \delta_j \sqsubseteq \perp$, $i \leq j \leq n$.

From left to right. Assume $\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp$. Then there is a model \mathcal{I} of \mathcal{T}_{δ_i} with an object $x \in \Delta^{\mathcal{I}}$ s.t. $x \in (C \sqcap \delta_i)^{\mathcal{I}}$. Divide $\Delta^{\mathcal{I}}$ in sets $L_i^{\mathcal{I}}, \dots, L_{n+1}^{\mathcal{I}}$ in the following way:

- for every $x \in \Delta^{\mathcal{I}}$, $x \in L_j^{\mathcal{I}}$ iff for each axiom $E \sqsubseteq F$ in $\mathcal{D}_j \cup \dots \cup \mathcal{D}_n$, either $x \in (E \sqcap F)^{\mathcal{I}}$ or $x \notin E^{\mathcal{I}}$, and there is an axiom $E' \sqsubseteq F' \in \mathcal{D}_{j-1}$ s.t. $x \in E'^{\mathcal{I}}$ and $x \notin F'^{\mathcal{I}}$.

Note that every x s.t. $x \in \delta_i^{\mathcal{I}}$ must be in $L_i^{\mathcal{I}}$. Now combine \mathcal{I} with $R_{\mathcal{K}}^\cup$ in a ranked interpretation $R' = \langle \Delta^{R'}, \cdot^{R'}, \prec^{R'} \rangle$ in the following way:

- $\Delta^{R'} = \Delta^{R_{\mathcal{K}}^\cup} \cup \Delta^{\mathcal{I}}$;
- for every role r , $r^{R'} = r^{R_{\mathcal{K}}^\cup} \cup r^{\mathcal{I}}$;
- for every concept C , $C^{R'} = C^{R_{\mathcal{K}}^\cup} \cup C^{\mathcal{I}}$;
- the layers $L_0^{R'}, \dots, L_n^{R'}$ are organised in the following way:
 - $L_0^{R'} = L_0^{R_{\mathcal{K}}^\cup}$;
 - \vdots
 - $L_{i-1}^{R'} = L_{i-1}^{R_{\mathcal{K}}^\cup}$;
 - $L_i^{R'} = L_i^{R_{\mathcal{K}}^\cup} \cup L_i^{\mathcal{I}}$;
 - \vdots
 - $L_{n+1}^{R'} = L_{n+1}^{R_{\mathcal{K}}^\cup} \cup L_{n+1}^{\mathcal{I}}$;

It is easy to prove that R' is a model of \mathcal{K} in which we have an object $x \in C^{R'}$ in the i^{th} layer, that is, R' is a model of \mathcal{K} s.t. $h_{R'}(C) \leq i$. Hence $r_{\mathcal{K}}(C) \leq i$. ■

Proposition 9 $C \sqsubseteq D$ is in the rational closure of $\langle \mathcal{T}, \mathcal{D} \rangle$ iff $\mathcal{T}^* \models C \sqsubseteq D$.

Proof: From right to left it is obvious. For the other direction, assume there is a model \mathcal{I} of \mathcal{T}^* that has an object a s.t. $a \in C^{\mathcal{I}}$ and $a \notin D^{\mathcal{I}}$. Now, we can create a ranked interpretation $R^{\mathcal{I}}$ of \mathcal{I} exactly in the same way we have done in the proof of Proposition 6. $R^{\mathcal{I}}$ would be a model of $\langle \mathcal{T}, \mathcal{D} \rangle$ s.t. $R^{\mathcal{I}} \not\models C \sqsubseteq D$, hence we would have also a countable infinite model of $\langle \mathcal{T}, \mathcal{D} \rangle$ that does not satisfy $C \sqsubseteq D$. Consequently $R_{\mathcal{K}}^{\mathcal{U}} \not\models C \sqsubseteq D$, where $R_{\mathcal{K}}^{\mathcal{U}}$ is the characteristic model of the RC of $\langle \mathcal{T}, \mathcal{D} \rangle$, and $C \sqsubseteq D$ would not be in the RC of $\langle \mathcal{T}, \mathcal{D} \rangle$. ■

Proposition 10 An ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ is rationally inconsistent iff $\mathcal{T}^* \models \top \sqsubseteq \perp$.

Proof: An ontology is rationally inconsistent iff it rationally entails $\top \sqsubseteq \perp$, that is, iff it rationally entails $\top \sqsubseteq \perp$, that is, by Proposition 9, iff $\mathcal{T}^* \models \top \sqsubseteq \perp$. ■

Lemma 1 Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and the correspondent ontology in normal form $\mathcal{K} = \langle \mathcal{T}', \mathcal{D}' \rangle$, $C \sqsubseteq D \in \mathcal{D}_i$ for some i iff $A_C \sqsubseteq A_D \in \mathcal{D}'_i$, where A_C is the new atom corresponding to C ($A_C = C \in \mathcal{T}'$), and analogously for A_D ($A_D = D \in \mathcal{T}'$).

Proof: Let $\langle \mathcal{T}^+, \mathcal{D}^+ \rangle$ the KB obtained adding to \mathcal{T} the axioms $\mathcal{A}_C = C$ and $\mathcal{A}_D = D$ for every axiom $C \sqsubseteq D \in \mathcal{D}$ (A_C, A_D being new atomic concepts), while \mathcal{D}^+ is obtained substituting in \mathcal{D} every axiom $C \sqsubseteq D$ with $A_C \sqsubseteq A_D$. The proposition can be proven by induction on the exceptionality function $E_{\mathcal{T}}$:

Therefore, it is sufficient to prove that for every $C \sqsubseteq D \in \mathcal{D}$, $\mathcal{T}_{\delta} \models C \sqcap \delta_0 \sqsubseteq \perp$ iff $\mathcal{T}_{\delta}^+ \models A_C \sqcap \delta_0 \sqsubseteq \perp$.

From left to right it is immediate, since $\mathcal{T}_{\delta} \models C \sqsubseteq D$ for every $C \sqsubseteq D \in \mathcal{T}_{\delta}^+$.

From right to left, if $\mathcal{T}_{\delta} \not\models C \sqcap \delta_0 \sqsubseteq \perp$ then there is a model \mathcal{I} of \mathcal{T}_{δ} (that does not interpret any atomic concept not appearing in \mathcal{T}_{δ}) s.t. $(C \sqcap \delta_0)^{\mathcal{I}} \neq \emptyset$. Extend the interpretation function $\cdot^{\mathcal{I}}$ of \mathcal{I} in such a way that $A_C^{\mathcal{I}} = C^{\mathcal{I}}$ for any new concept A_C introduced in \mathcal{T}_{δ}^+ ; this new interpretation is a model of \mathcal{T}_{δ}^+ , so $\mathcal{T}_{\delta}^+ \not\models A_C \sqsubseteq \perp$.

Since \mathcal{T}_{δ}' is just the normal form of \mathcal{T}_{δ}^+ , that preserves satisfaction, for every $C \sqsubseteq D \in \mathcal{D}$, $\mathcal{T}_{\delta} \models C \sqcap \delta_0 \sqsubseteq \perp$ iff $\mathcal{T}_{\delta}' \models A_C \sqcap \delta_0 \sqsubseteq \perp$, which concludes. ■

Proposition 11 Given an ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ and its normal form translation $\mathcal{K}' = \langle \mathcal{T}', \mathcal{D}' \rangle$, for every pair of \mathcal{EL}^{\perp} -concepts C, D , $\mathcal{K} \vdash_{rc} C \sqsubseteq D$ iff $\mathcal{K}' \vdash_{rc} C \sqsubseteq D$.

Proof: The schema of the proof of Lemma 1 can be used to prove that for every pair of concepts C, D , i is the lowest integer s.t. $0 \leq i \leq n$ and

$$\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp,$$

and

$$\mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq D$$

iff it is the lowest integer s.t. $0 \leq i \leq n$ and

$$\mathcal{T}'_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp ,$$

and

$$\mathcal{T}'_{\delta_i} \models C \sqcap \delta_i \sqsubseteq D .$$

■

6.1 Finite Model Property for Defeasible \mathcal{ALC} Knowledge Bases

We want to prove that defeasible \mathcal{ALC} ontologies satisfy the Finite Model Property. To this end, consider a finite defeasible \mathcal{ALC} knowledge base $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, and let $R = \langle \Delta^R, \cdot^R, \preceq^R \rangle$ be a ranked model of \mathcal{K} (with Δ^R possibly infinite, and with \prec^R being the strict part of \preceq^R). Let $\mathbf{N}_{\mathcal{C}} \cup \mathbf{N}_{\mathcal{R}}$ be the signature of our language, and let Γ be a set of concepts $\{C_1, \dots, C_n\}$ s.t. Γ is obtained closing under sub-concepts and negation the concepts appearing in the axioms in \mathcal{K} . Now we define the equivalence relation \sim_Γ as

$$\forall x, y \in \Delta^R, x \sim_\Gamma y \text{ iff } \forall C \in \Gamma, x \in C^R \text{ iff } y \in C^R .$$

We indicate with $[a]_\Gamma$ the equivalence class of the individuals that are related to an individual a through \sim_Γ :

$$[x]_\Gamma = \{y \mid x \sim_\Gamma y\} .$$

We introduce the new model $R' = \langle \Delta^{R'}, \cdot^{R'}, \preceq^{R'} \rangle$, defined as:

- $\Delta^{R'} = \{[x]_\Gamma \mid x \in \Delta^R\}$;
- for every $A \in \mathbf{N}_{\mathcal{C}} \cap \Gamma$, $A^{R'} = \{[x]_\Gamma \mid x \in A^R\}$;
- for every $A \notin \mathbf{N}_{\mathcal{C}} \cap \Gamma$, $A^{R'} = \emptyset$;
- for every $r \in \mathbf{N}_{\mathcal{R}}$, $r^{R'} = \{([x]_\Gamma, [y]_\Gamma) \mid (x, y) \in r^R\}$;
- For every $[x]_\Gamma, [y]_\Gamma \in \Delta^{R'}$, $[x]_\Gamma \preceq^{R'} [y]_\Gamma$ if there is an object $z \in [x]_\Gamma$ s.t. for all the objects $v \in [y]_\Gamma$, $z \prec^R v$; otherwise, $[y]_\Gamma \preceq^{R'} [x]_\Gamma$.

Let $\prec^{R'}$ and $\equiv^{R'}$ defined as usual:

- $[x]_\Gamma \prec^{R'} [y]_\Gamma$ iff $[x]_\Gamma \preceq^{R'} [y]_\Gamma$ and $[y]_\Gamma \not\preceq^{R'} [x]_\Gamma$;
- $[x]_\Gamma \equiv^{R'} [y]_\Gamma$ iff $[x]_\Gamma \preceq^{R'} [y]_\Gamma$ and $[y]_\Gamma \preceq^{R'} [x]_\Gamma$.

Note that $[x]_\Gamma \prec^{R'} [y]_\Gamma$ iff there is an object $z \in [x]_\Gamma$ s.t. for all the objects $v \in [y]_\Gamma$, $z \prec^R v$, while $[x]_\Gamma \equiv^{R'} [y]_\Gamma$ iff for every $z \in [x]_\Gamma$ there is a $v \in [y]_\Gamma$ s.t. $v \preceq^R z$, and for every $v \in [y]_\Gamma$ there is a $z \in [x]_\Gamma$ s.t. $z \preceq^R v$.

Given that Γ is finite, $\Delta^{R'}$ is clearly finite. The following results are easy to prove.

Lemma 4 *For every $C \in \Gamma$ and every $x \in \Delta^R$, $x \in C^R$ iff $[x]_\Gamma \in C^{R'}$.*

Proof: The proof is by straightforward induction on the construction of the concepts. ■

Lemma 5 *The preorder $\preceq^{R'}$ is a modular preorder.*

Proof: Reflexivity: Assume $[a]_\Gamma \not\preceq^{R'} [a]_\Gamma$. By the definition of $\preceq^{R'}$, it implies that we could not have any $a' \in [a]_\Gamma$ s.t. $a' \prec^R a''$ for every $a'' \in [a]_\Gamma$, that in turn would imply $[a]_\Gamma \preceq^{R'} [a]_\Gamma$, and we would have an absurdity.

Transitivity: Assume $[a]_\Gamma \preceq^{R'} [b]_\Gamma$ and $[b]_\Gamma \preceq^{R'} [c]_\Gamma$. We have four possible cases.

If $[a]_\Gamma \prec^{R'} [b]_\Gamma$ and $[b]_\Gamma \prec^{R'} [c]_\Gamma$, that means that there is an individual $a' \in [a]_\Gamma$ s.t. $a' \prec^R b'$ for every $b' \in [b]_\Gamma$, and that there is a $b^* \in [b]_\Gamma$ s.t. $b^* \prec c'$ for every $c' \in [c]_\Gamma$. Hence $a' \prec^R c'$ for every $c' \in [c]_\Gamma$, and $[a]_\Gamma \prec^{R'} [c]_\Gamma$.

Assume that $[a]_\Gamma \prec^{R'} [b]_\Gamma$ and $[b]_\Gamma \equiv^{R'} [c]_\Gamma$. Then there is an individual $a' \in [a]_\Gamma$ s.t. $a' \prec^R b'$ for every $b' \in [b]_\Gamma$, for every $b' \in [b]_\Gamma$ there is at least a $c' \in [c]_\Gamma$ s.t. $c' \preceq^R b'$, and for every $c' \in [c]_\Gamma$ there is at least a $b' \in [b]_\Gamma$ s.t. $b' \preceq^R c'$. It must be the case that $a' \prec^R c'$ for every $c' \in [c]_\Gamma$, that is, $[a]_\Gamma \prec^{R'} [c]_\Gamma$; otherwise we would have that there is a $c' \in [c]_\Gamma$ s.t. $c' \preceq^R a'$, that, since there is a $b' \in [b]_\Gamma$ s.t. $b' \preceq^R c'$, by the transitivity of \preceq^R would imply $b' \preceq^R a'$, against the hypothesis that $[a]_\Gamma \prec^{R'} [b]_\Gamma$.

Assume that $[a]_\Gamma \equiv^{R'} [b]_\Gamma$ and $[b]_\Gamma \prec^{R'} [c]_\Gamma$. There must be a $b' \in [b]_\Gamma$ s.t. $b' \prec^R c'$ for every $c' \in [c]_\Gamma$, and there must be an $a' \in [a]_\Gamma$ s.t. $a' \preceq^R b'$. Hence $a' \prec^R c'$ for every $c' \in [c]_\Gamma$, and we can conclude that $[a]_\Gamma \prec^{R'} [c]_\Gamma$.

Assume that $[a]_\Gamma \equiv^{R'} [b]_\Gamma$ and $[b]_\Gamma \equiv^{R'} [c]_\Gamma$. Then it is easy to check for every $a' \in [a]_\Gamma$ there must be a $c' \in [c]_\Gamma$ s.t. $c' \preceq a'$ and for every $c' \in [c]_\Gamma$ there must be an $a' \in [a]_\Gamma$ s.t. $a' \preceq c'$.

Modularity: It is sufficient to prove that for every pair of individuals $[a]_\Gamma, [b]_\Gamma$ in R' , either $[a]_\Gamma \preceq^{R'} [b]_\Gamma$ or $[b]_\Gamma \preceq^{R'} [a]_\Gamma$, which is an immediate consequence of the definition of $\preceq^{R'}$. ■

Theorem 1 (FMP) *Given a finite ontology $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$, if \mathcal{K} has a ranked model R , then it has a finite ranked model R' s.t. for every $C, D \in \Gamma$, $C \preceq^R D$ iff $C \preceq^{R'} D$.*

Proof: Let $\mathcal{K} = \langle \mathcal{T}, \mathcal{D} \rangle$ be a defeasible ontology, R a model of \mathcal{K} and R' a finite interpretation constructed from R as defined above. Let $C \sqsubset D \in \mathcal{K}$. Hence, either $C^R = \emptyset$, or the height of $C \sqcap D$ in R is lower than the height of $C \sqcap \neg D$, that is, there is at least an individual b satisfying $C \sqcap D$ s.t. for every individual a satisfying $C \sqcap \neg D$, $b \prec^R a$. Since C, D and $\neg D$ are in Γ , the individual $[b]_\Gamma \in \Delta^{R'}$ (obtained from $b \in \Delta^R$, that hence satisfies $C \sqcap D$) must be preferred to all the individuals satisfying $C \sqcap \neg D$, that is, $[b]_\Gamma \prec^{R'} [a]_\Gamma$ for every individual $[a]_\Gamma$ s.t. $[a]_\Gamma \in (C \sqcap \neg D)^{R'}$. Hence $R' \models C \sqsubset D$. ■

References

- [1] Alessandro Artale, Diego Calvanese, Roman Kontchakov, and Michael Zakharyashev. The DL-Lite family and relations. *Journal of Artificial Intelligence Research*, 36:1–69, 2009.

- [2] F. Baader, S. Brandt, and C. Lutz. Pushing the \mathcal{EL} envelope. In *Proceedings of the Nineteenth International Joint Conference on Artificial Intelligence (IJCAI-05)*, pages 364–369, Edinburgh, UK, 2005. Morgan-Kaufmann Publishers.
- [3] F. Baader, D. Calvanese, D. McGuinness, D. Nardi, and P. Patel-Schneider, editors. *The Description Logic Handbook: Theory, Implementation and Applications*. Cambridge University Press, 2 edition, 2007.
- [4] F. Baader and B. Hollunder. Embedding defaults into terminological knowledge representation formalisms. *Journal of Automated Reasoning*, pages 306–317, 1995.
- [5] Franz Baader and Bernhard Hollunder. Priorities on defaults with prerequisites, and their application in treating specificity in terminological default logic. *Journal of Automated Reasoning*, 15(1):41–68, 1995.
- [6] Piero A. Bonatti, Marco Faella, Carsten Lutz, Luigi Sauro, and Frank Wolter. Decidability of circumscribed description logics revisited. In *Advances in Knowledge Representation, Logic Programming, and Abstract Argumentation - Essays Dedicated to Gerhard Brewka on the Occasion of His 60th Birthday*, number 9060 in Lecture Notes in Computer Science, pages 112–124, 2015.
- [7] Piero A. Bonatti, Marco Faella, Iliana Petrova, and Luigi Sauro. A new semantics for overriding in description logics. *Artificial Intelligence Journal*, 222:1–48, 2015.
- [8] Piero A. Bonatti, Marco Faella, and Luigi Sauro. Adding default attributes to $EL++$. In *Proceedings of the 25th AAAI Conference on Artificial Intelligence (AAAI-11)*. AAAI Press, 2011.
- [9] Piero A. Bonatti, Marco Faella, and Luigi Sauro. Defeasible inclusions in low-complexity dls. *Journal of Artificial Intelligence Research*, 42:719–764, 2011.
- [10] Piero A. Bonatti, Carsten Lutz, and Frank Wolter. The complexity of circumscription in description logic. *J. Artif. Int. Res.*, 35(1):717–773, 2009.
- [11] R. Booth and J.B. Paris. A note on the rational closure of knowledge bases with both positive and negative knowledge. *Journal of Logic, Language and Information*, 7(2):165–190, 1998.
- [12] K. Britz, G. Casini, T. Meyer, K. Moodley, and I. Varzinczak. Ordered interpretations and entailment for defeasible description logics. Technical report, CAIR, CSIR Meraka and UKZN, South Africa, 2013.
- [13] K. Britz, J. Heidema, and T. Meyer. Semantic preferential subsumption. In J. Lang and G. Brewka, editors, *Proceedings of the 11th International Conference on Principles of Knowledge Representation and Reasoning (KR)*, pages 476–484. AAAI Press/MIT Press, 2008.
- [14] K. Britz, T. Meyer, and I. Varzinczak. Semantic foundation for preferential description logics. In D. Wang and M. Reynolds, editors, *Proceedings of the 24th Australasian Joint Conference on Artificial Intelligence*, number 7106 in LNAI, pages 491–500. Springer, 2011.

- [15] Marco Cadoli, Francesco M. Donini, and Marco Schaerf. Closed world reasoning in hybrid systems. In Zbigniew W. Ras, Maria Zemankova, and Mary L. Emrich, editors, *Proc. of the 5th Int. Sym. on Methodologies for Intelligent Systems (ISMIS-90)*, pages 474–481. North-Holland Publ. Co., Amsterdam, 1990.
- [16] G. Casini, T. Meyer, K. Moodley, and R. Nortjé. Relevant closure: A new form of defeasible reasoning for description logics. In E. Fermé and J. Leite, editors, *Proceedings of JELIA-14*, volume 8761 of *Lecture Notes in Computer Science*, pages 92–106. Springer, 2014.
- [17] G. Casini, T. Meyer, K. Moodley, and I. Varzinczak. Nonmonotonic reasoning in description logics: Rational closure for the abox. In *Proceedings of the 26th International Workshop on Description Logics*, pages 600–615, 2013.
- [18] G. Casini and U. Straccia. Rational closure for defeasible description logics. In T. Janhunen and I. Niemelä, editors, *Proceedings of the 12th European Conference on Logics in Artificial Intelligence (JELIA)*, number 6341 in LNCS, pages 77–90. Springer-Verlag, 2010.
- [19] G. Casini and U. Straccia. Defeasible inheritance-based description logics. *Journal of Artificial Intelligence Research*, 48:415–473, 2013.
- [20] G. Casini and U. Straccia. Lexicographic closure for defeasible description logics. In *Proceedings of the 8th Australasian Ontology Workshop (AOW)*, Forthcoming.
- [21] Giovanni Casini and Umberto Straccia. Towards rational closure for fuzzy logic: The case of propositional Gödel logic. In *Proceedings of the 19th International Conferences on Logic for Programming, Artificial Intelligence and Reasoning (LPAR-13)*, volume 8312 of *Lecture Notes in Computer Science, Advanced Research in Computing and Software Science*, pages 213–227. Springer Verlag, 2013.
- [22] F.M. Donini, D. Nardi, and R. Rosati. Description logics of minimal knowledge and negation as failure. *ACM Transactions on Computational Logic*, 3(2):177–225, 2002.
- [23] Francesco M. Donini, Daniele Nardi, and Riccardo Rosati. Autoepistemic description logics. In *Proc. of the 15th Int. Joint. Conf. on Artificial Intelligence (IJCAI’97)*, pages 136–141, 1997.
- [24] Thomas Eiter, Thomas Lukasiewicz, Roman Schindlauer, and Hans Tompits. Combining answer set programming with description logics for the semantic web. In *Proceedings of the 9th International Conference on Principles of Knowledge Representation and Reasoning (KR-04)*. AAAI Press, 2004.
- [25] L. Giordano, V. Gliozzi, N. Olivetti, and G.L. Pozzato. A minimal model semantics for rational closure. In *Proceedings of the 14th International Workshop on Nonmonotonic Reasoning (NMR)*, 2012.
- [26] L. Giordano, N. Olivetti, V. Gliozzi, and G.L. Pozzato. A minimal model semantics for nonmonotonic reasoning. In L. Fariñas del Cerro, A. Herzig, and J. Mengin, editors, *Proceedings of the 13th European Conference on Logics in Artificial Intelligence (JELIA)*, number 7519 in LNCS, pages 228–241. Springer, 2012.

- [27] L. Giordano, N. Olivetti, V. Gliozzi, and G.L. Pozzato. Minimal model semantics and rational closure in description logics. In *Proceedings of the 26th International Workshop on Description Logics*, 2013.
- [28] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Prototypical reasoning with low complexity description logics: Preliminary results. In *Proceedings of the 10th International Conference on Logic Programming and Nonmonotonic Reasoning (LPNMR-09)*, volume 5753 of *Lecture Notes In Computer Science*, pages 430–436, Berlin, Heidelberg, 2009. Springer-Verlag.
- [29] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Preferential vs rational description logics: which one for reasoning about typicality? In *19th European Conference on Artificial Intelligence (ECAI-10)*, volume 215 of *Frontiers in Artificial Intelligence and Applications*, pages 1069–1070. IOS Press, 2010.
- [30] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Reasoning about typicality in low complexity DLs: The logics $\text{EL}^\perp_{\text{min}}$ and $\text{DL-Lite}_{\text{c}} \text{t}_{\text{min}}$. In *International Joint Conference on Artificial Intelligence (IJCAI-11)*, pages 894–899. IJCAI/AAAI, 2011.
- [31] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. A tableau calculus for a nonmonotonic extension of \mathcal{EL}^\perp . In *20th International Conference on Automated Reasoning with Analytic Tableaux and Related Methods (TABLEAUX-11)*, volume 6763 of *Lecture Notes in Computer Science*, pages 180–195. Springer Verlag, 2011.
- [32] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Preferential low complexity description logics: Complexity results and proof methods. In *Proceedings of the 2012 International Workshop on Description Logics (DL-12)*, volume 846 of *CEUR Workshop Proceedings*, 2012.
- [33] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. A non-monotonic description logic for reasoning about typicality. *Artificial Intelligence Journal*, 195:165–202, 2013.
- [34] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Minimal models for rational closure in SHIQ. In *Proceedings of the 15th Italian Conference on Theoretical Computer Science (ICTCS-14)*, CEUR Workshop Proceedings, pages 271–277, 2014.
- [35] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Rational closure in SHIQ. In *Proceedings of the 27th International Workshop on Description Logics (DL-14)*, CEUR Workshop Proceedings, pages 543–555, 2014.
- [36] Laura Giordano, Valentina Gliozzi, Nicola Olivetti, and Gian Luca Pozzato. Semantic characterization of rational closure: From propositional logic to description logics. *Artificial Intelligence Journal*, 226:1–33, 2015.
- [37] S. Grimm and P. Hitzler. A preferential tableaux calculus for circumscriptive \mathcal{ALCO} . In *RR '09: Proceedings of the 3rd International Conference on Web Reasoning and*

- Rule Systems*, volume 5837 of *Lecture Notes In Computer Science*, pages 40–54, Berlin, Heidelberg, 2009. Springer-Verlag.
- [38] S. O. Hansson. *A Textbook of Belief Dynamics. Theory Change and Database Updating*. Kluwer, 1999.
 - [39] M. Horridge. *Justification based explanation in ontologies*. PhD thesis, The University of Manchester, 2011.
 - [40] S. Kraus, D. Lehmann, and M. Magidor. Nonmonotonic reasoning, preferential models and cumulative logics. *Artificial Intelligence*, 44:167–207, 1990.
 - [41] Patrick Lambrix, Nahid Shahmehri, and Niclas Wahlloef. A default extension to description logics for use in an intelligent search engine. In *HICSS '98: Proceedings of the Thirty-First Annual Hawaii International Conference on System Sciences-Volume 5*, page 28, Washington, DC, USA, 1998. IEEE Computer Society.
 - [42] D. Lehmann. Another perspective on default reasoning. *Annals of Mathematics and Artificial Intelligence*, 15(1):61–82, 1995.
 - [43] D. Lehmann and M. Magidor. What does a conditional knowledge base entail? *Artificial Intelligence*, 55:1–60, 1992.
 - [44] M. Ludwig and Rafael Peñaloza. Error-tolerant reasoning in the description logic \mathcal{EL} . In E. Fermé and J. Leite, editors, *Proceedings of JELIA-14*, volume 8761 of *Lecture Notes in Computer Science*, pages 107–121. Springer, 2014.
 - [45] Thomas Lukasiewicz. Expressive probabilistic description logics. *Artificial Intelligence*, 172(6-7):852–883, 2008.
 - [46] Thomas Lukasiewicz. Probabilistic description logic programs under inheritance with overriding for the semantic web. *International Journal of Approximate Reasoning*, 49(31):18–34, 2008.
 - [47] D. Makinson. *Bridges from Classical to Nonmonotonic Logic*, volume 5 of *Texts in Computing*. King’s College Publications, 2005.
 - [48] OWL 2 Web Ontology Language Document Overview. <http://www.w3.org/TR/2009/REC-owl2-overview-20091027/>. W3C, 2009.
 - [49] OWL 2 Web Ontology Language Profiles. <http://www.w3.org/TR/2009/REC-owl2-profiles-20091027/>. W3C, 2009.
 - [50] OWL 2 Web Ontology Language Profiles: OWL 2 EL. http://www.w3.org/TR/2009/REC-owl2-profiles-20091027/#OWL_2_EL. W3C, 2009.
 - [51] OWL 2 Web Ontology Language Profiles: OWL 2 RL. http://www.w3.org/TR/2009/REC-owl2-profiles-20091027/#OWL_2_RL. W3C, 2009.
 - [52] J. Quantz. A preference semantics for defaults in terminological logics. In *Proceedings of the 3rd International Conference on Principles of Knowledge Representation and Reasoning (KR)*, pages 294–305, 1992.

- [53] R. Stevens, M. E. Aranguren, K. Wolstencroft, U. Sattler, N. Drummond, M. Horridge, and A. Rector. Using OWL to model biological knowledge. *Intern. Journ. of Human-Computer Studies*, 65(7):583 – 594, 2007.
- [54] Umberto Straccia. Default inheritance reasoning in hybrid KL-ONE-style logics. In *Proceedings of IJCAI-93, 13th International Joint Conference on Artificial Intelligence*, pages 676–681, Chambéry, France, 1993.
- [55] David S. Touretzky. *The mathematics of inheritance systems*. Pitman, London, GB, 1986.

Procedure LexicographicClosure(\mathcal{K}, α)

Input: Ontology \mathcal{K} and defeasible axiom α of the form $C \sqsubseteq D$
Output: **true** iff $C \sqsubseteq D$ is in the Lexicographic Closure of \mathcal{K}

```

1   $CL := \mathcal{T} \models C \sqsubseteq D$  // Check if  $\alpha$  holds classically;
2  if  $CL$  then
3    return  $CL$ 
4   $\langle \langle \mathcal{T}^*, \mathcal{D}^* \rangle, \{\mathcal{D}_0, \dots, \mathcal{D}_n\} \rangle := \text{ComputeRanking}(\mathcal{K})$ ;
5   $CL := \mathcal{T}^* \models C \sqsubseteq D$  // Check if  $\alpha$  holds classically, after finding strict knowledge in  $\mathcal{D}$ ;
6  if  $CL$  then
7    return  $CL$ 
8  // Compute  $C$ 's rank  $i$ ;
9   $i := 0$ ;  $\mathcal{D}_{\mathfrak{R}} := \mathcal{D}^*$ ;
10  $\mathcal{T}_{\delta_0} := \mathcal{T}^* \cup \{E \sqcap \delta_0 \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D}_{\mathfrak{R}}\}$ , where  $\delta_0$  is a new atomic concept;
11 while  $\mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq \perp$  and  $\mathcal{D}_{\mathfrak{R}} \neq \emptyset$  do
12    $\mathcal{D}_{\mathfrak{R}} := \mathcal{D}_{\mathfrak{R}} \setminus \mathcal{D}_i$ ;  $i := i + 1$ ;
13    $\mathcal{T}_{\delta_i} := \mathcal{T}^* \cup \{E \sqcap \delta_i \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D}_{\mathfrak{R}}\}$ , where  $\delta_i$  is a new atomic concept;
14 // Check if  $\alpha$  holds under RC;
15  $RC := (\mathcal{T}_{\delta_i} \not\models C \sqcap \delta_i \sqsubseteq \perp) \wedge (\mathcal{T}_{\delta_i} \models C \sqcap \delta_i \sqsubseteq D)$ ;
16 if  $RC$  then
17   return  $RC$ 
18 // Compute  $\min_{C, \prec_{ser}}(\mathcal{D})$ ;
19 if  $i \leq n$  then
20    $\overline{\mathcal{D}} := \mathcal{D}_i \cup \dots \cup \mathcal{D}_n$ 
21 else
22    $\overline{\mathcal{D}} := \emptyset$ 
23  $k = i$ ,  $\min C_k := \{\overline{\mathcal{D}}\}$ ,  $\min C := \min C_k$ ;
24 while  $k > 0$  do
25    $\min C_{k-1} := \emptyset$ ;
26    $card := |\mathcal{D}_{k-1}|$ ,  $\min Card := 1$ ;
27   while  $card \geq \min Card$  do
28     foreach  $\Psi_j \subseteq \mathcal{D}_{k-1}$  s.t.  $|\Psi_j| = card$  do
29       foreach  $\Theta \in \min C$  do
30          $\Theta' = \Psi_j \cup \Theta$ ;
31          $\mathcal{T}_{\Theta'} := \mathcal{T}^* \cup \{E \sqcap \delta_{\Theta'} \sqsubseteq F \mid E \sqsubseteq F \in \Theta'\}$ , where  $\delta_{\Theta'}$  is a new atomic concept;
32         if  $\mathcal{T}_{\Theta'} \not\models C \sqcap \delta_{\Theta'} \sqsubseteq \perp$  then
33            $\min C_{k-1} := \min C_{k-1} \cup \{\Theta'\}$ ;
34           if  $card > \min Card$  then
35              $\min Card := card$ 
36        $card := card - 1$ 
37   if  $\min C_{k-1} \neq \emptyset$  then
38      $\min C := \min C_{k-1}$ 
39    $k := k - 1$ 
40 // Check now if  $\alpha$  holds under LC;
41 if  $\min C = \min C_i$  then
42   return false // No change w.r.t. RC
43 foreach  $\Theta \in \min C$  do
44   if  $\mathcal{T}_{\Theta} \not\models C \sqcap \delta_{\Theta} \sqsubseteq D$  then
45     return false
46 return true

```

Procedure InheritanceBasedRationalClosure(\mathcal{K}, α)

Input: Ontology \mathcal{K} and defeasible \mathcal{EL}^\perp axiom α
Output: true iff $\mathcal{K} \vdash_{in} \alpha$

- 1 $\langle \mathcal{K}, \alpha \rangle := \text{Normalise}(\mathcal{K}, \alpha)$ //normalise both \mathcal{K} and α ;
- 2 $CTD := \text{RationalClosure}(\mathcal{K}, \top \sqsubseteq \perp)$ //Check if \mathcal{K} rationally inconsistent;
- 3 **if** CTD **then**
- 4 **return** CTD
- 5 $N_{\mathcal{K}} := \text{BuildInheritanceNet}(\mathcal{K})$ //Build inheritance net $N_{\mathcal{K}}$ from \mathcal{K} ;
- 6 $\mathcal{D}_{in} := \mathcal{D}$;
- 7 **foreach** $C, D \in N_{\mathcal{K}}$ **do**
- 8 $\Delta_{C,D} := \{E \rightarrow F \mid E \rightarrow F \text{ defeasible link occurring in a duct from } C \text{ to } D\}$;
- 9 $\mathcal{D}' := \{E \sqsubseteq F \in \mathcal{D} \mid E \rightarrow F \in \Delta_{C,D}\}$;
- 10 $\mathcal{K}' := \langle \mathcal{T}, \mathcal{D}' \rangle$;
- 11 **if** $\text{RationalClosure}(\mathcal{K}', C \sqsubseteq D)$ **then**
- 12 $\mathcal{D}_{in} := \mathcal{D}_{in} \cup \{C \sqsubseteq D\}$
- 13 // Check now if α holds under Inheritance-Based RC;
- 14 $\mathcal{K}_{in} := \langle \mathcal{T}, \mathcal{D}_{in} \rangle$;
- 15 $IRC := \text{RationalClosure}(\mathcal{K}_{in}, \alpha)$;
- 16 **return** IRC ;

Procedure BasicRelevantClosure(\mathcal{K}, α)

Input: Ontology \mathcal{K} and defeasible \mathcal{EL}^\perp axiom α of the form $C \sqsubseteq D$
Output: true iff $C \sqsubseteq D$ is in the Basic Relevant Closure of \mathcal{K}

```

1  $CL := \mathcal{T} \models C \sqsubseteq D$  //Check if  $\alpha$  holds classically;
2 if  $CL$  then
3   return  $CL$ 
4  $\langle \mathcal{T}, \mathcal{D} \rangle, \{\mathcal{D}_0, \dots, \mathcal{D}_n\} := \text{ComputeRanking}(\mathcal{K})$ ;
5  $CL := \mathcal{T} \models C \sqsubseteq D$  //Check if  $\alpha$  holds classically, after finding strict knowledge in  $\mathcal{D}$ ;
6 if  $CL$  then
7   return  $CL$ 
8  $\{\mathcal{J}_1, \dots, \mathcal{J}_m\} := \text{ComputeJustifications}(\mathcal{K}, C)$ ;
9  $\overline{\mathcal{J}} := \bigcup_{j=1}^m \mathcal{J}_j$ ;
10  $i := 0, exit := \text{false}$ ;
11 repeat
12    $\mathcal{J}'_i := \mathcal{J} \cap \bigcup_{j \geq i} \mathcal{D}_j$ ;
13    $CL := \mathcal{T} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D} \setminus \overline{\mathcal{J}}\} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{J}'_i\} \models C \sqcap \delta \sqsubseteq \perp$ ;
14   if  $CL$  and  $(i < n)$  then
15      $i := i + 1$ 
16   else
17     if  $CL$  and  $(i = n)$  then
18        $\mathcal{J}'_i := \emptyset$ ;
19        $exit := \text{true}$ 
20     else
21        $exit := \text{true}$ 
22 until  $exit$ ;
23  $BRC := \mathcal{T} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D} \setminus \overline{\mathcal{J}}\} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{J}'_i\} \models C \sqcap \delta \sqsubseteq D$ ;
24 return  $BRC$ ;

```

Procedure MinimalRelevantClosure(\mathcal{K}, α)

Input: Ontology \mathcal{K} and defeasible \mathcal{EL}^\perp axiom α of the form $C \sqsubseteq D$
Output: true iff $C \sqsubseteq D$ is in the Minimal Relevant Closure of \mathcal{K}

```

1  $CL := \mathcal{T} \models C \sqsubseteq D$  //Check if  $\alpha$  holds classically;
2 if  $CL$  then
3   return  $CL$ 
4  $\langle \langle \mathcal{T}, \mathcal{D} \rangle, \{\mathcal{D}_0, \dots, \mathcal{D}_n\} \rangle := \text{ComputeRanking}(\mathcal{K})$ ;
5  $CL := \mathcal{T} \models C \sqsubseteq D$  //Check if  $\alpha$  holds classically, after finding strict knowledge in  $\mathcal{D}$ ;
6 if  $CL$  then
7   return  $CL$ 
8  $\{\mathcal{J}^1, \dots, \mathcal{J}^m\} := \text{ComputeJustifications}(\mathcal{K}, C)$ ;
9 foreach  $\mathcal{J}^j$  do
10    $\mathcal{J}_{\min}^j := \{D \sqsubseteq E \in \mathcal{J}^j \mid r_{\mathcal{K}}(D) \leq r_{\mathcal{K}}(F) \text{ for every } F \sqsubseteq G \in \mathcal{J}^j\}$ ;
11  $\mathcal{J}_{\min} := \bigcup_{j=1}^m \mathcal{J}_{\min}^j$ ;
12  $i := 0$ ,  $exit := \text{false}$ ;
13 repeat
14    $\mathcal{J}'_i := \mathcal{J} \cap \bigcup_{j \geq i} \mathcal{D}_j$ ;
15    $CL :=$ 
      $\mathcal{T} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D} \setminus \mathcal{J}_{\min}\} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{J}'_i\} \models C \sqcap \delta \sqsubseteq \perp$ ;
16   if  $CL$  and  $(i < n)$  then
17      $i := i + 1$ 
18   else
19     if  $CL$  and  $(i = n)$  then
20        $\mathcal{J}'_i := \emptyset$ ;
21        $exit := \text{true}$ 
22     else
23        $exit := \text{true}$ 
24 until  $exit$ ;
25  $MRC :=$ 
      $\mathcal{T} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{D} \setminus \mathcal{J}_{\min}\} \cup \{E \sqcap \delta \sqsubseteq F \mid E \sqsubseteq F \in \mathcal{J}'_i\} \models C \sqcap \delta \sqsubseteq D$ ;
26 return  $MRC$ ;

```
