Schema documentation for CDE_schema.xsd

october 24, 2018

Table of Contents

Schema(s)

Main schema `CDE_schema.xsd`

Element(s)

Element `data_element_set`

Diagram	
Model	id , name , description , (url | index_codes | modality | biological_sex | age_range | person | organization | (event*)) , elements
Instance	``` <data_element_set> <id>{1,1}</id> <name>{1,1}</name> <description>{1,1}</description> <url>{1,1}</url> <index_codes>{1,1}</index_codes> <modality>{1,1}</modality> <biological_sex>{1,1}</biological_sex> <age_range>{1,1}</age_range> <person>{1,1}</person> <organization>{1,1}</organization> <event>{0,unbounded}</event> <elements>{1,1}</elements> </data_element_set> ```

Element `data_element_set / id`

Annotations	Each set has a unique identifier of the format "RDES[0-9]+" (e.g., "RDES42") and a textual name.
Diagram	

Type	restriction of xs:string	
Facets	pattern	RDES\d+

Element `name`

Diagram	
	name Type xs:string — xs:string Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Elements data_element_set, element, organization, person, value_set/value

Element `description`

| Diagram	
	description Type xs:string — xs:string Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Element data_element_set

Element `data_element_set / url`

Diagram	
	url Type xs:anyURI — xs:anyURI Built-in primitive type. The anyURI datatype represents a Uniform Resource Identifier Reference (URI).
Type	xs:anyURI

Element `index_codes`

Diagram	
	index_codes — ⊟ — 1..∞ index_code
Used by	Elements data_element_set, element, value_set/value
Model	index_code+

Instance	`<index_codes>`
	  `<index_code>`{1,unbounded}`</index_code>`
	`</index_codes>`

Element `index_code`

Diagram	
	index_code — system Type Restriction of 'xs:token' code Type xs:normalizedString href Type xs:anyURI display Type xs:string
Used by	Element index_codes
Model	system , code , href{0,1} , display{0,1}

Instance	`<index_code>`
	  `<system>`{1,1}`</system>`
	  `<code>`{1,1}`</code>`
	  `<href>`{0,1}`</href>`
	  `<display>`{0,1}`</display>`

```
</index_code>
```

Element `index_code / system`

Diagram	
	system Type Restriction of 'xs:token' — restricts: xs:token
Type	restriction of xs:token
Facets	enumeration RADLEX
	enumeration SNOMEDCT
	enumeration LOINC

Element `index_code / code`

Diagram	
	code Type xs:normalizedString — xs:normalizedString Built–in derived type. The normalizedString datatype represents white space normalized strings. The base type of...
Type	xs:normalizedString

Element `index_code / href`

Diagram	
	href Type xs:anyURI — xs:anyURI Built–in primitive type. The anyURI datatype represents a Uniform Resource Identifier Reference (URI).
Type	xs:anyURI

Element `display`

Diagram	
	display Type xs:string — xs:string Built–in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Element index_code

Element `modality`

Diagram	
	modality — system Type Restriction of 'xs:token' code Type Restriction of 'xs:token' href Type Restriction of 'xs:token'
Used by	Elements data_element_set, element
Model	system , code , href

Instance	`<modality>`
	`  <system>{1,1}</system>`
	`  <code>{1,1}</code>`
	`  <href>{1,1}</href>`
	`</modality>`

Element `modality / system`

Diagram	
	system Type Restriction of 'xs:token' — restricts: xs:token

Type	restriction of xs:token	
Facets	enumeration	`DICOM`

Element `modality / code`

Diagram	
Diagram	code Type | Restriction of 'xs:token' — restricts: xs:token

Type	restriction of xs:token	
Facets	enumeration	`CR`
	enumeration	`CT`
	enumeration	`DX`
	enumeration	`IVUS`
	enumeration	`MG`
	enumeration	`MR`
	enumeration	`NM`
	enumeration	`PT`
	enumeration	`RF`
	enumeration	`RG`
	enumeration	`US`
	enumeration	`XA`

Element `modality / href`

Diagram	
Diagram	href Type | Restriction of 'xs:token' — restricts: xs:token

Type	restriction of xs:token	

Facets	enumeration	`http://dicom.nema.org/`
		`medical/dicom/`
		`current/output/html/`
		`part03.html#sect_C.7.3.1.1.1`

Element `biological_sex`

Diagram	
Diagram	biological_sex Type | Restriction of 'xs:token' — restricts: xs:token

Type	restriction of xs:token	
Facets	enumeration	`M`
	enumeration	`F`
Used by	Elements	data_element_set, element

Element `age_range`

| Diagram	
Diagram	age_range — upper_bound Type | xs:float / lower_bound Type | xs:float
Used by	Elements	data_element_set, element
Model	upper_bound{0,1} , lower_bound{0,1}

Instance	`<age_range>`
	`  <upper_bound>{0,1}</upper_bound>`
	`  <lower_bound>{0,1}</lower_bound>`
	`</age_range>`

Element `upper_bound`

Diagram	
	Built-in primitive type. Corresponds to the IEEE single-precision 32-bit floating point type [IEEE 754-1985].
Type	xs:float
Used by	Element age_range

Element `lower_bound`

Diagram	
	Built-in primitive type. Corresponds to the IEEE single-precision 32-bit floating point type [IEEE 754-1985].
Type	xs:float
Used by	Element age_range

Element `person`

Diagram	
Used by	Elements data_element_set, image
	Element Group authors
Model	name , (orcid_id | twitter_handle | url | role)

Instance	`<person>`
	  `<name>`{1,1}`</name>`
	  `<orcid_id>`{1,1}`</orcid_id>`
	  `<twitter_handle>`{1,1}`</twitter_handle>`
	  `<url>`{1,1}`</url>`
	  `<role>`{1,1}`</role>`
	`</person>`

Element `orcid_id`

Diagram	
	Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Element person

Element `twitter_handle`

Diagram	
	Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Element person

Element `person / url`

Diagram	
	 url Type xs:string xs:string Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string

Element `person / role`

Diagram		
	 role Type Restriction of 'xs:token' restricts: xs:token	
Type	restriction of xs:token	
Facets	enumeration	`author`
	enumeration	`editor`
	enumeration	`translator`
	enumeration	`reviewer`
	enumeration	`contributor`

Element `organization`

Diagram		
	organization 0..∞ name (Type xs:string) abbreviation (Type xs:string) url (Type xs:anyURI) comment (Type xs:string) role (Type Restriction of 'xs:token')	
Used by	Elements	data_element_set, image
	Element Group	authors
Model	name | abbreviation | url | comment | role	

Instance	`<organization>`
	  `<name>`{1,1}`</name>`
	  `<abbreviation>`{1,1}`</abbreviation>`
	  `<url>`{1,1}`</url>`
	  `<comment>`{1,1}`</comment>`
	  `<role>`{1,1}`</role>`
	`</organization>`	

Element `abbreviation`

Diagram	
	 abbreviation Type xs:string xs:string Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Element organization

Element `organization / url`

Diagram	
	 url Type xs:anyURI xs:anyURI Built-in primitive type. The anyURI datatype represents a Uniform Resource Identifier Reference (URI).
Type	xs:anyURI

Element `comment`

Diagram	
Type	xs:string
Used by	Element organization

Element `organization / role`

Diagram		
Type	restriction of xs:token	
Facets	enumeration	contributor
	enumeration	sponsor
	enumeration	translator
	enumeration	reviewer
	enumeration	author

Element `event`

Diagram	
Used by	Element Group history
Model	date , status

Instance	`<event>`
	  `<date>`{1,1}`</date>`
	  `<status>`{1,1}`</status>`
	`</event>`

Element `date`

Diagram	
Type	xs:date
Used by	Element Group status_attrs

Element `status`

Diagram		
Type	restriction of xs:token	
Facets	enumeration	proposed
	enumeration	approved
	enumeration	published
	enumeration	deprecated
Used by	Element Group	status_attrs

Element `elements`

| Diagram	
Used by	Element data_element_set
Model	element+

Instance	`<elements>`
	  `<element>`{1,unbounded}`</element>`
	`</elements>`

Element `element`

Annotations	Each data element has a unique identifier of the format "RDE[0-9]+" (e.g., "RDE54") and a textual name.
Diagram	
Used by	Element elements
Model	id , name , definition , version , index_codes{0,1} , modality* , biological_sex{0,1} , age_range{0,1} , person* , organization* , event* , (integer_values | float_values | boolean_values | value_set)

Instance	`<element>`
	  `<id>`{1,1}`</id>`
	  `<name>`{1,1}`</name>`
	  `<definition>`{1,1}`</definition>`
	  `<version>`{1,1}`</version>`
	  `<index_codes>`{0,1}`</index_codes>`
	  `<modality>`{0,unbounded}`</modality>`
	  `<biological_sex>`{0,1}`</biological_sex>`
	  `<age_range>`{0,1}`</age_range>`
	  `<person>`{0,unbounded}`</person>`
	  `<organization>`{0,unbounded}`</organization>`
	  `<event>`{0,unbounded}`</event>`
	  `<integer_values>`{1,1}`</integer_values>`

```
  <float_values>{1,1}</float_values>
  <boolean_values>{1,1}</boolean_values>
  <value_set>{1,1}</value_set>
</element>
```

Element `element / id`

Diagram	
	id Type Restriction of 'xs:string' — restricts: xs:string
Type	restriction of xs:string
Facets	pattern RDE\d+

Element `definition`

Diagram	
	definition Type xs:string — xs:string Built-in primitive type. The string datatype represents character strings in XML.
Type	xs:string
Used by	Elements element, value_set/value

Element `version`

Diagram	
	version_number Type xs:positiveInteger status_attrs date Type xs:date status Type Restriction of 'xs:token'
Used by	Element element
Model	version_number , date , status

Instance	`<version>`
	  `<version_number>{1,1}</version_number>`
	  `<date>{1,1}</date>`
	  `<status>{1,1}</status>`
	`</version>`

Element `version_number`

Diagram	
	version_number Type xs:positiveInteger — xs:positiveInteger Built-in derived type. The positiveInteger datatype is derived from nonNegativeInteger by setting the value of...
Type	xs:positiveInteger
Used by	Element version

Element `integer_values`

Diagram	
	min Type xs:integer max Type xs:integer integer_values — step Type xs:integer unit Type xs:Name

Used by	Element	element
Model	min{0,1} , max{0,1} , step{0,1} , unit{0,1}	

Instance	`<integer_values>`
	  `<min>`{0,1}`</min>`
	  `<max>`{0,1}`</max>`
	  `<step>`{0,1}`</step>`
	  `<unit>`{0,1}`</unit>`
	`</integer_values>`	

Element `integer_values / min`

Diagram	
	min Type xs:integer xs:integer Built-in derived type. The integer datatype is derived from decimal by fixing the value of fractionDigits to be 0. This...
Type	xs:integer

Element `integer_values / max`

Diagram	
	max Type xs:integer xs:integer Built-in derived type. The integer datatype is derived from decimal by fixing the value of fractionDigits to be 0. This...
Type	xs:integer

Element `step`

Diagram	
	step Type xs:integer xs:integer Built-in derived type. The integer datatype is derived from decimal by fixing the value of fractionDigits to be 0. This...
Type	xs:integer
Used by	Elements float_values, integer_values

Element `unit`

Diagram	
	unit Type xs:Name xs:Name Built-in derived type. Name represents XML Names. The base type of Name is token.
Type	xs:Name
Used by	Elements float_values, integer_values

Element `float_values`

Diagram	
	float_values min Type xs:float / max Type xs:float / step Type xs:integer / unit Type xs:Name
Used by	Element element
Model	min{0,1} , max{0,1} , step{0,1} , unit{0,1}

Instance	`<float_values>`
	  `<min>`{0,1}`</min>`
	  `<max>`{0,1}`</max>`

Type	xs:positiveInteger	
Used by	Element	value_set

Element `value_set / value`

|	
Diagram	
Model	value , name , definition{0,1} , images{0,1} , index_codes{0,1}

Instance	```xml
	<value>
	  <value>{1,1}</value>
	  <name>{1,1}</name>
	  <definition>{0,1}</definition>
	  <images>{0,1}</images>
	  <index_codes>{0,1}</index_codes>
	</value>
	``

Element `value_set / value / value`

Diagram	
Type	xs:Name

Element `images`

Diagram		
Used by	Element	value_set/value
Model	image+	

Instance	```xml
	<images>
	  <image>{1,unbounded}</image>
	</images>
	``	

Element `image`

Diagram		
Used by	Element	images

13

| Model	url | height | width | caption | rights | source | person | organization

Instance	```xml
	<image>
	  <url>{1,1}</url>
	  <height>{1,1}</height>
	  <width>{1,1}</width>
	  <caption>{1,1}</caption>
	  <rights>{1,1}</rights>
	  <source>{1,1}</source>
	  <person>{1,1}</person>
	  <organization>{1,1}</organization>
	</image>
	``

Element `image / url`

Diagram	
Type	xs:anyURI

Element `height`

Diagram	
Type	xs:positiveInteger
Used by	Element image

Element `width`

Diagram	
Type	xs:positiveInteger
Used by	Element image

Element `caption`

Diagram	
Type	xs:string
Used by	Element image

Element `rights`

Diagram	
Type	xs:string
Used by	Element image

Element `source`

Diagram	

Type	xs:string	
Used by	Element	image

Element Group(s)

Element Group `history`

Diagram	
Used by	Elements data_element_set, element
Model	event*

Element Group `status_attrs`

Diagram	
Used by	Elements event, version
Model	date , status

Element Group `authors`

Diagram	
Used by	Element element
Model	person* , organization*