

Outdoor Long-Range Microwave Sensor

Long Range Motion Detection For Large Areas



PRODUCT OVERVIEW

Avi-on's Outdoor Long Range Microwave Sensor is suited to cover large open areas like open manufacturing and warehouse floors or large outdoor areas. When side mounted, the sensor can cover areas up to 100 wide by 250 long, allowing much fewer sensors per fixture than PIR or other sensor options. The sensor includes an Avi-on Bluetooth Radio and functions as a stand alone network component for zoned sensor applications. The sensor does not include a daylight harvesting sensor or 0-10V dimming output. IP 65 Rated

Use it for: Large open area motion detection side mounted up to 100ft wide covering areas up to 250 feet long where side or bottom knockout or IP rating is important. Can also be ceiling mounted up to 40 feet.

Use other products for:

Office, low bay, sensor per fixture, troffer behind the lens mounting: Use AVI-DC-MW.

High bay ceiling mount with warehouse aisles or other obstructions: Use AVI-DC-PIR

Features

- Long range allows a single sensor to cover up to 100 ft x 250 ft
- 12-24VDC power
- Side or top knockout mount
- IP 65 outdoor rated

ORDERING INFORMATION

Part Number	Description	Antenna	Input Voltage
AVI-SEN-MFM-24-BLE	Long Range Microwave, Side/Bottom Mount, Outdoor Rated IP65	Internal	12 - 24 VDC

To order please contact Avi-on sales at **(877) AVION-US**, (877) 284-6687 or prosales@avi-on.com for information on becoming an Avi-on partner and order details.

Project		Location/ Type	
---------	--	-------------------	--

SPECIFICATIONS

Input Voltage:	12-24VDC
Power Consumption:	85mA
Sensor Frequency:	10.525 Ghz
Sensor Range:	20-40 ft (vertical mount) 20-150 ft (horizontal mount)
Size:	2.28in x 2.28in x 1.02in (58mm x 58mm x 26mm)
Mounting:	Screw holes (see diagrams)
Weight:	3.5 oz (98g)
Outdoor Rating:	IP 65
Connection Wires:	22 AWG
Operating Temperature:	-22F to +158F (-30C to +70C)
Storage Temperature:	-40F to +176F (-40C to +80C)
Humidity Rating:	90-95% non-condensing

Microwave Radio Freq:	10.525 Ghz
Mesh Radio Freq:	2.4GHz
Wireless Standard:	BLE 4.2 with Avi-on Mesh
Point to Point Range*:	80ft with obstructions and 350ft unobstructed
Security:	AES 128-bit encryption for device to device communication AES 256-bit encryption for device to cloud communication
Warranty:	5 years; 10 years optional
Regulatory:	
Network:	FCC: 2AFZI-AV1010 B IC: 20544-AV1010 B BQB: D031801, DID: 86303
Sensor:	FCC: ZZ0WCM-01 UL E341446

**When communicating through the mesh, range is essentially unlimited (5000ft+)*

DIMENSIONS




Figure 1. Microwave Sensor Dimensions



Figure 2. Side & Top Mounting

DIAGRAMS




Figure 3. Wiring Diagram




Figure 4. Coverage Pattern

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE. The information contained herein is believed to be reliable. Avi-on makes no warranty, representation or guarantee regarding the information contained herein, the suitability of the products for any particular purpose, or the continuing production of any product. Avi-on assumes no responsibility or liability whatsoever for the use of the information contained herein. The information contained herein, or any use of such information does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other intellectual property rights, whether with regard to such information itself or anything described by such information.

