



cloudshell X

cloudshell X



Welcome to Cloud Shell! Type "help" to get started, or type "gemini" to try prompting with Gemini CLI.
To set your Cloud Platform project in this session use `gcloud config set project [PROJECT\_ID]`.
You can view your projects by running `gcloud projects list`.

rubashree512@cloudshell:~\$ uname

Linux

rubashree512@cloudshell:~\$ uptime

16:40:52 up 49 min, 0 user, load average: 0.09, 0.31, 0.45

rubashree512@cloudshell:~\$ hostname

cs-1068389980895-default

rubashree512@cloudshell:~\$ dmesg

dmesg: read kernel buffer failed: Operation not permitted

rubashree512@cloudshell:~\$

```
cs-1068389980895-default
rubashree512@cloudshell:~$ dmesg
dmesg: read kernel buffer failed: Operation not permitted
rubashree512@cloudshell:~$ top
top - 16:41:40 up 49 min,  0 user,  load average: 0.04, 0.27, 0.43
Tasks:  38 total,   1 running,  37 sleeping,   0 stopped,   0 zombie
%Cpu(s):  0.0 us,  4.8 sy,   0.0 ni, 95.2 id,   0.0 wa,   0.0 hi,   0.0 si,   0.0 st
MiB Mem :  7947.4 total,  4249.0 free,  2117.4 used,  1823.5 buff/cache
MiB Swap:   0.0 total,   0.0 free,   0.0 used.  5829.9 avail Mem
```

PID	USER	PR	NI	VIRT	RES	SHR	S	%CPU	%MEM	TIME+	COMMAND
1	root	20	0	4324	3328	3048	S	0.0	0.0	0:00.09	bash
8	syslog	20	0	222140	3900	2544	S	0.0	0.0	0:00.02	rsyslogd
24	root	20	0	38768	27976	10876	S	0.0	0.3	0:00.66	python
25	root	20	0	6196	2620	2380	S	0.0	0.0	0:00.00	logger
66	root	10	-10	12024	3984	2872	S	0.0	0.0	0:00.00	sshd
299	root	20	0	2087444	85440	62236	S	0.0	1.0	0:00.46	dockerd
412	root	20	0	1234268	12364	8268	S	0.0	0.2	0:00.31	editor-proxy
413	root	20	0	16328	6412	5488	S	0.0	0.1	0:00.02	sudo
418	root	20	0	1226100	2712	1976	S	0.0	0.0	0:00.00	tmux-agent
451	root	20	0	1793224	45692	31988	S	0.0	0.6	0:00.92	containerd
641	root	10	-10	13996	9660	8284	S	0.0	0.1	0:00.03	sshd
651	root	20	0	2696	1580	1484	S	0.0	0.0	0:00.00	sleep
652	root	10	-10	13996	9752	8380	S	0.0	0.1	0:00.02	sshd
654	rubashr+	10	-10	14256	6252	4596	S	0.0	0.1	0:00.00	sshd
656	rubashr+	10	-10	7340	3792	3544	S	0.0	0.0	0:00.00	bash
657	rubashr+	10	-10	14256	6420	4768	S	0.0	0.1	0:00.02	sshd
660	rubashr+	10	-10	7604	4344	3728	S	0.0	0.1	0:00.00	bash
663	rubashr+	10	-10	7340	3772	3520	S	0.0	0.0	0:00.00	bash
664	rubashr+	10	-10	7340	3692	3432	S	0.0	0.0	0:00.00	start-shell.sh
665	rubashr+	10	-10	6880	3276	2976	S	0.0	0.0	0:00.00	tmux
667	rubashr+	10	-10	7280	2812	2040	S	0.0	0.0	0:00.07	tmux

```
rubashree512@cloudshell:~$ free
              total        used         free       shared    buff/cache   available
Mem:           8138088       2168972       4350244          1148       1867324       5969116
Swap:              0              0              0
```

```
rubashree512@cloudshell:~$ █
```

PID	USER	PR	NI	VIRT	RES	SHR	S	%CPU	%MEM	TIME+	COMMAND
1	root	20	0	4324	3328	3048	S	0.0	0.0	0:00.09	bash
8	syslog	20	0	222140	3900	2544	S	0.0	0.0	0:00.02	rsyslogd
24	root	20	0	38768	27976	10876	S	0.0	0.3	0:00.66	python
25	root	20	0	6196	2620	2380	S	0.0	0.0	0:00.00	logger
66	root	10	-10	12024	3984	2872	S	0.0	0.0	0:00.00	sshd
299	root	20	0	2087444	85440	62236	S	0.0	1.0	0:00.46	dockerd
412	root	20	0	1234268	12364	8268	S	0.0	0.2	0:00.31	editor-proxy
413	root	20	0	16328	6412	5488	S	0.0	0.1	0:00.02	sudo
418	root	20	0	1226100	2712	1976	S	0.0	0.0	0:00.00	tmux-agent
451	root	20	0	1793224	45692	31988	S	0.0	0.6	0:00.92	containerd
641	root	10	-10	13996	9660	8284	S	0.0	0.1	0:00.03	sshd
651	root	20	0	2696	1580	1484	S	0.0	0.0	0:00.00	sleep
652	root	10	-10	13996	9752	8380	S	0.0	0.1	0:00.02	sshd
654	rubashr+	10	-10	14256	6252	4596	S	0.0	0.1	0:00.00	sshd
656	rubashr+	10	-10	7340	3792	3544	S	0.0	0.0	0:00.00	bash
657	rubashr+	10	-10	14256	6420	4768	S	0.0	0.1	0:00.02	sshd
660	rubashr+	10	-10	7604	4344	3728	S	0.0	0.1	0:00.00	bash
663	rubashr+	10	-10	7340	3772	3520	S	0.0	0.0	0:00.00	bash
664	rubashr+	10	-10	7340	3692	3432	S	0.0	0.0	0:00.00	start-shell.sh
665	rubashr+	10	-10	6880	3276	2976	S	0.0	0.0	0:00.00	tmux
667	rubashr+	10	-10	7280	2812	2040	S	0.0	0.0	0:00.07	tmux

```
rubashree512@cloudshell:~$ free
```

	total	used	free	shared	buff/cache	available
Mem:	8138088	2168972	4350244	1148	1867324	5969116
Swap:	0	0	0			

cloudshell X cloudshell X + ▾

```
1506 rubashr+ 20 0 31.4g 216856 60520 S 0.0 2.7 0:10.69 node
```

```
rubashree512@cloudshell:~$ htop
rubashree512@cloudshell:~$ lsb_release
No LSB modules are available.
rubashree512@cloudshell:~$ arch
x86_64
rubashree512@cloudshell:~$ ls
hello.txt  hi.txt  README-cloudshell.txt
rubashree512@cloudshell:~$ cd hi.txt
rubashree512@cloudshell:~/hi.txt$ pwd
/home/rubashree512/hi.txt
rubashree512@cloudshell:~/hi.txt$ mkdir mlop.txt
rubashree512@cloudshell:~/hi.txt$ touch
touch: missing file operand
Try 'touch --help' for more information.
rubashree512@cloudshell:~/hi.txt$ touch hi.txt
rubashree512@cloudshell:~/hi.txt$ rm hi.txt
rubashree512@cloudshell:~/hi.txt$ ls
mlop.txt
rubashree512@cloudshell:~/hi.txt$ cd ..
rubashree512@cloudshell:~$ ls
hello.txt  hi.txt  README-cloudshell.txt
rubashree512@cloudshell:~$ cd hi.txt
rubashree512@cloudshell:~/hi.txt$ cp hi.txt
cp: missing destination file operand after 'hi.txt'
Try 'cp --help' for more information.
rubashree512@cloudshell:~/hi.txt$ cp hi.txt hello.txt
```

```
rubashree512@cloudshell:~$ nano newfile.txt
```

```
rubashree512@cloudshell:~$ awk
```

```
Usage: mawk [Options] [Program] [file ...]
```

Program:

The `-f` option value is the name of a file containing program text.

If no `-f` option is given, a `--` ends option processing; the following parameters are the program text.

Options:

<code>-f program-file</code>	Program text is read from file instead of from the command-line. Multiple <code>-f</code> options are accepted.
<code>-F value</code>	sets the field separator, FS, to value.
<code>-v var=value</code>	assigns value to program variable var.
<code>--</code>	unambiguous end of options.

Implementation-specific options are prefixed with `-W`. They can be abbreviated:

<code>-W version</code>	show version information and exit.
<code>-W compat</code>	pre-POSIX 2001.
<code>-W dump</code>	show assembler-like listing of program and exit.
<code>-W help</code>	show this message and exit.
<code>-W interactive</code>	set unbuffered output, line-buffered input.
<code>-W exec file</code>	use file as program as well as last option.
<code>-W posix</code>	stricter POSIX checking.

```
-W posix          stricter POSIX checking.
-W random=number  set initial random seed.
-W sprintf=number adjust size of sprintf buffer.
-W usage          show this message and exit.
```

```
rubashree512@cloudshell:~$ sed
```

```
Usage: sed [OPTION]... {script-only-if-no-other-script} [input-file]...
```

```
-n, --quiet, --silent
    suppress automatic printing of pattern space
--debug
    annotate program execution
-e script, --expression=script
    add the script to the commands to be executed
-f script-file, --file=script-file
    add the contents of script-file to the commands to be executed
--follow-symlinks
    follow symlinks when processing in place
-i[SUFFIX], --in-place[=SUFFIX]
    edit files in place (makes backup if SUFFIX supplied)
-l N, --line-length=N
    specify the desired line-wrap length for the 'l' command
--posix
    disable all GNU extensions.
-E, -r, --regexp-extended
    use extended regular expressions in the script
    (for portability use POSIX -E).
-s, --separate
```

```
To set your Cloud Platform project in this session use `gcloud config set project [PROJECT_ID]`.
You can view your projects by running `gcloud projects list`.
rubashree512@cloudshell:~$ ifconfig
docker0: flags=4099<UP,BROADCAST,MULTICAST> mtu 1460
    inet 172.17.0.1 netmask 255.255.0.0 broadcast 172.17.255.255
    ether be:30:05:18:ce:a0 txqueuelen 0 (Ethernet)
    RX packets 0 bytes 0 (0.0 B)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 0 bytes 0 (0.0 B)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1460
    inet 10.88.0.3 netmask 255.255.0.0 broadcast 10.88.255.255
    ether 9a:de:2d:5d:f0:fd txqueuelen 1000 (Ethernet)
    RX packets 52415 bytes 17039125 (17.0 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 40712 bytes 43027624 (43.0 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
    inet 127.0.0.1 netmask 255.0.0.0
    loop txqueuelen 1000 (Local Loopback)
    RX packets 32925 bytes 80788285 (80.7 MB)
    RX errors 0 dropped 0 overruns 0 frame 0
    TX packets 32925 bytes 80788285 (80.7 MB)
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0

```
rubashree512@cloudshell:~$ ip
```

```
Usage: ip [ OPTIONS ] OBJECT { COMMAND | help }
```

```
ip [ -force ] -batch filename
```

```
where OBJECT := { address | addrlabel | amt | fou | help | ila | ioam | l2tp |
link | macsec | maddress | monitor | mptcp | mroute | mrule |
neighbor | neighbour | netconf | netns | nexthop | ntable |
ntbl | route | rule | sr | tap | tcpmetrics |
token | tunnel | tuntap | vrf | xfrm }

OPTIONS := { -V[ersion] | -s[tatistics] | -d[etails] | -r[esolve] |
-h[uman-readable] | -iec | -j[son] | -p[retty] |
-f[amily] { inet | inet6 | mpls | bridge | link } |
-4 | -6 | -M | -B | -O |
-l[oops] { maximum-addr-flush-attempts } | -br[ief] |
-o[neline] | -t[imestamp] | -ts[hort] | -b[atch] [filename] |
-rc[vbuf] [size] | -n[etns] name | -N[umeric] | -a[ll] |
-c[olor]}
```

```
rubashree512@cloudshell:~$
```



```
-rc[vbuf] [size] | -n[etns] name | -N[umeric] | -a[ll] |  
-c[olor]}
```

```
rubashree512@cloudshell:~$ ping google.com
```

```
PING google.com (142.251.12.139) 56(84) bytes of data.
```

```
64 bytes from se-in-f139.1e100.net (142.251.12.139): icmp_seq=1 ttl=114 time=0.863 ms
```

```
64 bytes from se-in-f139.1e100.net (142.251.12.139): icmp_seq=2 ttl=114 time=0.688 ms
```

```
64 bytes from se-in-f139.1e100.net (142.251.12.139): icmp_seq=3 ttl=114 time=0.628 ms
```

```
64 bytes from se-in-f139.1e100.net (142.251.12.139): icmp_seq=4 ttl=114 time=0.552 ms
```

```
64 bytes from se-in-f139.1e100.net (142.251.12.139): icmp_seq=5 ttl=114 time=0.530 ms
```

```
^C
```

```
--- google.com ping statistics ---
```

```
5 packets transmitted, 5 received, 0% packet loss, time 4076ms
```

```
rtt min/avg/max/mdev = 0.530/0.652/0.863/0.119 ms
```

```
rubashree512@cloudshell:~$
```

5 packets transmitted, 5 received, 0% packet loss, time 4076ms
rtt min/avg/max/mdev = 0.530/0.652/0.863/0.119 ms

rubashree512@cloudshell:~\$ netstat

Active Internet connections (w/o servers)

Proto	Recv-Q	Send-Q	Local Address	Foreign Address	State
tcp	0	0	localhost:58096	localhost:971	ESTABLISHED
tcp	0	0	localhost:54978	localhost:ssh	TIME_WAIT
tcp	0	0	localhost:971	localhost:58096	ESTABLISHED
tcp	0	0	localhost:58034	localhost:ssh	ESTABLISHED
tcp	0	0	localhost:971	localhost:58084	ESTABLISHED
tcp	0	0	localhost:36446	localhost:970	ESTABLISHED
tcp	0	0	cs-1068389980895-:39498	sl-in-f95.1e100.n:https	ESTABLISHED
tcp	0	0	localhost:ssh	localhost:44734	ESTABLISHED
tcp	0	0	cs-1068389980895-:47356	se-in-f113.1e100.:https	ESTABLISHED
tcp	0	0	localhost:ssh	localhost:58034	ESTABLISHED
tcp	0	0	localhost:36440	localhost:970	ESTABLISHED
tcp	0	0	localhost:44734	localhost:ssh	ESTABLISHED
tcp	0	0	localhost:58084	localhost:971	ESTABLISHED
tcp6	0	0	localhost:970	localhost:36440	ESTABLISHED
tcp6	0	0	cs-1068389980895-de:980	10.95.147.12:46414	ESTABLISHED
tcp6	0	0	localhost:970	localhost:36446	ESTABLISHED
tcp6	0	0	cs-1068389980895-de:980	10.95.145.12:36708	ESTABLISHED
tcp6	0	0	cs-1068389980895-de:980	10.95.145.12:51522	ESTABLISHED
tcp6	0	0	cs-1068389980895-de:980	10.95.145.12:45952	ESTABLISHED
tcp6	0	0	cs-1068389980895-de:980	10.95.147.12:52830	ESTABLISHED
tcp6	0	0	cs-1068389980895-de:980	10.95.147.12:52816	ESTABLISHED

```
rubashree512@cloudshell:~$ nslookup google.com
```

```
Server:          169.254.169.254
```

```
Address:         169.254.169.254#53
```

```
Non-authoritative answer:
```

```
Name:   google.com
```

```
Address: 172.253.134.100
```

```
Name:   google.com
```

```
Address: 172.253.134.113
```

```
Name:   google.com
```

```
Address: 172.253.134.139
```

```
Name:   google.com
```

```
Address: 172.253.134.102
```

```
Name:   google.com
```

```
Address: 172.253.134.101
```

```
Name:   google.com
```

```
Address: 172.253.134.138
```

```
Name:   google.com
```

```
Address: 2404:6800:4003:c06::66
```

```
Name:   google.com
```

```
Address: 2404:6800:4003:c06::8b
```

```
Name:   google.com
```

```
Address: 2404:6800:4003:c06::65
```

```
Name:   google.com
```

```
Address: 2404:6800:4003:c06::64
```

```
rubashree512@cloudshell:~$ dig google.com
```

```
;; <<>> DiG 9.18.39-0ubuntu0.24.04.3-Ubuntu <<>> google.com
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 4464
;; flags: qr rd ra; QUERY: 1, ANSWER: 6, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 512
;; QUESTION SECTION:
;google.com.                IN      A

;; ANSWER SECTION:
google.com.                279     IN      A      172.253.134.100
google.com.                279     IN      A      172.253.134.113
google.com.                279     IN      A      172.253.134.139
google.com.                279     IN      A      172.253.134.102
google.com.                279     IN      A      172.253.134.101
google.com.                279     IN      A      172.253.134.138

;; Query time: 1 msec
;; SERVER: 169.254.169.254#53(169.254.169.254) (UDP)
;; WHEN: Thu May 14 18:11:59 UTC 2026
;; MSG SIZE rcvd: 135
```

To see your cloud platform projects in this session use `gcloud config`.

You can view your projects by running `gcloud projects list`.

```
rubashree512@cloudshell:~$ ps
  PID TTY          TIME CMD
 3837 pts/5      00:00:00 bash
 4204 pts/5      00:00:00 ps
rubashree512@cloudshell:~$
```

4204 pts/5 00:00:00 ps

rubashree512@cloudshell:~\$ pgrep chrome

rubashree512@cloudshell:~\$ pkill chrome

rubashree512@cloudshell:~\$ kill 1234

-bash: kill: (1234) - No such process

rubashree512@cloudshell:~\$ jobs

rubashree512@cloudshell:~\$ sleep 100

^Z

[1]+ Stopped sleep 100

rubashree512@cloudshell:~\$ jobs

[1]+ Stopped sleep 100

rubashree512@cloudshell:~\$ bg

[1]+ sleep 100 &

rubashree512@cloudshell:~\$ fg

sleep 100

