ajax support datatype : json

1. Which of the following file is **the base template for a razor application**?
   a. **_Layout.cshtml**
   b. Default.cshtml
   c. Index.cshtml
   d. home.cshtml

2. Which of the following **Razor syntax** is used to **create partial view**?
   a. **_PartialLayout.cshtml**
   b. @html.PartialView
   c. @html.PartialLeyout

Q4. Which Ajax control accomplish communication with **server from client**?
A. UpdatePanel
B. UpdateProgress
C. Timer
D. **ScriptManager**

Ans: D

Q5. In an ASP.NET page which control do you use **to update part of the page**?
A. Panel
B**. UpdatePanel**
C. UpdateProgress
D. Timer

Ans: B

Q2. **Properties of Detail View**
A. **Triggers property**

Q10. Which one is a **single item control**?
A. GridView
B. DataList
C. Repeater
D**. DetailsView**

Ans: D

Q12. Which action is **not supported by a GridView control**?
A. Select
B**. Insert**
C. Update
D. Delete

Ans: B

Q13. Which controls serve as a bridge between the **user interface** and **the database**?
A. Data-bound controls
B. **Data source controls**
C. List controls
D. Object source controls

Ans: B

Q14. **MVC stands** for _____
A. Model Via Controller
B. **Model View Controller**
C. Model View Connection
D. Model View Control

Ans: B

Q15. What is the **extension razor view**?
A. .aspx
B. .html
C. .vhtml
D**. .cshtml or .vbhtml**

Ans: D

Q16. What is extension of **ASPX view**?
A**. .aspx**
B. .html
C. .vhtml
D. .cshtml or .vbhtml

Ans: A

Q17. Which one **default master page** created by visual studio in MVC project that uses **razor view engine**?

A. Site.master
B. Site.cshtml
C. **_Layout.master**
D. _Layout.cshtml

Ans: C

Q18. Which property of razor view is used **to set master page**?
A. Master
B**. Layout**
C. _Layout
D. None

Ans: B

Q19. Which method is used to **insert view content in a layout page**?
A. @Render()
B**. @RenderBody()**
C. @RenderSection()
D. @Body()

Ans: B

Q22. Which one is a **key/value pair** collection that is used to **pass data from action method to a view**?
A. ViewBag
B**. ViewData**
C. Model object
D. Custom helper

Ans: B

Q22. Which one is used to pass data from action method to a view **by adding dynamic properties to it**?
A. **ViewBag**
B. ViewData
C. Model object
D. Custom helper

Ans: A

Q25. Which one do you use for Enumeration to be mapped to data column?
A. [DataType(DataType.Enum)]

B. [DataType(typeof(name of enum))]
C. [Enum(typeof(name of enum))]
D. **[EnumDataType(typeof(name of enum))]**

Ans: D

Q28. Which one is used for showing an **unordered list (<ul>) model-level errors only**?
A. **@Html.ValidationSummary(true)**
B. @Html.ValidationSummary(false)
C. @Html.Summary(true)
D. @Html.Errors(true)

Ans: A

Q32. Which one should you use to allow **only authenticated users**?
A. [Authenticate]
B. **[Authorize]**
C. [Deny]
D. [Restrict]

Ans: B

Q32. Which one should you use with action method allow **all users to request a view**?
A. [Authorize(Allow="?")]
B. [Authorize(AllowAnonymous)]
C. [Allow]
D. **[AllowAnonymous]**

Ans: D

5. Which of the following is the **default routing** format of ASP.NET Web ?

    a.   {controller}/{action}
    b.   {controller}/{action}/{id}
    c.   {controller}/{default}
    d.   {controller}/{default}/{id}