

1. Which one is the best way to add custom attributes?

- A. Prefix the attribute with "data-"
- B. Prefix the attribute with "custom-"
- C. Prefix the attribute with "-"
- D. HTML4 or HTML5 does not allow custom attributes

Answer: A

2. Which browsers support conditional comments?

- A. Internet explorer
- B. Goggle chrome
- C. Firefox
- D. Safari
- E. Opera

Answer: A

3. Which function do you use to query the user for input by displaying a modal message prompt?

- A. alert
- B. prompt
- C. confirm
- D. input

Answer: B

4. Which function do you use to query whether he agree to take certain action?

- A. alert
- B. prompt
- C. confirm
- D. input

Answer: C

5. Which one is the null coalescing operator?

- A. ??
- B. &
- C. |
- D. ||

Answer: D

6. Which attribute do you use in <link> element to specify target device?

- I. device
- J. media
- K. user-agent
- L. type

Answer: B

7. Which one enables you to import a CSS file to the current style sheet?

- A. @include
- B. @insert
- C. @import
- D. @use

Answer: C

8. How do you define custom font that will be downloaded to user machine if it is not available?

- A. Using @font-family rule
- B. Using @face rule
- C. Using @font-face rule
- D. Using @font-url rule

Answer: C

9. Which one the selector of hyperlinks that are direct children of list item

- A. li a
- B. li + a
- C. li ~ a
- D. li > a

Answer: D

10. Which one locates the <p> element is preceded by a <h1> element as the previous sibling p?

- A. h1 + p
- B. h1 > p
- C. h1 p
- D. h1 ~ p

Answer: A

11. Which one locates all hyperlinks whose href attribute value starts with http?

- A. `a[href^='http']`
- B. `a[href*='http']`
- C. `a[href$='http']`
- D. `a[href~='http']`

Answer: A

12. Which one of the following HTML5 tags is not a layout container?

- A. `<section>`
- B. `<article>`
- C. `<aside>`
- D. `<abbr>`

Answer: D

13. Which element should you use to group multiple heading element?

- A. `<headergroup>`
- B. `<hgroup>`
- C. `<group>`
- D. `<heading>`

Answer: B

14. Which one is an ARIA attribute, used in elements, define by WAI? (NOT SURE)

- A. `title`
- B. `role`
- C. `id`
- D. `class`

Answer: B

15. What element should you use instead of `<1>`?

- A. ``
- B. Any of `<h1>` to `<h6>`

- C. <bold>
- D.

Answer: D

16. What is a privileged method?

- A. Private method that accesses public data
- B. A public method that accesses private data
- C. A static method
- D. A method that is attached to the object's prototype chain

Answer: B

17. Which one correctly activates jQuery IntelliSense?

- A. `/// <reference path="jquery-1.8.2.js" />`
- B. `// <reference path="jquery-1.8.2.js" />`
- C. `/* <reference path="jquery-1.8.2.js" /> */`
- D. `<reference path="jquery-1.8.2.js" />`

Answer: A

18. Which syntax jQuery uses to locate document object model (DOM) elements?

- A. `$(selector)`
- B. `$get(selector)`
- C. `$(selector)`
- D. `querySelector(selector)`

Answer: A

19. Which method of jQuery object is used to get or set the value of a DOM element that has a value property?

- A. value
- B. val
- C. get, set
- D. eval

Answer: B

20. Which category of status codes indicate server error?

- A. 1xx
- B. 2xx
- C. 3xxx
- D. 4xx

E. 5xx

Answer: E

21. Which one is the manifest file in Node.js package?

- A. package.json
- B. README.md
- C. lib\main.js.
- D. bin\app.js

Answer: A

22. Which command of the Node Package Manager creates the package manifest file package.json?

- A. npm start
- B. npm create
- C. npm init
- D. npm -g install

Answer: C

23. Which method chains asynchronous operations?

- A. pipe()
- B. done()
- C. resolve()
- D. always()

Answer: A

24. Which method creates a resolved promise object?

- A. resolve()
- B. done()
- C. \$.when()
- D. \$.Deferred().

Answer: C

Upto this from Sir's question.

25. The _____ enables a persistent connection between the client (browser) and the server?

- A. WebSocket
- B. Web worker
- C. Geolocation
- D. HTTP protocol

Answer: A

26. When working with the WebSocket object, which event can be used to retrieve the data that was received from the server?

- A. onopen
- B. onclose
- C. onmessage
- D. onerror

Answer: C

27. Which library would you use if you are creating a Node.js website and want to write browser-independent code that uses WebSocket?

- A. signalR
- B. Socket.IO
- C. FarmSockets
- D. AgnosticSocket

Answer: B

28. Consider the code

```
var age = "21";
```

```
alert ( age + 1);
```

What will be displayed?

- A. 21
- B. 20
- C. 201
- D. Code will produce error

Answer: C

29. Consider the code

```
var age = "21";
```

```
alert ( Number(age) + 1);
```

What will be displayed?

- A. 21
- B. 20
- C. 201
- D. Code will produce error

Answer: A

30.Q# What element is used for preventing malware and annoyances such as pop-ups from being introduced when the content is embedded on your HTML page?

Sandbox

31Q# Which method to remove an event listener?

Off

32Q# Which one is unary operator?

+23

33. What are the types in JavaScript a value can't be?

- A. object
- B. primitive
- C. function
- D. user defined

Answer: D

34. What is the highest integer number that can be represented in JavaScript?

2^{53}

35.. In JavaScript 64-bit number is divided into how many components?

3

36. What is the size of each frame of WebSocket protocol?

2 bytes

37. Parallel execution done using which method?

\$.when().then()

38. jQuery promise objects is created by using which method?

\$.Deferred()

39. which programming method works in the back-end of node.js?

JavaScript

40. Which one is HTML5 global attribute?

Accesskey

41. Which one is void element?

Area

42. Which one is example of entity number?

&

43. Which of the following is a logical operator?

|

```
44. var pizzaMeatParts = ['pepperoni', 'ham', 'bacon'];  
var meatParts = pizzaMeatParts.join();  
alert(meatParts );
```

What will be the result?

pepperoni, ham, bacon

45. What is websocket protocol?

ws://and wss// for secure WebSocket protocol.

46. websocket is based on?

tcp

47.

48.

50.