

432. All O`one Data Structure

Design a data structure to store the strings' count with the ability to return the strings with minimum and maximum counts.

Implement the AllOne class:

- AllOne() Initializes the object of the data structure.
- inc(String key) Increments the count of the string key by 1. If key does not exist in the data structure, insert it with count 1.
- dec(String key) Decrements the count of the string key by 1. If the count of key is 0 after the decrement, remove it from the data structure. It is guaranteed that key exists in the data structure before the decrement.
- getMaxKey() Returns one of the keys with the maximal count. If no element exists, return an empty string "".
- getMinKey() Returns one of the keys with the minimum count. If no element exists, return an empty string "".

Note that each function must run in $O(1)$ average time complexity.

Example 1:

Input

```
["AllOne", "inc", "inc", "getMaxKey", "getMinKey", "inc", "getMaxKey", "getMinKey"]
```

```
[[], ["hello"], ["hello"], [], [], ["leet"], [], []]
```

Output

```
[null, null, null, "hello", "hello", null, "hello", "leet"]
```

Explanation

```
AllOne allOne = new AllOne();

allOne.inc("hello");

allOne.inc("hello");

allOne.getMaxKey(); // return "hello"

allOne.getMinKey(); // return "hello"

allOne.inc("leet");

allOne.getMaxKey(); // return "hello"

allOne.getMinKey(); // return "leet"
```

Constraints:

- $1 \leq \text{key.length} \leq 10$
- key consists of lowercase English letters.
- It is guaranteed that for each call to dec, key is existing in the data structure.
- At most $5 * 10^4$ calls will be made to inc, dec, getMaxKey, and getMinKey.