

146. LRU Cache

Design a data structure that follows the constraints of a Least Recently Used (LRU) cache.

Implement the LRUCache class:

- LRUCache(int capacity) Initialize the LRU cache with positive size capacity.
- int get(int key) Return the value of the key if the key exists, otherwise return -1.
- void put(int key, int value) Update the value of the key if the key exists. Otherwise, add the key-value pair to the cache. If the number of keys exceeds the capacity from this operation, evict the least recently used key.
- The functions get and put must each run in O(1) average time complexity.

Example 1:

Input

- ["LRUCache", "put", "put", "get", "put", "get", "put", "get", "get", "get"]
- [[2], [1, 1], [2, 2], [1], [3, 3], [2], [4, 4], [1], [3], [4]]

Output

- [null, null, null, 1, null, -1, null, -1, 3, 4]

Explanation

- `LRUCache lRUCache = new LRUCache(2);`
- `lRUCache.put(1, 1);` // cache is {1=1}
- `lRUCache.put(2, 2);` // cache is {1=1, 2=2}
- `lRUCache.get(1);` // return 1
- `lRUCache.put(3, 3);` // LRU key was 2, evicts key 2, cache is {1=1, 3=3}
- `lRUCache.get(2);` // returns -1 (not found)
- `lRUCache.put(4, 4);` // LRU key was 1, evicts key 1, cache is {4=4, 3=3}
- `lRUCache.get(1);` // return -1 (not found)
- `lRUCache.get(3);` // return 3
- `lRUCache.get(4);` // return 4

Constraints:

- $1 \leq \text{capacity} \leq 3000$
- $0 \leq \text{key} \leq 10^4$
- $0 \leq \text{value} \leq 10^5$
- At most $2 * 10^5$ calls will be made to get and put.