

[Refresh](#)

This website [www.javatpoint.com/java-math](https://www.javatpoint.com/java-math) is currently offline. [Cloudflare's Always Online™](#) shows a snapshot of this web page from the [Internet Archive's Wayback Machine](#). To check for the live version, click **Refresh**.

[Home](#)[Java](#)[Programs](#)[OOps](#)[String](#)[Exception](#)[Multithreading](#)[Collections](#)

## Java Math class

Java Math class provides several methods to work on math calculations like min(), max(), avg(), sin(), cos(), tan(), round(), ceil(), floor(), abs() etc.

Unlike some of the StrictMath class numeric methods, all implementations of the equivalent function of Math class can't define to return the bit-for-bit same results. This relaxation permits implementation with better-performance where strict reproducibility is not required.

If the size is int or long and the results overflow the range of value, the methods addExact(), subtractExact(), multiplyExact(), and toIntExact() throw an ArithmeticException.

For other arithmetic operations like increment, decrement, divide, absolute value, and negation overflow occur only with a specific minimum or maximum value. It should be checked against the maximum and minimum value as appropriate.

### Example 1

```
public class JavaMathExample1
{
    public static void main(String[] args)
    {
        double x = 28;
        double y = 4;

        // return the maximum of two numbers
        System.out.println("Maximum number of x and y is: " + Math.max(x, y));

        // return the square root of y
        System.out.println("Square root of y is: " + Math.sqrt(y));

        //returns 28 power of 4 i.e. 28*28*28*28
        System.out.println("Power of x and y is: " + Math.pow(x, y));
    }
}
```

```
// return the logarithm of given value
System.out.println("Logarithm of x is: " + Math.log(x));
System.out.println("Logarithm of y is: " + Math.log(y));

// return the logarithm of given value when base is 10
System.out.println("log10 of x is: " + Math.log10(x));
System.out.println("log10 of y is: " + Math.log10(y));

// return the log of x + 1
System.out.println("log1p of x is: " + Math.log1p(x));

// return a power of 2
System.out.println("exp of a is: " + Math.exp(x));

// return (a power of 2)-1
System.out.println("expm1 of a is: " + Math.expm1(x));
}
}
```

**Test it Now**

### Output:

```
Maximum number of x and y is: 28.0
Square root of y is: 2.0
Power of x and y is: 614656.0
Logarithm of x is: 3.332204510175204
Logarithm of y is: 1.3862943611198906
log10 of x is: 1.4471580313422192
log10 of y is: 0.6020599913279624
log1p of x is: 3.367295829986474
exp of a is: 1.446257064291475E12
expm1 of a is: 1.446257064290475E12
```

## Example 2

```
public class JavaMathExample2
{
    public static void main(String[] args)
    {
        double a = 30;

        // converting values to radian
        double b = Math.toRadians(a);
    }
}
```

```
// return the trigonometric sine of a
System.out.println("Sine value of a is: " + Math.sin(a));

// return the trigonometric cosine value of a
System.out.println("Cosine value of a is: " + Math.cos(a));

// return the trigonometric tangent value of a
System.out.println("Tangent value of a is: " + Math.tan(a));

// return the trigonometric arc sine of a
System.out.println("Sine value of a is: " + Math.asin(a));

// return the trigonometric arc cosine value of a
System.out.println("Cosine value of a is: " + Math.acos(a));

// return the trigonometric arc tangent value of a
System.out.println("Tangent value of a is: " + Math.atan(a));

// return the hyperbolic sine of a
System.out.println("Sine value of a is: " + Math.sinh(a));

// return the hyperbolic cosine value of a
System.out.println("Cosine value of a is: " + Math.cosh(a));

// return the hyperbolic tangent value of a
System.out.println("Tangent value of a is: " + Math.tanh(a));
}
}
```

#### Test it Now

#### Output:

```
Sine value of a is: -0.9880316240928618
Cosine value of a is: 0.15425144988758405
Tangent value of a is: -6.405331196646276
Sine value of a is: NaN
Cosine value of a is: NaN
Tangent value of a is: 1.5374753309166493
Sine value of a is: 5.343237290762231E12
Cosine value of a is: 5.343237290762231E12
Tangent value of a is: 1.0
```

## Java Math Methods

The **java.lang.Math** class contains various methods for performing basic numeric operations such as the logarithm, cube root, and trigonometric functions etc. The various java math methods are as follows:

### Basic Math methods

Method	Description
<code>Math.abs()</code>	It will return the Absolute value of the given value.
<code>Math.max()</code>	It returns the Largest of two values.
<code>Math.min()</code>	It is used to return the Smallest of two values.
<code>Math.round()</code>	It is used to round of the decimal numbers to the nearest value.
<code>Math.sqrt()</code>	It is used to return the square root of a number.
<code>Math.cbrt()</code>	It is used to return the cube root of a number.
<code>Math.pow()</code>	It returns the value of first argument raised to the power to second argument.
<code>Math.signum()</code>	It is used to find the sign of a given value.
<code>Math.ceil()</code>	It is used to find the smallest integer value that is greater than or equal to the argument or mathematical integer.
<code>Math.copySign()</code>	It is used to find the Absolute value of first argument along with sign specified in second argument.
<code>Math.nextAfter()</code>	It is used to return the floating-point number adjacent to the first argument in the direction of the second argument.
<code>Math.nextUp()</code>	It returns the floating-point value adjacent to d in the direction of positive infinity.
<code>Math.nextDown()</code>	It returns the floating-point value adjacent to d in the direction of negative infinity.
<code>Math.floor()</code>	It is used to find the largest integer value which is less than or equal to the argument and is equal to the mathematical integer of a double value.
<code>Math.floorDiv()</code>	It is used to find the largest integer value that is less than or equal to the algebraic quotient.
<code>Math.random()</code>	It returns a double value with a positive sign, greater than or equal to 0.0 and less than 1.0.
<code>Math rint()</code>	It returns the double value that is closest to the given argument and equal to mathematical integer.
<code>Math.hypot()</code>	It returns $\sqrt{x^2 + y^2}$ without intermediate overflow or underflow.
<code>Math.ulp()</code>	It returns the size of an ulp of the argument.

<b>Math.getExponent()</b>	It is used to return the unbiased exponent used in the representation of a value.
<b>Math.IEEEremainder()</b>	It is used to calculate the remainder operation on two arguments as prescribed by the IEEE 754 standard and returns value.
<b>Math.addExact()</b>	It is used to return the sum of its arguments, throwing an exception if the result overflows an int or long.
<b>Math.subtractExact()</b>	It returns the difference of the arguments, throwing an exception if the result overflows an int.
<b>Math.multiplyExact()</b>	It is used to return the product of the arguments, throwing an exception if the result overflows an int or long.
<b>Math.incrementExact()</b>	It returns the argument incremented by one, throwing an exception if the result overflows an int.
<b>Math.decrementExact()</b>	It is used to return the argument decremented by one, throwing an exception if the result overflows an int or long.
<b>Math.negateExact()</b>	It is used to return the negation of the argument, throwing an exception if the result overflows an int or long.
<b>Math.toIntExact()</b>	It returns the value of the long argument, throwing an exception if the value overflows an int.

## Logarithmic Math Methods

Method	Description
<b>Math.log()</b>	It returns the natural logarithm of a double value.
<b>Math.log10()</b>	It is used to return the base 10 logarithm of a double value.
<b>Math.log1p()</b>	It returns the natural logarithm of the sum of the argument and 1.
<b>Math.exp()</b>	It returns E raised to the power of a double value, where E is Euler's number and it is approximately equal to 2.71828.
<b>Math.expm1()</b>	It is used to calculate the power of E and subtract one from it.

## Trigonometric Math Methods

Method	Description
<b>Math.sin()</b>	It is used to return the trigonometric Sine value of a Given double value.
<b>Math.cos()</b>	It is used to return the trigonometric Cosine value of a Given double value.
<b>Math.tan()</b>	It is used to return the trigonometric Tangent value of a Given double value.

<code>Math.asin()</code>	It is used to return the trigonometric Arc Sine value of a Given double value
<code>Math.acos()</code>	It is used to return the trigonometric Arc Cosine value of a Given double value.
<code>Math.atan()</code>	It is used to return the trigonometric Arc Tangent value of a Given double value.

## Hyperbolic Math Methods

Method	Description
<code>Math.sinh()</code>	It is used to return the trigonometric Hyperbolic Cosine value of a Given double value.
<code>Math.cosh()</code>	It is used to return the trigonometric Hyperbolic Sine value of a Given double value.
<code>Math.tanh()</code>	It is used to return the trigonometric Hyperbolic Tangent value of a Given double value.

## Angular Math Methods

Method	Description
<code>Math.toDegrees</code>	It is used to convert the specified Radians angle to equivalent angle measured in Degrees.
<code>Math.toRadians</code>	It is used to convert the specified Degrees angle to equivalent angle measured in Radians.

[< Prev](#)[Next >](#)

 **For Videos Join Our Youtube Channel: [Join Now](#)**

## Feedback

- Send your Feedback to [feedback@javatpoint.com](mailto:feedback@javatpoint.com)






## Help Others, Please Share



## Learn Latest Tutorials

 Splunk tutorial Splunk	 SPSS tutorial SPSS	 Swagger tutorial Swagger	 T-SQL tutorial Transact-SQL	 Tumblr tutorial Tumblr
 React tutorial ReactJS	 Regex tutorial Regex	 Reinforcement learning tutorial Reinforcement Learning	 R Programming tutorial R Programming	 RxJS tutorial RxJS
 React Native tutorial React Native	 Python Design Patterns Python Design Patterns	 Python Pillow tutorial Python Pillow	 Python Turtle tutorial Python Turtle	 Keras tutorial Keras











## Preparation

 Aptitude Aptitude	 Logical Reasoning Reasoning	 Verbal Ability Verbal Ability	 Interview Questions Interview Questions	 Company Interview Questions Company Questions
---	---	---	---	---
















## Trending Technologies

 Artificial Intelligence	 AWS Tutorial AWS	 Selenium tutorial	 Cloud Computing	 Hadoop tutorial Hadoop
--	--	--	--	--



 Artificial Intelligence		 Selenium	 Cloud Computing	
 ReactJS Tutorial ReactJS	 Data Science Tutorial Data Science	 Angular 7 Tutorial Angular 7	 Blockchain Tutorial Blockchain	 Git Tutorial Git
 Machine Learning Tutorial Machine Learning	 DevOps Tutorial DevOps			

## B.Tech / MCA

 DBMS tutorial DBMS	 Data Structures tutorial Data Structures	 DAA tutorial DAA	 Operating System Operating System	 Computer Network tutorial Computer Network
 Compiler Design tutorial Compiler Design	 Computer Organization and Architecture Computer Organization	 Discrete Mathematics Tutorial Discrete Mathematics	 Ethical Hacking Ethical Hacking	 Computer Graphics Tutorial Computer Graphics
 Software Engineering Software Engineering	 html tutorial Web Technology	 Cyber Security tutorial Cyber Security	 Automata Tutorial Automata	 C Language tutorial C Programming
 C++ tutorial C++	 Java tutorial Java	 .Net Framework tutorial .Net	 Python tutorial Python	 List of Programs Programs



Control  
Systems tutorial

Control System



Data Mining  
Tutorial

Data Mining



Data  
Warehouse  
Tutorial

Data Warehouse