

8. Environment Variables in Unix Shell

```
labex:navyav/ $ nano lab8.sh
labex:navyav/ $ chmod +x lab8.sh
labex:navyav/ $ ./lab8.sh
----- Environment Variable Manager -----
1. Display variables (printenv)
2. Set new variable
3. Display variables (env)
4. Exit
Enter choice: 4
labex:navyav/ $
```

```
GNU nano 6.2 lab8.sh
#!/bin/bash

display_env() {
    echo "Current Environment Variables:"
    printenv
}

set_env() {
    read -p "Enter variable name: " name
    read -p "Enter variable value: " value
    export $name=$value
    echo "Variable $name set successfully."
}

show_env() {
    echo "Environment variables using env command:"
    env
}

while true
do
    echo "----- Environment Variable Manager -----"
    echo "1. Display variables (printenv)"
    echo "2. Set new variable"
    echo "3. Display variables (env)"
    echo "4. Exit"

    read -p "Enter choice: " ch

    # Remove dot if user types 1. or 2.
    ch=${ch%.*}
done
```

```
do
    echo "----- Environment Variable Manager -----"
    echo "1. Display variables (printenv)"
    echo "2. Set new variable"
    echo "3. Display variables (env)"
    echo "4. Exit"

    read -p "Enter choice: " ch

    # Remove dot if user types 1. or 2.
    ch=${ch%.*}

    case $ch in
        1) display_env ;;
        2) set_env ;;
        3) show_env ;;
        4) exit ;;
        *) echo "Invalid choice" ;;
    esac

    echo
done
```