

# ??? Paper Title ???

Ben Trovato  
Institute for Clarity in  
Documentation  
1932 Wallamaloo Lane  
Wallamaloo, New Zealand  
trovato@corporation.com

G.K.M. Tobin  
Institute for Clarity in  
Documentation  
P.O. Box 1212  
Dublin, Ohio 43017-6221  
webmaster@marysville-  
ohio.com

Lars Thørväld  
The Thørväld Group  
1 Thørväld Circle  
Hekla, Iceland  
larst@affiliation.org

Lawrence P. Leipuner  
Brookhaven Laboratories  
Brookhaven National Lab  
P.O. Box 5000  
lleipuner@researchlabs.org

Sean Fogarty  
NASA Ames Research Center  
Moffett Field  
California 94035  
fogartys@amesres.org

Charles Palmer  
Palmer Research  
Laboratories  
8600 Datapoint Drive  
San Antonio, Texas 78229  
cpalmer@prl.com

## ABSTRACT

The abstract should preferably be between 100 and 200 words.

## Author Keywords

sonification, ???

## ACM Classification

H.5.5 [Information Interfaces and Presentation] Sound and Music Computing, H.5.2 [Information Interfaces and Presentation] User Interfaces—Haptic I/O, I.2.9 [Artificial Intelligence] Robotics—Propelling mechanisms. ??? TO DO

## 1. INTRODUCTION

- motivation
- challenges
- the Vicon system

## 2. STATE OF THE ART

- Vicon & related projects
- interactive / movement sonification examples[1].
- “Sound in space” represents another innovative element in this project because introduces the concept of “tactile sound”. This means that the sound is an entity, gets a materialization and it becomes switchable. It is not about the **localization** of sound in space, it is about its **position**, the coordinates of the sound in space, like an actual *object*. “Sound objects” concept represents an innovative tool for multimedia arts such as sketches, imaginary games and realtime interactions.

## 3. PROJECT DESCRIPTION

### 3.1 Concept

- Performance aesthetic
- Gestures, virtual objects, dynamic mapping

- Visual environment

### 3.2 Implementation

- Character design (Nexus)
- Vicon extensions (SDK plugin)

#### 3.2.1 Max modules

- Objects generation & performance mechanics

Max is a realtime visual programming environment for music and multimedia arts that helps you build stand-alone applications, plugins and mixing audio signals. In order to create interactive sounds, attractive graphics and special effects, MAX creates a connection between virtual objects and subpatches<sup>1</sup>. Manipulating objects algorithm consists of 3 big steps: object generation, finding the object and releasing the object on the floor. Object generation is realized by random generators with the help of *drunk* object, but with certain limits. These limitations are influenced by the dimensions of the room in which the Vicon system is installed. Finding the object supposes continuous mathematic operations between the coordinates of the object and coordinates of the left hand's marker. This process comes with an audio feedback. When these coordinates are close enough one to another, the object is retrieved and manipulated by performer (eg. define gesture). After all these processes, a simple comparison between the coordinates of the floor and the value of the z axes of the marker is done in order to put down the object. According to this, a performer can handle as many objects as he wants.

- Gesture recognition

Interaction between sound control and human gesture has constantly increased over the last years [2]. Probabilistic models for analysing motion and sound relationships became a necessity and a forthcoming tool [3]. *Mubu* containers provided by Ircam laboratories in MAX/MSP software represent a handy tool to record and analyze gesture, captured with Vicon system [4]. Our gesture recognition algorithm is based on Hierarchical Hidden Markov Model implemented in *mubu.hhmm* object of MAX/MSP. Hierarchical Hidden Markov Model is a generalization of HMM where each state is considered to be a self-contained probabilistic model [5]. The system is trained by captured data

<sup>1</sup>See <http://www.cycling74.com/>.



Licensed under a Creative Commons Attribution 4.0 International License (CC BY 4.0). Copyright remains with the author(s).

NIME'17, May 15-19, 2017, Aalborg University Copenhagen, Denmark.

which is essentially a gesture. This process requires a predefined indicator in order to delimitate gestures from all data flow. The algorithm analyzes all input data and generates a probability of similarity between data and saved gestures. In order to control every generated object, there are associated 2 or 3 gestures saved by the performer, but there is a limited time for the gestures to be executed. Predefined gestures offer the possibility to delete the gesture just saved and also indicate the moment the gesture is recorded. to be continued...

- Sound design
- Visualisation (jitter)

## **4. CASE STUDIES**

### **4.1 Interactive Installation**

### **4.2 Performance**

- Solo / duet / tutti ...

## **5. CONCLUSIONS AND FUTURE WORK**

- Areas of improvement
- Eye tracking?

## **6. ACKNOWLEDGMENTS**

This section is optional; it is a location for you to acknowledge grants, funding, editing assistance and what have you.

## **7. REFERENCES**

- [1] T. Hermann, A. Hunt, and J. G. Neuhoff. *The sonification handbook*. Logos Verlag Berlin, 2011.
- [2] K. N. Jorge Solis. *Musical Robots and Interactive Multimodal Systems*. Springer-Verlag Berlin Heidelberg, Berlin, 2011.
- [3] R. B. F. B. Jules Francoise, Norbert Schnell. Probabilistic models for designing motion and sound relationships. *International Conference on New Interfaces for Musical Expression*, pages 287–292, June 2014.
- [4] D. S. G. P. R. B. Norbert Schnell, Axel Robel. Mubu and friends assembling tools. *International Computer Music Association*, pages 423–426, August 2009.
- [5] N. T. Shai Fine, Yoram Singer. The hierarchical hidden markov model: Analysis and applications. *Machine Learning*.