

Ex. No.: 10b)

Date:

FIRST FIT

Aim:

To write a C program for implementation memory allocation methods for fixed partition using first fit.

Algorithm:

1. Define the max as 25.
- 2: Declare the variable frag[max],b[max],f[max],i,j,nb,nf,temp, highest=0, bf[max],ff[max]. 3: Get the number of blocks,files,size of the blocks using for loop.
- 4: In for loop check bf[j]!=1, if so temp=b[j]-f[i]
- 5: Check highest

Program Code:

```
#include<stdio.h>
#include<conio.h>
#define max 25
void main()
{
int frag[max],b[max],f[max],i,j,nb,nf,temp;
static int bf[max],ff[max];
clrscr();
printf("\nEnter the number of blocks:");
scanf("%d",&nb);
printf("Enter the number of files:");
scanf("%d",&nf);
printf("\nEnter the size of the blocks:-\n");
for(i=1;i<=nb;i++)
{
printf("Block %d:",i);
scanf("%d",&b[i]);
}
printf("Enter the size of the files:-\n");
for(i=1;i<=nf;i++)
{
printf("File %d:",i);
scanf("%d",&f[i]);
}
for(i=1;i<=nf;i++)
{
for(j=1;j<=nb;j++)
{
if(bf[j]!=1)
{
temp=b[j]-f[i];
if(temp>=0)
{
```

```

ff[i]=j;
break;
}
}
}
frag[i]=temp;
bf[ff[i]]=1;
}
printf("\nFile_no:\tFile_size :\tBlock_no:\tBlock_size:\tFragment");
for(i=1;i<=nf;i++)
printf("\n%d\t\t%d\t\t%d\t\t%d\t\t%d",i,f[i],ff[i],b[ff[i]],frag[i]);
getch();
}

```

Output:

```

Enter the number of blocks:4
Enter the number of files:3

Enter the size of the blocks:-
Block 1:5
Block 2:8
Block 3:4
Block 4:10
Enter the size of the files:-
File 1:1
File 2:4
File 3:7

File_no:      File_size :      Block_no:      Block_size:      Fragment
1             1             1             5             4
2             4             2             8             4
3             7             4             10            3_

```

52