

Association Analysis: Basic Concepts

Li, Jia

DSA Thrust, Information Hub
HKUST Guangzhou

Oct 27, 2025

Association Rule Mining

- Given a set of transactions, find rules that will predict the occurrence of an item based on the occurrences of other items in the transaction

Market-Basket transactions

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Example of Association Rules

$\{\text{Diaper}\} \rightarrow \{\text{Beer}\},$
 $\{\text{Milk, Bread}\} \rightarrow \{\text{Eggs, Coke}\},$
 $\{\text{Beer, Bread}\} \rightarrow \{\text{Milk}\},$

Implication means co-occurrence, not causality!

Definition: Frequent Itemset

- **Itemset**
 - A collection of one or more items
 - Example: {Milk, Bread, Diaper}
 - k-itemset
 - An itemset that contains k items
- **Support count (σ)**
 - Frequency of occurrence of an itemset
 - E.g. $\sigma(\{\text{Milk, Bread, Diaper}\}) = 2$
- **Support**
 - Fraction of transactions that contain an itemset
 - E.g. $s(\{\text{Milk, Bread, Diaper}\}) = 2/5$
- **Frequent Itemset**
 - An itemset whose support is greater than or equal to a *minsup* threshold

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Definition: Association Rule

- **Association Rule**

- An implication expression of the form $X \rightarrow Y$, where X and Y are itemsets
- Example:
 $\{\text{Milk, Diaper}\} \rightarrow \{\text{Beer}\}$

- **Rule Evaluation Metrics**

- Support (s)
 - Fraction of transactions that contain both X and Y
- Confidence (c)
 - Measures how often items in Y appear in transactions that contain X

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Example:

$$\{\text{Milk, Diaper}\} \Rightarrow \{\text{Beer}\}$$

$$s = \frac{\sigma(\text{Milk, Diaper, Beer})}{|T|} = \frac{2}{5} = 0.4$$

$$c = \frac{\sigma(\text{Milk, Diaper, Beer})}{\sigma(\text{Milk, Diaper})} = \frac{2}{3} = 0.67$$


Association Rule Mining Task

- **Given a set of transactions T , the goal of association rule mining is to find all rules having**
 - support $\geq \textit{minsup}$ threshold
 - confidence $\geq \textit{minconf}$ threshold
- **Brute-force approach:**
 - List all possible association rules
 - Compute the support and confidence for each rule
 - Prune rules that fail the *minsup* and *minconf* thresholds

⇒ **Computationally prohibitive!**

Computational Complexity

- **Given d unique items:**
 - Total number of itemsets = 2^d
 - Total number of possible association rules:



$$R = \sum_{k=1}^{d-1} \left[\binom{d}{k} \times \sum_{j=1}^{d-k} \binom{d-k}{j} \right]$$
$$= 3^d - 2^{d+1} + 1$$

If $d=6$, $R = 602$ rules

Mining Association Rules

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Bread, Diaper, Beer, Eggs
3	Milk, Diaper, Beer, Coke
4	Bread, Milk, Diaper, Beer
5	Bread, Milk, Diaper, Coke

Example of Rules:

$\{\text{Milk, Diaper}\} \rightarrow \{\text{Beer}\}$ (s=0.4, c=0.67)
 $\{\text{Milk, Beer}\} \rightarrow \{\text{Diaper}\}$ (s=0.4, c=1.0)
 $\{\text{Diaper, Beer}\} \rightarrow \{\text{Milk}\}$ (s=0.4, c=0.67)
 $\{\text{Beer}\} \rightarrow \{\text{Milk, Diaper}\}$ (s=0.4, c=0.67)
 $\{\text{Diaper}\} \rightarrow \{\text{Milk, Beer}\}$ (s=0.4, c=0.5)
 $\{\text{Milk}\} \rightarrow \{\text{Diaper, Beer}\}$ (s=0.4, c=0.5)


Observations:

- All the above rules are binary partitions of the same itemset: {Milk, Diaper, Beer}
- Rules originating from the same itemset have identical support but can have different confidence
- Thus, we may decouple the support and confidence requirements

Mining Association Rules

- **Two-step approach:**
 1. **Frequent Itemset Generation**
 - Generate all itemsets whose support \geq minsup
 2. **Rule Generation**
 - Generate high confidence rules from each frequent itemset, where each rule is a binary partitioning of a frequent itemset
- **Frequent itemset generation is still computationally expensive**


Frequent Itemset Generation



Given d items, there are 2^d possible candidate itemsets

Frequent Itemset Generation

- **Brute-force approach:**
 - Each itemset in the lattice is a **candidate** frequent itemset
 - Count the support of each candidate by scanning the database



- Match each transaction against every candidate
- Complexity $\sim O(NMw) \Rightarrow$ **Expensive since $M = 2^d$!!!**

Frequent Itemset Generation Strategies

- Reduce the **number of candidates** (M)
 - Complete search: $M=2^d$
 - Use pruning techniques to reduce M
- Reduce the **number of transactions** (N)
 - Reduce size of N as the size of itemset increases
 - Used by DHP and vertical-based mining algorithms
- Reduce the **number of comparisons** (NM)
 - Use efficient data structures to store the candidates or transactions
 - No need to match every candidate against every transaction

Reducing Number of Candidates

- **Apriori principle:**


- If an itemset is frequent, then all of its subsets must also be frequent

- **Apriori principle holds due to the following property of the support measure:**

$$\forall X, Y : (X \subseteq Y) \Rightarrow s(X) \geq s(Y)$$

- Support of an itemset never exceeds the support of its subsets
- This is known as the **anti-monotone** property of support

Illustrating Apriori Principle



Illustrating Apriori Principle

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk



Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3$$

$$6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$

Illustrating Apriori Principle

<i>TID</i>	<i>Items</i>
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk



Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3 \\ 6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$

Illustrating Apriori Principle

Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3



Itemset
{Bread, Milk}
{Bread, Beer }
{Bread, Diaper}
{Beer, Milk}
{Diaper, Milk}
{Beer, Diaper}

TID	Items
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3 \\ 6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$

Illustrating Apriori Principle

Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3 \\ 6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$



TID	Items
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk

Itemset	Count
{Bread, Milk}	3
{Beer, Bread}	2
{Bread, Diaper}	3
{Beer, Milk}	2
{Diaper, Milk}	3
{Beer, Diaper}	3

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)

Illustrating Apriori Principle

Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3 \\ 6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$

TID	Items
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk



Itemset	Count
{Bread, Milk}	3
{Beer, Bread}	2
{Bread, Diaper}	3
{Beer, Milk}	2
{Diaper, Milk}	3
{Beer, Diaper}	3

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)



Triplets (3-itemsets)

Itemset
{ Beer, Diaper, Milk }
{ Beer, Bread, Diaper }
{ Bread, Diaper, Milk }
{ Beer, Bread, Milk }

Illustrating Apriori Principle

Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3 \\ 6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$

TID	Items
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk



Itemset	Count
{Bread, Milk}	3
{Beer, Bread}	2
{Bread, Diaper}	3
{Beer, Milk}	2
{Diaper, Milk}	3
{Beer, Diaper}	3

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)



Triplets (3-itemsets)

Itemset	Count
{ Beer, Diaper, Milk}	2
{ Beer, Bread, Diaper}	2
{Bread, Diaper, Milk}	2
{Beer, Bread, Milk}	1

Illustrating Apriori Principle

Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,
 ${}^6C_1 + {}^6C_2 + {}^6C_3$
 $6 + 15 + 20 = 41$
 With support-based pruning,
 $6 + 6 + 4 = 16$
 $6 + 6 + 1 = 13$

TID	Items
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk



Itemset	Count
{Bread, Milk}	3
{Beer, Bread}	2
{Bread, Diaper}	3
{Beer, Milk}	2
{Diaper, Milk}	3
{Beer, Diaper}	3

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)



Triplets (3-itemsets)

Itemset	Count
{ Beer, Diaper, Milk }	2
{ Beer, Bread, Diaper }	2
{Bread, Diaper, Milk}	2
{Beer, Bread, Milk}	1

Apriori Algorithm

- F_k : frequent k-itemsets
- L_k : candidate k-itemsets
- **Algorithm**
 - Let $k=1$
 - Generate $F_1 = \{\text{frequent 1-itemsets}\}$
 - Repeat until F_k is empty
 - **Candidate Generation**: Generate L_{k+1} from F_k
 - **Candidate Pruning**: Prune candidate itemsets in L_{k+1} containing subsets of length k that are infrequent
 - **Support Counting**: Count the support of each candidate in L_{k+1} by scanning the DB
 - **Candidate Elimination**: Eliminate candidates in L_{k+1} that are infrequent, leaving only those that are frequent $\Rightarrow F_{k+1}$

Candidate Generation: Brute-force method




Figure 5.6. A brute-force method for generating candidate 3-itemsets.

Candidate Generation: Merge F_{k-1} and F₁ itemsets




Figure 5.7. Generating and pruning candidate k -itemsets by merging a frequent $(k-1)$ -itemset with a frequent item. Note that some of the candidates are unnecessary because their subsets are infrequent.

Candidate Generation: $F_{k-1} \times F_{k-1}$ Method

- Merge two frequent $(k-1)$ -itemsets if their first $(k-2)$ items are identical
- $F_3 = \{\underline{ABC}, \underline{ABD}, \underline{ABE}, \underline{ACD}, \underline{BCD}, \underline{BDE}, \underline{CDE}\}$
 - Merge(ABC, ABD) = ABCD
 - Merge(ABC, ABE) = ABCE
 - Merge(ABD, ABE) = ABDE
 - Do not merge(ABD, ACD) because they share only prefix of length 1 instead of length 2

Candidate Pruning

- Let $F_3 = \{ABC, ABD, ABE, ACD, BCD, BDE, CDE\}$ be the set of frequent 3-itemsets
- $L_4 = \{ABCD, ABCE, ABDE\}$ is the set of candidate 4-itemsets generated (from previous slide)
- **Candidate pruning**
 - Prune ABCE because ACE and BCE are infrequent
 - Prune ABDE because ADE is infrequent
- **After candidate pruning: $L_4 = \{ABCD\}$**

Candidate Generation: $F_{k-1} \times F_{k-1}$ Method




Figure 5.8. Generating and pruning candidate k -itemsets by merging pairs of frequent $(k-1)$ -itemsets.

Illustrating Apriori Principle

Items (1-itemsets)

Item	Count
Bread	4
Coke	2
Milk	4
Beer	3
Diaper	4
Eggs	1

Minimum Support = 3

If every subset is considered,

$${}^6C_1 + {}^6C_2 + {}^6C_3 \\ 6 + 15 + 20 = 41$$

With support-based pruning,

$$6 + 6 + 4 = 16$$



Itemset	Count
{Bread, Milk}	3
{Beer, Bread}	2
{Bread, Diaper}	3
{Beer, Milk}	2
{Diaper, Milk}	3
{Beer, Diaper}	3

Pairs (2-itemsets)

(No need to generate candidates involving Coke or Eggs)



Triplets (3-itemsets)

Itemset	Count
{Bread, Diaper, Milk}	2

Use of $F_{k-1} \times F_{k-1}$ method for candidate generation results in only one 3-itemset. This is eliminated after the support counting step.

TID	Items
1	Bread, Milk
2	Beer, Bread, Diaper, Eggs
3	Beer, Coke, Diaper, Milk
4	Beer, Bread, Diaper, Milk
5	Bread, Coke, Diaper, Milk

Alternate $F_{k-1} \times F_{k-1}$ Method

- Merge two frequent $(k-1)$ -itemsets if the last $(k-2)$ items of the first one is identical to the first $(k-2)$ items of the second.
- $F_3 = \{ABC, ABD, ABE, ACD, BCD, BDE, CDE\}$
 - Merge(ABC, BCD) = ABCD
 - Merge(ABD, BDE) = ABDE
 - Merge(ACD, CDE) = ACDE
 - Merge(BCD, CDE) = BCDE

Candidate Pruning for Alternate $F_{k-1} \times F_{k-1}$ Method

- Let $F_3 = \{ABC, ABD, ABE, ACD, BCD, BDE, CDE\}$ be the set of frequent 3-itemsets
- $L_4 = \{ABCD, ABDE, ACDE, BCDE\}$ is the set of candidate 4-itemsets generated (from previous slide)
- Candidate pruning
 - Prune ABDE because ADE is infrequent
 - Prune ACDE because ACE and ADE are infrequent
 - Prune BCDE because BCE
- After candidate pruning: $L_4 = \{ABCD\}$

Rule Generation

- Given a frequent itemset L , find all non-empty subsets $f \subset L$ such that $f \rightarrow L - f$ satisfies the minimum confidence requirement

- If $\{A,B,C,D\}$ is a frequent itemset, candidate rules:

$ABC \rightarrow D,$	$ABD \rightarrow C,$	$ACD \rightarrow B,$	$BCD \rightarrow A,$
$A \rightarrow BCD,$	$B \rightarrow ACD,$	$C \rightarrow ABD,$	$D \rightarrow ABC$
$AB \rightarrow CD,$	$AC \rightarrow BD,$	$AD \rightarrow BC,$	$BC \rightarrow AD,$
$BD \rightarrow AC,$	$CD \rightarrow AB,$		

- If $|L| = k$, then there are $2^k - 2$ candidate association rules (ignoring $L \rightarrow \emptyset$ and $\emptyset \rightarrow L$)

Rule Generation

- **In general, confidence does not have an anti-monotone property**
 $c(ABC \rightarrow D)$ can be larger or smaller than $c(AB \rightarrow D)$

- **But confidence of rules generated from the same itemset has an anti-monotone property**


- E.g., Suppose $\{A, B, C, D\}$ is a frequent 4-itemset:

$$c(ABC \rightarrow D) \geq c(AB \rightarrow CD) \geq c(A \rightarrow BCD)$$

- Confidence is anti-monotone w.r.t. number of items on the RHS of the rule

Rule Generation for Apriori Algorithm

Lattice of rules



Q&A