

optimex: A Python Package for Time-Explicit Life Cycle Optimization

Timo Diepers¹ and Jan Tautorus²

¹ Institute of Technical Thermodynamics (LTT), RWTH Aachen University, Germany ² Interdisciplinary Transformation University Austria (IT:U), Austria

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [Open Journals](#)

Reviewers:

- [@openjournals](#)

Submitted: 01 January 1970

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

optimex is an open-source Python package for time-explicit Life Cycle Optimization (LCO). LCO extends Life Cycle Assessment (LCA) by treating process selection, capacity installation, and operation as decision variables, determining process portfolios and deployment schedules that minimize an environmental objective subject to system constraints. optimex makes this optimization *time-explicit*: instead of collapsing each process's life cycle into a single instant, it tracks *when* every flow across its life cycle and supply chain occurs and lets each flow's magnitude reflect the state of technology and the surrounding economy *at that time*. Decisions made today are therefore evaluated against the conditions they will actually encounter in the future, which is what determines whether a transition pathway is genuinely feasible and environmentally sustainable once deployed.

Concretely, optimex simultaneously accounts for:

- the **temporal distribution** of flows across a process life cycle (construction, multi-year operation, maintenance, and end-of-life occur at different times);
- the **temporal evolution** of foreground technologies through vintage-dependent parameters (a process installed in 2035 is more efficient than one installed in 2025);
- time-specific background supply chains**, so that upstream electricity, hydrogen, or steel inputs are assessed against future rather than present conditions; and
- dynamic impact assessment**, where characterization factors vary over time.

The package embeds these temporal dimensions directly into the optimization problem, then determines installation timing, capacities, and operational levels under time-resolved environmental objectives and constraints. optimex builds on the Brightway LCA ecosystem ([Mutel, 2017](#)), sources dynamic characterization factors from `dynamic_characterization` ([Brightway LCA software framework, 2025](#)), and uses Pyomo ([Bynum et al., 2021](#)) as its mathematical programming backend.

Statement of need

Designing sustainable transitions requires decisions about *which* processes to deploy, *when* to deploy them, and *how* to operate them over time while accounting for impacts across their entire life cycle. LCO is well suited to this task because it links process and supply-chain decisions to environmental objectives and constraints ([Heijungs & Suh, 2002](#)). However, existing LCO approaches treat life cycles as static, instantaneous events, collapsing the flows from construction, operation, maintenance, and end-of-life into a single point in time. This simplification neglects two temporal dimensions that are essential for transition pathways: flows are *distributed* over time, and product systems *evolve* over time. Crucially, the two dimensions are interlinked — when a flow occurs dictates the system conditions it encounters

— so both must be considered jointly. Resolving when each flow actually occurs is decisive for whether a designed pathway is genuinely feasible and environmentally sustainable once deployed: the relevant limits are themselves time-dependent, spanning cumulative stock limits such as carbon budgets and finite mineral reserves as well as flow-related limits on the rate at which resources can be extracted or emissions absorbed. A pathway that appears compliant under static, time-aggregated accounting can breach these limits in practice, for example by concentrating demand for a scarce resource into a transient bottleneck that static models never reveal.

opt_{imex} addresses this gap by providing a general, open-source implementation of time-explicit LCO. Its target audience comprises LCA practitioners, energy- and industrial-systems modelers, and sustainability researchers who design technology transition pathways and need to optimize them against time-resolved environmental objectives and constraints. Because opt_{imex} is built on Brightway, practitioners can temporalize foreground models they have already built for standard LCA and turn them into optimization problems without rebuilding anything from scratch; temporalized product systems prepared with the time-explicit *assessment* framework `bwtimex` (Müller et al., 2025) can be reused directly.

State of the field

Holistically evaluating the environmental sustainability of a system requires accounting for entire life cycles across a broad range of environmental impact categories, which is the purpose of LCA (Heijungs & Suh, 2002). LCA is traditionally static, but several methods have been proposed to add temporal considerations. Dynamic LCA tools such as Temporalis (Cardellini et al., 2018) capture *temporal distribution*, the timing of flows as they cascade through the many tiers of the supply chain, while assuming a fixed product system (Beloïn-Saint-Pierre et al., 2020). Prospective LCA tools such as premise (Sacchi et al., 2022), Futura (Joyce & Björklund, 2022), and pathways (Sacchi & Hahn-Menacho, 2024) instead capture *temporal evolution* but assess product systems at individual points in time (Arvidsson et al., 2024). Recent tools combine both dimensions, including `bwtimex` (Müller et al., 2025), ProsperDyn (L. Lang-Quantzendorff & Beermann, 2025), and TRAILS (Sacchi, 2026), but all assess a predefined product system rather than determining an optimal one from a set of alternatives.

Resolving time, however, multiplies the number of viable alternatives: which technology to deploy, when, and how to operate it all interact through distributed flows and evolving conditions. This combinatorial complexity is precisely what optimization is meant to handle, yet conventional optimization tools cannot. Integrated Assessment Models and energy system models operate at too coarse a technological resolution to capture environmental impacts across full supply chains and multiple impact categories (Reinert et al., 2022; Weyant, 2017). Life Cycle Optimization fills this role by embedding full LCA inventories into mathematical programs (Azapagic & Clift, 1998; Kätelhön et al., 2016), but resolves time only partially. Multi-period LCO distributes installation decisions across a transition horizon, introducing temporal distribution at the level of installation, though it typically still relies on static inventory data. Such formulations can additionally draw on prospective inventory data to reflect technology evolution. The recent open-source tool PULPO (Lechtenberg et al., 2024), built on the same Brightway and Pyomo libraries as opt_{imex}, supports exactly this combination of multi-period optimization and prospective data. Even then, however, each technology's flows are placed at the moment of its installation, resolving only the first tier of the supply chain (*single-tier* distribution). Resolving the timing of flows throughout all tiers of the product system (*multi-tier* distribution) remains an open gap (Ladislaus Lang-Quantzendorff & Beermann, 2025; Turner et al., 2025).

In contrast, opt_{imex} explicitly resolves the timing of all flows throughout the product system, combining this multi-tier temporal distribution with temporal evolution. We achieve this by extending the traditional matrix-based LCA formulation with explicit time dimensions, exposing capacity installation and operation as time-indexed decision variables; we refer to Diepers et al.

(2026a) for the full formulation. Because every flow is placed at the time it actually occurs, the resulting pathways can be checked against time-dependent stock- and flow-related limits, surfacing transient bottlenecks and cumulative-budget violations that static accounting hides. To our knowledge, `optimex` is the first tool to deliver time-explicit LCO in a consolidated, documented, and tested package.

Software design

A time-explicit LCO with `optimex` follows a four-stage pipeline.

First, **LCA processing** temporalizes the foreground system and gathers all data for the optimization. As in conventional LCA, the user models products, processes, and their intermediate and elementary flows using the traditional Brightway workflows. Three additional steps make this representation time-explicit: process-relative temporal distributions (rTDs) are attached to exchanges to describe how each flow is distributed over time relative to the consuming or emitting process (Cardellini et al., 2018); operation-dependent flows are marked so they can be scaled separately from capacity installation; and vintage-dependent scaling factors are specified to capture technology evolution. In addition, a set of time-specific background databases (e.g., generated with `premise` (Sacchi et al., 2022)) can be specified. For dynamic impact assessment, users can draw from the Brightway library `dynamic_characterization` (Brightway LCA software framework, 2025). From these inputs, `optimex` constructs time-explicit tensors that describe the temporalized product system.

Second, **model conversion** validates the temporalized product system and converts it to Pyomo-compatible sets. A Pydantic model checks that processes, flows, and time indices are consistent across all tensors. Further, additional constraints can be added, e.g., deployment and operation limits, category impact limits, process coupling, and existing (brownfield) capacities.

Third, **optimization** builds a Pyomo model with time-indexed decision variables for installed capacity and operational level. Constraints enforce demand fulfilment, deployment and operation limits, the coupling of operation to installed capacity, and process linkages; the objective minimizes the total impact in a chosen category and metric. The backend is solver-agnostic, defaulting to Gurobi but compatible with open-source solvers.

Finally, **post-processing** extracts results as DataFrames and provides visualizations of impacts, installations, operation, and product balances.

Several design choices were central to the research application. Embedding the time dimension directly into the traditional LCA matrices keeps the formulation within the familiar matrix-based LCA structure (Heijungs & Suh, 2002) while allowing flexible temporal resolution. Separating capacity-dependent from operation-dependent flows is what enables vintage-specific, flexible dispatch. Inputs are scaled for numerical stability before being handed to the solver and denormalized during post-processing, improving computational stability. Moreover, the deep Brightway integration lets `optimex` work with any Brightway-compatible inventory and reuse product systems already built for standard LCA, avoiding data lock-in and facilitating adoption. Finally, `optimex` can export both the processed LCA data and the initialized or solved Pyomo model, supporting reproducibility, model sharing, and fast re-optimization without recomputing the LCA inputs.

Research impact statement

`optimex` is the reference implementation of the time-explicit LCO framework introduced in the accompanying methodological work (Diepers et al., 2026a), where it is applied to an integrated methanol and pig iron production system. There, time-explicit LCO uncovers transition strategies that remain invisible to conventional, static LCO: prioritizing early installation of high-efficiency technologies so that older processes can be idled once operational savings

139 outweigh the embodied impacts of stranded assets, and diversifying technology portfolios to
140 avoid transient resource bottlenecks.

141 Beyond this methodological work, `optimex` has been presented to the scientific community at
142 two scientific conferences (Diepers et al., 2025, 2026b), and has been applied in two student
143 theses (Lange, 2026; Tautorus, 2025).

144 The package is built for reuse, community uptake and collaboration. It is distributed via
145 PyPI and conda, developed openly on GitHub with a continuous-integration test suite and
146 code-coverage reporting, and supported by comprehensive documentation, runnable example
147 notebooks, and a Binder environment for zero-install exploration (Diepers & Tautorus, 2025b,
148 2025a). By integrating with the widely used Brightway ecosystem and accepting temporalized
149 models from `bw_timex`, `optimex` connects to an existing community of LCA practitioners rather
150 than requiring them to adopt a wholly new workflow.

151 AI usage disclosure

152 During development, the authors used AI coding assistants, namely Claude Code and GitHub
153 Copilot, to aid implementation. The core test suite was written by the authors, and all
154 AI-assisted output was reviewed and verified by the authors, who take full responsibility for the
155 correctness of the code. Generative AI tools were also used to assist with editing portions of
156 the documentation and this manuscript, with all text checked and approved by the authors.

157 References

- 158 Arvidsson, R., Svanström, M., Sandén, B. A., Thonemann, N., Steubing, B., & Cucurachi, S.
159 (2024). Terminology for future-oriented life cycle assessment: Review and recommendations.
160 *The International Journal of Life Cycle Assessment*, 29(4), 607–613. [https://doi.org/10.](https://doi.org/10.1007/s11367-023-02265-8)
161 [1007/s11367-023-02265-8](https://doi.org/10.1007/s11367-023-02265-8)
- 162 Azapagic, A., & Clift, R. (1998). Linear programming as a tool in life cycle assessment. *The*
163 *International Journal of Life Cycle Assessment*, 3(6), 305–316. [https://doi.org/10.1007/](https://doi.org/10.1007/BF02979340)
164 [BF02979340](https://doi.org/10.1007/BF02979340)
- 165 Beloin-Saint-Pierre, D., Albers, A., Hélias, A., Tiruta-Barna, L., Fantke, P., Levasseur, A.,
166 Benetto, E., Benoist, A., & Collet, P. (2020). Addressing temporal considerations in life
167 cycle assessment. *Science of The Total Environment*, 743, 140700. [https://doi.org/10.](https://doi.org/10.1016/j.scitotenv.2020.140700)
168 [1016/j.scitotenv.2020.140700](https://doi.org/10.1016/j.scitotenv.2020.140700)
- 169 Brightway LCA software framework. (2025). *Dynamic_characterization: Dynamic characteriza-*
170 *tion of life cycle inventories*. https://github.com/brightway-lca/dynamic_characterization
- 171 Bynum, M. L., Hackebeil, G. A., Hart, W. E., Laird, C. D., Nicholson, B. L., Sirola, J. D.,
172 Watson, J.-P., & Woodruff, D. L. (2021). *Pyomo — Optimization Modeling in Python*
173 (3rd ed., Vol. 67). Springer. <https://doi.org/10.1007/978-3-030-68928-5>
- 174 Cardellini, G., Mutel, C. L., Vial, E., & Muys, B. (2018). Temporalis, a generic method and
175 tool for dynamic Life Cycle Assessment. *Science of The Total Environment*, 645, 585–595.
176 <https://doi.org/10.1016/j.scitotenv.2018.07.044>
- 177 Diepers, T., & Tautorus, J. (2025a). *Optimex documentation: Time-explicit Life Cycle*
178 *Optimization*. <https://optimex.readthedocs.io>
- 179 Diepers, T., & Tautorus, J. (2025b). *Optimex: Time-explicit Life Cycle Optimization*. [https:](https://github.com/RWTH-LTT/optimex)
180 [/github.com/RWTH-LTT/optimex](https://github.com/RWTH-LTT/optimex)
- 181 Diepers, T., Tautorus, J., Hartmann, J., & von der Assen, N. (2025). *Optimizing transition path-*
182 *ways using time-explicit life cycle assessment*. Presentation, 12th International Conference

- 183 on Industrial Ecology (ISIE), Singapore. <https://doi.org/10.18154/RWTH-2025-06519>
- 184 Diepers, T., Tautorus, J., Hartmann, J., & von der Assen, N. (2026a). *A framework for*
185 *time-explicit life cycle optimization of transition pathways*.
- 186 Diepers, T., Tautorus, J., Hartmann, J., & von der Assen, N. (2026b). *Time-explicit life cycle*
187 *optimization for transition pathways: An open-source Python implementation*. Poster,
188 SETAC Europe 36th Annual Meeting, Maastricht, The Netherlands. <https://doi.org/10.5281/zenodo.20156266>
189
- 190 Heijungs, R., & Suh, S. (2002). *The Computational Structure of Life Cycle Assessment* (A.
191 Tukker, Ed.; Vol. 11). Springer Netherlands. <https://doi.org/10.1007/978-94-015-9900-9>
- 192 Joyce, P. J., & Björklund, A. (2022). Futura: A new tool for transparent and shareable scenario
193 analysis in prospective life cycle assessment. *Journal of Industrial Ecology*, 26(1), 134–144.
194 <https://doi.org/10.1111/jiec.13115>
- 195 Kätelhön, A., Bardow, A., & Suh, S. (2016). Stochastic technology choice model for conse-
196 quential life cycle assessment. *Environmental Science & Technology*, 50(23), 12575–12583.
197 <https://doi.org/10.1021/acs.est.6b04270>
- 198 Lange, L. (2026). *Determining cost-optimal transition pathways based on time-explicit life*
199 *cycle assessment* [Bachelor's thesis]. RWTH Aachen University.
- 200 Lang-Quantzendorff, Ladislaus, & Beermann, M. (2025). Time-differentiating methods for life
201 cycle assessment of the industry transition toward climate neutrality: A review. *Journal of*
202 *Industrial Ecology*, 29(5), 1523–1550. <https://doi.org/10.1111/jiec.70068>
- 203 Lang-Quantzendorff, L., & Beermann, M. (2025). Prosperdyn—a tool to describe dynamic
204 transitions in prospective life cycle assessment. *The International Journal of Life Cycle*
205 *Assessment*. <https://doi.org/10.1007/s11367-025-02515-x>
- 206 Lechtenberg, F., Guillén-Gosálbez, G., & Espuña, A. (2024). PULPO: A framework for efficient
207 integration of life cycle inventory models into life cycle product optimization. *Journal of*
208 *Industrial Ecology*, 28(6), 1449–1463. <https://doi.org/10.1111/jiec.13561>
- 209 Müller, A., Diepers, T., Jakobs, A., Cardellini, G., von der Assen, N., Guinée, J., & Steubing, B.
210 (2025). Time-explicit life cycle assessment: A flexible framework for coherent consideration
211 of temporal dynamics. *The International Journal of Life Cycle Assessment*. <https://doi.org/10.1007/s11367-025-02539-3>
212
- 213 Mutel, C. (2017). Brightway: An open source framework for Life Cycle Assessment. *Journal*
214 *of Open Source Software*, 2(12), 236. <https://doi.org/10.21105/joss.00236>
- 215 Reinert, C., Schellhas, L., Mannhardt, J., Shu, D. Y., Kämper, A., Baumgärtner, N., Deutz,
216 S., & Bardow, A. (2022). SecMOD: An open-source modular framework combining multi-
217 sector system optimization and life-cycle assessment. *Frontiers in Energy Research*, 10,
218 884525. <https://doi.org/10.3389/fenrg.2022.884525>
- 219 Sacchi, R. (2026). *TRAILS: Temporal routing and aggregation of impacts across life-cycle*
220 *systems* (Version v1.0.0). <https://trails.readthedocs.io/en/latest/>
- 221 Sacchi, R., & Hahn-Menacho, A. J. (2024). Pathways: Life cycle assessment of energy
222 transition scenarios. *Journal of Open Source Software*, 9(103), 7309. <https://doi.org/10.21105/joss.07309>
223
- 224 Sacchi, R., Terlouw, T., Siala, K., Dirnaichner, A., Bauer, C., Cox, B., Mutel, C., Daioglou,
225 V., & Luderer, G. (2022). PRospective EnvironMental Impact asSEment (*premise*):
226 A streamlined approach to producing databases for prospective life cycle assessment
227 using integrated assessment models. *Renewable and Sustainable Energy Reviews*, 160.
228 <https://doi.org/10.1016/j.rser.2022.112311>
- 229 Tautorus, J. (2025). *Coupling dynamic-prospective life cycle assessment with transition pathway*

- 230 *optimization* [Master's thesis]. RWTH Aachen University.
- 231 Turner, C., Bamber, N., Andrews, O., & Pelletier, N. (2025). Systematic review of the
232 life cycle optimization literature, and recommendations for performance of life cycle
233 optimization studies. *Renewable and Sustainable Energy Reviews*, 208, 115058. <https://doi.org/10.1016/j.rser.2024.115058>
234 <https://doi.org/10.1016/j.rser.2024.115058>
- 235 Weyant, J. (2017). Some contributions of integrated assessment models of global climate
236 change. *Review of Environmental Economics and Policy*, 11(1), 115–137. <https://doi.org/10.1093/reep/rew018>
237 <https://doi.org/10.1093/reep/rew018>

DRAFT