



Eidgenössische Technische Hochschule Zürich
Swiss Federal Institute of Technology Zurich

Lecture with Computer Exercises:
Modelling and Simulating Social Systems with MATLAB

Project Report

**Civil Violence: Modelling Genocides
Model Extension and Global Sensitivity Analysis**

Ruben Wälchli & Zoran Bjelobrk

Zurich
December 10, 2014

Agreement for free-download

We hereby agree to make our source code for this project freely available for download from the web pages of the SOMS chair. Furthermore, we assure that all source code is written by ourselves and is not violating any copyright restrictions.

Ruben Wälchli

Zoran Bjelobrk

Contents

1	Abstract	4
2	Individual contributions	4
3	Introduction and Motivations	4
4	Description of the Model	4
4.1	Base Model	4
4.1.1	Specification of the Civilians	4
4.1.2	Specification of the LEOs	5
4.1.3	Evolution of the Simulation	5
4.2	Modification of the Model	6
4.2.1	Individual Perceived Legitimacy and Threshold	6
4.2.2	Updating the Perceived Legitimacy	7
5	Implementation	7
5.1	Base Model	7
5.2	Sensitivity Analysis	9
5.2.1	Sample Generation	9
5.2.2	Model Output Generation	9
5.2.3	Sensitivity Indice Computation	10
5.3	Qualitative Assessment of the Input Parameters	10
6	Simulation Results and Discussion	11
6.1	Global Sensitivity Analysis	11
6.2	Qualitative Assessment of the Input Parameters	13
6.2.1	Reproduction Literature Results	13
7	Summary and Outlook	15
8	References	15

1 Abstract

2 Individual contributions

3 Introduction and Motivations

Ethnical conflicts were omnipresent throughout human history and still are a major source for civil violence in these days. For instance, the wars leading to the decay of former Yugoslavia are an example in recent history. When studying the project suggestions, this topic immediately drew our interest. Our project is a so-called "model-driven" project. The base model was described by Epstein in 2002. It contains some very strong simplifications as further described in section 4.1. Our approach was to modify the model in a way that describes reality better in our opinion and to compare the results of the model runs to those presented in literature. To further assess the model in a quantitative manner, a global sensitivity analysis was performed for various model parameters based on a method described in literature.

4 Description of the Model

4.1 Base Model

The model is a so-called agent-based model. There are two fundamental classes of agents: civilians and law enforcement officers (LEOs). The only purpose of the LEO is to prevent violence through arresting active, this means violent, civilians. The civilians are further divided into two ethnical groups. They become active or stay quiet (peaceful) based on the values of their individual characteristics and the environment within their range of sight. The agents are placed on a two-dimensional map on which they can move and interact with each other.

4.1.1 Specification of the Civilians

The will of a civilian to become violent is described by its grievance G . This individual grievance is described by two components: the hardship H of the civilian and his/her perceived legitimacy of the other ethnic group L .

$$G = H(1 - L) \tag{1}$$

The grievance of the individual civilian is according to this formula given by the hardship multiplied by the "illegitimacy" $(1 - L)$ of the other ethnic group. The hardship is heterogeneous across the civilians. It is initialized for each civilian at the beginning of the simulation by drawing it from the uniform distribution on the interval

$[0, 1]$ ($U(0, 1)$) and it remains constant over the course of the simulation. L is homogeneous across all civilians and also stays constant. It is also equal for both ethnic groups. It is defined at the beginning of the simulation and also lies between 0 and 1.

R is the risk aversion of the civilian. It is heterogeneous across the population and also drawn upon initialization from $U(0, 1)$. A civilian inspects its environment before deciding whether to go active or stay quiet (and vice versa). The civilians have the vision v , which is homogeneous across the population and is defined at the beginning of the simulation.

$$P = 1 - \exp \left(-k_P \left(\frac{LEO}{A} \right)_v \right) \quad (2)$$

P is the arrest probability estimated by the civilian. $(LEO/A)_v$ is the LEO-to-active ratio within the civilians vision. A is always at least 1, because the civilian counts himself as active when calculating the arrest probability. The reasoning behind this calculation is, that it is less likely for the civilian to be arrested, when already a lot of other civilians are acting violently and very few LEOs are present around him. The opposite can be said, if there are a lot of LEOs and only few or no active civilians. k is a constant parameter, that is calculated by setting $P = 0.9$ when $(LEO/A)_v = 1$. With the risk aversion and the estimated arrest probability the so-called net risk of the civilian of going active can be calculated:

$$N = RP \quad (3)$$

The difference $G - N$ is the civilian's net utility of becoming active. This is compared to a threshold value T . If $(G - N) > T$ the civilian becomes or stays active and if $(G - N) \leq T$ the civilian stays or becomes quiet. The threshold value T is equal for all civilians and defined at the beginning of the simulation.

4.1.2 Specification of the LEOs

The LEOs have only one characteristic, their vision v^* . They inspect the map within their vision and randomly arrest an active civilian.

4.1.3 Evolution of the Simulation

After choosing values for the global parameters, the three different types of agents are placed on the map randomly and their individual attributes are initialized. The number of civilians and LEOs that are placed on the map are determined by their corresponding selected densities. In each iteration begins by the random selection of

one agent (civilian or LEO). This agent moves to a random empty position within his vision. There he inspects his environment. If the agent is a civilian he takes the decision to be active or quiet. When he decides to become active, he tries to kill a random civilian of the other ethnic group within his vision. If the selected agent is a LEO, he arrests a random active civilian within his vision. The arrested civilian is assigned a jail term and moved to the jail. The jail term is drawn from $U(0, J_{\max})$. The ages both of the civilians on the map as well as of those in jail are updated and the civilians that have reached their maximum age are removed. The number of turns of the inmates spent in jail are updated and those who have served their time are released onto random positions on the map.

4.2 Modification of the Model

4.2.1 Individual Perceived Legitimacy and Threshold

In our opinion, the assumption that the perceived legitimacy of the other ethnic group and the threshold value are identical for all individuals of the population is too harsh. Therefore, we wanted to make them individual quantities. To us it also seemed not realistic to have the perceived legitimacy uniformly distributed throughout the population. Therefore, we decided to use the Gaussian distribution truncated to the interval $[0, 1]$. In the modified model the perceived legitimacy of the other ethnic group is initialized for all civilians by drawing it from this distribution. This adds two parameters to the model: the mean μ_L and the standard deviation σ_L of the legitimacy.

The threshold T can be seen as the level of "extremism" an individual has. Epstein describes it as the utility of not publicly expressing one's private grievance. A very extreme individual will see absolutely no utility in holding his private grievance back, whether a very conservative individual will almost never publicly express his private grievance. The difference $(G - N)$ on the other hand is the perceived utility to describe one's private grievance and it can take values in the interval $[-1, 1]$. A civilian with $T = -1$ will always be active, whereas a civilian with $T = 1$ will never be active. As said before, it is probably unrealistic to have the threshold value uniformly distributed over the population. Therefore, it is also drawn upon initialization of the civilians from the truncated Gaussian distribution on the interval $[-1, 1]$ adding another two parameters to the model (μ_T and σ_T).

For the sake of simplicity and to make the sensitivity analysis described later not computationally too expensive it is renounced to also change the distributions of the other individual characteristics of the civilians (H and R) to the described truncated

Gaussian distribution.

4.2.2 Updating the Perceived Legitimacy

It seems quite obvious that the perceived legitimacy of the other ethnic group should not be a constant over the course of the simulation. Violence committed by one ethnic group will probably decrease its perceived legitimacy in the eyes of the other ethnic group. The opposite effect will possibly have the arrest of a active (violent) civilian on the perceived legitimacy of its ethnic group. In our expansion of the model, these effects are limited to the range of sight of the involved killed or active civilian. The update in the case of violence is the following:

$$L_{\text{new}} = L_{\text{old}} (1 - k_L) \quad (4)$$

When an active civilian is arrested, the updates is given by:

$$L_{\text{new}} = L_{\text{old}} + k_L (1 - L_{\text{old}}) \quad (5)$$

The reasoning behind both formulas is that if the perceived legitimacy is either very high or very low, violence and arrests only change little in the legitimacy (saturation effect). On the other hand, when a civilian is unsure, if the other ethnic group has the right to exist (medium value of L) such events can have a strong influence.

5 Implementation

The whole implementation is based on arrays of structs. This way of implementation may not be the fastest possible, but it is in our opinion the most intuitive one.

5.1 Base Model

The fields of the struct used to describe the agents are shown in table 1. The central part of the program is the map, an array of size $(N_{\text{map}} \times N_{\text{map}})$ containing this struct as entries, where N is the map size. The individual values of the fields are initialized at the beginning using the function *fun_init_map()*, which returns the initialized map array with all the civilians and LEOs. Type equal to 1, 2 or 3 indicates that the agent is a civilian of the ethnic group 1, group 2 or a LEO. For a LEO only the field v is also different from the default value. The jail is an array of size $(J_{\text{max}} \times 1)$ with the struct from table 1 as entries. The reasoning behind the size of the jail array is that it has to be large enough that theoretically in every iteration a civilian could be send to jail. The function *fun_movement()* moves the randomly selected agent, updates the map accordingly and returns the new position of the agent. If the agent

Table 1: The fields of the struct used to describe the single agents and their meaning and default value.

Field Name	Quantity	Default Value
type	Type of the Agent	0
H	Agent's Hardship	0
L	Agent's Perceived Legitimacy	0
v	Agent's Vision	0
T	Agent's Violence Threshold	0
R	Agent's Risk Aversion	0
state	Agent's State	0
age	Agent's Age	0
life_exp	Agent's Life Expectancy	0
sentenced	Agent's Jail Term	0
served	Agent's Served Time in Jail	0

is a LEO, the function *fun_action_LEO()* inspects the fields within vision of the new position and if active civilians are present there, randomly moves one of them to the jail. To do so, it first assigns the civilian a random jail term (field "sentenced"). Then copies the civilians struct entries to an empty position in the jail and erases the civilian from the map by setting the struct fields at its position to the default values.

If the selected and moved agent is a civilian, the function *fun_action_civ()* is called. It first inspects the surrounding of the new position and determines the current value of P and with this the net risk N . The grievance G is also computed and it is checked if $(G - N)$ is larger or smaller than T . If it is larger, civilians of the other ethnic group within vision are searched. When there is one present, he is killed by setting all the values of the struct at his position to the default values. If there is no such civilian present, the agent remains quiet although he wants to become active. If $(G - N)$ is smaller than T , the selected civilian remains or becomes quiet in any case. When the civilian was initially active, wants to stay active but does not find a opponent to kill, he however stays active. The function returns the changed map and if there has been a kill.

After moving the agent and performing its action, the function *fun_clone()* is called. It goes through all civilians on the map in a random order. For each civilian it checks, if there are empty position right next to him. When there is an empty position, the civilian is cloned with probability P_c onto this position by copying the struct of the

selected civilian. The age of the newly created civilian is reset to 0.

The *fun_update_map()* function updates the ages of the civilians on the map and removes those who have reached their life expectancy by resetting the struct on those positions to the default one.

The jail is updated using the function *fun_update_jail()*. First it updates the ages and the served times of the civilians in jail, then it removes civilians that have reached their life expectancy and releases the civilians that have served their sentence onto random empty positions on the map. The structs of those civilians in the jail array are reset to the default values. The civilians are released in the quiet state, all other characteristics remain unchanged.

5.2 Sensitivity Analysis

For both models, the output variable describing the extent of violence that occurred during the simulation was defined as the cumulative number of kills divided by the initial population size. The normalization to the population size was done in order to investigate also the initial population density as input parameter of the models.

5.2.1 Sample Generation

The size N of the base sample generated was 100. The necessary $(N \times 2k)$ base sample matrix of random numbers, where k is the number of parameters investigated, was generated as suggested in the literature using the *sobolset* class, which is an implementation of Sobol's random number generator in MATLAB. The procedure to obtain the matrix from a created point set object of this class was directly taken from the documentation of the software. This matrix was divided as described in literature into the two matrices \mathbf{A} and \mathbf{B} , which in turn were used to construct the k matrices \mathbf{C}_i . The matrix \mathbf{C}_i corresponds to the generic parameter i and contains all columns of \mathbf{B} except the i^{th} , which is taken from the i^{th} column of \mathbf{A} . The sample generation was done inside the program *sample_generation* and the created sample matrices were exported into .txt files.

5.2.2 Model Output Generation

The implemented models were integrated each into a function called *fun_model()* which takes the defined input parameters as arguments and returns the normalized cumulative number of kills. This function was used to generate the output values corresponding to the sets of input parameters contained in the rows of the matrices

\mathbf{A} , \mathbf{B} and \mathbf{C}_i . Sobol’s quasi-random number generator produces numbers between 0 and 1. Therefore, the input parameters had to be converted inside the functions *fun_model()* in order have their values in the desired ranges. This was done using interval mapping, which here should be illustrated shortly:

$$\begin{aligned} x \in [0, 1] &\longmapsto x' \in [a, b] \\ x' &= (b - a) \cdot x + a \end{aligned}$$

For input parameters that should take integer values, the MATLAB function *round()* was used. The interval $[a, b]$ was extended by 0.5 on both ends for those parameters in order not to decrease the probability of having the parameter values a and b . The output values were stored in the $(N \times 1)$ vectors \mathbf{y}_A , \mathbf{y}_B and \mathbf{y}_{C_i} . All of this was done inside the program *output_generation*.

5.2.3 Sensitivity Indice Computation

5.3 Qualitative Assessment of the Input Parameters

After the global sensitivity analysis failed by yielding no sensible results, a more qualitative approach was taken to nevertheless be able to discuss the effect of certain input parameters on the simulation outcome, both of the base and the modified model. For the base model it was mainly tried to reproduce the observation made in literature regarding the dependence on the density of LEOs on the map. The values of the other model parameters that were fixed for this and the following examinations are shown in table 2. In this frame it was renounced to normalize the

Table 2:

Parameter	Value
Size of the Map	(40×40)
Max. Age	200
Initial Pop. Density	0.7
Initial Fraction of Ethinc Group 1	0.5
Cloning Probability	0.025
Vision of the Civilians	2
Vision of the LEOs	3
k_P	2.3
Max. Jail Term	30
Legitimacy	0.8
Violence Threshold	0.1
Number of Iterations	200

cumulative number of kills to the initial population size, because this parameter was never varied. The initial LEO/civilian ratio was varied from 0 to 0.1 in steps of 0.004. The model was run 10 times at each input parameter value. The mean and the standard deviation of the output variables were taken. This is not an exact reproduction of the analysis done in the reference. There the number of iterations was set to 15000 and for each value of the initial LEO density the simulation was run 50 times. As measure for the extent of violence the time until one ethnic group is completely exterminated was taken (it was set to 15000, if there was no extinction of one group). In our opinion, this is not a very good way to assess the violence during the simulation. Very violent conflicts can never lead to the extinction of one ethnic group, but to very high number of casualties. Also this method was not feasible for us, given our computational resources. Therefore, we decided to let the simulation run for one generation of civilians.

An other minor difference to the reference is the selection of the LEO density. In the reference model, the LEO density on the map can be set independently from the population density of the civilians. In our implementation of the model, only the initial LEO/civilian ratio can be selected. This was mainly done in order to prevent situations where there are too many agents to be placed on the map upon initialization. However, this leads only to minor differences, the general trends should not be affected by this.

For comparison, the same analysis was done using the modified model. In this case μ_L was set to 0.8, μ_T to 0.1 and both σ_L and σ_T to 0.1. The parameter k_L was set to 0.1. The value for the standard deviations of those parameters was selected by evaluating the broadness of the distributions by eye and selecting a sensible value. The effect of k_L will be discussed later and for the time being its value was just a guess.

6 Simulation Results and Discussion

6.1 Global Sensitivity Analysis

The computed sensitivity indices of the input parameters of the base and the modified model are presented in tables 3 and 4, respectively. It is right away obvious that those values cannot be correct. For instance, the S_i have to take by definition values in the interval $[0, 1]$ and the sum of the S_i has to be equal to 1. Also, S_i^T has to be larger or equal to S_i . To our knowledge, we have made no mistake in the implementation of the global sensitivity analysis in MATLAB. One possible explanation for the failure could be an insufficiently large base sample, leading to inaccurate estimates of the

sensitivity indices. But it goes past our computational resources to increase the sample size significantly in order to check, if that is actually the case.

Table 3: Sensitivity indices computed for the base model input parameters.

Parameter	S_i	S_i^T
1	0.4748	0.2421
2	-0.0147	-0.7522
3	0.0464	-1.0529
4	0.0360	-1.1220
5	0.0810	-1.1282
6	0.0640	-1.1080
7	0.0559	-1.1037
8	0.0765	-1.0351
9	0.3150	-0.0658
10	0.1213	-0.9992

Table 4: Sensitivity indices computed for the modified model input parameters.

Parameter	S_i	S_i^T
1	0.3993	1.0651
2	-0.1700	0.7317
3	-0.2336	0.8763
4	-0.1632	0.7517
5	-0.1535	0.7772
6	-0.1971	0.7879
7	-0.1700	0.7482
8	-0.2087	0.8419
9	-0.2013	0.7784
10	-0.2031	0.8355
11	-0.0380	0.9466
12	-0.1666	0.8387
13	-0.1948	0.7765

6.2 Qualitative Assessment of the Input Parameters

6.2.1 Reproduction Literature Results

The result of the analysis regarding the initial LEO/civilian ratio is shown in figure . The anticipated dependence of the mean cumulative number of kills on the LEO/civilian ratio was observed. However, the standard deviation did not increase as one might expect from the results presented in literature. This might be due to the different violence measure used or the effect of the initial LEO/civilian ratio on the standard deviation might only manifest itself at larger numbers of iterations. Also the smaller number of runs per parameter value might affect the result. The




Figure 1: Effect of the initial LEO/civilian ratio on the cumulative number of kills at the end of the simulation using the base model. As expected, the mean formed out of 10 runs decreases with increasing LEO/civ ratio. The standard deviation on the other hand remains constant. It is shown via the error bars.

result of the similar analysis done for the modified model is shown in figure 2. It does not differ from that using the base model. This implies that the heterogeneity of the perceived legitimacy and the violence threshold as well as the updating of the legitimacy has no effect on the dependency of the cumulative number of kills on the initial LEO/civilian ratio, at least not at those values of all the other parameters.




Figure 2: Effect of the initial LEO/civilian ratio on the cumulative number of kills at the end of the simulation using the modified model. Basically the same result as with the base model is obtained. Again, the mean formed out of 10 runs decreases with increasing LEO/civ ratio. The standard deviation shown through remains fairly constant.

7 Summary and Outlook

8 References