Assignment 3 - Graph Algorithms for a Campus Festival

Course: Design and Analysis of Algorithms

1. Purpose and scope

This assignment applies graph algorithms to three aspects of campus festival planning: connecting venues, organising preparation tasks and finding delivery routes. Cable connections are undirected; task dependencies and delivery routes are directed. Each part uses a separate input graph.

Implement six algorithms in the supplied GitHub template: DSU, Kruskal, Prim, Kosaraju SCC, DFS topological ordering and shortest paths in a directed acyclic graph (DAG). Choose one language: Java, Python, C++ or C#. Java 17+ is the primary language in the syllabus; this assignment retains its existing four-language choice.

The completed submission must contain the implementations, student tests and an analysis in ANALYSIS.md. The template provides the main program, JSON input/output adapters, examples and public tests.

2. Work plan

1. Create your repository using **Use this template → Create a new repository**. If the repository is private, give the instructor access.

2. Set the language field in submission.json to Java, Python, Cpp or CSharp. Implement the six methods in the corresponding file below.

3. Complete Parts 1-5, run the public tests and add your own test cases.

4. Compare Kruskal and Prim, demonstrate route reconstruction and complete ANALYSIS.md.

5. Submit the commit link and its successful Public checks run in Moodle.

Language	Implementation file
Java	Java/source/Algorithms.java
Python	Python/source/algorithms.py
C++	Cpp/source/algorithms.hpp
C#	CSharp/source/Algorithms.cs

Implement dsu, kruskal, prim, scc, topo and dag. Helper functions, classes and additional source files may be placed directly in the selected source folder. Standard collections, sorting and priority queues are permitted; the required algorithms must be implemented by the student.

3. General requirements

Vertices are numbered from 0 to n-1. An edge ID is its position in the input edges array, starting at 0. The program must preserve the supplied JSON interface, produce one result per request and reset algorithm state between requests. Use standard output for results only.

Support up to 100,000 vertices and 250,000 edges or DSU operations. For weighted graphs, edge weights range from -1,000,000,000 to 1,000,000,000. Use integer arithmetic that safely represents signed 64-bit totals and distances. DFS implementations must handle deep graphs without a call-stack failure. Exact request formats and input limits are specified in CONTRACTS.md. Requests and results are UTF-8 JSON lines: one input object and one output object per line, including consecutive requests of different tasks and sizes. JSON field names and task names are case-sensitive. Inputs satisfy the published domain; malformed JSON is not assessed.

Task	Vertex limit	Edge / operation limit	Weights
dsu	0 <= n <= 100000	0 <= q <= 250000; q=0 if n=0	not used
kruskal / prim	0 <= n <= 100000	0 <= m <= 250000	-1000000000 <= w <= 1000000000
scc / topo	0 <= n <= 100000	0 <= m <= 250000	not used
dag	1 <= n <= 100000	0 <= m <= 250000	-1000000000 <= w <= 1000000000

In the complexity requirements, n denotes the number of vertices, m the number of edges and q the number of DSU operations. Memory bounds include the returned result.

4. Part 1: Connectivity with DSU

Festival venues are connected by cables added one at a time. After each addition, determine the number of connected components and the size of the largest component.

Implement dsu using disjoint-set union with path compression and union by size or rank. Initially, each vertex forms a separate component. Repeated unions and self-unions must leave an existing component unchanged. Path compression must preserve the path to the root while updating parents. If union by rank is used, maintain component sizes separately: rank is not the component size. Initially largest=1 when n>0 and largest=0 when n=0.

Input: n and operations, a sequence of vertex pairs. **Output:** states, with one [components, largest] pair after each operation. For n=0, operations and states are empty.

Example: for n=4 and operations [[0,1],[1,2],[0,2],[3,3]], return states=[[3,2],[2,3],[2,3],[2,3]]. The last two operations do not merge components.

Required complexity: O(n+q α(n)) amortised time and O(n+q) memory. Initialisation takes O(n); the q operations take O(q α(n)) amortised time. The looser O((n+q) α(n)) remains a valid upper bound.

5. Part 2: Minimum-cost cable network

Given an undirected weighted graph, find a minimum spanning forest. Within every connected component, the selected edges must connect all vertices without cycles and have minimum total weight. Isolated vertices count as components.

Provide two separate implementations: kruskal, using sorted edges and DSU; and prim, using adjacency lists and a priority queue. Prim must restart at an unvisited vertex until every component has been processed.

Input: n and edges, with each edge represented by [u,v,weight]. **Output:** cost, edge_ids and components. Each selected edge ID must occur once. Parallel edges and negative weights are permitted; self-loops must not be selected. Any optimal forest is accepted. If the input has c connected components, return exactly n-c selected edges. In Kruskal, accept an edge only when find(u) != find(v). A lightest edge crossing a cut that respects the current forest is safe by the cut property. For n=0, return cost=0, edge_ids=[] and components=0.

Example: n=4, edges=[[0,1,4],[1,2,2],[0,2,3]]. Selecting edge IDs [1,2] gives cost=5 and components=2; vertex 3 is isolated. When optimal forests are tied, Kruskal and Prim may return different valid edge IDs.

Required complexity: Kruskal O(n+m log(m+1)); Prim O(n+m log(m+1)) with a lazy heap, or O((n+m) log(n+1)) with an indexed heap. Memory: O(n+m).

6. Part 3: Strongly connected components

In a preparation graph, an edge u→v means that task u must be completed before task v. Identify the strongly connected components (SCCs): maximal groups of vertices that are mutually reachable along directed edges.

Implement scc using Kosaraju's algorithm, with two DFS passes and the transposed graph. Return a component label for every vertex and the condensation graph. Process the second pass in decreasing finish order of the first pass. The passes may use G then its transpose, or the transpose then G, with the matching finish order. Component labels may be any nonnegative integers. Equal labels must identify exactly one SCC.

Input: n and directed edges [u,v]. **Output:** component and condensation. Each condensation edge is a pair of component labels. Include each directed pair between distinct components once; exclude internal edges and repeated pairs. Isolated vertices form separate SCCs. Duplicate edges and self-loops are permitted. For n=0, both arrays are empty.

Example: edges 0→1, 1→0, 1→2, 0→2, 2→3 allow component=[5,5,7,9] and condensation=[[5,7],[7,9]]. The two edges from the first SCC to vertex 2 produce one condensation edge.

Required complexity: O(n+m) expected time when a hash set removes duplicate component pairs; O(n+m) memory.

7. Part 4: Preparation order

For a directed dependency graph, determine whether all preparation tasks can be scheduled. If so, return a topological order in which every prerequisite precedes its dependent task.

Implement topo using DFS with unvisited, active and finished states. An edge to an active vertex indicates a cycle; an edge to a finished vertex alone does not. Reverse the DFS finishing order to obtain the result for an acyclic graph.

Input: n and directed edges [u,v]. **Output:** acyclic and order. If any component contains a cycle, return acyclic=false and order=[]. Otherwise, return acyclic=true and a valid order containing every vertex exactly once, including isolated vertices. For n=0, return acyclic=true and order=[]. A self-loop is a cycle.

Example: edges 0→2, 1→2, 2→3 allow order=[0,1,2,3] or [1,0,2,3].

Required complexity: O(n+m) time and memory.

8. Part 5: Shortest delivery routes

Given a directed weighted graph and a source vertex, find the shortest paths from the source using DAG shortest-path processing. Negative edge weights are permitted.

Implement dag. Check the entire graph for cycles, then process an acyclic graph in topological order and relax outgoing edges from reachable vertices only. A cycle must be rejected even if it is unreachable from the source.

Input: n, edges [u,v,weight] and source, with n≥1 and 0≤source<n. **Output:** acyclic, distance and parent_edge. For cyclic input, return acyclic=false and two empty arrays. For an acyclic graph, return acyclic=true and one distance and parent edge per vertex. The source has distance=0 and parent_edge=-1; an unreachable vertex has distance=null and parent_edge=-1. For every other vertex, parent_edge identifies an incoming edge on a shortest path from the source. Any shortest path is accepted when costs tie, including either optimal parallel edge ID. Use null for unreachable distance: -1 can be a valid negative shortest distance. An edge ID is not a predecessor vertex number.

Example: n=5, source=0, edges=[[0,1,3],[0,2,8],[1,2,-7],[2,3,4]]. Return distance=[0,3,-4,0,null] and parent_edge=[-1,0,2,3,-1]. The route to vertex 3 is 0→1→2→3, with total cost 0.

Add a helper that reconstructs the vertex sequence of a route from parent_edge. Call the helper in your own tests for a reachable vertex, the source and an unreachable vertex, and record the results in your analysis. A reachable route is in source-to-target order; the source route is [source]; document the no-route result for an unreachable target. Follow the actual parent edge IDs, including parallel edges. The helper is part of your implementation, not an extra JSON task. Parallel edges are permitted; a self-loop makes the graph cyclic.

Required complexity: O(n+m) time and memory; O(route length) time and output space for route reconstruction.

9. Testing and analysis

After pushing changes, open **Actions → Public checks** in your repository. The supplied workflow compiles or launches the selected implementation and runs the public algorithm tests. The submitted commit must have a successful Public checks run. Optional local commands are documented in TESTING.md.

Add your own cases to tests/student/, recording the input, expected result and actual result. Cover the applicable cases: empty and disconnected graphs, isolated vertices, repeated edges or operations, self-loops, negative weights, cycles, unreachable vertices and deep DFS traversal.

Complete ANALYSIS.md in English. For each of the six algorithms, provide 3-5 sentences explaining its main steps, state or invariant, relevant edge cases, and time and memory complexity. Explain how state is reset and how deep DFS traversal is handled.

Compare Kruskal and Prim on the same graphs at three input sizes. Record n and m, reproducible input generation, commands or Actions links, at least three timing measurements per algorithm at each size, and median times. Record the same hardware/runner, runtime version and timing boundary for both methods. Exclude compilation from algorithm timing. State whether graph construction, parsing, I/O and warm-up are included or excluded, and apply the same choice to both methods. Check correctness before measuring. Verify equal minimum costs and valid forests, then explain the observed performance. A few timing measurements illustrate practical behaviour; they do not prove an asymptotic bound. Include the route reconstruction examples and acknowledge sources and assistance according to the syllabus.

After the deadline, the instructor will run additional tests on the submitted commit and review the required implementations and analysis.

10. Assessment and course policies

Practical work is worth 50 points and the individual quiz is worth 50 points; together they form Assignment 3 out of 100. Assignment 3 retains its 20% contribution to the second attestation. The practical score is 50 automatic points; the 18 groups in RUBRIC.md retain their original weights and are summed directly. There is no manual component, 0.8 scaling, oral defence or oral score recovery. Methods/helper, English analysis, own tests and benchmark remain required learning deliverables without separate manual points or discretionary deductions. A faulty test or question/key is corrected consistently for all affected work, using the original submission/attempt. Standard collections, sorting and priority queues are allowed; replacing a required algorithm with a library implementation does not demonstrate the required method.

The syllabus permits AI assistance for brainstorming, debugging and code suggestions with explicit written acknowledgement. In ANALYSIS.md identify tools/resources, their contribution and your verification. You remain responsible for correctness, originality and quality. The syllabus treats submission of AI-generated work without modification or acknowledgement as plagiarism. The instructor may ask you to explain submitted work; code style alone is not evidence of misconduct.

Submit through Moodle by the dates shown there, including any approved individual extension. Under the syllabus, late work is not graded except where an extension has been approved for documented valid reasons. Requests for extensions should be made before the deadline. Moodle contains the applicable dates and organisational instructions; this document does not change them.

11. Submission

Submit two links in Moodle's **Online text** field:

1. The GitHub commit containing the completed implementations, analysis and student tests. Open that commit and copy its URL.

2. The successful **Public checks** run for the same commit. Open the run in Actions and copy its URL.

Complete submission using **Submit assignment**. The commit linked in Moodle is the version assessed. Before the deadline, any replacement submission must include both updated links. A private repository must remain accessible to the instructor.

12. Reading and clarifications

Week 6 covers DSU and MST; week 7 covers SCC, topological ordering and DAG shortest paths. Relevant reading: CLRS 4e §§19.3-19.4, 20.3-20.5, 21.1-21.2, 22.2; Sedgewick & Wayne 4e §§1.5, 4.2-4.4; Skiena 3e §§7.10, 8.1 and 8.3 (general shortest paths). These support correctness, complexity and empirical analysis. The required methods remain the six listed above.

Read Lecture_Clarifications_EN_RU.pdf: lecture 6 slide 9 has an incorrect equality in Kruskal; lecture 7 slide 14 uses a generic unreachable sentinel that is not the A3 JSON contract. The original lecture files have not been replaced.