Solving PDE

Rauan

September 19, 2024

Abstract

Contents

1 Problem statement 2

1 Problem statement

Let

$$\mathbf{v}(x, y, t) = (u(x, y, t), v(x, y, t))$$

and onsider non-dimensionalized incompressible Navier-Stokes system of equations

Momentum:
$$\frac{\partial \mathbf{v}}{\partial t} + \mathbf{v} \cdot \nabla \mathbf{v} = -\nabla p + \epsilon \nabla \cdot \nabla \mathbf{v},$$
 (1.1a)
$$\epsilon = \frac{1}{\mathbf{R} \mathbf{o}}, 0 \le x \le 1, 0 \le y \le 1, t \ge 0.$$

Continuity:
$$\nabla \cdot \boldsymbol{v} = 0$$
, (1.1b)

0 < x < 1, 0 < y < 1, t > 0.

Inlet:
$$\mathbf{v}(t,0,y) = \mathbf{v}(t,x,1) = (1 + A\cos(kx - \omega t + \phi_0), v),$$
 (1.1c)
 $\{A < 1, k, \omega, \phi_0\} \subset \mathbb{R}.$

No-slip wall BC:
$$v(t, x, 0) = (0, 0)$$
. (1.1d)

Outlet and freestream BC: Artificial boundary conditions.

Initial condition:
$$\mathbf{v}(0, x, y) = (1, 0)$$
. (1.1f)

We are to determine appropriate boundary conditions for top side of the domain. Taking derivative of BC (1.1c) w.r.t x

$$\frac{\partial u}{\partial x} = -kA\sin\left(kx - \omega t + \phi_0\right),\tag{1.2}$$

(1.1e)

and making use of continuity Eq. (1.1b) leads to

$$\frac{\partial v}{\partial y} = kA\sin\left(kx - \omega t + \phi_0\right). \tag{1.3}$$

We can integrate Eq. (1.3) over dy to obtain general expression for vertical velocity component

$$v(x, y, t) = ykA\sin(kx - \omega t + \phi_0) + g(x, t). \tag{1.4}$$

In case of g(x,t)=0, plugging Eq. (1.4) together with BC (1.1c) into Eq. (1.1a) leads to

$$\frac{\partial p}{\partial x} = 0 \tag{1.5}$$

for x-momentum. If we now take $\frac{\partial}{\partial y}$ of Eq. (1.5) and plug into $\frac{\partial}{\partial x}$ of y-momentum we will obtain

$$\frac{A k^{4} y \cos(kx + \omega t + \phi_{0})}{\text{Re}} - A k^{2} \omega y \sin(kx + \omega t + \phi_{0})
-A k^{3} y \sin(kx + \omega t + \phi_{0}) (A \cos(kx + \omega t + \phi_{0}) + 1)
+A^{2} k^{3} y \cos(kx + \omega t + \phi_{0}) \sin(kx + \omega t + \phi_{0}) = 0,$$
(1.6)

which is obviously not always true for all A, k, ω . Therefore $g(x, t) \neq 0 \quad \forall x, t$.

Keeping g(x,t) term and repeating the above process leads to third order PDE

$$\left(\frac{\partial^{2}}{\partial x^{2}}g(x,t) - Ak^{3}y\sin(kx + \omega t + \phi_{0})\right) (A\cos(kx + \omega t + \phi_{0}) + 1)$$

$$-\frac{1}{\text{Re}}\left(\frac{\partial^{3}}{\partial x^{3}}g(x,t) - Ak^{4}y\cos(kx + \omega t + \phi_{0})\right)$$

$$+\frac{\partial}{\partial x}\frac{\partial}{\partial t}g(x,t) + Ak^{2}\cos(kx + \omega t + \phi_{0})\left(g(x,t) + Aky\sin(kx + \omega t + \phi_{0})\right)$$

$$-Ak^{2}wy\sin(kx + \omega t + \phi_{0}) = 0.$$
(1.7)

We now need to determine boundary conditions for Eq. (1.7). It is known that at the left boundary v(0, y, t) = 0. Then Eq. (1.4) at y=1 gives

$$g(x=0,t) = -kA\sin\left(-\omega t + \phi_0\right). \tag{1.8}$$

Outlet BC (1.1e) $\frac{\partial v}{\partial x}=0$ at x=1,y=1 with Eq. (1.4) leads to

$$\frac{\partial}{\partial x}g(x=1,t) = -k^2A\cos\left(k - \omega t + \phi_0\right). \tag{1.9}$$

Initial condition at t=0 we assumed (Eq. (1.1f)) to be v(x,y=1,t=0)=0, then Eq. (1.4) provides us

$$g(x, t = 0) = -kA\sin(kx + \phi_0). \tag{1.10}$$