

- NOTES:
1. SCHEDULE PARSED VERBATIM FROM spec/00 §9 – THE FROZEN AUTHORITY.
 2. CERAMIC JOINT RULE: CERAMIC IN COMPRESSION ONLY; NO THREADS IN CERAMIC (spec/00 §9).
 3. BELLEVILLE SELECTION PER spec/00 §9; RF HARDWARE SILVER-PLATED PER SEWCP-903.
 4. ALIGNMENT LOCATORS ARE THEIR OWN FASTENER – 1.2 N·m (ECR-D-009, spec/06).

FASTENER SCHEDULE (spec/00 §9)

JOINT / FASTENER	QTY	GRADE	NOTES
M6 × 40 SHCS – Lower circuit: Base Plate ↔ Support Ring bottom fla	8	A4-70	torque 6.0 N·m; Ø16 flat + Belleville stack
M6 × 16 SHCS – Upper circuit: Support Ring top flange ↔ Cooling Pl	8	A4-70	torque 6.0 N·m; Ø16 flat + Belleville stack
M5 × 25 SHCS – Cooling Plate ↔ Heater Plate (outer choke)	12	A4-70	torque 3.5 N·m; Ti washer + Belleville
M5 × 25 SHCS – Cooling Plate ↔ Heater Plate (inner choke)	4	A4-70	torque 3.5 N·m; Ti washer + Belleville
M4 × 16 SHCS – Vacuum Port flange	4	A4-70	torque 1.8 N·m; Flat
M6 × 16 SHCS – RF strap to Cooling Plate land	2	A4-70, silve	torque 6.0 N·m; Silver-plated flat + Belleville
M6 × 20 SHCS – RF bracket clamp to Base Plate	2	A4-70	torque 6.0 N·m; Flat
M4 × 12 SHCS – Temp sensor bracket	4	A4-70	torque 1.8 N·m; Flat

TITLE	NUMBER	REV
SEWCP MASTER ASSEMBLY – Fastener and SEWCP-903-01 Sh 3	SEWCP-903-01	A
MATERIAL	FINISH	SCALE
–	–	1:3 / 1:1.1
UNITS	DATE	ORIGIN
mm	2026-08-11	AIEF autonomous run