

- NOTES:
1. INTERPRET PER ASME Y14.5-2018. UNITS mm. UNLESS NOTED: X.X $\pm$ 0.2, X.XX $\pm$ 0.05.
 2. BREAK ALL EDGES 0.2-0.4 UNLESS NOTED. NO BURRS.
 3. VENT ALL BLIND HOLES IN VACUUM-EXPOSED PARTS PER DR-6 (spec/00).
 4. PROVENANCE: EVERY DIMENSION TRACES PER THE SIDECAR PROVENANCE FILE OF THIS DRAWING (AIEF).
 5. 0.50 C10100 OFHC STRIP; SILVER 8-13 μ m DIRECTLY ON COPPER - NO NICKEL (RS-D08/09, DR-7).
 6. FORM ON R20 MANDREL; ANNEAL; FLATTEN PADS 0.05 TIR; 4-WIRE $\leq$ 3 mΩ.
 7. HOLES COINCIDENT WITH CP-IF-8 TAPS: 29.94 CTRS AT PAD STATION 9.82 FROM END (ECR-D-013 DISPOSITION A, DEC-01).
 8. SEWCP-904 DEPOSITION SHROUD: NO DIMENSIONAL AUTHORITY IN spec/08 - CARRIED (NOT DRAWN).

