



# Kubernetes Networking



CLARUSWAY®  
WAY TO REINVENT YOURSELF

Students, write your response!

Pear Deck Interactive Slide  
Do not remove this bar



## Table of Contents

- ▶ Cluster Networking
- ▶ Services
- ▶ Service Types
- ▶ Labels and loose coupling



1

# Cluster Networking



## Cluster Networking


There are 4 distinct networking problems to address:

1. container-to-container communications:  
This is solved by Pods and localhost communications via loopback.
2. Pod-to-Pod communications:  
Each Kubernetes Pod gets its own IP address.
3. Pod-to-Service communications: this is covered by services.
4. External-to-Service communications: this is covered by services.




2

## Services



## Services


Each Kubernetes Pod gets its own IP address. But Kubernetes **Pods** are mortal. They are born and when they die, they are not resurrected. If you use a Deployment to run your app, it can create and destroy Pods dynamically. So, Pod IPs are unreliable.





## Services

A **Service** offers a single **DNS entry** for a containerized application managed by the Kubernetes cluster, regardless of the number of replicas, by providing a common **load balancing** access point to a set of pods logically grouped and managed by a **controller** such as a Deployment, ReplicaSet, or DaemonSet.



CLARUS

WAY TO REINVENT YOURSELF

7




## Services

The **Service** is associated with the Pods, and provides them with a stable IP, DNS and port. It also **loadbalances** requests across the Pods.

**Service** logically groups Pods and defines a policy to access them.


This grouping is achieved via **Labels** and **Selectors**.



CLARUS

WAY TO REINVENT YOURSELF


8



## CLARUS K8s Network

WAY TO REINVENT YOURSELF

9




## K8s Network

CLARUSWAY©

WAY TO REINVENT YOURSELF

10

## K8s Cluster




## Services

### Kubernetes Service

A service allows you to dynamically access a group of replica pods.

Kubernetes **Services** enable communication between various components **within** and **outside** of the application. Kubernetes Services helps us connect applications together with other applications or users.





## ► kube-proxy

- Each cluster node runs a daemon called **kube-proxy**, that watches the API server on the master node for the addition, updates, and removal of Services and endpoints.
- **kube-proxy** is responsible for *implementing the Service configuration* on behalf of an administrator or developer, in order to enable traffic **routing** to an exposed application running in Pods.
- For each new Service, on each node, **kube-proxy** configures **iptables** rules to capture the traffic for its **ClusterIP** and forwards it to one of the Service's endpoints.
- Therefore any node can receive the external traffic and then route it internally in the cluster based on the **iptables** rules.
- When the Service is removed, **kube-proxy** removes the corresponding **iptables** rules on all nodes as well.




## ► Service Discovery

- Kubernetes has an add-on for **DNS**, which creates a DNS record for each Service and its format is **web-svc.my-namespace.svc.cluster.local**.
- Services within the same Namespace find other Services just by their names.
- If we add a Service **redis-master** in **my-ns** Namespace, all Pods in the same **my-ns** Namespace lookup the Service just by its name, **redis-master**.




# Service Discovery


- Pods from other Namespaces, such as **test-ns**, lookup the same Service by adding the respective Namespace as a suffix, such as **redis-master.my-ns** or providing the **FQDN** of the service as **redis-master.my-ns.svc.cluster.local**.



## my-ns



## test-ns



To connect to the "db pod":

From "web pod" -> hostname: redis-master:port

From "log pod" -> hostname: redis-master.my-ns:port

From "log pod" -> hostname: redis-master.my-ns.svc.cluster.local:port





3


## Service Types



## Service Types


There are 4 major service types:

- ClusterIP (default)
- NodePort
- LoadBalancer
- ExternalName





## Service Types



### ClusterIP:

Exposes the Service on a cluster-internal IP. Choosing this value makes the Service only reachable from within the cluster. This is the default ServiceType.


Good for service of database & back-end apps.



## Service Types

**NodePort:** Exposes the Service on each Node's IP at a static port (the NodePort). A ClusterIP Service, to which the NodePort Service **routes**, is automatically created. Port can either be **statically** defined, or **dynamically** taken from a range between 30000-32767.

With the **NodePort** ServiceType, in addition to a ClusterIP, a high-port is mapped to the respective Service, from all the worker nodes.






# Service Types


## NodePort:

The **NodePort** *ServiceType* is useful when we want to make our Services accessible from the external world. The end-user connects to any worker node on the specified high-port, which proxies the request internally to the ClusterIP of the Service, then the request is forwarded to the applications running inside the cluster. Let's not forget that the Service is load balancing such requests, and only forwards the request to one of the Pods running the desired application. To manage access to multiple application Services from the external world, administrators can configure a reverse proxy - an ingress, and define rules that target specific Services within the cluster.



# Service Types

**LoadBalancer:** Exposes the Service externally using a cloud provider's load balancer. The external load balancer routes to the automatically created NodePort and ClusterIP Services.






# Service Types

## LoadBalancer:

- NodePort and ClusterIP are automatically created, and the external load balancer will route to them
- The Service is exposed at a static port on each worker node
- The Service is exposed externally using the underlying cloud provider's load balancer feature.



# Service Types

## LoadBalancer:

- The **LoadBalancer ServiceType** will only work if the underlying infrastructure supports the automatic creation of Load Balancers and have the respective support in Kubernetes, as is the case with the Google Cloud Platform and AWS.
- If no such feature is configured, the **LoadBalancer IP** address field is **not populated**, it remains in **Pending** state, but the **Service will still work as a typical NodePort type Service**.



## Service Types

**ExternalName:** Maps the Service to the contents of the externalName field (e.g. example.com), by returning a CNAME record with its value.

```
apiVersion: v1
kind: Service
metadata:
  name: example-prod
spec:
  type: ExternalName
spec:
  externalName: example.com
```



## Service Types

**ExternalName** is a special *ServiceType*, that has no Selectors and does not define any endpoints.


When accessed within the cluster, it returns a **CNAME** record of an externally configured Service.

The primary use case of this *ServiceType* is to make externally configured Services like **my-database.example.com** available to applications inside the cluster.


If the externally defined Service resides within the same Namespace, using just the name **my-database** would make it available to other applications and Services within that same Namespace.

```
kind: Service
apiVersion: v1
metadata:
  name: service-python
spec:
  ports:
    - port: 3000
      protocol: TCP
      targetPort: 443
  type: ExternalName
  externalName: remote.server.url.com
```

Now **pod-nginx** can simply connect to `http://service-python:3000`, just like with a ClusterIP service.



## Service Types





4

## Labels and loose coupling

## ► Labels and loose coupling




- Labels and Selectors use a **key/value** pair format.
- Pods and Services are loosely coupled via labels and label selectors.
- For a Service to match a set of Pods, and therefore provide stable networking and load-balance, it only needs to match some of the Pods labels.
- However, for a Pod to match a Service, the Pod must match all of the values in the Service's label selector.




## Labels and loose coupling

The figure below shows an example where 3 Pods are labeled as **zone=prod** and **version=1**, and the Service has a label selector that matches. This Service provides stable networking to all three Pods. It also provides simple load-balancing.



## Labels and loose coupling

The figure below shows an example where the Service does not match any of the Pods. This is because the Service is selecting on two labels, but the Pods only have one of them. The logic behind this is a Boolean AND operation.








## ► Labels and loose coupling

This figure shows an example that does work. It doesn't matter that the Pods have additional labels that the Service is not selecting on.




5

## Kubernetes hands-on-03




## Pod to Pod Connection

**db** pod can connect to **web** pod directly, if only it knows the IP and port number of the **web** pod.




## ClusterIP






## ClusterIP



```
apiVersion: v1
kind: Service
metadata:
  name: web-flask-svc
  labels:
    app: web-flask
spec:
  type: ClusterIP
  ports:
    - port: 3000
      targetPort: 5000
  selector:
    app: web-flask
```

## NodePort




```
apiVersion: v1
kind: Service
metadata:
  name: web-flask-svc
  labels:
    app: web-flask
spec:
  ports:
    - port: 3000
      protocol: TCP
      targetPort: 5000
      nodePort: 30480
  selector:
    app: web-flask
  type: NodePort
```



# Endpoint

loadbalances



CLARUSWAY©  
WAY TO REINVENT YOURSELF

**Endpoints** are created and managed automatically by the **Service**, not by the Kubernetes cluster administrator.



# THANKS!

## Any questions?

You can find me at:

- [joe@clarusway.com](mailto:joe@clarusway.com)



CLARUSWAY©  
Students, write your response!

Pear Deck Interactive Slide  
Do not remove this bar

4  
0