



THE CHEMICAL FACTORY

Built to Dominate

Chem 2k Shield

Two-component elastomeric cementitious waterproof coating for concrete and masonry surfaces



FAST
DRYING



EXCELENT
ADHESION



CORROSION
RESISTANT



EASY
APPLICATION



DESCRIPTION

CHEM 2K SHIELD is a two-component elastomeric cementitious waterproof coating composed of a cementitious powder and a specially formulated acrylic polymer liquid. When combined, the components form a flexible, durable and strongly adherent waterproof barrier for concrete and masonry substrates, suitable for above- and below-ground applications.

- ✓ Resists water penetration and helps protect concrete structures.
- ✓ Practical two-component system for efficient site application.
- ✓ Water-vapour permeable while providing waterproof protection.
- ✓ Suitable for brush, roller or spray application.
- ✓ Strong adhesion to sound concrete and masonry substrates.



RECOMMENDE USES

- Basement tanking and below-ground structures
- Water reservoirs and water-retaining structures
- Tunnels and underground construction
- Swimming pools and water-retaining areas
- Long Lasting Protection



SERVICES



Admixtures



Surface Treatment



Concrete Repair



Water Proofings



Industrial Flooring System



Grouts & Anchors



Adhesives



Joint Sealants



Bitumin Products



Miscellaneous



STRONG
WATERPROOFING



FAST & EFFECTIVE
INJECTION



LONG LASTING
PROTECTION



Office #1, building 99-c, jami commercial
street no 11, phase 7, DHA Karachi.



+92 21 35885870



www.thechemicalfactory.com



info@dechemicalfactory.com





TECHNICAL DATA

Property	Value
Appearance / Components	Cementitious powder + acrylic polymer liquid
Colour	Grey and white
Wet Density	Approx. 1800 kg/m ³
Compressive Strength	55.0 N/mm ²
Tensile Strength ↑	3.7 N/mm ²
Flexural Strength ↑	7.6 N/mm ²
Adhesive Strength ↑	2.5 N/mm ²
Water Vapour Permeability	86–120
Maximum Particle Size	0.8 mm
Pot Life at 20°C	Approx. 1 hour
Pot Life at 40°C	Approx. 30 minutes
Packing	16 kg double-pack consisting of 11 kg cementitious powder and 5 kg liquid polymer solution.



CONSUMPTION

Coverage:

Approximately 150–200 sq.ft. per 16 kg pack. Actual coverage varies with substrate roughness, porosity, surface condition and application technique.

Guidance:

Clean mixing and application equipment immediately after use with clean water. Once the material has hardened, removal becomes more difficult.



STANDARDS

- Colour: Grey And White
- Density: Approx. 1800 kg/m³



IMPORTANT INFORMATION

Supplied in: 16 kg Box

Storage: Storage Condition Cool, covered and dry place; protect from direct sunlight and heat

Self Life: 1 year

Hazard Class: Non-hazardous goods.



APPLICATION GUIDELINES



DISPENSING

CHEM 2K SHIELD should be applied only to properly prepared, sound substrates. The following procedure is intended as general application guidance; site conditions and project specifications should be considered before application.



MIXING

CHEM 2K SHIELD is supplied in pre-measured components and should be mixed on site using clean containers. For mechanical mixing, gradually blend the powder component into the liquid while mixing with a suitable paddle at low speed (approximately 400–600 rpm).



USES

The substrate must be clean, structurally sound and mechanically prepared. Remove surface coatings, defective renders, foreign matter, formwork treatments and other contaminants that could interfere with adhesion. Abrasive blasting or high-pressure water treatment may be used as appropriate. After preparation, wash the surface with clean water to remove dust and loose material.



APPLICATION

Pre-dampen the prepared substrate before application. High-suction substrates may require additional dampening compared with dense substrates.



STORAGE & HANDLING

Store under cover and clear of the ground. Keep the material dry and protect both components from moisture and frost. Do not stack more than six bags high. Keep packaging closed until required for use.



SAFETY

Wear suitable protective gloves, clothing and eye protection during mixing and application. Avoid unnecessary contact with skin and eyes. Provide adequate ventilation during application, particularly in enclosed areas. Read and follow the product Safety Data Sheet (SDS) before use.



ENHANCED
DURABILITY



FASTER
PLACEMENT



BETTER FINISH
& PERFORMANCE

The information above reflects The Chemical Factory's current knowledge and is provided to assist specifiers and contractors. It does not replace project-specific trials to confirm suitability. Data are typical values under standard conditions; on-site results may vary. Recommendations are offered in good faith without warranty, as factors beyond our control can affect performance. The Chemical Factory may revise specifications without prior notice. Users are responsible for compliance with applicable standards and regulations. Technical assistance is available on request.



Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.



+92 21 35885870



www.thechemicalfactory.com



info@dechemicalfactory.com