



THE CHEMICAL FACTORY

— Built to Dominate —

Chem PU Elasto Pro

Pure polyurethane, liquid-applied roof waterproofing membrane with Superior Elastic and Durability



FAST DRYING



EXCELLENT
ADHESION



CORROSION
RESISTANT



EASY
APPLICATION



DESCRIPTION

CHEM PU ELASTO PRO is a high performance, single-component, cold-applied, moisture-triggered aliphatic-aromatic polyurethane liquid waterproofing membrane. It forms seamless, elastic and durable coating that provides Long-term protection to concrete and metal surfaces. Designed for superior flexibility, weather resistance and chemical stability, it is ideal for both new and existing structure.

- ✓ Waterproofing for roofs, terraces and podiums.
- ✓ Protection for concrete and metal surface.
- ✓ Ideal for new construction and refurbishment projects.
- ✓ Suitable for residential, commercial and industrial building.
- ✓ long-lasting protection against harsh weather condition and UV exposure.



RECOMMENDED USES

- Exposed and non-exposed flat roof waterproofing.
- Pitched roof and roof-deck waterproofing.
- Protective waterproofing layer beneath compatible subsequent finishes.
- Waterproofing of concrete and cementitious substrates.
- Concrete surface before coating.



SERVICES



Admixtures



Surface Treatment



Concrete Repair



Water Proofings



Industrial Flooring System



Grouts & Anchors



Adhesives



Joint Sealants



Bitumin Products



Miscellaneous



STRONG
WATERPROOFING



FAST & EFFECTIVE
INJECTION



LONG LASTING
PROTECTION



Office #1, building 99-c, jami commercial
street no 11, phase 7, DHA Karachi.



+92 21 35885870



www.thechemicalfactory.com



info@dechemicalfactory.com



TECHNICAL DATA

Property	Value
Chemical Base	Two-component polyurethane (Polyurethane resin + Hardner)
Form	Liquid
Typical Appearance	Smooth coating; standard colour as supplied
Density	Approx. 1.35 kg/L
Solids Content	Approx. 95% by weight
Flash Point	Flash Point Approx. 80 °C (closed-cup method)
Crack Bridging	Up to 3 mm, no cracking reported (ASTM C836)*
Elongation at Break	Approx. 700% (ASTM D412)*
Tear Strength	Approx. 16.5 N/mm (ASTM D624)*
Tensile Strength	Approx. 6 N/mm ² (ASTM D412)*
Pull-Off Adhesion	< 2 N/mm ² (ASTM D4541)*
VOC	< 250 g/L (ASTM D2369)*

* Performance varies with substrate, film build, temperature and application method.



APPLICATION GUIDELINES



DISPENSING

Use Brush or roller for even application.



MIXING

Adheres to various substance including concrete, cementitious substrates and bitumen sheets.



USES

Waterproofing Membrane on exposed flat and pitched roofs both for new construction and refurbishment of old roofs.



APPLICATION

Ensure surface and clean, dry and free from dust oil or loose particles. Apply in 2-3 coats for best performance.



STORAGE & HANDLING

Store in a cool, dry and well-ventilated area, away from direct sunlight and heat sources. Keep the product in its original, tightly closed container until ready for use.



SAFETY

Use gloves, goggles and protective clothing. Avoid skin and eye contact.



CONSUMPTION

Coverage:

Approximately 1.5–2.0 kg/m² per mm of thickness, depending on surface condition, porosity and application method.

Guidance:

Clean all tools and application equipments with Thinner C immediately after use. Hardened and/or cured material can only be removed mechanically.



STANDARDS

- Solid Content: ~95% by weight (+23°C/50%r.h.
- Flash Point: 80 °C (Closed cup method)
- Density: ~2.0 kg/L



IMPORTANT INFORMATION

Supplied in: 20 Kg Bucket

Storage: Store dry, frost-free, out of direct sunlight

Self Life: 1 years in original packaging

Hazard Class: Non-hazardous goods.



ENHANCED
DURABILITY



FASTER
PLACEMENT



BETTER FINISH
& PERFORMANCE

The information above reflects The Chemical Factory's current knowledge and is provided to assist specifiers and contractors. It does not replace project-specific trials to confirm suitability. Data are typical values under standard conditions; on-site results may vary. Recommendations are offered in good faith without warranty, as factors beyond our control can affect performance. The Chemical Factory may revise specifications without prior notice. Users are responsible for compliance with applicable standards and regulations. Technical assistance is available on request.



Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.



+92 21 35885870



www.thechemicalfactory.com



info@dechemicalfactory.com