THE CHEMICAL FACTORY

*Built to Dominate*

# Chem 2k Sheild Pro

## Two-Component Flexible Elastomeric Cementitious Waterproof Coating



FAST DRYING | EXCELLENT ADHESION | CORROSION RESISTANT | EASY APPLICATION

## DESCRIPTION

CHEM 2K SHIELD PRO is a two-component elastomeric cementitious waterproofing system comprising a cement-based powder and a specially formulated acrylic polymer liquid. When mixed together, the components form a flexible, durable and strongly adherent waterproof barrier for prepared concrete and masonry surfaces. The system is suitable for above- and below-ground waterproofing applications.

- Resists positive water pressure and helps control water ingress.
- Two-component system designed for efficient site application.
- Water-vapour permeable, allowing moisture vapour to pass through the coating.
- Flexible cured coating accommodates normal substrate movement.
- Solvent-free formulation.

## RECOMMENDE USES

- Basement tanking and below-ground structures.
- Water reservoirs and water-retaining structures.
- Tunnels and underground construction.
- Swimming pools and water-retaining areas.
- Fish ponds and tanks.



## SERVICES

- Admixtures
- Surface Treatment
- Concrete Repair
- Water Proofings
- Industrial Flooring System
- Grouts & Anchors
- Adhesives
- Joint Sealants
- Bitumin Products
- Miscellaneous

STRONG WATERPROOFING | FAST & EFFECTIVE INJECTION | LONG LASTING PROTECTION

Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.

+92 21 35885870

www.thechemicalfactory.com

info@dechemicalfactory.com

## TECHNICAL DATA

| Property | Value |
|---|---|
| Property | Typical Value |
| Form / Components | Cementitious powder + acrylic polymer liquid |
| Colour | Grey and white |
| Wet Density | Approx. 1800 kg/m³ |
| Compressive Strength | 55.0 N/mm² |
| Tensile Strength | 3.7 N/mm² |
| Flexural Strength | 7.6 N/mm² |
| Adhesive Strength | 2.5 N/mm² |
| Water Vapour Permeability | 86–120 |
| Maximum Particle Size | 0.8 mm |
| Pot Life at 20°C | Approx. 1 hour |
| Pot Life at 40°C | Approx. 30 minutes |
| Packaging | 20 kg double-pack: 15 kg powder + 5 kg liquid. |

## CONSUMPTION

**Coverage:** Indicative coverage is approximately 150–200 sq.ft. per 20 kg pack, depending on substrate texture, porosity and application method.

**Guidence:** Actual consumption may vary with surface condition and application technique.

## STANDARDS

- Colour: Grey and white
- Density: Approx. 1800 kg/m³

## IMPORTANT INFORMATION

**Supplied in:** 20 Kg Box

**Storage:** Storage Condition Cool, covered and dry place; protect from direct sunlight and heat

**Self Life:** 1 years

**Hazard Class:** Non-hazardous goods.

## APPLICATION GUIDELINES

### DISPENSING

The substrate should be structurally sound, clean and free from dust, oil, loose material and other contaminants. Mechanically prepare the surface where required and remove standing water before application. Pre-dampen the prepared substrate.

### MIXING

Gradually add the powder component into the polymer liquid while mixing at low speed with a suitable paddle mixer until a uniform, l ump-free consistency is achieved. Allow approximately 10 minutes maturation before application. Do not re-temper the mix.

### USES

Protect the applied coating from premature drying. Where practical, fog-spray with clean water after initial set. Longer curing may be required under cold or humid conditions.

### APPLICATION

Pre-dampen the prepared substrate before application. Apply the first coat at approximately 1.0 kg/m² minimum.
Allow the first coat to a dequately cure before applying the second coat.
Apply the second coat at approximately 1.0 kg/m² minimum.

### STORAGE & HANDLING

Keep both components sealed until use. Store under cover, clear of the ground and protected from moisture, frost, excessive heat and direct sunlight. Shelf life is 12 months in original unopened packaging when stored as recommended.

### SAFETY

Wear suitable gloves, protective clothing and eye protection during handling and application. Avoid unnecessary skin and eye contact. Provide adequate ventilation and consult the Safety Data Sheet (SDS) before use.



ENHANCED DURABILITY

FASTER PLACEMENT

BETTER FINISH & PERFORMANCE

The information above reflects The Chemical Factory's current knowledge and is provided to assist specifiers and contractors.
It does not replace project-specific trials to confirm suitability. Data are typical values under standard conditions; on-site results may vary.
Recommendations are offered in good faith without warranty, as factors beyond our control can affect performance. The Chemical Factory may revise specifications without prior notice. Users are responsible for compliance with applicable standards and regulations.
Technical assistance is available on request.



Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.

+92 21 35885870

www.thechemicalfactory.com

info@ dechemicalfactory.com