THE CHEMICAL FACTORY

Built to Dominate

Chem Styro Bond Pro

Advanced Styrene-Butadiene Rubber (SBR) Latex. Cementitious Bonding & Modification



FAST BONDING | **STRONG ADHESION** | **WATER RESISTANCE** | **EASY MIXING**

DESCRIPTION

CHEM SBR PRO is a premium Styrene-Butadiene Rubber (SBR) latex emulsion designed to modify cement-based construction materials. This product improves bonding, flexural, and tensile performance for cementitious mortars, screeds, renders, and waterproofing systems. CHEM SBR PRO is ideal for repair and refurbishment projects that require enhanced adhesion, reduced water permeability, and resistance to service movement.

- Advanced SBR polymer modification for cementitious construction systems.
- Enhances flexural performance and flexibility of modified mortar systems.
- Improves tensile strength of suitable cement-based formulations.
- Reduces water permeability in appropriately formulated cementitious systems.
- Non-corrosive to steel.

RECOMMENDE USES

- High-strength floor screeds.
- Patching and repair mortars.
- Thin-section screeds.
- Waterproofing of cementitious surfaces.
- Patching and general repair mortars.



SERVICES

- Admixtures
- Surface Treatment
- Concrete Repair
- Water Proofings
- Industrial Flooring System
- Grouts & Anchors
- Adhesives ✓
- Joint Sealants
- Bitumin Products
- Miscellaneous

STRONG WATERPROOFING | **FAST & EFFECTIVE INJECTION** | **LONG LASTING PROTECTION**

Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.

+92 21 35885870

www.thechemicalfactory.com

info@dechemicalfactory.com

TECHNICAL DATA

Property	Value
Product Type	Styrene-Butadiene Rubber (SBR) latex emulsion
Appearance / Form	Liquid
Colour	White
Solids Content	50% ± 2%
Density	Approx. 1.01 kg/L
Minimum Application Temperature	+5 °C
Flexural Strength	Approx. 30–40% improvement compared with unmodified mortar
Tensile Strength	Approx. 20–30% improvement
Abrasion Resistance	Up to 2005*
Bonding Grout	5M/L*

* The abrasion-resistance and bonding-grout statistics shown above are taken from the given reference material. The reference does not specify the test method or units for these two items, so they should be confirmed against the approved CHEM SBR PRO laboratory specification before inclusion in project specifications or certificates.

CONSUMPTION

Coverage: 1 to 1.5 square meters per liter for a standard 1 mm to 2 mm slurry coat or bonding slurry

Guidence: The most widely used general-purpose synthetic elastomer, composed typically of 75% butadiene and 25% styrene.

STANDARDS

- Solid Content: 50% ± 1%
- Hardness: Approx. 4 Shore A
- Density: Approx. 1.01 kg/L

IMPORTANT INFORMATION

Supplied in: Bucket

Storage: Storage Condition Cool, covered and dry place; protect from direct sunlight and heat

Self Life: 6 Month

Hazard Class: Non-hazardous goods.

APPLICATION GUIDELINES

DISPENSING

CHEM STYRO BOND PRO (SBR) dispensing is the application or metering of liquid SBR latex or SBR-based adhesives, sealants, and modified cement binders in manufacturing and building operations.

MIXING

CHEM STYRO BOND PRO should be incorporated into cementitious mixes according to the approved formulation for the intended application. It should not be used as a standalone bonding grout without cement.

USES

Apply The SBR/Cement bonding grout to the prepared substrate. Do not allow the bonding coat to dry before subsequent layers.

APPLICATION

Styrene-Butadiene Rubber (SBR) is a versatile synthetic elastomer that is widely used in automotive, construction, and industrial manufacture because of its good abrasion resistance, high tensile strength, and low cost.

STORAGE & HANDLING

Chem Styro Bond Pro in its originalsealed container. Protect from extreme temperatures, contamination and adverse weather exposure.

SAFETY

Avoid unnecessary skin/eye contact. Provide ventilation where required and refer to the current SDS for detailed safety information.



ENHANCED DURABILITY

FASTER PLACEMENT

BETTER FINISH & PERFORMANCE

The information above reflects The Chemical Factory's current knowledge and is provided to assist specifiers and contractors.
It does not replace project-specific trials to confirm suitability. Data are typical values under standard conditions; on-site results may vary.
Recommendations are offered in good faith without warranty, as factors beyond our control can affect performance. The Chemical Factory may revise specifications without prior notice. Users are responsible for compliance with applicable standards and regulations.
Technical assistance is available on request.



Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.

+92 21 35885870

www.thechemicalfactory.com

info@dechemicalfactory.com