THE CHEMICAL FACTORY

Built to Dominate

Chem PVC Water Block

Adaptable PVC Water Block for Construction Joints



PREVENT WATER LEAKAGE | **HIGH STRENGTH** | **EXCELLENT BOND** | **DURABLE FINISH**

DESCRIPTION

Chem PVC Water Block are high grade PVC extrusion formulated to meet the highest performance specifications. Chem PVC Water Block are supplied as straight lengths along with factory fabricated junction pieces to simply layouts and site jointing.

- Unique design
- Full range of profiles
- Easy jointing system
- Continuous 4 valve network
- Complete selection of pre-manufactured junctions
- Strengthened edge flange featuring brass grommets in internal areas for reliable attachment.

RECOMMENDE USES

- Water Retaining:

  Tanks, reservoirs and sewerage plants, swimming pools,
  Elevated water towers, Oil storage tank bond walls, Culverts, Canals and dams.

- Water Excluding:

  Basements, Underground car parks, Buried storage tanks, Retaining walls,
  Tunnels and subways.



SERVICES

- Admixtures
- Surface Treatment
- Concrete Repair
- Water Proofings
- Industrial Flooring System
- Grouts & Anchors
- Adhesives
- Joint Sealants
- Bitumin Products
- Miscellaneous

SUPERIOR WATERPROOFING | **LONG LASTING DURABILITY** | **ENHANCED SURFACE PROTECTION**

Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.

+92 21 35885870

www.thechemicalfactory.com

info@dechemicalfactory.com

TECHNICAL DATA

Property	Value
Property	Value
Type	PVC Water Block
Density	1.45 ± 0.15 kg/l
Chemical Base	Polyvinyl Chloride
Service Temperatures	-35°C to +55°C
Tensile Strength	10 N/mm² (DIN 53455)
	12 N/mm² (CRD-C-573, ASTM D412)
	11 N/mm² (BS2782 M320A)
Tear Strength	12 N/mm² (DIN 53507A)
Shore A Hardness	90±5 (DIN 53505)
Elongation at Break	300% (DIN 53455)
	300% (CRD-C 573, ASTM D412)
	300% (BS 2782 M320A)
Chemical Resistance	Water, seawater, sewage, road salt solution
Temporarily	Diluted inorganic alkalis, mineral acids and mineral oils
Alkali Resistance	Passed. CRD-C 572-65

CONSUMPTION

Guidence: A water stopper (or waterbar) is a flexible sealing strip embedded in concrete joints to prevent water leakage and block moisture migration.

Coverage: Supplied and calculated per running foot (RFT) or per meter to match the exact total linear span of concrete joints, expansion gaps, and perimeters

STANDARDS

- Tested in accordance with DIN 1048 Water Permeability Test.
- Complies with Water Research Council requirements for potable water contact.

IMPORTANT INFORMATION

Supplied in: 100 Rft Roll

Storage: Store in dry and cool place below 35°C

Shelf life: 1 year in original packaging

Hazard Class: Non-hazardous goods.

APPLICATION GUIDELINES

Selection

The choice of an appropriate Chem Water Block is determined by the joint type, thickness of concrete, concrete grade, placement of reinforcement, anticipated movement (expansion/shear), and the water head exposure.

Application

A Chem PVC Water Block (also called a waterstop) is a building material embedded in concrete joints to block water from leaking through gaps.

General Guide Lines

Experience indicates that following a few straightforward guidelines will lead to a positive outcome.

Curing & Protection

Proper curing of the surrounding concrete and physical protection of the embedded profile are essential for a Chem PVC Water Block to form a permanent, watertight seal.

Installation / Fixation

Installation at the heart of the concrete structures. Simple attachment of Chem PVC Water Block to reinforcement using specialized clips (5 per meter). Surface Chem PVC Water Block must be installed on the formwork surface or on the base/dry lean concrete surface.

Precautions & Limitations

Welding must occur in a well-ventilated space or with an oxygen mask on.



ENHANCED DURABILITY

FASTER PLACEMENT

BETTER FINISH & PERFORMANCE

The information above reflects The Chemical Factory's current knowledge and is provided to assist specifiers and contractors. It does not replace project-specific trials to confirm suitability. Data are typical values under standard conditions; on-site results may vary. Recommendations are offered in good faith without warranty, as factors beyond our control can affect performance. The Chemical Factory may revise specifications without prior notice. Users are responsible for compliance with applicable standards and regulations. Technical assistance is available on request.



Office #1, building 99-c, jami commercial street no 11, phase 7, DHA Karachi.

+92 21 35885870

www.thechemicalfactory.com

info@ dechemicalfactory.com