Forecasting the 2026 U.S. Holiday Retail Season

Classical, machine-learning and AI-chatbot forecasters compared - and a planning tool for small retailers

UCLA Anderson School of Management · Time Series Analysis and Forecasting · Dr. William Yu
Group project, October 2026 · Charlotte Zhu, Shihan Wang, Jing Chang, Rachel Liu
Interactive dashboard: https://holiday-retail-planner.streamlit.app
Code and data: https://github.com/RachelLiu13/holiday-retail-forecast

Contents

Executive summary . . . 2
1. Motivation and research questions . . . 2
2. Data . . . 3
3. Methodology . . . 5
4. Results . . . 6
5. The 2026 holiday forecast (Q1) . . . 10
6. The product: Holiday Retail Planner dashboard (Option B) . . . 11
7. Conclusions . . . 13
8. Limitations . . . 13
9. Use of AI tools . . . 14
References . . . 14
Appendix A. Data quality checks . . . 14
Appendix B. Example LLM prompt and both models' answers . . . 14
Appendix C. SARIMA orders selected by AIC . . . 15
Appendix D. Reproducibility . . . 15

Executive summary

November and December generate about **18% of U.S. retail sales** (22% for clothing stores), yet retailers must commit to holiday inventory in late summer. Small retailers typically plan on *'same as last year'*. Using U.S. Census monthly retail sales by category (1992 to August 2026), we tested seven statistical and machine-learning forecasters and two AI chatbots on **11 past holiday seasons**, each time forecasting from the end of August with only the data available then. We then forecast the 2026 season and built an interactive dashboard that turns the forecast into an order recommendation for a small store.

- **2026 outlook:** our ensemble forecasts Nov+Dec total retail sales of **$1,383.1B**, **+5.2%** over 2025. E-commerce leads (+9.6%); grocery is weakest (+1.1%). The first month already published after our forecast date (September 2026, total retail) came in within 1.7% of the forecast.
- **Forecasting beats habit:** 'same as last year' missed the holiday total by 5.3% on average; our ensemble (SARIMA + ETS + XGBoost) missed by **2.3%** and beat it in 77% of category-seasons.
- **Consumer sentiment does not improve the forecast** (error change +0.02 points). How shoppers say they feel and what they spend have diverged.
- **AI chatbots - hindsight, not foresight:** Told the category and the year, Claude looked like the best forecaster of all (2.0% average error). With them hidden, its error rose to 2.5%. The named prompt won in 65% of 77 category-seasons ($p = 0.002$, statistically significant), and the gap was largest in 2020-2022 (+1.2 points vs +0.5 overall) - exactly when knowing what really happened (the pandemic, inflation) helps most. That is hindsight, not forecasting, so only anonymized scores measure skill.
- **Fairly tested, chatbots are good but not better:** On anonymized data, the chatbots missed the holiday total by Claude 2.5%, GPT 2.9%, vs 2.3% for our ensemble and 5.3% for 'same as last year'; the ensemble was better than Claude in 57% of cases ($p = 0.08$, not statistically significant); the ensemble was better than GPT in 61% of cases ($p = 0.004$, statistically significant).
- **Product:** a public dashboard with the forecast, a full model comparison, a Holiday Planner that sizes a store's order and safety stock, and an AI advisor that explains the results in plain English using only computed numbers.

Recommendation for retailers: plan the holiday season on a statistical forecast rather than last year's numbers, size safety stock from measured forecast error, and treat AI-chatbot forecasts with caution: they can look excellent on the past for the wrong reason.

1. Motivation and research questions

The holiday season is retail's most important and least forgiving period. Inventory is ordered months in advance; under-ordering means empty shelves during the busiest weeks, over-ordering means January markdowns. Large chains employ forecasting teams; small and independent retailers - who often lack such resources - commonly plan by copying last year. Meanwhile, generative AI tools such as ChatGPT and Claude are increasingly asked for business forecasts, though it is unclear whether they forecast or merely recall published data. We address five questions:

- **Q1.** How much will Americans spend in the 2026 holiday season (November-December), by category?
- **Q2.** Do forecasting models beat 'same as last year', and which model is most accurate?
- **Q3.** Can large language models forecast as well as statistical models, once memorization is ruled out?
- **Q4.** Does a customer-side indicator - consumer sentiment - improve the forecast?
- **Q5.** How can a small retailer turn a national category forecast into an order quantity?

Our deliverables use AI in both ways suggested by the course: **Option A**, LLMs as forecasters compared with conventional models under identical out-of-sample conditions; and **Option B**, an interactive dashboard with an AI advisor.

2. Data

All data come from FRED (Federal Reserve Bank of St. Louis), downloaded programmatically. Retail sales are from the U.S. Census Bureau's **Monthly Retail Trade Survey**, in millions of dollars and **not seasonally adjusted** - the seasonal spike is exactly what we forecast. The customer-side indicator is the University of Michigan **Index of Consumer Sentiment**.

Series	FRED ID	Holiday share 2025	Dec / Oct 2025
Total Retail (ex. food services)	RSXFSN	18.0%	1.11x
Clothing & Accessories Stores	MRTSSM448USN	22.7%	1.59x
Electronics & Appliance Stores	MRTSSM443USN	21.2%	1.42x
Sporting Goods, Hobby, Book & Music Stores	MRTSSM451USN	21.9%	1.55x
General Merchandise Stores	MRTSSM452USN	19.1%	1.20x
E-commerce (Electronic Shopping & Mail-Order)	MRTSSM4541USN	20.2%	1.26x
Grocery Stores (control: no holiday peak)	MRTSSM445USN	17.5%	1.06x
University of Michigan Consumer Sentiment	UMCSENT	-	-

Table 1. Data series. 'Holiday share' = Nov+Dec as a share of 2025 annual sales.

Coverage and quality. Category series run from January 1992 to August 2026; total retail to September 2026. Checks found no missing months inside the range and no duplicate records. Model training starts in 1999 to avoid early-1990s level shifts while keeping 25+ years of seasonal history. **COVID-19.** The March-June 2020 lockdowns produced extreme outliers (clothing store sales fell by about 85% in April 2020). For model training only, each of those months is replaced by the same month of 2019 scaled by January-February 2020 growth - the pre-pandemic trajectory, using only information available at the time. Evaluation always uses the actual, uncleaned values.

Figure 1. Total U.S. retail sales excluding food services, not seasonally adjusted




Figure 2a. December vs. an average month





Figure 2b. Monthly profile, 2022-2025



Figure 2 shows why category matters: clothing and hobby stores sell over 1.5 times an average month in December, while grocery barely moves and building materials actually decline. Grocery is included as a **control** with no holiday peak.

Figure 3. E-commerce (electronic shopping & mail-order) share of retail, 12-month average



E-commerce has grown from 8.3% of retail (Jan-Aug 2015) to 17.4% (Jan-Aug 2026), with a step change during the pandemic and steady gains since (16.9% in 2025). Note that this Census category understates online shopping, because web sales of store-based retailers are counted with their stores.

3. Methodology

3.1 Models

Model	Specification	Why include it
Seasonal Naive	y(t+h) = y(t+h-12)	The retailer's habit; the benchmark to beat
Naive + Growth	Last year's month × exp(avg. YoY log growth of last 3 months)	A stronger rule of thumb
ETS	ETS(A,Ad,A) on log sales: additive error, damped trend, monthly seasonality	Classic exponential smoothing
SARIMA	(p,1,q)(P,1,Q)12 on log sales; p,q,P,Q in {0,1} chosen by AIC per origin	Box-Jenkins benchmark
SARIMAX + Sentiment	SARIMA + log consumer sentiment lagged 4 months	Tests Q4 (customer side)
XGBoost	Gradient boosting pooled over 7 categories; target = YoY log growth of month t+h; features: recent YoY growth, momentum, last year's growth for the target month, month, horizon, category, sentiment	Machine-learning comparison
Ensemble	Geometric mean of SARIMA, ETS and XGBoost	Combining forecasts usually helps
Claude Opus 5.5 / GPT-5.5	LLM prompted with 120 months of history; returns 4 numbers as JSON	Tests Q3 (Option A)

Table 2. Forecasting models. All models except the LLMs run on log sales, so forecasts are back-transformed medians.

3.2 Out-of-sample design

We use a **rolling-origin backtest** that mimics a real planning decision. For each year 2015-2025, every model stands at the end of August, is estimated only on data through August (SARIMA orders are re-selected each time), and forecasts September-December (horizons 1-4). All models share the same origin, horizon and information set. The sentiment variable is lagged four months, so every value a forecast needs is already published at the origin. This gives 7 categories × 11 seasons = **77 holiday forecasts per model**. The identical code then runs from August 2026 for the live forecast.

3.3 Accuracy measures

- **Holiday APE** (main metric): |forecast – actual| / actual for the November+December total - the number a retailer orders against.
- **MAPE, MAE, RMSE** over the four forecast months. MAPE is appropriate because retail sales are never near zero.
- **MASE**: MAE divided by the in-sample seasonal-naive MAE (training data only), comparable across categories of very different size.
- **Coverage80**: share of actual values inside a model's 80% prediction interval (ETS and SARIMA), to check whether the uncertainty is honest.
- **Paired Wilcoxon signed-rank tests** on the 77 matched category-seasons to judge whether differences between two models are significant.

3.4 LLM forecasting protocol and the memorization problem

LLMs are trained on large web corpora that very likely include the published Census figures and news about past holiday seasons. A backtest that names the series and year could reward *recall*, not forecasting. We therefore ran two framings. **Anonymized** (main test, both LLMs): 120 months rescaled to an index (first month = 100), labelled only by calendar month - no category, no year, no units. **Named** (Claude only): the same history with real dates, the category name and dollar values. If named prompts are systematically more accurate on past seasons, the difference measures hindsight. Both LLMs received the same system instruction ('use only the numbers provided ... forecast the next 4 months') and returned JSON with a short explanation; Claude ran at high reasoning effort with schema-constrained output, GPT-5.5 with JSON mode. All prompts and responses are stored in the repository for audit. For 2026 nothing can be memorized, so the named framing is used. An excerpt of an anonymized prompt (clothing, August 2024):

```
Below are 120 consecutive months of an anonymous monthly sales index (first month = 100).
Only the calendar month is shown; the series runs oldest to newest.
... (96 earlier months) ...
Sep: 117.4    Oct: 123.0    Nov: 141.9    Dec: 198.6    Jan: 96.5     Feb: 104.0
Mar: 123.6    Apr: 122.5    May: 131.4    Jun: 122.8    Jul: 125.7    Aug: 134.3
Sep: 117.6    Oct: 120.5    Nov: 143.2    Dec: 204.2    Jan: 95.4     Feb: 109.1
Mar: 124.5    Apr: 119.5    May: 136.7    Jun: 125.3    Jul: 126.7    Aug: 135.2
Forecast the next 4 months (Sep, Oct, Nov, Dec) on the same index scale.
```


3.5 From forecast to order

The Holiday Planner converts the national forecast into a store-level order. Expected sales = the store's own Nov+Dec 2025 sales × (1 + forecast category growth + an optional store adjustment). Uncertainty $\sigma = \sqrt{(\sigma_{national}^2 + \sigma_{store}^2)}$, where $\sigma_{national}$ is the root-mean-square of the ensemble's past holiday % errors for that category (excluding COVID seasons) and σ_{store} is the owner's estimate of how far the store usually misses plan; the two are independent, so variances add. Safety stock = $z \times \sigma$ × expected sales for a chosen service level, and the recommended order = max(0, expected + safety stock − on hand − on order). Conservative and optimistic scenarios use $\pm 1.28\sigma$ (10th/90th percentiles).

4. Results

4.1 Overall accuracy (Q2)

Figure 4. Backtest accuracy, 2015-2025 (lower is better; purple = LLM)



Model	Nov+Dec error	excl. COVID	Monthly MAPE	MASE	80% cover.	Beats naive
Claude (named)	2.00%	1.97%	2.07%	0.61	-	73%
Ensemble	**2.29%**	**2.15%**	**2.40%**	**0.73**	**-**	**77%**
SARIMA	2.34%	2.23%	2.42%	0.73	83%	75%
SARIMAX + Sentiment	2.36%	2.26%	2.43%	0.73	82%	71%
Claude (anonymized)	2.52%	2.35%	2.56%	0.77	-	68%
Naive + Growth	2.55%	2.19%	2.74%	0.80	-	68%
ETS	2.70%	2.51%	2.54%	0.76	82%	69%
XGBoost	2.75%	2.28%	2.88%	0.87	-	71%
GPT (anonymized)	2.86%	2.51%	2.70%	0.82	-	69%
Seasonal Naive	5.32%	3.78%	5.44%	1.61	-	-

Table 3. Backtest accuracy over 77 category-seasons (11 for each of 7 categories). 'Beats naive' = share of category-seasons with a smaller holiday error than Seasonal Naive. *Claude (named) saw the real category and year and can recall what happened; it is shown only for the memorization test (Section 4.6).

Every model clearly beats 'same as last year' (5.32%): the ensemble cuts the holiday error by more than half to 2.29%. Among classical/ML models, SARIMA (2.34%) and the ensemble lead, while the simple 'last year × growth' rule (2.55%) is surprisingly competitive - the key improvement is accounting for the current trend at all. Differences of a few tenths of a point among the top models are within the noise of an 11-season sample, so **having a model matters more than which model**. XGBoost has the highest error among the learned models, plausibly because roughly 25 years of monthly data is a small sample for machine learning; pooling categories helps but does not overcome this.

4.2 Which categories are hard to forecast?

Figure 5. Nov+Dec error (%) by category and model




Total retail, grocery and general merchandise are easiest (errors near 1-2%): they are large, diversified and stable. Electronics, sporting/hobby and e-commerce are hardest: they depend on product cycles (new consoles and phones), shifting promotion calendars, and - for e-commerce - a structural trend that changed abruptly in 2020. The table shows the same ranking for every model, so

difficulty is a property of the category, not the method.

4.3 Over time and COVID

Figure 6. Holiday error by season (average over the 7 categories)



Seasonal Naive fails badly in 2020 and 2021 because last year's pattern was no guide during and right after the pandemic; trend-aware models adapt. Excluding those two seasons narrows but does not close the gap (3.78% vs 2.15%). 2018 was the hardest season for every model.

4.4 Are the prediction intervals honest?

SARIMA's nominal 80% intervals contained 83% of actual values and ETS's 82% - close to 80%, so the stated uncertainty can be trusted. This is why the planner sizes safety stock from measured forecast errors rather than from a guess, and why the dashboard only shows intervals for models that produce a statistically valid one.

4.5 Does consumer sentiment help? (Q4)

No. Adding lagged consumer sentiment to SARIMA changed the average holiday error by +0.02 points (2.36% vs 2.34%). Sentiment has been historically weak through 2025-2026 (down 10-30% year over year) while nominal spending kept growing 3-8%. What consumers say about their mood is a poor guide to what they spend - at least once trend and seasonality are already modelled.

4.6 Can AI chatbots forecast? (Q3)

Forecaster	Nov+Dec error	excl. COVID	Monthly MAPE	Beats naive
Claude (anonymized)	2.52%	2.35%	2.56%	68%
GPT (anonymized)	2.86%	2.51%	2.70%	69%
Claude (named)	2.00%	1.97%	2.07%	73%
Ensemble	2.29%	2.15%	2.40%	77%
SARIMA	2.34%	2.23%	2.42%	75%
Seasonal Naive	5.32%	3.78%	5.44%	-

Table 4. LLM forecasters compared with the classical models on the same 77 category-seasons.

Comparison (A vs B)	B better in	Mean diff (pts)	p-value
Claude (anonymized) vs Claude (named)	65% of 77	+0.52	0.0019
GPT (anonymized) vs Ensemble	61% of 77	+0.57	0.0040

Comparison (A vs B)	B better in	Mean diff (pts)	p-value
Claude (anonymized) vs Ensemble	57% of 77	+0.23	0.0785
GPT (anonymized) vs Claude (anonymized)	57% of 77	+0.33	0.2237


Table 5. Paired Wilcoxon signed-rank tests. Mean diff = A's error minus B's, in percentage points.

Told the category and the year, Claude looked like the best forecaster of all (2.0% average error). With them hidden, its error rose to 2.5%. The named prompt won in 65% of 77 category-seasons (p = 0.002, statistically significant), and the gap was largest in 2020-2022 (+1.2 points vs +0.5 overall) - exactly when knowing what really happened (the pandemic, inflation) helps most. That is hindsight, not forecasting, so only anonymized scores measure skill.

On anonymized data, the chatbots missed the holiday total by Claude 2.5%, GPT 2.9%, vs 2.3% for our ensemble and 5.3% for 'same as last year'; the ensemble was better than Claude in 57% of cases (p = 0.08, not statistically significant); the ensemble was better than GPT in 61% of cases (p = 0.004, statistically significant).


Reading the models' own explanations (saved with every response) shows how the LLMs work: they compute last year's ratios of November and December to the late-summer level and apply them to the current level - essentially a careful 'seasonal ratio' method. That is sensible and explains why they beat 'same as last year', but it does not use the information a statistical model extracts from 25 years of history, and it gives no calibrated uncertainty. The practical lesson: an LLM that is told what and when it is forecasting can look better than any model on past data, for the wrong reason. Backtests of LLM forecasts must hide information that can be recalled.

Figure 7. Forecasts made in August vs. what happened



4.7 What drives the machine-learning model?

Figure 9. XGBoost feature importance (model trained through August 2025)




The most important XGBoost inputs are the growth rates: last year's growth for the same target month (which captures shifts in the holiday calendar, such as a late Thanksgiving moving sales between November and December), the latest year-over-year growth and its 12-month average. Consumer sentiment carries little weight, consistent with Section 4.5. In other words, the model learns what the statistical models assume - that this year's holiday season is last year's pattern scaled by the current trend - and it adds little beyond that with only about 25 years of data per category.

5. The 2026 holiday forecast (Q1)

Category	Nov+Dec 2025	Nov+Dec 2026 forecast	Growth	SARIMA	Claude	GPT
Total Retail (ex. food services)	**$1,314.7B**	**$1,383.1B**	**+5.2%**	**+5.5%**	**+4.5%**	**+4.6%**
Clothing & Accessories Stores	$68.0B	$70.0B	+2.9%	+4.2%	+3.8%	+4.3%
Electronics & Appliance Stores	$18.2B	$19.3B	+5.8%	+6.4%	+6.7%	+6.7%
Sporting Goods, Hobby, Book & Music Stores	$20.8B	$22.4B	+7.7%	+8.3%	+8.1%	+9.2%
General Merchandise Stores	$179.1B	$185.7B	+3.7%	+4.0%	+2.7%	+3.4%
E-commerce (Electronic Shopping & Mail-Order)	$258.5B	$283.3B	+9.6%	+10.7%	+7.9%	+8.7%
Grocery Stores (control: no holiday peak)	$175.7B	$177.7B	+1.1%	+1.4%	+0.6%	+0.9%


Table 6. 2026 holiday forecast (ensemble) with growth from other forecasters for comparison. Forecast origin: August 2026.

Figure 8. The Sep-Dec 2026 forecast



We expect a solid season: total retail sales of $1,383.1B in November-December, +5.2% over 2025 - a little faster than 2025's holiday growth, consistent with the 3-7% year-over-year gains seen through 2026. E-commerce (+9.6%) and sporting/hobby stores (+7.7%) lead; clothing (+2.9%) slows after strong 2025 growth; grocery (+1.1%) barely moves. Growth is nominal - it includes price increases.

Figure 10. 2026 holiday growth forecast by category and forecaster



The forecasters broadly agree on direction and ranking - e-commerce and hobby stores fastest, grocery slowest - which adds confidence to the outlook. The LLMs, asked with the real series names, tend to be more conservative for some categories; their explanations (saved with each response) show they anchor on the year-to-date growth rate and last year's November and December ratios. Because LLM forecasts were less accurate than the ensemble when tested fairly, we use the ensemble for planning and show the LLM forecasts as a second opinion in the dashboard.


Early reality check. Census published September 2026 total retail ($635.1B) after our August forecast date. The ensemble forecast $624.2B, an error of -1.7% - within the range of its backtest errors.

6. The product: Holiday Retail Planner dashboard (Option B)


The dashboard (https://holiday-retail-planner.streamlit.app) is built with Streamlit and reads the same saved outputs as this report - nothing is re-estimated in the app, so what users see is exactly what the code produced. It has seven tabs:

- **Story** - motivation and headline findings.


- **Market** - history by category, the size of each December spike, e-commerce share.
- **2026 Forecast** - choose a category and any forecasters; SARIMA's 80% interval as a band; the LLMs' own explanations.
- **Model Battle** - all backtest metrics with or without COVID seasons, the category heatmap, a replay of any past season, and the LLM memorization test.
- **Holiday Planner** - the order calculator of Section 3.5 with scenario table and November/December timing.
- **AI Advisor** - a chat assistant (Claude) that answers questions such as 'Why do you recommend this order?' or 'Which model is most accurate?'. It receives a fact sheet generated from the results plus the user's planner inputs, is instructed to quote numbers exactly and never invent forecasts or ranges, and says when the information is missing.
- **About** - objectives, data, methods, validation, usage instructions and AI-tool disclosure.



Screenshot 1. Model Battle tab: backtest accuracy of every forecaster; named LLM results are flagged as hindsight.



Screenshot 2. Holiday Planner tab with the worked example below.



Screenshot 3. AI Advisor answering 'Why do you recommend this order for my store?' - every number in the answer comes from the planner's computation.

Worked example. A clothing boutique sold 5,000 units in Nov+Dec 2025, has 1,200 on hand, wants a 90% chance of not running out and estimates its sales usually miss plan by ±10%. National clothing growth is +2.9%, so expected demand is 5,144 units. The ensemble's past clothing error is 1.2%; combined with the store's ±10%, σ = 10.1%, giving safety stock of 664 units and a **recommended order of 4,609 units**. Note that store-level volatility, not national forecast error, dominates the buffer - an honest message for small retailers.

7. Conclusions

- **Use a model, not last year.** Any trend-aware forecast halves the holiday planning error; the ensemble is the most accurate and most consistent choice.
- **Sentiment surveys add nothing** beyond trend and seasonality for nominal holiday spending.
- **Be careful with AI-chatbot forecasts.** They can look better than any model on past data because they remember the past; tested fairly they are reasonable but not better than standard methods, and they provide no calibrated uncertainty. Their best role is explaining forecasts - which is how our AI advisor uses them.
- **2026 should be a good holiday season** (+5.2%), with e-commerce continuing to take share.
- **Forecast error is measurable and should drive safety stock** - and for a small store, its own volatility matters more than the national forecast error.

8. Limitations

- National category totals, not a specific store or product; the planner scales a store's own history by national growth.
- FRED provides today's revised data. Forecasters in past years saw earlier, unrevised figures, so real-time accuracy would be somewhat lower for all models.
- Eleven seasons per category is a small sample; differences of a few tenths of a point between the best models are not decisive, which is why we report paired significance tests.

- LLM outputs are not deterministic, and each prompt was run once; model versions will change. Anonymization removes direct recall but an LLM might still recognize a series' shape (e.g. the 2020 shock).
- No inventory-cost or stock-out data, so we make no claim about money saved; growth figures are nominal.

9. Use of AI tools

- **Claude Code** (Anthropic) wrote most of the code - data pipeline, models, backtest, evaluation, dashboard and the report generators - and first drafts of the text, working from the team's research questions and design decisions. The team reviewed the code, checked results against the raw data and decided what to present.
- **Claude Opus 5.5** (Anthropic API) and **GPT-5.5** (OpenAI API) were used as forecasters in the comparison (Option A).
- **Claude Opus 5.5** powers the dashboard's AI advisor (Option B), restricted to computed results.

References

- U.S. Census Bureau, Monthly Retail Trade Survey; retrieved from FRED, Federal Reserve Bank of St. Louis (series listed in Table 1).
- University of Michigan, Surveys of Consumers, Index of Consumer Sentiment (UMCSENT), via FRED.
- Hyndman, R.J. and Athanasopoulos, G. *Forecasting: Principles and Practice*, 3rd ed., OTexts.
- Chen, T. and Guestrin, C. (2016). XGBoost: A Scalable Tree Boosting System. *Proc. KDD*.
- Seabold, S. and Perktold, J. (2010). statsmodels: Econometric and Statistical Modeling with Python.

Appendix A. Data quality checks

Series	First month	Last month	Months	Missing	Duplicates
Total retail	1992-01	2026-09	417	0	0
Clothing	1992-01	2026-08	416	0	0
Electronics	1992-01	2026-08	416	0	0
Sporting & hobby	1992-01	2026-08	416	0	0
General merchandise	1992-01	2026-08	416	0	0
E-commerce	1992-01	2026-08	416	0	0
Grocery	1992-01	2026-08	416	0	0

Appendix B. Example LLM prompt and both models' answers

System instruction (both models): 'You are a careful time-series forecaster. You are given a monthly history and must forecast the next 4 months. Use only the numbers provided. Think about level, trend, and month-of-year seasonality, then return your forecast in the requested JSON format.'

User prompt for total retail, forecast origin August 2025 (the 120 monthly values are abbreviated here to the first and last 12):

```
Below are 120 consecutive months of an anonymous monthly sales index (first month = 100).
Only the calendar month is shown; the series runs oldest to newest.
Sep: 100.0    Oct: 102.8    Nov: 103.4    Dec: 120.7    Jan: 92.3     Feb: 95.2
Mar: 106.0    Apr: 103.4    May: 108.1    Jun: 107.3    Jul: 106.4    Aug: 109.0
... (96 more months) ...
Sep: 150.8    Oct: 162.0    Nov: 163.6    Dec: 179.0    Jan: 147.2    Feb: 141.1
Mar: 162.4    Apr: 162.5    May: 168.2    Jun: 160.2    Jul: 167.2    Aug: 166.4
Forecast the next 4 months (Sep, Oct, Nov, Dec) on the same index scale.
```

Claude Opus 5.5 forecast (index): 156.0, 165.0, 167.5, 183.0. *Explanation:* "The index has plateaued at a high level since the earlier jump, with year-over-year growth recently running about +4 to +6. Seasonality is strong: September dips about 10 below August, October and November recover, and December peaks. I applied last year's Sep–Dec pattern plus roughly a +4 to +5 year-over-year uplift."

GPT-5.5 forecast (index): 157.0, 166.5, 168.0, 183.5. *Explanation:* "The last completed year averaged about 160.9, up 4.3 points from the prior year, so I used a modest continuation of that underlying rise rather than the faster mid-history growth. Recent seasonality shows Sep dropping from Aug, Oct and Nov near/slightly above the annual level, and Dec strongly above it. I blended recent same-month year-over-year gains with the recent Sep-Dec seasonal pattern, allowing Sep to rebound from the weak last Sep but keeping Dec at a new seasonal high."

Appendix C. SARIMA orders selected by AIC

Category	Most frequent order	Seasonal order
Total Retail (ex. food services)	(1, 1, 1)	(1, 1, 1, 12)
Clothing & Accessories Stores	(0, 1, 1)	(1, 1, 1, 12)
Electronics & Appliance Stores	(0, 1, 1)	(0, 1, 1, 12)
Sporting Goods, Hobby, Book & Music Stores	(0, 1, 1)	(1, 1, 1, 12)
General Merchandise Stores	(1, 1, 1)	(0, 1, 1, 12)
E-commerce (Electronic Shopping & Mail-Order)	(1, 1, 1)	(1, 1, 1, 12)
Grocery Stores (control: no holiday peak)	(1, 1, 1)	(1, 1, 1, 12)

Appendix D. Reproducibility

All code, data and LLM responses: https://github.com/RachelLiu13/holiday-retail-forecast. A self-contained notebook (notebooks/Holiday_Retail_Forecast.ipynb) downloads the data and reproduces every model and table in this report; LLM forecasts are loaded from the saved results unless re-run with API keys.