

Assignment 9.3

February 27, 2022

0.1 Assignment 9.3

```
[1]: import os
import shutil
import json
from pathlib import Path

import pandas as pd

from kafka import KafkaProducer, KafkaAdminClient
from kafka.admin.new_topic import NewTopic
from kafka.errors import TopicAlreadyExistsError

from pyspark.sql import SparkSession
from pyspark.streaming import StreamingContext
from pyspark import SparkConf
from pyspark.sql.functions import window, from_json, col, expr, to_json,
    ↳ struct, when
from pyspark.sql.types import StringType, TimestampType, DoubleType,
    ↳ StructField, StructType
from pyspark.sql.functions import udf

current_dir = Path(os.getcwd()).absolute()
checkpoint_dir = current_dir.joinpath('checkpoints')
joined_checkpoint_dir = checkpoint_dir.joinpath('joined')

if joined_checkpoint_dir.exists():
    shutil.rmtree(joined_checkpoint_dir)

joined_checkpoint_dir.mkdir(parents=True, exist_ok=True)
```

0.1.1 Configuration Parameters

```
[2]: config = dict(
    bootstrap_servers=['kafka.kafka.svc.cluster.local:9092'],
    first_name='Rachel',
    last_name='Nelson'
```

```

)

config['client_id'] = '{}-{}'.format(
    config['last_name'],
    config['first_name']
)

config['topic_prefix'] = '{}-{}'.format(
    config['last_name'],
    config['first_name']
)

config['locations_topic'] = '{}-locations'.format(config['topic_prefix'])
config['accelerations_topic'] = '{}-accelerations'.
    ↪format(config['topic_prefix'])
config['joined_topic'] = '{}-joined'.format(config['topic_prefix'])

config

```

```

[2]: {'bootstrap_servers': ['kafka.kafka.svc.cluster.local:9092'],
      'first_name': 'Rachel',
      'last_name': 'Nelson',
      'client_id': 'NelsonRachel',
      'topic_prefix': 'NelsonRachel',
      'locations_topic': 'NelsonRachel-locations',
      'accelerations_topic': 'NelsonRachel-accelerations',
      'joined_topic': 'NelsonRachel-joined'}

```

0.1.2 Create Topic Utility Function

The `create_kafka_topic` helps create a Kafka topic based on your configuration settings. For instance, if your first name is *John* and your last name is *Doe*, `create_kafka_topic('locations')` will create a topic with the name `DoeJohn-locations`. The function will not create the topic if it already exists.

```

[3]: def create_kafka_topic(topic_name, config=config, num_partitions=1,
    ↪replication_factor=1):
    bootstrap_servers = config['bootstrap_servers']
    client_id = config['client_id']
    topic_prefix = config['topic_prefix']
    name = '{}-{}'.format(topic_prefix, topic_name)

    admin_client = KafkaAdminClient(
        bootstrap_servers=bootstrap_servers,
        client_id=client_id
    )

    topic = NewTopic(

```

```

        name=name,
        num_partitions=num_partitions,
        replication_factor=replication_factor
    )

    topic_list = [topic]
    try:
        admin_client.create_topics(new_topics=topic_list)
        print('Created topic "{}"'.format(name))
    except TopicAlreadyExistsError as e:
        print('Topic "{}" already exists'.format(name))

create_kafka_topic('joined')

```

Topic "NelsonRachel-joined" already exists

TODO: This code is identical to the code used in 9.1 to publish acceleration and location data to the LastnameFirstname-simple topic. You will need to add in the code you used to create the df_accelerations dataframe. In order to read data from this topic, make sure that you are running the notebook you created in assignment 8 that publishes acceleration and location data to the LastnameFirstname-simple topic.

```

[4]: spark = SparkSession\
    .builder\
    .appName("Assignment09")\
    .getOrCreate()

df_locations = spark \
    .readStream \
    .format("kafka") \
    .option("kafka.bootstrap.servers", "kafka.kafka.svc.cluster.local:9092") \
    .option("subscribe", config['locations_topic']) \
    .load()

## TODO: Add code to create the df_accelerations dataframe
df_accelerations = spark \
    .readStream \
    .format("kafka") \
    .option("kafka.bootstrap.servers", "kafka.kafka.svc.cluster.local:9092") \
    .option("subscribe", config['accelerations_topic']) \
    .load()

```

The following code defines a Spark schema for location and acceleration data as well as a user-defined function (UDF) for parsing the location and acceleration JSON data.

```

[5]: location_schema = StructType([
    StructField('offset', DoubleType(), nullable=True),
    StructField('id', StringType(), nullable=True),

```

```

    StructField('ride_id', StringType(), nullable=True),
    StructField('uuid', StringType(), nullable=True),
    StructField('course', DoubleType(), nullable=True),
    StructField('latitude', DoubleType(), nullable=True),
    StructField('longitude', DoubleType(), nullable=True),
    StructField('geohash', StringType(), nullable=True),
    StructField('speed', DoubleType(), nullable=True),
    StructField('accuracy', DoubleType(), nullable=True),
])

acceleration_schema = StructType([
    StructField('offset', DoubleType(), nullable=True),
    StructField('id', StringType(), nullable=True),
    StructField('ride_id', StringType(), nullable=True),
    StructField('uuid', StringType(), nullable=True),
    StructField('x', DoubleType(), nullable=True),
    StructField('y', DoubleType(), nullable=True),
    StructField('z', DoubleType(), nullable=True),
])

udf_parse_acceleration = udf(lambda x: json.loads(x.decode('utf-8')),
    ↪ acceleration_schema)
udf_parse_location = udf(lambda x: json.loads(x.decode('utf-8')),
    ↪ location_schema)

```

TODO:

- Complete the code to create the `accelerationsWithWatermark` dataframe.
 - Select the `timestamp` field with the alias `acceleration_timestamp`
 - Use the `udf_parse_acceleration` UDF to parse the JSON values
 - Select the `ride_id` as `acceleration_ride_id`
 - Select the `x`, `y`, and `z` columns
 - Use the same watermark timespan used in the `locationsWithWatermark` dataframe

```

[30]: locationsWithWatermark = df_locations \
    .select(
        col('timestamp').alias('location_timestamp'),
        udf_parse_location(df_locations['value']).alias('json_value')
    ) \
    .select(
        col('location_timestamp'),
        col('json_value.ride_id').alias('location_ride_id'),
        col('json_value.speed').alias('speed'),
        col('json_value.latitude').alias('latitude'),
        col('json_value.longitude').alias('longitude'),
        col('json_value.geohash').alias('geohash'),
        col('json_value.accuracy').alias('accuracy')
    ) \

```

```
.withWatermark('location_timestamp', "2 seconds")
```

```
[35]: accelerationsWithWatermark = df_accelerations \
      .select(
        col('timestamp').alias('timestamp'),
        udf_parse_acceleration(df_accelerations['value']).alias('json_value')
      ) \
      .select(
        col('timestamp'),
        col('json_value.ride_id').alias('acceleration_ride_id'),
        col('json_value.uuid').alias('uuid'),
        col('json_value.x').alias('x'),
        col('json_value.y').alias('y'),
        col('json_value.z').alias('z')
      ) \
      .withWatermark('timestamp', "30 seconds")
```

TODO:

- Complete the code to create the df_joined dataframe. See <http://spark.apache.org/docs/latest/structured-streaming-programming-guide.html#stream-stream-joins> for additional information.

```
[40]: df_joined = locationsWithWatermark.
      ↪join(accelerationsWithWatermark, expr("location_ride_id =_
      ↪acceleration_ride_id"))
df_joined
```

```
[40]: DataFrame[location_timestamp: timestamp, location_ride_id: string, speed:
double, latitude: double, longitude: double, geohash: string, accuracy: double,
timestamp: timestamp, acceleration_ride_id: string, uuid: string, x: double, y:
double, z: double]
```

If you correctly created the df_joined dataframe, you should be able to use the following code to create a streaming query that outputs results to the LastnameFirstname-joined topic.

```
[41]: ds_joined = df_joined \
      .withColumn(
        'value',
        to_json(
          struct(
            'ride_id', 'location_timestamp', 'speed',
            'latitude', 'longitude', 'geohash', 'accuracy',
            'acceleration_timestamp', 'x', 'y', 'z'
          )
        )
      ).withColumn(
        'key', col('ride_id')
```

```

    ) \
    .selectExpr("CAST(key AS STRING)", "CAST(value AS STRING)") \
    .writeStream \
    .format("kafka") \
    .option("kafka.bootstrap.servers", "kafka.kafka.svc.cluster.local:9092") \
    .option("topic", config['joined_topic']) \
    .option("checkpointLocation", str(joined_checkpoint_dir)) \
    .start()

try:
    ds_joined.awaitTermination()
except KeyboardInterrupt:
    print("STOPPING STREAMING DATA")

```

```

↳ -----

AnalysisException                                Traceback (most recent call↳
↳ last)

<ipython-input-41-72756735dc4c> in <module>
----> 1 ds_joined = df_joined \
      2     .withColumn(
      3         'value',
      4         to_json(
      5             struct(

/usr/local/spark/python/pyspark/sql/dataframe.py in withColumn(self,↳
↳ colName, col)
      2094         """
      2095         assert isinstance(col, Column), "col should be Column"
-> 2096         return DataFrame(self._jdf.withColumn(colName, col._jc),↳
↳ self.sql_ctx)
      2097
      2098         @ignore_unicode_prefix

/usr/local/spark/python/lib/py4j-0.10.9-src.zip/py4j/java_gateway.py in↳
↳ __call__(self, *args)
      1302
      1303         answer = self.gateway_client.send_command(command)
-> 1304         return_value = get_return_value(
      1305             answer, self.gateway_client, self.target_id, self.name)
      1306

```

```

/usr/local/spark/python/pyspark/sql/utils.py in deco(*a, **kw)
135             # Hide where the exception came from that shows a
↳non-Pythonic
136             # JVM exception message.
--> 137             raise_from(converted)
138         else:
139             raise

```

```

/usr/local/spark/python/pyspark/sql/utils.py in raise_from(e)

```

```

AnalysisException: cannot resolve ``ride_id`` given input columns:
↳[acceleration_ride_id, accuracy, geohash, latitude, location_ride_id,
↳location_timestamp, longitude, speed, timestamp, uuid, x, y, z];
'Project [location_timestamp#555-T2000ms, location_ride_id#560, speed#561,
↳latitude#562, longitude#563, geohash#564, accuracy#565,
↳timestamp#612-T30000ms, acceleration_ride_id#617, uuid#618, x#619, y#620,
↳z#621, to_json(struct(NamePlaceholder, 'ride_id, location_timestamp,
↳location_timestamp#555-T2000ms, speed, speed#561, latitude, latitude#562,
↳longitude, longitude#563, geohash, geohash#564, accuracy, accuracy#565,
↳NamePlaceholder, 'acceleration_timestamp, x, x#619, y, y#620, z, z#621),
↳Some(Etc/UTC)) AS value#712]
+- Join Inner, (location_ride_id#560 = acceleration_ride_id#617)
:- EventTimeWatermark location_timestamp#555: timestamp, 2 seconds
: +- Project [location_timestamp#555, json_value#557.ride_id AS
↳location_ride_id#560, json_value#557.speed AS speed#561, json_value#557.
↳latitude AS latitude#562, json_value#557.longitude AS longitude#563,
↳json_value#557.geohash AS geohash#564, json_value#557.accuracy AS accuracy#565]
: +- Project [timestamp#12 AS location_timestamp#555,
↳<lambda>(value#8) AS json_value#557]
: +- StreamingRelationV2 org.apache.spark.sql.kafka010.
↳KafkaSourceProvider@593fa79d, kafka, org.apache.spark.sql.kafka010.
↳KafkaSourceProvider$KafkaTable@475b8a60, org.apache.spark.sql.util.
↳CaseInsensitiveStringMap@e275a43b, [key#7, value#8, topic#9, partition#10,
↳offset#11L, timestamp#12, timestampType#13], StreamingRelation DataSource(org.
↳apache.spark.sql.
↳SparkSession@39467d30,kafka,List(),None,List(),None,Map(subscribe ->
↳NelsonRachel-locations, kafka.bootstrap.servers -> kafka.kafka.svc.cluster.
↳local:9092),None), kafka, [key#0, value#1, topic#2, partition#3, offset#4L,
↳timestamp#5, timestampType#6]
+- EventTimeWatermark timestamp#612: timestamp, 30 seconds
+- Project [timestamp#612, json_value#614.ride_id AS
↳acceleration_ride_id#617, json_value#614.uuid AS uuid#618, json_value#614.x AS
↳x#619, json_value#614.y AS y#620, json_value#614.z AS z#621]

```

```

      +- Project [timestamp#33 AS timestamp#612, <lambda>(value#29) AS
↳ json_value#614]
      +- StreamingRelationV2 org.apache.spark.sql.kafka010.
↳ KafkaSourceProvider@58b5f988, kafka, org.apache.spark.sql.kafka010.
↳ KafkaSourceProvider$KafkaTable@13a047e1, org.apache.spark.sql.util.
↳ CaseInsensitiveStringMap@7646614c, [key#28, value#29, topic#30, partition#31,
↳ offset#32L, timestamp#33, timestampType#34], StreamingRelation DataSource(org.
↳ apache.spark.sql.
↳ SparkSession@39467d30,kafka,List(),None,List(),None,Map(subscribe ->
↳ NelsonRachel-accelerations, kafka.bootstrap.servers -> kafka.kafka.svc.cluster.
↳ local:9092),None), kafka, [key#21, value#22, topic#23, partition#24,
↳ offset#25L, timestamp#26, timestampType#27]

```

[]: