Database ER Diagram

contact_info_ty...
- id_contact_info_type INT
- name INT

users_contact_in...
- id_users_contact_info INT
- value VARCHAR(100)
- enabled BIT(1)
- last_update DATETIME
- id_user INT
- id_contact_info_type INT

users
- id_user INT
- name VARCHAR(60)
- cedula VARCHAR(30)
- contraseña VARBINARY(170)
- id_language INT
- last_update DATETIME
- countries_country_id INT
- email VARCHAR(180)

languages
- id_language INT
- name VARCHAR(45)
- culture VARCHAR(2...

translations
- id_translations INT
- code VARCHAR(20)
- caption VARCHAR(20...
- enabled BIT(1)
- id_language INT

servi_suscritos
- id_servisuscritos INT
- nombreservidelusuario VARCHAR(45)
- contrato VARCHAR(45)
- enabled BIT(1)
- servi_available_id INT
- id_user INT

logs
- id_logs INT
- description VARCHAR(200)
- posttime DATETIME
- computer VARCHAR(45)
- user_name VARCHAR(120)
- trace VARCHAR(45)
- reference_id_1 BIGINT(8)
- reference_id_2 BIGINT(8)
- value_1 VARCHAR(180)
- value_2 VARCHAR(180)
- checksum VARBINARY(20...
- id_log_type INT
- id_log_source INT
- id_log_severity INT

log_types
- id_log_type INT
- name VARCHAR(45)
- ref_1_des VARCHAR(4...
- ref_2_des VARCHAR(4...
- val_1_des VARCHAR(4...
- val_2_des VARCHAR(180)

log_sourc...
- id_log_source INT
- name VARCHAR(45)

log_severiti...
- id_log_severity INT
- name VARCHAR(45)

countries
- country_id INT
- name VARCHAR(80)

pay_method
- id_pay_method INT
- name VARCHAR(30)
- api_url VARCHAR(200)
- secret_key VARBINARY(25...
- key VARCHAR(200)
- enabled BIT(1)

available_pay_metho...
- id_available_pay_methods INT
- name VARCHAR(45)
- token VARCHAR(45)
- exp_token_date DATETIME
- mask_account VARCHAR(45)
- callback_url VARCHAR(45)
- pay_method_id_pay_method INT
- users_id_user INT

users_suscription
- suscription_id INT
- description VARCHAR(255)
- logo_url VARCHAR(200)
- startdate DATETIME
- enddate DATETIME
- deleted BIT(1)
- enabled BIT(1)
- id_user INT

plan_prices
- id_plan_prices INT
- amount INT
- recurrency_type VARCHAR(2...
- posttime DATETIME
- enddate DATETIME
- current BIT(1)
- company_id INT

services_availa...
- serviavailable_id INT
- nameservi VARCHAR(45)
- type_service_id INT
- company_id INT

company_provider
- company_id INT
- namecompany VARCHAR(45)

type_service
- typeservi_id INT
- nametype VARCHAR(30)

payments
- id_payments INT
- amount DECIMAL
- actual_amount DECIMAL
- result VARCHAR(200)
- auth VARCHAR(45)
- reference VARCHAR(45)
- change_token VARBINARY(25...
- description VARCHAR(200)
- error VARCHAR(4)
- date DATETIME
- checksum VARBINARY(255)
- id_user INT
- id_available_pay_methods INT
- id_pay_method INT
- id_currency INT

trans_typ...
- id_trans_types INT
- name INT

pay_notification
- id_notification INT
- date DATETIME
- contrato VARCHAR(45)
- montoactual DECIMAL
- confirmation BIT(1)
- mensaje VARCHAR(255)
- source VARCHAR(45)
- destiny VARCHAR(45)
- notification_status VARCHAR(20)
- id_notification_medium INT
- id_user INT
- id_payments INT
- id_users_contact_info INT

features
- id_features...
- value INT
- enabled BIT...
- id_suscriptio...
- id_plan_feat...

plan_features
- id_plan_features INT
- description VARCHAR(4...
- enabled BIT(1)
- datatype VARCHAR(200)

person_plan_lim...
- id_person_plan_limits INT
- limit INT
- id_plan_features INT
- id_plan_person INT

plan_person
- id_plan_person INT
- adquisition_date DATETI...
- enabled BIT(1)
- id_user INT
- id_schedules INT

schedules
- id_schedules INT
- name VARCHAR(45)
- recurrency_type VARCHAR(2...
- repeat BIT(1)
- end_type VARCHAR(45)
- repetitions VARCHAR(45)
- end_date DATETIME

schedule_deta...
- id_schedule_details INT
- deleted BIT(1)
- base_date DATETIME
- date_part DATETIME
- last_execution DATETIME
- next_execution DATETIME
- id_schedules INT

user_balance
- id_user_balance BIGINT(30)
- balance DECIMAL
- last_balance INT
- last_update DATETIME
- checksum VARBINARY(255)
- freeze_amount INT
- id_user INT
- id_currency INT

trans_sub_typ...
- id_trans_sub_types INT
- name INT

transactions
- id_transaction BIGINT(30)
- amount DECIMAL
- description VARCHAR(100)
- datetime DATETIME
- posttime DATETIME
- transdatetime DATETIME
- ref_number VARCHAR(45)
- checksum VARBINARY(255)
- id_trans_types INT
- id_user INT
- id_trans_sub_types INT
- id_user_balance BIGINT(30)
- id_currency INT
- id_exchange_rate INT
- id_system INT
- transaction_receipt_id_transaction_rec...
- id_payments INT

currency
- id_currency INT
- name VARCHAR(45)
- acronym VARCHAR(...
- symbol VARCHAR(8)

exchange_rate
- id_exchange_rate INT
- startdate DATETIME
- enddate DATETIME
- rate DECIMAL
- enabled BIT(1)
- current_exchange_rate BIT(1)
- id_currency_s INT
- id_currency_d INT

roles
- id_roles INT
- name VARCHAR(45)

user_roles
- id_role INT
- last_update DATETIME
- user_name VARCHAR(45)
- checksum VARBINARY(255)
- enabled BIT(1)
- deleted BIT(1)
- id_roles INT
- id_user INT

user_permissions
- id_user_permissions INT
- enabled BIT(1)
- deleted BIT(1)
- last_update DATETIME
- user_name VARCHAR(45)
- checksum VARBINARY(25...
- id_permission INT

role_permissions
- id_permission INT
- enabled BIT(1)
- deleted BIT(1)
- last_update DATETIME
- roles_id_roles INT
- user_name VARCHAR(45)
- checksum VARBINARY(255)
- permissions_id_permission I...

permissions
- id_permission INT
- description VARCHAR(45)
- code VARCHAR(45)
- permission_modules_id_module TINYINT(...

permission_modul...
- id_module TINYINT(8)
- name VARCHAR(40)

notification_medi...
- id_notification_medium INT
- name VARCHAR(45)

transaction_receipt
- id_transaction_receipt INT
- pdfURL VARCHAR(200)
- deleted BIT(1)
- id_transaction_receipt_mediatype I...

transaction_receipt_mediatype...
- id_transaction_receipt_mediatype INT
- name VARCHAR(20)
- player_impl VARCHAR(100)

ai_sessions
- session_id INT
- session_uuid VARCHAR(5...
- bot_id VARCHAR(50)
- bot_alias_id VARCHAR(50)
- start_time DATETIME
- id_user INT

user_tactile_feedba...
- feedback_id INT
- event_type VARCHAR(45)
- button_pressed VARCHAR(45)
- touch_duration DECIMAL
- timestamp DATETIME
- session_id INT
- id_user INT

ai_requests
- request_id INT
- input_mode ENUM(...)
- text_content TEXT
- audio_recording BLOB
- content_type VARCHAR(5...
- jsonConfig JSON
- session_id INT
- transcription_id INT
- audio_recording_id INT
- feedback_id INT

ai_errors
- error_id INT
- confidence DECIMAL
- timestamp DATETIME
- occurrence_count INT
- error_type_id INT
- session_id INT

error_types
- error_type_id INT
- name VARCHAR(45)
- description VARCHAR(15...

transcriptions
- transcription_id INT
- start_time FLOAT
- end_time FLOAT
- is_partial BIT(1)
- result_ID VARCHAR(5...
- trans_conf_id INT

transcription_configuratio...
- trans_conf_id INT
- media_enc VARCHAR(50)
- sample_rate INT
- language_code VARCHAR(10)
- identify_language BIT(1)
- identify_multiple_languages BIT(1)
- jsonConfig JSON
- audio_recording_id INT

transcription_items
- trans_item_id INT
- transcription_id INT
- content TEXT
- start_time FLOAT
- end_time FLOAT
- stable BIT(1)
- type VARCHAR(45)
- vocabulary_filter_match BIT(...

audio_recordings
- audio_recording_id INT
- audio_path VARCHAR(200)
- upload_date DATETIME
- deleted BIT(1)
- id_user INT

ai_intents
- intent_id INT
- name VARCHAR(100)
- confirmation_state VARCHAR(5...
- state VARCHAR(50)
- confidence DECIMAL
- user_confirmation BIT(1)
- timestamp DATETIME
- session_id INT
- request_id INT

recognized_entiti...
- entity_id INT
- entity_name VARCHAR(100)
- entity_value TEXT
- session_id INT
- intent_id INT
- entity_type_id INT

ai_abandonmen...
- abandonment_id INT
- reason TEXT
- timestamp DATETIME
- request_id INT
- session_id INT

entity_type
- entity_type_id INT
- name VARCHAR(45)
- description VARCHAR(15...

responses
- response_id INT
- content_type VARCHAR(10...
- content TEXT
- audio_data BLOB
- timestamp DATETIME
- session_id INT
- request_id INT

ai_actions
- action_id INT
- action_text TEXT
- confidence DECIMAL
- confirmation BIT(1)
- jsonPayConfig JSON
- execution_status VARCHAR(45)
- executed_at DATETIME
- execution_time DECIMAL
- command_id INT
- session_id INT
- intent_id INT
- request_id INT

ai_correctio...
- correction_id INT
- timestamp DATETIME
- ori_request_id INT
- corr_request_id INT
- ori_response_id INT
- corr_response_id INT

ai_commands
- command_id INT
- command_name VARCHAR(20)
- command_description VARCHAR(150)
- command VARCHAR(50)