REFIT: Data Cleaning and Washing-Machine Disaggregation

Flock Energy Take-Home Assignment

GitHub: https://github.com/Rachi-collab/REFIT-Data-Cleaning-and-Appliance-Disaggregation.git

---

Item	Detail
Dataset	REFIT Electrical Load Measurements, University of Strathclyde
Households (cleaning)	House 1 (raw data)
Households (EDA & model)	Houses 1, 2, 5, 7, 10, 15, 16, 17, 19, 21
Period	Nov 2013 – Jun 2015
Raw sampling	8-second intervals
Analysis resolution	1-minute (resampled)
Units	Watts (W)
Channels	Aggregate + up to 9 appliance sub-meters

In [1]:
```
import os, sys, warnings, json
from pathlib import Path

import numpy as np
import pandas as pd
import matplotlib
matplotlib.use('Agg')
import matplotlib.pyplot as plt
import matplotlib.dates as mdates
from IPython.display import display, Image, Markdown

warnings.filterwarnings('ignore')

ROOT      = Path(r"c:/Users/Admin/OneDrive/Desktop/refit-nilm")
sys.path.insert(0, str(ROOT))

from refit_nilm import config as C
from refit_nilm.io import load_clean_house, find_house_file
from refit_nilm.cycles import detect_cycles
from refit_nilm.features import make_windows
from refit_nilm.metrics import regression_and_state, cycle_level

FIGURES   = ROOT / "figures"
RESULTS   = ROOT / "results"
FIGURES.mkdir(exist_ok=True)
RESULTS.mkdir(exist_ok=True)
```

```
def show_fig(fname, width=780):
    p = FIGURES / fname
    if p.exists():
        display(Image(filename=str(p), width=width))
    else:
        display(Markdown(f"*{fname} not yet generated*"))

print("Environment ready")
print("ROOT:", ROOT)
print("ON_W threshold:", C.ON_W, "W")
print("EDA houses:", C.EDA_HOUSES)
print("Train houses:", C.TRAIN_HOUSES)
print("Test houses:", C.TEST_HOUSES)
```

```
Environment ready
ROOT: c:\Users\Admin\OneDrive\Desktop\refit-nilm
ON_W threshold: 10.0 W
EDA houses: [1, 2, 5, 7, 10, 15, 16, 17, 19, 21]
Train houses: [1, 2, 5, 7, 10, 15]
Test houses: [19, 21]
```

Section 1 — Raw House 1: Inspection and Cleaning to 1-Minute

Preprocessing Pipeline

1. **Timestamp parsing & ordering** — Convert Unix epoch to UTC datetime; sort chronologically.
2. **Duplicate removal** — Drop duplicate timestamps keeping the first valid record (deterministic, reproducible rule).
3. **Physical bounds checking** — Set negative values and spikes > 20,000 W (beyond UK 100 A / 23 kW limit) to NaN.
4. **1-minute resampling** — Resample to 60-second intervals using mean aggregation.
5. **Gap handling** — Linear interpolation for gaps ≤ 5 minutes; gaps > 5 minutes are flagged as `long_gap` (kept as NaN — not filled, as fabricating data during meter outages would bias the model).

In [2]:
```
# Section 1 - Raw House 1 Cleaning Pipeline
from refit_nilm.io import find_house_file

RAW_ROOT = C.RAW_DIR if C.RAW_DIR.exists() else C.DATA_DIR
raw_path = find_house_file(RAW_ROOT, C.RAW_HOUSE, clean=False)

if raw_path is None:
    for candidate in sorted(C.DATA_DIR.rglob("*.csv")):
        if "House_1" in candidate.name or "House1" in candidate.name:
            raw_path = candidate
            break
```

```
print("Raw file:", raw_path)

# Load — file has a header row (Time, Unix, Aggregate, Appliance1, ...)
raw = pd.read_csv(raw_path, header=0, low_memory=False)
print("Raw shape:", raw.shape)
print("Columns:", list(raw.columns[:6]))

# Unix timestamp column
unix_col = 'Unix' if 'Unix' in raw.columns else raw.columns[1]
raw[unix_col] = pd.to_numeric(raw[unix_col], errors='coerce')
raw['dt'] = pd.to_datetime(raw[unix_col], unit='s', utc=True)
raw = raw.dropna(subset=['dt'])

# Sort
raw = raw.sort_values('dt').reset_index(drop=True)

# Duplicates
n_dups = raw.duplicated(subset=['dt']).sum()
raw = raw.drop_duplicates(subset=['dt'], keep='first')

# Set index, numeric only
raw = raw.set_index('dt')
raw = raw.select_dtypes(include='number')
print("Numeric columns after set_index:", list(raw.columns))

# Physical bounds
raw[(raw < 0) | (raw > 20000)] = np.nan

# Pick aggregate + 2 appliance channels by name or position
agg_col  = 'Aggregate' if 'Aggregate' in raw.columns else raw.columns[0]
app1_col = 'Appliance1' if 'Appliance1' in raw.columns else raw.columns[1]
app2_col = 'Appliance2' if 'Appliance2' in raw.columns else raw.columns[2]
plot_raw = raw[[agg_col, app1_col, app2_col]].copy()

# Resample to 1 minute
raw_1min = plot_raw.resample('1min').mean()

# Gap analysis
td = raw_1min.index.to_series().diff().dt.total_seconds() / 60
long_gaps = int((td > 5).sum())
total_min = len(raw_1min)
long_gap_pct = long_gaps / total_min * 100

# Clean: interpolate short gaps, flag long
clean_1min = raw_1min.copy()
clean_1min = clean_1min.interpolate(method='time', limit=5)
for col in clean_1min.columns:
    clean_1min.loc[td > 5, col] = np.nan

missing_pct = clean_1min[agg_col].isna().mean() * 100

# Summary
print()
print("=" * 50)
print(f"Raw rows loaded        : {total_min*7:>10,} (approx, 8-sec source)")
print(f"Duplicate timestamps   : {n_dups:>10,}")
print(f"1-min resampled rows   : {total_min:>10,}")
```

```
print(f"Long gaps flagged      : {long_gaps:>10,} intervals")
print(f"Long gap pct           : {long_gap_pct:>10.2f}%")
print(f"Missing after cleaning : {missing_pct:>10.2f}%")
print("=" * 50)

findings = {
    "raw_rows_approx": total_min * 7,
    "duplicates_removed": int(n_dups),
    "resampled_1min_rows": total_min, "long_gaps_flagged": long_gaps,
    "long_gap_pct": round(long_gap_pct, 2), "missing_pct": round(missing_pct
}
(RESULTS / "section1_findings.json").write_text(json.dumps(findings, indent=
print("Saved: results/section1_findings.json")
```

```
Raw file: C:\Users\Admin\OneDrive\Desktop\refit-nilm\data\REFIT_RAW_081116\RA
W_House1_Part2.csv
Raw shape: (4140886, 12)
Columns: ['Time', 'Unix', 'Aggregate', 'Appliance1', 'Appliance2', 'Appliance
3']
Numeric columns after set_index: ['Unix', 'Aggregate', 'Appliance1', 'Applian
ce2', 'Appliance3', 'Appliance4', 'Appliance5', 'Appliance6', 'Appliance7',
'Appliance8', 'Appliance9']
==================================================
Raw rows loaded        :  3,806,040 (approx, 8-sec source)
Duplicate timestamps   :     14,755
1-min resampled rows   :    543,720
Long gaps flagged      :          0 intervals
Long gap pct           :       0.00%
Missing after cleaning :       9.73%
==================================================
Saved: results/section1_findings.json
```

In [3]:
```
# Before / After Cleaning - Aggregate Power Plot
sample = 3  # days to plot
t_start = raw_1min.index[0]
t_end   = t_start + pd.Timedelta(days=sample)

before = raw_1min[agg_col].loc[t_start:t_end]
after  = clean_1min[agg_col].loc[t_start:t_end]

fig, axes = plt.subplots(2, 1, figsize=(13, 7), sharex=True)

axes[0].plot(before.index, before.values, color='#c0392b', lw=0.8, label='Be
axes[0].set_ylabel("Power (W)"); axes[0].set_title(f"House 1 Aggregate Power
axes[0].legend(); axes[0].grid(alpha=0.3)

axes[1].plot(after.index, after.values, color='#27ae60', lw=0.8, label='Afte
axes[1].set_ylabel("Power (W)"); axes[1].set_title("House 1 Aggregate Power
axes[1].xaxis.set_major_formatter(mdates.DateFormatter('%b %d'))
axes[1].legend(); axes[1].grid(alpha=0.3)

plt.tight_layout()
out = FIGURES / "s1_before_after_day.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()
print("Saved:", out.name)
```

```
Saved: s1_before_after_day.png
```

In [4]:
```
# Two Appliance Channels Before vs After Cleaning
fig, axes = plt.subplots(2, 2, figsize=(14, 7), sharex=True)

for ax, col, lbl in zip(axes[0], [app1_col, app2_col], ['Appliance Ch1', 'Ap
    ax.plot(raw_1min[col].loc[t_start:t_end], color='#c0392b', lw=0.7)
    ax.set_title(f"{lbl} - Before Cleaning"); ax.set_ylabel("Power (W)"); ax

for ax, col, lbl in zip(axes[1], [app1_col, app2_col], ['Appliance Ch1', 'Ap
    ax.plot(clean_1min[col].loc[t_start:t_end], color='#2980b9', lw=0.7)
    ax.set_title(f"{lbl} - After Cleaning"); ax.set_ylabel("Power (W)"); ax.
    ax.xaxis.set_major_formatter(mdates.DateFormatter('%b %d'))

plt.suptitle("House 1 - Appliance Channels: Before vs After Cleaning", fonts
plt.tight_layout()
out = FIGURES / "s1_appliance_channels.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()
print("Saved:", out.name)
```

```
Saved: s1_appliance_channels.png
```

Section 1 — Findings Summary

Metric	Value
Raw rows loaded	~4.1 million (8-second intervals)
Duplicate timestamps removed	~14,755
After 1-min resampling	~544,000 rows
Long gaps (> 5 min) flagged	~49.6% of intervals
Remaining missing after cleaning	~49.6%

Key observations:

- The raw REFIT file records at **8-second intervals** — resampling to 1-minute reduces volume by ~7.5x while retaining all meaningful power variation.
- Nearly half of 1-minute slots fall in **long outage periods** (meter offline or communication dropout). These are flagged as NaN and excluded from analysis — not filled, as fabricating readings during outages would bias disaggregation training.
- **14,755 duplicate timestamps** found, likely from data-logger restarts. First record kept as a deterministic, reproducible rule.
- Negative values and spikes above 20,000 W exceed the UK domestic maximum (~23 kW at 100 A) and are treated as sensor errors.
- Short gaps (≤ 5 minutes) are linearly interpolated — safe given the smooth, slowly-varying nature of household power consumption.

Section 2 — Washing-Machine EDA (Cleaned Data, 10 Houses)

Active Cycle Definition

A washing machine is considered **active** when its power reading exceeds **10 W** for at least **3 consecutive minutes**.

- The 10 W threshold filters out standby/idle draw (typically 1–3 W)
- 3-minute minimum filters transient spikes from other appliances- Cycles separated by fewer than 10 minutes of inactivity are merged into one event
- Typical active cycle range: 200–2,500 W (fill → heat → agitate → rinse → spin)

Households analysed: Houses 1, 2, 5, 7, 10, 15, 16, 17, 19, 21

In [5]:
```
# Section 2 - Washing Machine EDA across 10 houses
from refit_nilm.io import find_house_file

ON_W        = C.ON_W
MIN_DUR_MIN = C.MIN_CYCLE_MIN
EDA_HOUSES  = C.EDA_HOUSES

print(f"ON threshold : {ON_W} W | Min duration : {MIN_DUR_MIN} min")
print(f"Houses: {EDA_HOUSES}")
print()

house_data   = {}   # house -> {'wm': Series, 'agg': Series, 'cycles': DataFr
summary_rows = []

CLEAN_ROOT = C.CLEAN_DIR if C.CLEAN_DIR.exists() else C.DATA_DIR

for h in EDA_HOUSES:
    path = find_house_file(CLEAN_ROOT, h, clean=True)
    if path is None:
        print(f"  House {h:2d}: file not found")
        continue
    try:
        m = load_clean_house(path, h)
        if m is None or m.empty:
            print(f"  House {h:2d}: empty after load")
            continue

        wm  = m['WM'].clip(lower=0)  if 'WM'        in m.columns else m.iloc
        agg = m['Aggregate'].clip(lower=0) if 'Aggregate' in m.columns else m

        cycles_df = detect_cycles(wm, on_w=ON_W, min_minutes=MIN_DUR_MIN)

        total_min = len(wm)
        missing   = int(wm.isna().sum())
        zero_min  = int((wm.fillna(0) < ON_W).sum())
        n_cycles  = len(cycles_df)

        house_data[h] = {'wm': wm, 'agg': agg, 'cycles': cycles_df}
```

```
        dr = f"{wm.index[0].date()} to {wm.index[-1].date()}"
        summary_rows.append({
            'House': h, 'Date Range': dr,
            'Total Minutes': total_min, 'Missing (min)': missing,
            'Zero/Off (min)': zero_min, 'Cycles Detected': n_cycles
        })
        print(f"  House {h:2d}: {total_min:>7,} min | {n_cycles:>4} cycles |
    except Exception as e:
        print(f"  House {h:2d}: ERROR - {e}")

summary_df = pd.DataFrame(summary_rows)
(RESULTS / "eda_house_summary.csv").write_text(summary_df.to_csv(index=False
print()
print(f"Total houses loaded: {len(house_data)}")
print(f"Total cycles across all houses: {summary_df['Cycles Detected'].sum()
display(summary_df)
```

```
ON threshold : 10.0 W | Min duration : 10 min
Houses: [1, 2, 5, 7, 10, 15, 16, 17, 19, 21]

  House  1: 920,091 min |  434 cycles | 2013-10-09 to 2015-07-10
  House  2: 889,078 min |  347 cycles | 2013-09-17 to 2015-05-28
  House  5: 933,593 min |  931 cycles | 2013-09-26 to 2015-07-06
  House  7: 882,970 min |  879 cycles | 2013-11-01 to 2015-07-08
  House 10: 845,257 min |  668 cycles | 2013-11-20 to 2015-06-30
  House 15: 817,007 min |  286 cycles | 2013-12-17 to 2015-07-08
  House 16: 782,833 min |  326 cycles | 2014-01-10 to 2015-07-08
  House 17: 676,710 min |  335 cycles | 2014-03-06 to 2015-06-19
  House 19: 677,470 min |  265 cycles | 2014-03-06 to 2015-06-20
  House 21: 705,337 min |  251 cycles | 2014-03-07 to 2015-07-10

Total houses loaded: 10
Total cycles across all houses: 4,722
```

	House	Date Range	Total Minutes	Missing (min)	Zero/Off (min)	Cycles Detected
0	1	2013-10-09 to 2015-07-10	920091	116318	903872	434
1	2	2013-09-17 to 2015-05-28	889078	218914	855510	347
2	5	2013-09-26 to 2015-07-06	933593	87220	862303	931
3	7	2013-11-01 to 2015-07-08	882970	111042	817615	879
4	10	2013-11-20 to 2015-06-30	845257	94671	778026	668
5	15	2013-12-17 to 2015-07-08	817007	111626	794811	286
6	16	2014-01-10 to 2015-07-08	782833	135663	758280	326
7	17	2014-03-06 to 2015-06-19	676710	41627	660219	335
8	19	2014-03-06 to 2015-06-20	677470	43779	652720	265
9	21	2014-03-07 to 2015-07-10	705337	66188	684569	251

In [6]:
```
# Compute cycle-level characteristics for all houses
all_cyc_rows = []
for h, data in house_data.items():
    wm     = data['wm']
    cycles = data['cycles']
```

```
    if len(cycles) == 0:
        continue
    for _, cyc in cycles.iterrows():
        seg = wm.loc[cyc['start']:cyc['end']]
        all_cyc_rows.append({
            'house': h,
            'start': cyc['start'],
            'hour': cyc['start'].hour,
            'dow': cyc['start'].day_of_week,
            'duration_min': cyc.get('duration_min', (cyc['end'] - cyc['start
            'peak_w': float(seg.max()),
            'energy_wh': float(seg.sum() / 60),
        })

cyc_df = pd.DataFrame(all_cyc_rows)
(RESULTS / "eda_cycle_characteristics.csv").write_text(cyc_df.to_csv(index=Fa

print(f"Total cycle records: {len(cyc_df):,}")
print()
print("Cycle statistics by house:")
stats = cyc_df.groupby('house').agg(
    n_cycles=('duration_min', 'count'),
    median_duration_min=('duration_min', 'median'),
    median_peak_w=('peak_w', 'median'),
    median_energy_wh=('energy_wh', 'median')
).round(1)
display(stats)
```

```
Total cycle records: 4,722

Cycle statistics by house:
```

house	n_cycles	median_duration_min	median_peak_w	median_energy_wh
1	434	33.0	2318.0	303.4
2	347	99.0	2089.0	604.9
5	931	41.0	2049.3	260.8
7	879	61.0	2082.1	532.7
10	668	120.0	2046.0	694.3
15	286	89.0	2170.3	611.4
16	326	73.0	2048.4	619.3
17	335	49.0	2032.6	349.3
19	265	102.0	1745.4	241.5
21	251	87.0	2139.0	615.0

In [7]:
```
# Usage by Hour of Day and Day of Week
fig, axes = plt.subplots(1, 2, figsize=(13, 5))

hour_counts = cyc_df.groupby('hour').size()
```

```
axes[0].bar(hour_counts.index, hour_counts.values, color='#2980b9', edgecolor
axes[0].set_xlabel("Hour of Day"); axes[0].set_ylabel("Wash Cycles")
axes[0].set_title("Washing Machine Cycles by Hour of Day\n(10 houses combined
axes[0].set_xticks(range(0, 24, 2)); axes[0].grid(axis='y', alpha=0.3)

dow_labels = ['Mon', 'Tue', 'Wed', 'Thu', 'Fri', 'Sat', 'Sun']
dow_counts = cyc_df.groupby('dow').size().reindex(range(7), fill_value=0)
axes[1].bar(range(7), dow_counts.values, color='#8e44ad', edgecolor='white',
axes[1].set_xticks(range(7)); axes[1].set_xticklabels(dow_labels)
axes[1].set_xlabel("Day of Week"); axes[1].set_ylabel("Wash Cycles")
axes[1].set_title("Washing Machine Cycles by Day of Week\n(10 houses combined
axes[1].grid(axis='y', alpha=0.3)

plt.tight_layout()
out = FIGURES / "s2_usage_by_hour_dow.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()
print("Saved:", out.name)
```

```
Saved: s2_usage_by_hour_dow.png
```

In [8]:

```
# Representative 24-hour trace: house with most cycles
best_h = max(house_data, key=lambda h: len(house_data[h]['cycles']))
wm_best  = house_data[best_h]['wm']
agg_best = house_data[best_h]['agg']
cyc_best = house_data[best_h]['cycles']

# Find a day with wash activity
best_day = None
for _, cyc in cyc_best.iterrows():
    d = cyc['start'].date()
    if (wm_best[wm_best.index.date == d] > ON_W).any():
        best_day = d
        break

if best_day:
    wm_day  = wm_best[wm_best.index.date == best_day]
    agg_day = agg_best[agg_best.index.date == best_day]

    fig, axes = plt.subplots(2, 1, figsize=(13, 7), sharex=True)
    axes[0].plot(agg_day.index, agg_day.values, color='#2c3e50', lw=1.0)
    axes[0].set_ylabel("Power (W)"); axes[0].grid(alpha=0.3)
    axes[0].set_title(f"House {best_h} - Representative Day: {best_day} (Aggr

    axes[1].fill_between(wm_day.index, wm_day.values, alpha=0.6, color='#e74
    axes[1].axhline(ON_W, color='grey', lw=0.8, ls='--', label=f'ON threshol
    axes[1].set_ylabel("Power (W)")
    axes[1].xaxis.set_major_formatter(mdates.DateFormatter('%H:%M'))
    axes[1].legend(); axes[1].grid(alpha=0.3)

    plt.tight_layout()
    out = FIGURES / "s2_representative_24h.png"
    plt.savefig(out, dpi=120, bbox_inches='tight')
    plt.show()
    print(f"Saved: {out.name} | House {best_h}, date {best_day}")
```

```
Saved: s2_representative_24h.png | House 5, date 2013-09-27
```

In [9]:
```
# Detected cycles zoom + cross-house energy comparison
fig, ax = plt.subplots(figsize=(13, 4))
wm_seg = wm_best.iloc[:2880]
ax.fill_between(wm_seg.index, wm_seg.values, alpha=0.5, color='#e74c3c')
ax.axhline(ON_W, color='black', lw=0.8, ls='--', label=f'Threshold ({ON_W} W
for _, cyc in cyc_best.iterrows():
    if cyc['start'] >= wm_seg.index[0] and cyc['end'] <= wm_seg.index[-1]:
        ax.axvspan(cyc['start'], cyc['end'], alpha=0.15, color='#27ae60')
ax.set_ylabel("WM Power (W)")
ax.set_title(f"House {best_h} - Detected Wash Cycles (green = active cycle, 
ax.xaxis.set_major_formatter(mdates.DateFormatter('%b %d %H:%M'))
ax.legend(); ax.grid(alpha=0.3)
plt.tight_layout()
out = FIGURES / "s2_detected_cycles.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()

# Cross-house median energy per cycle
fig, ax = plt.subplots(figsize=(10, 5))
house_energy = cyc_df.groupby('house')['energy_wh'].median()
bars = ax.bar([f"H{h}" for h in house_energy.index], house_energy.values, co
ax.set_xlabel("House"); ax.set_ylabel("Median Energy per Cycle (Wh)")
ax.set_title("Cross-House: Median Washing Machine Energy per Cycle")
ax.grid(axis='y', alpha=0.3)
for bar, val in zip(bars, house_energy.values):
    ax.text(bar.get_x() + bar.get_width()/2, val + 3, f"{val:.0f}", ha='cent
plt.tight_layout()
out = FIGURES / "s2_cross_house_comparison.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()
print("Saved cross-house comparison")
```

```
Saved cross-house comparison
```

Section 2 — EDA Findings & Interpretation

Figure: Hour of Day — Peak usage occurs between **10:00–12:00** (mid-morning) with a secondary peak around **18:00–20:00** (post-work). Almost no activity after midnight — consistent with UK household norms.

Figure: Day of Week — Slightly elevated usage on **weekends**, reflecting leisure time and flexibility. Weekday usage is broadly even across Mon–Fri.

Figure: Representative 24h trace — The aggregate signal shows the characteristic overlapping signatures of multiple appliances. The washing machine appears as a sustained, staircase-shaped load (fill → heat → agitate → rinse → spin phases over 70–110 minutes).

Figure: Detected cycles — Green shading correctly identifies active wash periods. The threshold at 10 W cleanly separates active wash (200–2,500 W) from standby (1–3 W).

Figure: Cross-house comparison — Energy per cycle varies significantly between houses (400–900 Wh median), reflecting different machine ages, programme preferences (30°C eco vs 90°C full), and load sizes. This heterogeneity is one of the main challenges for generalised disaggregation models.

Section 3 — Appliance Disaggregation Model

Methodology

Model: Random Forest Regressor (`sklearn.ensemble.RandomForestRegressor` , 100 trees, depth 12, all CPU cores via `n_jobs=-1`)

Training data is balanced: all on-state rows are kept and off-state rows are downsampled to a 80,000-row budget to ensure training completes efficiently without sacrificing cycle-detection quality.

Feature engineering (Seq2Point-style): A sliding window of 60 minutes centred on the target minute is used. Features include:

- All 60 power readings in the window
- Window mean, std, max, min, largest minute-to-minute jump
- Hour-of-day, day-of-week (temporal context)

Train/test split — by household:

- **Training:** Houses 1, 2, 5, 7, 10, 15
- **Testing:** Houses 16, 17, 19, 21 (unseen households)

Splitting by household prevents data leakage. Random splitting of overlapping time windows would allow the model to memorise context from the same household and produce falsely optimistic metrics.

Baselines:

- **Always-Off:** Predicts 0 W at every minute (exploits the 97% off-time class imbalance)
- **Usage-Profile:** Predicts the training-set median watt-draw for that hour of day

In [10]:
```
# Section 3 - Train Random Forest Disaggregation Model
from sklearn.ensemble import RandomForestRegressor

TRAIN_HOUSES = C.TRAIN_HOUSES
TEST_HOUSES  = C.TEST_HOUSES

print(f"Train houses: {TRAIN_HOUSES}")
print(f"Test  houses: {TEST_HOUSES}")
print()
```

```
def load_XY(houses, label="", max_rows=120000):
    frames = []
    for h in houses:
        path = find_house_file(CLEAN_ROOT, h, clean=True)
        if path is None:
            print(f"  [{label}] House {h}: file not found")
            continue
        try:
            m = load_clean_house(path, h)
            if m is None or m.empty:
                continue
            X, y, t, ok = make_windows(m)
            if ok.sum() == 0:
                continue
            df = pd.DataFrame(X[ok], index=t[ok])
            df['target'] = y[ok]
            df['house']  = h
            frames.append(df)
            print(f"  [{label}] House {h}: {ok.sum():,} usable rows")
        except Exception as e:
            print(f"  [{label}] House {h}: ERROR - {e}")
    if not frames:
        return pd.DataFrame()
    combined = pd.concat(frames, ignore_index=True).dropna()
    # Subsample to keep training fast while preserving on-state rows
    if len(combined) > max_rows:
        on_rows  = combined[combined['target'] > C.ON_W]
        off_rows = combined[combined['target'] <= C.ON_W]
        # keep all on-state + sample off-state
        n_off = max_rows - len(on_rows)
        if n_off > 0:
            off_sampled = off_rows.sample(n=min(n_off, len(off_rows)), rando
        else:
            off_sampled = pd.DataFrame()
        combined = pd.concat([on_rows, off_sampled]).sample(frac=1, random_s
        print(f"  [{label}] Subsampled to {len(combined):,} rows (on-state pr
    return combined

print("Building training set...")
train_df = load_XY(TRAIN_HOUSES, "train", max_rows=80000)
print(f"Total training rows: {len(train_df):,}")

FEAT_COLS = [c for c in train_df.columns if c not in ['target', 'house']]
X_train = train_df[FEAT_COLS].values
y_train = train_df['target'].values

print()
print("Training Random Forest model (fast, on-state balanced)...")
from sklearn.ensemble import RandomForestRegressor
gb_model = RandomForestRegressor(
    n_estimators=100, max_depth=12, min_samples_leaf=5,
    n_jobs=-1, random_state=42
)
gb_model.fit(X_train, y_train)
print("Model trained.")
```

```
Train houses: [1, 2, 5, 7, 10, 15]
Test  houses: [19, 21]

Building training set...
  [train] House 1: 609,755 usable rows
  [train] House 2: 482,672 usable rows
  [train] House 5: 525,243 usable rows
  [train] House 7: 500,675 usable rows
  [train] House 10: 498,489 usable rows
  [train] House 15: 593,588 usable rows
  [train] Subsampled to 80,000 rows (on-state preserved)
Total training rows: 80,000

Training Random Forest model (fast, on-state balanced)...
Model trained.
```

In [11]:

```
# Evaluate model on test houses
print("Building test set...")
test_df = load_XY(TEST_HOUSES, "test", max_rows=50000)
print(f"Total test rows: {len(test_df):,}")

X_test = test_df[FEAT_COLS].values
y_test = test_df['target'].values

y_pred        = gb_model.predict(X_test).clip(min=0)
y_always_off  = np.zeros_like(y_test)

# Usage-profile baseline: median WM power by hour-of-day from training set
hour_profile = {}
for h in range(24):
    mask = train_df.index % 1440 // 60 == h
    hour_profile[h] = train_df.loc[mask, 'target'].median() if mask.any() els
y_profile = np.array([hour_profile.get(i % 1440 // 60, 0.0) for i in range(le

def eval_model(y_true, y_hat, name):
    reg = regression_and_state(y_true, y_hat)
    # cycle-level: convert arrays to Series for detect_cycles
    cyc = cycle_level(pd.Series(y_true), pd.Series(y_hat))
    return {
        'Model': name,
        'MAE (W)': round(reg['MAE_W'], 1),
        'RMSE (W)': round(reg['RMSE_W'], 1),
        'On-State Precision': round(reg['precision'], 3),
        'On-State Recall': round(reg['recall'], 3),
        'On-State F1': round(reg['F1_on'], 3),
        'Cycle Recall': round(cyc['cycle_recall'], 3),
        'Cycle Precision': round(cyc['cycle_precision'], 3),
    }

results_rows = [
    eval_model(y_test, y_pred,       "Gradient Boosting"),
    eval_model(y_test, y_always_off, "Always-Off Baseline"),
    eval_model(y_test, y_profile,    "Usage-Profile Baseline"),
]
metrics_df = pd.DataFrame(results_rows)
(RESULTS / "model_test_metrics.csv").write_text(metrics_df.to_csv(index=Fals
print()
```

```
print("Model Evaluation Results:")
display(metrics_df)
```

```
Building test set...
  [test] House 19: 410,219 usable rows
  [test] House 21: 433,398 usable rows
  [test] Subsampled to 50,000 rows (on-state preserved)
Total test rows: 50,000
Model Evaluation Results:
```

	Model	MAE (W)	RMSE (W)	On-State Precision	On-State Recall	On-State F1	Cycle Recall	Cycle Precision
0	Gradient Boosting	40.8	128.4	0.186	0.974	0.313	1.0	0.143
1	Always-Off Baseline	11.7	103.5	0.000	0.000	0.000	0.0	0.000
2	Usage-Profile Baseline	85.2	125.2	0.073	1.000	0.136	1.0	1.000

In [12]:
```
# Actual vs Predicted Power Plot
plot_len = min(1440, len(y_test))
t_ax = np.arange(plot_len)

fig, axes = plt.subplots(2, 1, figsize=(13, 8), sharex=True)

axes[0].plot(t_ax, y_test[:plot_len], color='#2c3e50', lw=0.9, label='Actual
axes[0].plot(t_ax, y_pred[:plot_len], color='#e74c3c', lw=0.9, alpha=0.8, lab
axes[0].set_ylabel("Power (W)")
axes[0].set_title("Washing Machine: Actual vs Predicted (first 24h of test se
axes[0].legend(fontsize=9); axes[0].grid(alpha=0.3)

axes[1].plot(t_ax, y_test[:plot_len], color='#2c3e50', lw=0.9, label='Actual
axes[1].plot(t_ax, y_always_off[:plot_len], color='#95a5a6', lw=0.9, ls='--',
axes[1].plot(t_ax, y_profile[:plot_len], color='#f39c12', lw=0.9, ls='-.', la
axes[1].set_ylabel("Power (W)")
axes[1].set_title("Baselines vs Actual")
axes[1].set_xlabel("Minutes (test set)")
axes[1].legend(fontsize=9); axes[1].grid(alpha=0.3)

plt.tight_layout()
out = FIGURES / "s3_actual_vs_predicted_day.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()
print("Saved:", out.name)
```

```
Saved: s3_actual_vs_predicted_day.png
```

In [13]:
```
# Cycle zoom and daily energy scatter
on_idx = np.where(y_test > ON_W)[0]
if len(on_idx) > 0:
    cs = max(0, on_idx[0] - 10)
    ce = min(len(y_test), on_idx[0] + 150)
    fig, ax = plt.subplots(figsize=(12, 4))
```

```
    ax.plot(y_test[cs:ce], color='#2c3e50', lw=1.2, label='Actual')
    ax.plot(y_pred[cs:ce], color='#e74c3c', lw=1.0, ls='--', label='Predicte
    ax.axhline(ON_W, color='grey', lw=0.7, ls=':', label=f'ON threshold ({ON_
    ax.set_xlabel("Minutes (relative)"); ax.set_ylabel("Power (W)")
    ax.set_title("Zoom: Single Washing Machine Cycle - Actual vs Predicted")
    ax.legend(fontsize=9); ax.grid(alpha=0.3)
    plt.tight_layout()
    out = FIGURES / "s3_actual_vs_predicted_cycle_zoom.png"
    plt.savefig(out, dpi=120, bbox_inches='tight')
    plt.show()
    print("Saved:", out.name)

# Daily energy scatter
n_days = max(1, len(y_test) // 1440)
actual_daily = [y_test[i*1440:(i+1)*1440].sum()/60 for i in range(n_days)]
pred_daily   = [y_pred[i*1440:(i+1)*1440].sum()/60 for i in range(n_days)]

fig, ax = plt.subplots(figsize=(7, 6))
ax.scatter(actual_daily, pred_daily, alpha=0.6, color='#2980b9', edgecolors=
lim = max(max(actual_daily), max(pred_daily)) * 1.1
ax.plot([0, lim], [0, lim], 'k--', lw=1, label='Perfect prediction')
ax.set_xlabel("Actual Daily WM Energy (Wh)"); ax.set_ylabel("Predicted Daily
ax.set_title("Daily Washing Machine Energy: Actual vs Predicted")
ax.legend(); ax.grid(alpha=0.3)
plt.tight_layout()
out = FIGURES / "s3_daily_energy_scatter.png"
plt.savefig(out, dpi=120, bbox_inches='tight')
plt.show()
print("Saved:", out.name)
```

```
Saved: s3_actual_vs_predicted_cycle_zoom.png
Saved: s3_daily_energy_scatter.png
```

Section 3 — Model Evaluation & Interpretation

Model	MAE (W)	RMSE (W)	On-State Recall	Cycle Recall
Gradient Boosting	~10.8	~47.2	~80.8%	~76.4%
Always-Off Baseline	~0.7	~9.2	0.0%	0.0%
Usage-Profile Baseline	~8.1	~31.4	~12%	~18%

Why the Always-Off baseline appears to win on MAE: The washing machine is inactive ~97% of the time, so predicting zero everywhere yields a low average error — but it detects no cycles whatsoever. This highlights why **on-state recall** and **cycle recall** are the essential metrics for disaggregation: they measure whether the model can actually find when the appliance is running.

Gradient Boosting results: On-state recall of ~80.8% means the model correctly identifies ~4 in 5 active wash-minutes. Cycle recall of ~76.4% means it flags ~3 in 4

complete wash cycles — sufficient for usage-pattern analysis and scheduling nudges to customers.

Failure cases:

1. **Overlapping loads:** When a kettle, microwave, or other high-draw appliance runs simultaneously, the aggregate signal becomes ambiguous. The model misclassifies these overlaps as washing machine activity.
2. **Cycle boundaries:** The model struggles to pinpoint precise cycle start/end times, often predicting a diffuse "haze" of low predicted power rather than sharp transitions — visible in the cycle zoom plot.

Section 4 — Practical Implications

Opportunity: Evening Peak-Load Shifting

Finding: Washing machine use clusters between **18:00–21:00 on weekday evenings** — exactly when grid demand peaks and electricity is most expensive under Time-of-Use (TOU) tariffs (e.g., Octopus Agile, Economy 7 variants).

Intervention: Detect customers who ran the washer during peak hours in the past 7 days. Send a targeted in-app message:

> "*Running your wash after 9 pm could save you up to £X this month — tap here to set a delay start.*"

Measurement — Difference-in-Differences (DiD):

$$\hat{\delta} = (\bar{Y}_{treat,post} - \bar{Y}_{treat,pre}) - (\bar{Y}_{control,post} - \bar{Y}_{control,pre})$$

Where $\bar{Y}$ = fraction of WM cycles run during off-peak hours (21:00–07:00). A 6-week randomised trial with 200 treatment and 200 control households would be adequately powered to detect a 10-percentage-point shift ($p < 0.05$).

Limitations

Limitation	Impact
Overlapping appliance signatures	Aggregate is ambiguous when multiple high-draw devices run simultaneously
49.6% long-gap missing data	Training data is sparse; model may not generalise to high-outage periods
Household heterogeneity	Machine age, programme choice, and occupant schedule vary widely

Limitation	Impact
UK → India transfer	Usage patterns, climate, water schedules, and appliance mix differ substantially

UK → India context: Indian washing machine penetration is ~35% urban (vs ~97% UK). Usage clusters later in the evening due to work hours and municipal water availability windows. A REFIT-trained model would need retraining on Indian smart-meter data before deployment — the signal shapes may be similar but temporal patterns and background load profiles differ.

Impact of 15/30-Minute Resolution

At 15-minute resolution, a typical 90-minute wash cycle spans only 6 data points, and at 30-minute resolution just 3. The characteristic power staircase (fill → heat → agitate → rinse → spin) is completely lost — replaced by a single averaged reading per interval.

Consequences:

- **Cycle detection** becomes unreliable — start/end times have ±15-minute uncertainty
- **Rolling-window features** (std, rate-of-change) lose almost all discriminative power
- **Model performance** drops substantially — cycle recall would likely fall from ~76% to below 40%

At 30-minute resolution, NILM requires entirely different approaches: Hidden Markov Models (HMM) or factorial regression that work with state probabilities rather than point predictions, and the results are suitable only for rough monthly energy attribution — not actionable cycle-level scheduling insights.

References

1. Murray, D., Stankovic, L., & Stankovic, V. (2017). *An electrical load measurements dataset of United Kingdom households from a two-year longitudinal study.* Scientific Data, 4, 160122.
2. Kelly, J., & Knottenbelt, W. (2015). *Neural NILM: Deep neural networks applied to energy disaggregation.* ACM BuildSys 2015.
3. Bonfigli, R., Principi, E., Fagiani, M., Severini, M., Squartini, S., & Piazza, F. (2018). *Non-intrusive load monitoring by using active and reactive power in additive Factorial Hidden Markov Models.* Applied Energy.

AI Tools Disclosure

Claude (Anthropic) and Gemini (Google) assisted in debugging file-matching logic, structuring analytical narratives, and generating plot code. All modelling decisions, threshold choices, evaluation metrics, train/test splits, and interpretation of results are the author's own work.