

| 🧩 Agentic architecture                                                                             |                                                                                                 |
|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|
| Wrong tool, thin desc. <span>✖</span> few-shot / classifier / merge                                | ✔ rewrite descriptions <i>boundary vs sibling, sample query</i>                                 |
| Wrong tool, desc already clear. <span>✖</span> add neg. examples                                   | ✔ keyword conditional in the system prompt <i>clue: desc isn't the cause</i>                    |
| Few-shot for tool pick. <span>✖</span> 10-15 clear / grouped                                       | ✔ 4-6 ambiguous cases + reasoning <i>model already nails clear ones</i>                         |
| Migration w/ unknowns. <span>✖</span> codemod / tests / module-by-module                           | ✔ Plan mode, approve approach first <i>others miss the design-level bug</i>                     |
| Subagent output too big. <span>✖</span> summarizer / bigger ctx / vector db                        | ✔ upstream returns structured data <i>fix at source, no extra hop</i>                           |
| Agents overlap. <span>✖</span> shared scratchpad / dedupe after                                    | ✔ coordinator partitions subtopics up front                                                     |
| Coverage gaps. <span>✖</span> blame synth/search agent                                             | ✔ coordinator decomposition too narrow                                                          |
| Worker dies silent. <span>✖</span> "all collected = ok" / abort                                    | ✔ require returned success per dispatched item <i>no result = fail</i>                          |
| Subagent error types. <span>✖</span> timeout & "0 results" both fail                               | ✔ timeout=retry, 0-results=valid; recover transient locally                                     |
| Conflicting data. <span>✖</span> keep higher-conf + footnote                                       | ✔ return both, mark unresolved, owner decides                                                   |
| Partial coverage. <span>✖</span> global preamble / soften all                                      | ✔ per-section confidence note                                                                   |
| Escalate? <span>✖</span> angry / threat / multi-concern / contradiction                            | ✔ only policy-interp gap OR dead-end (no route to act)                                          |
| Destructive write. <span>✖</span> prompt "wait" / snapshot / revert                                | ✔ approval checkpoint blocks the apply                                                          |
| Must-never (refund/credit/delete). <span>✖</span> session log / token / PostToolUse / guard clause | ✔ PreToolUse deny OR read authoritative record <i>independent of model, before money moves</i>  |
| Deterministic transform. <span>✖</span> temp=0 agent / regex / LSP                                 | ✔ codemod over the AST, run once <i>regex hits same-named local var</i>                         |
| Sequential indep. lookups. <span>✖</span> composite tool / speculative / max_tokens                | ✔ parallel tool_use blocks in one turn                                                          |
| 🧠 Context & batch                                                                                  |                                                                                                 |
| Batch fit? <span>✖</span> batch both / timeout-fallback / smaller batches                          | ✔ sync if blocks merge-push-release OR human deadline; batch only unattended                    |
| Batch + tool loop. <span>✖</span> batch the whole exchange                                         | ✔ keep gathering sync, batch only the final self-contained call                                 |
| Verbose discovery. <span>✖</span> /compact / multi-session / scratch-reload                        | ✔ Explore subagent returns a summary                                                            |
| Lost in the middle. <span>✖</span> summarize-all / bigger model / rotate                           | ✔ digest at start+end + headers; or verbatim quote per field                                    |
| Critical fact compacted. <span>✖</span> keep numbers in summary / raise threshold / pin turn       | ✔ write to external/case record, prepend every turn                                             |
| Cache read=0. <span>✖</span> 5-min TTL / workspace scope                                           | ✔ volatile id before breakpoint → move it after                                                 |
| 📁 Claude Code config                                                                               |                                                                                                 |
| Team / clone-ready. <span>✖</span> ~/.claude / root commands/ / doc section                        | ✔ commit .claude/commands/ or .claude/CLAUDE.md                                                 |
| Personal override of team skill. <span>✖</span> same name / override:true                          | ✔ a NEW command name /my-x <i>same name won't shadow</i>                                        |
| Skill won't auto-fire. <span>✖</span> phrasings in body / CLAUDE.md / few-shot                     | ✔ user phrasings in the description frontmatter                                                 |
| Modular, always-on. <span>✖</span> rules/ + paths glob                                             | ✔ @import lines in CLAUDE.md <i>rules+paths loads only for matching files</i>                   |
| Path/file-type rules. <span>✖</span> CLAUDE.md sections                                            | ✔ .claude/rules/ + paths: glob                                                                  |
| MCP creds, shared file. <span>✖</span> .env / :-default / op:// / user scope                       | ✔ \${ENV_VAR} in committed .mcp.json + document it                                              |
| 📄 Prompt & output                                                                                  |                                                                                                 |
| Structured output. <span>✖</span> "respond only JSON"+strip+retry / few-shot / temp 0              | ✔ forced tool_choice + input_schema, read tool_use <i>prefill { = smallest fix for preamble</i> |
| Force the tool. <span>✖</span> mark all fields required                                            | ✔ tool_choice forces the CALL                                                                   |
| Missing field. <span>✖</span> drop from required / "none" token                                    | ✔ keep required, type ["string", "null"]                                                        |
| Schema-validate fail. <span>✖</span> separate reformat call / pre-normalize                        | ✔ tool_result is_error:true, Claude reissues <i>only it has the source</i>                      |
| Self-review blind spot. <span>✖</span> self-critique prompt / extended thinking                    | ✔ 2nd independent instance, no generator reasoning                                              |
| Inconsistent severity. <span>✖</span> mapping table / relative-to-PR / reasoning-then-adjust       | ✔ explicit criteria + borderline anchor / fixed budget                                          |
| False-positive noise. <span>✖</span> uniform cut / confidence display / slow few-shot              | ✔ disable noisy category, fix offline, restore                                                  |
| Prose reinterpreted each iter. <span>✖</span> more precise spec / parser first                     | ✔ 2-3 input→output examples                                                                     |
| Ambiguous multi-match. <span>✖</span> re-query filters / confirm the one picked                    | ✔ list the matches, user picks, before acting                                                   |
| Hallucinated API names. <span>✖</span> typecheck+regen / dump SDK to CLAUDE.md                     | ✔ fetch real signatures from MCP doc, just-in-time                                              |
| CI accuracy gate. <span>✖</span> average / one field / vs last run                                 | ✔ gate on the MIN per-field rate                                                                |
| Scanned/low-quality docs. <span>✖</span> augment prompt / OCR→shared / pass label                  | ✔ own path per stream; scans read the image                                                     |